Nominal High Voltage Settings for Electron Arm Shower

Table 1: (Oct 10 1997)

Sh Blk	HAC6 HV slot. chan	HV (V)	Sh Blk	HAC6 HV slot chan	HV (V)	Sh Blk	HAC6 slot chan	HV (V)	Sh BJk	HAC6 slot. chan	HV (V)
1	1.0	1425	25	4.0	1470	49	7.0	1450	73	10.0	1500
2	1.1	1415	26	4.1	1395	50	7.1	1540	74	10.1	1315
3	1.2	1480	27	4.2	1475	51	7.2	1460	75	10.2	1440
4	1.3	1375	28	4.3	1470	52	7.3	1550	76	10.3	1550
5	1.4	1480	29	4.4	1400	53	7.4	1520	77	10.4	1395
6	1.5	1455	30	4.5	1435	54	7.5	1585	78	10.5	1445
7	1.6	1510	31	4.6	1440	55	7.6	1375	79	10.6	1575
8	1.7	1360	32	4.7	1460	56	7.7	1530	80	10.7	1415
9	1.8	1420	33	4.8	1430	57	7.8	1335	81	10.8	1415
10	1.9	1490	34	4.9	1580	58	7.9	1415	82	10.9	1380
11	1.10	1500	35	4.10	1405	59	7.10	1440	83	10.10	1600
12	1.11	1385	36	4.11	1515	60	7.11	1380	84	10.11	1540
13	2.0	1555	37	5.0	1385	61	8.0	1310	85	11.0	1480
14	2.1	1440	38	5.1	1490	62	8.1	1410	86	11.1	1395
15	2.2	1430	39	5.2	1425	63	8.2	1455	87	11.2	1400
16	2.3	1435	40	5.3	1435	64	8.3	1275	88	11.3	1465
17	2.4	1440	41	5.4	1465	65	8.4	1550	89	11.4	1455
18	2.5	1450	42	5.5	1350	66	8.5	1365	90	11.5	1440
19	2.6	1585	43	5.6	1470	67	8.6	1365	91	11.6	1500
20	2.7	1400	44	5.7	1415	68	8.7	1370	92	11.7	1700
21	2.8	1340	45	5.8	1390	69	8.8	1380	93	11.8	1550
22	2.9	1400	46	5.9	1365	70	8.9	1800	94	11.9	1435
23	2.10	1420	47	510	1380	71	8.10	1355	95	11.10	1550
24	2.11	1495	48	5.11	1445	72	8.11	1550	96	11.11	1500