

Notes on the **GlueX FSRoot** Format

Ryan Mitchell

June 9, 2019

Abstract

This document describes the **GlueX FSRoot** format.

Contents

1	Overview	1
2	Final States	1
3	Event Information	2
4	Particle Four-Momenta	2
5	Track Information	3
6	Shower Information	3
7	MC Truth Information	3
8	Final State Numbering	4

1 Overview

The **GlueX FSRoot** format is a flat **TTree** format. All variables are **float**. Multiple combinations within an event are listed as separate **TTree** entries, just like entries from distinct events. The format is designed to be compatible with the **FSRoot** package.

2 Final States

The **FSRoot** format can hold information from any final state composed of a combination of Λ (decaying to $p\pi^-$), $\bar{\Lambda}$ (decaying to $\bar{p}\pi^+$), e^+ , e^- , μ^+ , μ^- , p , \bar{p} , η (decaying to $\gamma\gamma$), γ , K^+ , K^- , K_S^0 (decaying to $\pi^+\pi^-$), π^+ , π^- , and π^0 (decaying to $\gamma\gamma$).

Final state particles are listed in trees in the following order:

Lambda ALambda e+ e- mu+ mu- p+ p- eta gamma K+ K- Ks pi+ pi- pi0

For example, in the process $\gamma p \rightarrow \pi^+ \pi^- J/\psi p; J/\psi \rightarrow \mu^+ \mu^-$, the μ^+ is particle 1, the μ^- is particle 2, the p is particle 3, the π^+ is particle 4, and the π^- is particle 5. Or as another example, in the process $\gamma p \rightarrow \gamma \chi_{c1} p; \chi_{c1} \rightarrow \eta \pi^0 \pi^0$, the p is particle 1, the η is particle 2, the γ is particle 3, one π^0 is particle 4, and the other π^0 is particle 5. In cases like this where there are identical particles, no ordering is assumed.

3 Event Information

The “Event Information” variables contain information about the event as a whole:

Run:	run number
Event:	event number
Chi2:	chi2 of the kinematic fit
Chi2DOF:	chi2/dof of the kinematic fit
RFTIME:	RF time determined from the kinematic fit
RFDeltaT:	difference between RF time and beam photon time
EnUnusedSh:	total energy of unused showers
ProdVx:	production vertex parameters
ProdVy:	"
ProdVz:	"
ProdVt:	"
PxPB:	kinematically fit beam parameters
PyPB:	"
PzPB:	"
EnPB:	"
RPxPB:	measured beam parameters
RPyPB:	"
RPzPB:	"
REnPB:	"
MCPxPB:	thrown beam parameters (MC only)
MCPyPB:	"
MCPzPB:	"
MCEnPB:	"

4 Particle Four-Momenta

The “Particle Four-Momenta” variables contain the four-momentum for each particle in the final state:

```

(prefix)PxP(n):  x momentum of particle (n)
(prefix)PyP(n):  y momentum of particle (n)
(prefix)PzP(n):  z momentum of particle (n)
(prefix)EnP(n):  energy of particle (n)

```

Different types of four-momenta are distinguished using prefixes. Raw four-momenta have a prefix **R**; the final four-momenta (the fully-constrained four-momenta resulting from the kinematic fit) have no prefix; MC truth information have a prefix **MC**.

Different particles are differentiated using the postfix **P(n)**, where **(n)** is the number of the particle in the ordered list. Four-momenta for secondaries originating from particle **(n)**, such as the two γ 's from a π^0 , are recorded using **P(n)a** and **P(n)b**, where the ordering follows the same conventions as above, or, in the case of identical daughter particles, no ordering is assumed. As two examples: in the process $\gamma p \rightarrow \pi^+ \pi^- J/\psi p$; $J/\psi \rightarrow \mu^+ \mu^-$, the raw energy of the π^+ is given by **REnP4**; and in the process $\gamma p \rightarrow \pi^+ \pi^- J/\psi p$; $J/\psi \rightarrow \pi^+ \pi^- \pi^0$, the y-momentum of a photon from the π^0 decay, after the kinematic fit, is given by **PyP6b**.

5 Track Information

Track information is written out for every reconstructed track that is part of a final state. The postfix **P(n)** follows the same convention as for the four-momenta (section 4).

```

TkChi2P(n):      chi2 of the track fit
TkNDFP(n):       number of degrees of freedom for the track fit

```

6 Shower Information

Shower information is written out for every reconstructed shower that is part of a final state. The postfix **P(n)** follows the same convention as for the four-momenta (section 4).

```

ShQualityP(n):   a shower quality score

```

7 MC Truth Information

The following variables can be used to help keep track of truth information.

```

MCDecayCode1:    the true code1, described in the
                  "final state numbering" section
MCDecayCode2:    the true code2, described in the

```

```

                                "final state numbering" section
MCEXtras:                    1000 * number of neutrinos +
                                100 * number of K_L +
                                10 * number of neutrons +
                                1 * number of antineutrons
MCSignal:                    1 if the reconstructed final state
                                matches the generated final state;
                                0 otherwise

```

8 Final State Numbering

Final states are designated using two integers, “code1” and “code2”. The digits of each integer are used to specify the number of different particle types in the final state:

```

code1 = abcdefg
    a = number of gamma
    b = number of K+
    c = number of K-
    d = number of Ks ( --> pi+ pi- )
    e = number of pi+
    f = number of pi-
    g = number of pi0 ( --> gamma gamma )

code2 = hijklmnop
    h = number of Lambda (--> p+ pi-)
    i = number of ALambda (--> p- pi+)
    j = number of e+
    k = number of e-
    l = number of mu+
    m = number of mu-
    n = number of p+
    o = number of p-
    p = number of eta ( --> gamma gamma )

```

These integers are sometimes combined into a single string of the form:

```
"code2_code1"
```

Here are a few examples:

```

"0_111":      pi+ pi- pi0
"0_1000002":  gamma pi0 pi0
"1_220000":   eta K+ K+ K- K-
"11000_110":  mu+ mu- pi+ pi-

```