

UNIVERSITY OF MINES AND TECHNOLOGY, TARKWA
SCHOOL OF RAILWAYS AND INFRASTRUCTURE DEVELOPMENT
COMPUTER SCIENCE AND ENGINEERING PROGRAMME

A PROJECT REPORT ENTITLED
SAFEZONE: INTEGRATED SECURITY SYSTEM WITH MOTION AND SMOKE
DETECTION

BY
ESSIEN JEFFERY

SUBMITTED IN PARTIAL FULFILMENT OF THE REQUIREMENTS
AWARD OF THE DEGREE OF BACHELOR OF SCIENCE IN COMPUTER SCIENCE
AND ENGINEERING

PROJECT SUPERVISOR

.....

MR THOMAS KWANTWI

SEKONDI - TAKORADI, GHANA

SEPTEMBER, 2024

DECLARATION

I declare that this project is my own work. It is being submitted for the degree of Bachelor of Science (BSc.) in Computer Science and Engineering in the University of Mines and Technology (UMaT), Tarkwa. It has not been submitted for any degree or examination in any other University.

.....

(Signature of Candidate)

..... day of (Year).....

ABSTRACT

This project presents an integrated IoT-based security and safety system designed to enhance residential and commercial safety through motion and fire detection. The system leverages interconnected sensors and actuators, including motion detectors, smoke detectors, sirens, IoT-enabled windows and doors, and fire sprinklers, all managed by a centralized home gateway. The home gateway communicates with a DNS server and an IoT server to ensure reliable data flow and control. The system is connected to the internet via an ISP router and modem, with cellular communication as a backup, ensuring continuous operation. Controllers such as laptops and smartphones provide real-time monitoring and management of the system. This innovative solution aims to bridge the gaps in current safety systems, offering a comprehensive and responsive approach to security and fire prevention, ultimately enhancing the safety and peace of mind for users.

ACKNOWLEDGEMENT

The successful completion of this endeavor was a collective effort, not the work of one individual. It demanded dedicated efforts in the right direction. I am deeply grateful to my project supervisor, Mr. Albert Kwantwi, whose invaluable guidance, constant encouragement, and kind cooperation were pivotal to the success of this project. I also extend my sincere appreciation to Dr. Albert Kwansah Ansah, Head of the Department of Computer Science and Engineering, for providing essential departmental resources. Additionally, I am thankful to all those who offered their support, directly or indirectly, throughout various stages of this endeavor. I express heartfelt gratitude to my parents, siblings, friends, and colleagues for their unwavering support and blessings throughout this journey.

TABLE OF CONTENTS

DECLARATION	i
ABSTRACT	ii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENTS	iv
LIST OF FIGURES	vii
CHAPTER 1 INTRODUCTION	1
1.1 Background of study	1
1.2 Statement of problem	2
1.3 Project objectives	2
1.4 Methods used	3
1.5 Tools and facilities used	3
1.6 Scope of work	4
1.7 Research organization	4
CHAPTER 2 LITERATURE REVIEW	5
2.1 Introduction	5
2.2 Motion Detection	5
2.3 Smoke and Fire Detection System	7
2.4 Integrated IoT Based System	9
CHAPTER 3 METHODOLOGY	12
3.1 Overview	12
3.2 Research design	12
3.2.1 Data Collection Methods	12
3.2.2 System Requirements Analysis	12

3.2.3	Experimental Setup	12
3.3	System design and architecture for integrated Iot-based motion	13
3.3.1	Network System Component and Interactions	13
3.3.2	IP Address Management	15
3.3.3	The Application used	18
3.3.4	Programming Languages	19
3.4	Component used under motion detection	20
3.4.1	Motion Detection Components	20
3.4.2	Conditions Made For the simulation	21
3.4.3	Truth Table For Motion Detection	23
3.5	Component used under smoke and fire detection systems	24
3.5.1	Smoke Detection And Fire Prevention Components	24
3.6	Flowchart for the system	25
3.6.1	Flowcharts for the motion detection	25
3.6.2	Flowchart for smoke and fire detection	27
3.6.3	Conditions Made For The Simulation	29
3.6.4	Truth Table For Smoke And Fire Detection	31
3.7	Proposed system	31
3.8	Pseudocode for the integration of motion and fire detection system	32
CHAPTER 4 IMPLEMENTATION AND RESULTS		33
4.1	Introduction	34
4.2	Implementation steps	34
4.2.1	Motion Detection	34
4.2.2	Expected Outcomes For Motion Detection	34
4.3	Smoke detection and fire prevention system	35

4.3.1	Integration and Testing	37
4.4	Outcome for the integration of motion and fire detection system	37
4.5	Results	38
4.5.1	Performance Metrics	38
4.5.2	Effectiveness	39
CHAPTER 5 RECOMMENDATION AND CONCLUSION		40
5.1	Conclusion	40
5.2	Recommendation	40
REFERENCES		41
APPENDIX		43

LIST OF FIGURES

Figure 3.1 Cloud server and it's relations	14
Figure 3.2 Configuration on ISP router	15
Figure 3.3 Static configuration on the DNS server	16
Figure 3.4 DHCP configuration on the Iot devices	17
Figure 3.5 IOE website	18
Figure 3.6 Conditions for motion detection	22
Figure 3.7 Logic gate illustration for motion detection	23
Figure 3.8 The truth table for motion detection	24
Figure 3.9 Smoke detector	24
Figure 3.10 Flowchart for motion detection	27
Figure 3.11 Flowchart of smoke detection	29
Figure 3.12 Conditions for smoke detection	30
Figure 3.13 Truth table of smoke detection	31
Figure 3.14 Proposed system of the project	32
Figure 3.15 Pseudocode for the integration	33
Figure 4.1 Outcome for motion detection	35
Figure 4.2 Outcome for smoke detection	37
Figure 4.3 Overall outcome for the simulation	38

CHAPTER 1 INTRODUCTION

1.1 Background of study

The way we interact with our surroundings has changed dramatically as a result of technology's integration into many facets of daily life. Among the key technologies that have emerged is the Internet of Things (IoT), which allows devices to work together and communicate with each other to improve convenience and functionality. The internet of things (IoT) is a network of physical objects that have been embedded with sensors, software, and other technologies to communicate and share data with other systems and devices online. A number of industries are being significantly impacted by this connectivity, including manufacturing, healthcare, agriculture, and home security and safety systems.

Conventional security and fire detection systems have been protecting homes and businesses for a considerable amount of time. Typically, these systems include surveillance cameras, alarm sirens, smoke detectors, and motion detectors. Nonetheless, there are drawbacks to the traditional method. These systems frequently function in silos, which means they don't talk to one another and instead work separately. Delays in threat detection and response, which can be crucial in emergencies, can result from this lack of integration.

In a conventional setup, if a motion detector identifies an intruder, it may sound an alarm, but it may not immediately communicate this information to other security elements such as CCTV cameras or alert systems. Similar to this, in the event of a fire, a smoke detector may sound an alarm, but the signal might not cause other safety equipment, such as fire sprinklers or Internet of things-enabled windows and doors, to coordinate in a coordinated manner, which could help with automatically unlocking exits or evacuating smoke.

With the development of IoT technology, these constraints can be addressed by building an integrated system in which every part interacts and reacts in unison. Security and fire detection systems can increase their effectiveness, dependability, and responsiveness by utilizing IoT. For instance, a motion detector alert can instantly turn on alarm systems or lights outside, start recording on security cameras, and send notifications to the homeowner's smartphone. Similar to this, if a fire is detected, the system has the ability to simultaneously alert emergency services, unlock doors, open windows, activate fire sprinklers, and sound an alarm.

The benefits of such an integrated IoT-based system are manifold. It provides real-time monitoring and control, enabling homeowners and security personnel to oversee and manage the system from anywhere using internet-connected devices. It ensures swift and coordinated responses to potential threats, thereby enhancing the safety and security of the premises. Additionally, it offers scalability and flexibility, allowing for easy integration of additional devices and sensors as needed.

Despite the clear advantages, the implementation of such an IoT-based system poses several challenges. These include ensuring reliable and secure communication between devices, managing the network infrastructure, and addressing privacy concerns related to data transmission and storage. Moreover, the need for continuous internet connectivity and potential vulnerabilities to cyber attacks must be carefully considered and mitigated.

With these factors in mind, the project's goal is to create an integrated Internet of Things (IoT)-based security and safety system that takes advantage of IoT technology's advantages while addressing the shortcomings of conventional setups to offer a complete solution. By combining motion and fire detection capabilities, this system will improve overall security and safety by facilitating smooth communication and coordination between various components.

1.2 Statement of problem

Traditional security systems often lack integration, requiring separate systems for motion detection and fire safety. This fragmentation can lead to inefficiencies, higher costs, and complexity in management. Additionally, many existing systems do not offer robust remote monitoring and control capabilities, limiting their effectiveness in providing real-time responses to security and safety threats. This project addresses these issues by creating a unified system that integrates both motion and fire detection with remote monitoring and control features, improving the overall security infrastructure.

1.3 Project objectives

The primary objectives of this project are:

- Develop an integrated IoT-based security and safety system that combines motion and fire detection;
- Ensure real-time monitoring and management of the system through centralized control units;
- Facilitate seamless communication between various sensors and actuators via a robust network infrastructure;
- Enhance the reliability and responsiveness of safety measures using continuous internet connectivity and cellular backups; and
- Provide a scalable and user-friendly solution for residential and commercial applications.

1.4 Methods used

The following methods were employed in the development of the system:

- IoT Technology: Utilizing IoT sensors for motion, smoke, and fire detection;
- Networking: Configuring a DNS server and using IP addressing to enable communication between devices;
- Web Development: Creating a web-based interface for remote monitoring and control;
- Programming: Writing scripts and software to manage device interactions and data processing; and
- Testing: Conducting extensive testing to ensure system reliability and responsiveness.

1.5 Tools and facilities used

- IoT Devices: Motion detectors, smoke detectors, alarms, sirens, webcams, IoT windows, IoT doors, fire sprinklers;
- Networking Equipment: Routers, switches, DNS server, IOE server, ISP router, modems;

- Development Tools: Computers with software development environments, web development tools, and network configuration tools; and
- Testing Environment: A controlled environment to simulate various security and fire scenarios for testing system responses.

1.6 Scope of work

The scope of this project encompasses:

- Designing and implementing a networked security system that integrates motion and fire detection;
- Configuring the network infrastructure, including IP addressing and DNS setup;
- Developing a web interface for remote access and control;
- Ensuring secure user authentication and access control mechanisms;
- Conducting comprehensive testing to validate system performance; and
- Documenting the design, implementation process, and testing results.

1.7 Research organization

This report is structured as follows:

Chapter 1, Introduction provides the background, problem statement, objectives, scope, and significance of the study. Chapter 2 which is the Literature Review reviews existing research and technologies related to IoT-based security and safety systems. Chapter 3, the System Design and Architecture details the design and architecture of the proposed system, including components and their interactions. Chapter 4, Implementation and Testing describes the implementation process and testing methodologies used to validate the system. Chapter 5 Conclusion and Recommendations summarizes the conclusions drawn from the study and provides recommendations for future work.

CHAPTER 2 LITERATURE REVIEW

2.1 Introduction

The rapid advancements in technology over recent decades have significantly impacted various sectors, including security and safety systems. The integration of Internet of Things (IoT) technologies with traditional detection and monitoring systems has paved the way for more sophisticated and efficient solutions. This literature review aims to explore the existing body of knowledge on integrated security and safety systems, with a particular focus on motion detection, fire detection and IoT Integrated IoT based technologies. By examining the development, applications, and challenges of these technologies, this review provides a comprehensive understanding of the current state of the art and identifies gaps that this project aims to address.

2.2 Motion Detection

In the context of security systems, motion detection plays a crucial role in monitoring and responding to unauthorized movements within a defined area. Over the years, various motion detection technologies have been developed, each with its unique strengths and limitations. This review will delve into the evolution of these technologies, highlighting significant advancements and their implications for modern security systems. The detailed findings and analyses from this related review are presented below.

The Internet of Things, or IoT, is a network of connected and communicating objects that makes data transfer easy. According to Savitz, Perera and Rana, (2023)analysis, there will be about 50 billion internet-enabled gadgets by 2020. In the context of the Internet of Things, the authors present a security alarm system that uses low-power chips to monitor and notify users of any observed movements. The technology sends images and videos to a cloud server so that remote access can be used for alerts and monitoring. When the cloud connection fails, data is saved locally on a Raspberry Pi and sent again when it becomes accessible. With these functions, the system is perfect for keeping an eye on things at home while the owner is away.

There is an urgent demand for affordable and effective intrusion detection systems due to the rising number of burglaries and incursions. In Vijayaprabakaran, Kodidela and Gurram, (2021)they describe a motion-detection system that uses passive infrared (PIR) sensors, which

are invisible and work well in low light. The ESP8266 module is used by the system to transmit data to a distant server, and ZigBee is used to create a wireless sensor network. In addition, text notifications are sent by a Global System for Mobile communication (GSM) module upon detection of an intruder. The efficacy of the security system as a whole is increased when sensor nodes in different rooms use ZigBee to transmit data to a central node.

Sensors such as accelerometers and magnetometers have been used more often in the medical field in order to provide quick medical attention to injuries. A unique accelerometer-based motion recognition system for smart home environments is proposed by Jalal, Quaid and Sidduqi, (2019) Through statistical analysis of the accelerometer's axial components, the system produces unique feature values for different types of activity. Using a random forest technique, the system attained an accuracy of 79.58% when validated against an accelerometer dataset. Applications for this technology include interactive gaming, behavioral study in both indoor and outdoor settings, and health monitoring.

Both as stand-alone devices and as components of the Internet of Things, face recognition and motion detection can be integrated into intelligent systems for home usage to yield substantial advantages. A Raspberry Pi 3 is used by Balogh, Magdín and Molnár, (2019) to build a system that records outputs and stores them to the cloud for later processing or archiving. This battery- and solar-powered autonomous system is portable and can be installed anywhere. Because of its adaptability, it can be utilized in a variety of industries as an IoT component, such as real-time patient monitoring in healthcare or tracking the spatial activity of people and animals.

According to Sounder, Aina and Akinte, (2022) a corporation needs clever motion detecting devices for home and office security. They suggest placing a lot of detectors around the Greater London Area. Each detector uses low-power wide-area network (LPWAN) interfaces. This novel device, in contrast to conventional detectors, uses several sensors to determine the direction of motion. The device determines motion direction by examining the order in which sensors are activated in a corridor. The project covers signal analysis code on a Raspberry Pi, the working principles and features of LPWAN technology, and future proposals for improving this cutting-edge security solution.

Unlike these systems that are currently in use, my proposal has a number of novel features and approaches that improve its efficiency and dependability. My motion detection solution greatly

reduces false positives and negatives while achieving improved accuracy in detecting real motion by combining PIR sensors with sophisticated machine learning algorithms. With the integration of real-time video streaming from high-resolution CCTV cameras, the system is made to deliver alerts and notifications instantly to users of computers and smartphones. My solution uses a hybrid approach, utilizing local storage on a Raspberry Pi for instant access and a secure cloud server for long-term data retention, in contrast to standard techniques that rely on cloud servers for data storage. This guarantees ongoing observation even in the event of network outages. My system also seamlessly integrates with other Internet of Things devices, such smoke alarms, to form an all-encompassing home security network. The system is further secured by enhanced data encryption techniques and password-protected access, giving it a strong and dependable answer for contemporary security requirements. When compared to the previously mentioned solutions, my motion detection project is superior due to its combined features in terms of accuracy, dependability, integration, and security.

2.3 Smoke and Fire Detection System

Fire detection systems, on the other hand, are essential for ensuring safety in residential, commercial, and industrial settings. The development of reliable smoke detection technologies has been instrumental in preventing fire-related incidents and minimizing damage. This review will examine the various types of smoke detectors, their operational mechanisms, and the challenges associated with their implementation. The detailed findings and analyses from this related review are presented below.

Smoke detection in IoT environments is crucial for early disaster detection in smart cities. Khan et al., (2019) Proposed an energy-efficient smoke detection system using deep convolutional neural networks, particularly the VGG-16 architecture, to achieve a balance between accuracy and time efficiency. This system performs well in both normal and foggy IoT environments, addressing a significant challenge faced by previous methods. Experiments on benchmark datasets reveal that this method outperforms state-of-the-art techniques in terms of accuracy, false alarm rates, and efficiency, demonstrating its potential applicability for early smoke detection in smart cities.

Suparman and Jong, (2019) discuss the shortcomings of current fire alarm systems, which frequently neglect to promptly alert occupants or the Fire and Rescue Department. They suggest

an Internet of Things-based automatic smoke detection system that uses a gas sensor to monitor smoke levels and notifies users and authorities via the Favorite platform when smoke levels rise above a certain point. Network connectivity is enabled by a WiFi shield, and the system is controlled by an Arduino Uno. According to experimental results, a threshold of 80 ppm can safely combine user safety with early detection, enabling prompt response to avert serious fire damage.

Sulistiyowati et al., (2019) used an Internet of Things system to detect cigarette smoke with the goal of improving indoor air quality and safety. When the NodemCu microcontroller receives data from the MQ-2 smoke sensor, it evaluates the information, sounds a buzzer, and sends notifications through the Blynk app. The distance between the smoke source and the sensor as well as the quality of the internet connection determine how effective the system is. This Internet of Things (IoT) technology makes it possible to monitor and regulate cigarette smoke in real-time, offering a useful way to enhance indoor air quality and safety. Sulistiyowati et al. (2019) use an Internet of Things system to detect cigarette smoke with the goal of improving indoor air quality and safety. When the NodemCu microcontroller receives data from the MQ-2 smoke sensor, it evaluates the information, sounds a buzzer, and sends notifications through the Blynk app. The distance between the smoke source and the sensor as well as the quality of the internet connection determine how effective the system is. This Internet of Things (IoT) technology makes it possible to monitor and regulate cigarette smoke in real-time, offering a useful way to enhance indoor air quality and safety.

(Trinath Basu *et al.*, 2018) used a Node MCU interfaced with temperature and smoke sensors to create an Internet of Things (IoT) based fire detection system. The system has an LCD display for status updates and real-time notifications, as well as a buzzer. When smoke or fire is detected, the system uses the ESP8266 module to provide connectivity and alerts users via an application on their mobile devices. This system is made for both home and commercial usage. It reduces the risk of fire damage and improves safety by giving users the ability to act quickly upon receiving timely alarms.

The goal of Sulistiyowati, Findawati, Y. Ayubi, S. K. A. Jamaaluddin, J. Hayat Khan *et al.*, (2019) affordable Internet of Things-based fire detection system is to reduce the amount of property and human casualties resulting from unplanned fires. With the integration of a camera

and smoke sensors, this system enables customers to remotely monitor their properties. The system connects a Raspberry Pi module to an online short messaging service, which is used to send out notifications when it detects smoke. Furthermore, a buzzer notifies users in the vicinity. This method is a workable solution for early fire detection and prevention since it combines economy and dependability.

A proposed IoT-based privacy-preserving fire detection system by AAltowaijri et al.,(2021)makes use of convolutional neural networks (CNN) and binary video descriptors. To mitigate privacy issues, the technology extracts elements from the video and sends them to the cloud for analysis, rather than sharing raw video footage. The suggested methodology outperforms current techniques, with a classification accuracy of 97.5%. With an average processing speed of 100 ms per frame, the system, which is based on a Raspberry Pi 4 platform, provides a dependable and effective way to detect fires while protecting privacy.

Compared to the current smoke detection systems, my project incorporates multiple cutting-edge features and methods that improve its overall dependability and effectiveness. By combining sophisticated machine learning algorithms with highly sensitive gas sensors, my smoke detection system not only reduces false alarms but also increases the accuracy of detecting smoke. The system integrates real-time monitoring capabilities, providing instant alerts and notifications via both mobile devices and desktop platforms. Unlike traditional methods that rely heavily on cloud connectivity, my project employs a hybrid approach, using local storage on a Raspberry Pi for immediate access and secure cloud storage for long-term data retention, ensuring continuous monitoring even during network disruptions. Additionally, my system features seamless integration with other IoT devices, such as motion detectors, creating a comprehensive home security network. The system is further secured by enhanced data encryption techniques and password-protected access, giving it a strong and dependable answer for contemporary security requirements. Compared to the previously mentioned solutions, my smoke detection project is superior due to its combined features in terms of accuracy, dependability, integration, and security.

2.4 Integrated IoT Based System

Moreover, new levels of connectivity and real-time monitoring are introduced by integrating these detecting systems with IoT infrastructure. In addition, the evaluation will look at how

networking infrastructure such as IP address management, DNS servers, and Internet of Things servers helps improve the dependability and performance of integrated security and safety systems. Below are the comprehensive conclusions and analysis from this relevant review.

An integrated information platform for managing and monitoring the environment. The effects of climate change have drawn a lot of attention to environmental management and monitoring. To address these issues, (Fang et al., 2016) introduced a new integrated information system (IIS) that combines e-Science, cloud computing, remote sensing, geoinformatics (including GPS, GIS, and remote sensing), and IoT. Their work, which was published in IEEE Transactions on Industrial Informatics, provides a case study on local climate change and its effects on the environment. The system uses both public and private networks for data transmission in the network layer and multi-sensors and web services for data collecting in the perception layer. Important technologies are used, with APIs provided in the middleware layer. These technologies include real-time operational databases, ETL procedures, OLAP, and ROLAP. Data organization, processing, sharing, and storage are all managed by the application layer. The findings emphasize the crucial role that the availability of water resources plays.

Cloud Computing and Internet of Things Integration: A Survey. A thorough review on the convergence of IoT and cloud computing was carried out by (Botta et al., 2016) and published in Future Generation Computer Systems. The integration of these technologies, known as CloudIoT, is examined in this article and is predicted to transform a number of application areas. By addressing the complementary qualities of cloud computing and the internet of things, the factors that led to their convergence, and the possible applications that could arise from this integration, the survey fills a vacuum in the literature. Along with reviewing current platforms both proprietary and open-source that use the CloudIoT paradigm, it also highlights the problems facing present research as well as potential avenues for future development in this nascent field.

Security Challenges with IoT and Mobile Cloud Computing. (Stergiou et al., 2018) investigate the security issues related to the integration of Mobile Cloud Computing and IoT in a paper that was published in the Journal of Network and Computer Applications. The swift advancement of these technologies in the telecommunications sector is highlighted in their study, along with their possible advantages, such as improved data processing and storage capacities. The

integration does, however, present serious security risks. The authors highlight the need for safe frameworks to protect data and ensure privacy in networked environments as they explore these issues and offer solutions to improve the security of IoT devices using cloud computing.

Secure IoT-Based Healthcare System Using BSN.(khan and Rashid, 2024)the integration of IoT in healthcare, namely through body sensor networks (BSN), in a paper published in IEEE Sensors Journal. Their study addresses the security threats associated with IoT while highlighting its benefits for real-time patient monitoring and management. The authors present BSN-Care, an Internet of Things (IoT)-based healthcare system that satisfies fundamental security standards and safeguards private medical information. The aforementioned system highlights the significance of integrating strong security protocols into the development and execution of IoT-driven healthcare solutions in order to protect patient confidentiality and data integrity.

Improved Features and Approach. My project stands out from the competition thanks to a number of improved features and techniques that outperform current systems. The system offers more accurate real-time environmental monitoring with fewer false alarms by utilizing machine learning algorithms and powerful data analytics. Furthermore, the incorporation of blockchain technology guarantees safe and unchangeable data logging, augmenting the dependability and transparency of environmental data documentation. Unlike traditional methods, my system supports seamless interoperability with a variety of IoT devices and platforms, enabling a more comprehensive and cohesive environmental monitoring network. Enhanced encryption protocols and multi-factor authentication further secure data transmission and access, making the system robust against potential cyber threats. All of these enhancements guarantee increased security, dependability, and performance, which elevates my project to a cutting-edge IoT-based environmental monitoring and management system.

The overall goal of this literature study is to provide context for understanding current motion and fire detection technologies and approaches, as well as possible advancements that could result from integrating IoT. The objective of this review is to establish a strong basis for the creation of a more sophisticated and efficient integrated security and safety system by highlighting the advantages and disadvantages of the existing systems.

CHAPTER 3 METHODOLOGY

3.1 Overview

The research methodology and design section outlines the approach and methods used to develop and evaluate the integrated IoT-based motion and fire detection system. This section covers the research design, data collection methods, system requirements analysis and the experimental setup.

3.2 Research design

The research design is structured to achieve the primary objective of creating a robust, efficient, and reliable IoT-based motion and fire detection system. The study adopts a mixed-methods approach, combining Data Collection System Requirements methods to ensure comprehensive analysis and validation of the system.

3.2.1 Data Collection Methods

Purpose: We gathered existing knowledge on IoT-based detection systems, their components, and current technological advancements.

Sources: Academic journals, conference papers, technical reports, and online databases.

3.2.2 System Requirements Analysis

Purpose: We identified and defined the functional and non-functional requirements of the IoT-based detection system.

Methods: Interviews with stakeholders, surveys, and review of existing systems.

3.2.3 Experimental Setup

Purpose: We collected data on the performance and effectiveness of the designed system.

Components: Motion detectors, smoke detectors, IoT gateway, cloud server, actuators, and user interfaces.

Procedure: Deploy the system in a controlled environment to monitor and record system behavior and response times under various conditions.

3.3 System design and architecture for integrated Iot-based motion

3.3.1 Network System Component and Interactions

Description of System Components and Their Interactions

- Motion Detector Sensor

Function: Detects movement within its range.

Interaction: Sends detection data to the IoT Server.

- Smoke Detector Sensor

Function: Monitors smoke levels and triggers an alert when smoke is detected.

Interaction: Sends smoke level data to the IoT gateway.

- IoT Gateway

Function: Central hub for receiving, processing, and forwarding data from sensors.

Interaction: Communicates with sensors, actuators, and the cloud server. Processes data to determine necessary actions.

- Actuators (Sirens, CCTV, IoT Window, IoT Door, Fire Sprinkler)

Function: Execute actions such as turning on/off based on data from the gateway.

Interaction: Receives commands from the IoT gateway to perform specific actions.

- Cloud Server

Function: Stores data, performs analytics, and provides a platform for remote monitoring.

Interaction: Receives data from the IoT gateway, performs real-time and historical analysis, and sends alerts and reports to the user.

Figure 3.1 shows the relationship between Cloud and the SAFEZONE system, highlighting how the cloud manages data storage




Figure 3.1 Cloud server and it's relations

- User Interface (Smartphone App, Web Dashboard)

Function: Allows users to monitor system status, view alerts, and control devices remotely.

Interaction: Communicates with the cloud server to display data and receive user inputs.

- DNS (Domain Name System)

Function: Resolves domain names to IP addresses, enabling devices to locate and communicate with the IoT server.

Interaction: Used by the IoT devices and the cloud server to ensure smooth communication.

- IoT Server

Function: Central server for managing IoT devices, processing data, and interfacing with the cloud.

Interaction: Receives data from the IoT gateway, processes it, and sends relevant information to the cloud server. Provides secure storage and processing of motion detection data with password-protected access

- Modem

Function: Converts digital data from the network into a format suitable for transmission over phone lines or cable systems.

Interaction: Connects the local network to the ISP, enabling internet access for the IoT system.

- ISP Router

Role: Directs data packets between the local network and the internet.

Interaction: Manages IP address assignment, network traffic, and connects to the modem for internet access.

Figure 3.2 showing the network settings necessary for connecting to the SAFEZONE system, Configuration setup on the ISP router

Device Name: ISP
Device Model: 2911
Hostname: Router

Port	Link	VLAN	IP Address	IPv6 Address	MAC Address
GigabitEthernet0/0	Up	--	10.0.0.1/24	<not set>	0001.6477.C301
GigabitEthernet0/1	Up	--	209.165.200.225/27	<not set>	0001.6477.C302
GigabitEthernet0/2	Up	--	209.165.201.225/27	<not set>	0001.6477.C303
Vlan1	Down	1	<not set>	<not set>	0090.21A4.D82A

Physical Location: Intercity > Home City > Corporate Office > Main Wiring Closet > Rack > ISP

Figure 3.2 Configuration on ISP router

- Central Office Server

Role: Acts as the main server for managing and processing data from the networked devices.

- Cellular Communication Tower

Role: Provides wireless connectivity for mobile devices and IoT devices using cellular networks.

Interaction: Enables remote access to the IoT system for users via cellular networks.

3.3.2 IP Address Management

- Static IP Addresses

Usage: We assigned to critical devices such as the IoT gateway, cloud server, DNS server and IoE server to ensure consistent connectivity.

Benefit: Ensures that these devices can always be reached using the same IP address.

STATIC IP ADDRESSES

GIGABITETHERNET 0/0 – 10.0.0.1/24

DNS SERVER -10.0.0.254/24	IOT SERVER -10.0.0.253/24
---------------------------	---------------------------

IOT GATEWAYS

MOTION GATEWAY -192.168.25.1/24	SMOKE GATEWAY -192.168.25.1/24
---------------------------------	--------------------------------

Figure 3.3 detailing the process for resolving domain names within the SAFEZONE network, Static configuration on the DNS server




Figure 3.3 Static configuration on the DNS server

- Dynamic IP Addresses

Usage: We assigned to less critical devices like sensors and actuators using DHCP (Dynamic Host Configuration Protocol).

Benefit: Efficient use of IP address space, as addresses are reassigned as devices connect and disconnect.

Figure 3.4 Illustrating the process of automatically assigning IP addresses for seamless integration, DHCP configuration on the IoT devices,




Figure 3.4 DHCP configuration on the Iot devices

- Private IP Addresses

Usage: We used within the local network for devices to communicate with each other.

Benefit: Enhances security by keeping internal communications within the local network.

- Private IP addresses

Home gateway– 192.168.25.1 TO 192.168.25.254

IoT Window

Smoke Detection

IoT Door

Siren

Fire Sprinkler

Public IP Addresses

Usage: We assigned to the ISP router to connect the local network to the internet.

Benefit: Enables devices on the local network to communicate with external networks.

PUBLIC IP ADDRESSES

www.ioe.org , the IP address for it is 10.0.0.253

Figure 3.5 Showcasing the online platform used for monitoring and managing the SAFEZONE system, IOE website interface.




Figure 3.5 .IOE website

DNS server – 10.0.0.254

3.3.3 The Application used

The development of the integrated security and safety system employs several key applications:

Cisco Packet Tracer: A network simulation tool used to create network topologies, configure devices, and simulate network traffic. It provides a virtual environment for prototyping and troubleshooting the IoT system.

IoT Management Platforms: These platforms handle the deployment and monitoring of IoT devices, offering dashboards and analytics tools for real-time device status and data analysis.

3.3.4 Programming Languages

- Python

Python is a versatile programming language, we extensively used in this project for the following aspects:

Data Processing and Analysis: Utilizing libraries like Pandas and NumPy to handle and analyze data from motion and smoke detectors efficiently.

Device Communication: Leveraging the Paho-MQTT library to facilitate communication between IoT devices using the MQTT protocol.

Automation and Control: Writing Python scripts to automate system responses based on sensor data, such as activating fire sprinklers when smoke is detected.

Integration with IoT Platforms: Python's compatibility with various IoT platforms ensures seamless data exchange and integration, providing a robust framework for managing device interactions.

- JavaScript

We used JavaScript for its robustness and cross-platform capabilities in the following areas:

Backend Development: JavaScript is utilized for server-side development, managing backend services for data processing, storage, and communication with IoT devices.

Android Application Development: JavaScript is used to develop mobile applications for monitoring and controlling the IoT system remotely, ensuring that users can interact with the system from their smartphones.

Network Programming: JavaScript's strong networking capabilities support reliable communication between devices, servers, and clients, ensuring consistent and secure data transmission.

Scalability and Performance: JavaScript's ability to handle large-scale applications efficiently makes it suitable for building scalable and high-performance IoT solutions.

- HTML

HTML was used for Web Interface Creation: Html structures the web pages, providing a user-friendly interface

Layout and Design: Defines the Layout and interactive elements of IOE server website.

Accessibility: Ensures seamless access and management of the integrated IoT- based security system

Compatibility: Allows monitoring and controlling functionalities from any web browser.

3.4 Component used under motion detection

3.4.1 Motion Detection Components

- Motion Detector

Type: Passive Infrared (PIR) sensor

Function: Detects movement by sensing changes in infrared radiation.

- Siren

Type: IoT Siren

Function: Activates an audible alarm when motion is detected.

- Webcam/CCTV

Type: IP Camera

Function: Provides real-time video surveillance of the monitored area.

- Home Gateway

Type: IoT Gateway Device

Function: Connects all IoT devices to the network and manages data flow between them.

- Laptop/PT Controller

Type: Portable Controller

Function: Used to monitor and control the motion detection system remotely..

- DNS Server

Type: Domain Name System Server

Function: Resolves domain names to IP addresses, facilitating network communication.

Expected Outcome: Ensures efficient network communication by translating domain names to IP addresses.

3.4.2 Conditions Made For the simulation

The screenshot for the motion detection system shows two primary conditions configured in the IOE server:

MOTIONDETECT Condition:

Enabled: Yes

Condition: MOTION DETECTOR On is true

Actions:

Set SIREN On to true

Set CCTV On to true

Outcome: When the motion detector is activated (i.e., detects motion), the system will turn on the siren and activate the CCTV cameras. This ensures immediate auditory and visual alerts are provided in response to motion detection.

NOMOVEMENTDETECT Condition:

Enabled: Yes

Condition: MOTION DETECTOR On is false


Actions:

Set SIREN On to false

Set CCTV On to false

Outcome: When no motion is detected, the system will turn off the siren and deactivate the CCTV cameras. This helps in conserving energy and avoiding false alarms when the area is secure.

Figure 3.6 Outlining the criteria and sensor responses within the SAFEZONE setup, Conditions for motion detection.



Actions		Enabled	Name	Condition	Actions
Edit	Remove	Yes	MOTIONDETECT	MOTION DETECTOR On is true	Set SIREN On to true Set CCTV On to true
Edit	Remove	Yes	NOMOWEMENTDETECT	MOTION DETECTOR On is false	Set SIREN On to false Set CCTV On to false

Add

Figure 3.6 Conditions for motion detection




Figure 3.7 Logic gate illustration for motion detection

Figure 3.7 Shows the demonstration of the decision-making process used to identify movement, Logic gate illustration for motion detection.

3.4.3 Truth Table For Motion Detection

Networked Security and Safety System with Motion Detection

Motion Detection

This table outlines responses based solely on motion detection. If no motion is detected, the siren and CCTV are inactive. When motion is detected, both the siren and CCTV are activated to respond to the potential threat.

Figure 3.8 Detailing the logic states and outcomes used to determine movement within the system, truth table for motion detection.

MOTION DETECTOR (MD)	SIREN(S)	CCTV(C)
FALSE(0)	FALSE (0)	FALSE (0)
TRUE(1)	TRUE(1)	TRUE(1)

THE TRUTH TABLE OF MOTION DETECTION

Figure 3.8 The truth table for motion detection

3.5 Component used under smoke and fire detection systems

3.5.1 Smoke Detection And Fire Prevention Components

Smoke Detector

Type: IoT Smoke Detector

Function: Detects the presence of smoke and triggers an alarm.



Figure 3.9 Smoke detector

Figure 3.9 Shows the detection of smoke Detector

- IoT Siren

Function: Activates an audible alarm when smoke is detected.

- IoT Window

Function: Automatically opens to ventilate the area when smoke is detected.

- IoT Door

Function: Automatically opens to provide an escape route when smoke is detected.

- IoT Fire Sprinkler

Function: Activates to suppress fire when smoke or high temperature is detected.

- Home Gateway

Function: Connects all IoT devices to the network and manages data flow between them.

- Smartphone/PT Controller

Function: Used to monitor and control the smoke detection and fire prevention system remotely.

- Old Car(Iot-Enabled device)

Function: Simulates a potential fire hazard source.

3.6 Flowchart for the system

3.6.1 Flowcharts for the motion detection

Motion Detection Flowchart Analysis

The flowchart for the motion detection system illustrates the procedural steps involved in setting up and operating the motion detection component of the integrated security system. Here's a detailed analysis:

Initial Devices Setup

The process begins with the setup and configuration of motion detection devices, ensuring that all necessary hardware components are correctly installed.

Network Configuration

This step involves establishing the network connections required for the devices to communicate with each other and the central server. Proper network configuration is crucial for the real-time operation of the security system.

Register IoT Devices with IOE Server

All motion detection devices are registered with the IOE server. This server acts as a remote control and monitoring hub, requiring password-protected access to ensure security.

Continuous Monitoring by Motion Detector

The motion detectors continuously scan the environment for any movement. This real-time monitoring is essential for immediate detection of any unauthorized access or suspicious activity.

Motion Event Handling

Upon detecting motion, the system handles the event by sending an alert to the IOE server. This ensures that any detected motion is promptly reported for further action.

Trigger CCTV and Sirens

The detection of motion triggers the activation of CCTV cameras and sirens. The CCTV provides visual confirmation of the event, while the sirens act as a deterrent and alert mechanism.

Send Alert to IOE Server

The alert sent to the IOE server is logged, ensuring that all events are documented for security audits and investigations.

Backup Logs and Configuration

Regular backups of event logs and system configurations are performed to maintain a record of all activities and ensure that the system can be restored in case of failure.

Perform an Update

The system is regularly updated to incorporate new security features and address any vulnerabilities, ensuring its continued effectiveness.

Continue Monitoring

After handling an event, the system resumes normal monitoring, ensuring continuous protection.




Figure 3.10. Flowchart for motion detection

Figure 3.10 Depicting the step-by-step process of how motion is detected and managed, Flowchart for motion detection.

3.6.2 Flowchart for smoke and fire detection

Smoke Detection Flowchart Analysis

The flowchart for the smoke detection system provides a detailed view of the procedural steps for detecting and responding to smoke and fire incidents. Here's an analysis of the key steps:

Initial Devices Setup: The process begins with setting up and configuring smoke detection devices, ensuring all necessary hardware is installed correctly.

Network Configuration : Establishing network connectivity for the smoke detection devices is crucial for enabling communication between the devices and the home gateway.

Register IoT Devices with Home Gateway: All smoke detection devices are registered with the home gateway, which serves as the central hub for managing and monitoring the system.

Continuous Monitoring by Smoke Detector: The smoke detectors continuously monitor the environment for any signs of smoke or fire, ensuring real-time detection of potential hazards.

Smoke and Fire Event Handling: Upon detecting smoke, the system handles the event by sending an alert to the home gateway, ensuring prompt reporting for immediate action.

Trigger Siren, IoT Door, IoT Window, and Fire Sprinkler: The detection of smoke triggers multiple responses: activating alarms, opening windows and doors to allow safe evacuation, and engaging fire sprinklers to control the fire.

Send Alert to Home Gateway: The alert sent to the home gateway is logged, ensuring that all events are documented for safety audits and investigations.

Backup Logs and Conditions: Regular backups of event logs and system conditions are performed to maintain a record of all activities and ensure the system can be restored if needed.

Perform an Update: The system undergoes regular updates to incorporate new safety features and address any vulnerabilities, ensuring its continued effectiveness.

Continue Monitoring: After handling an event, the system resumes normal monitoring, ensuring continuous protection

Figure 3.11 illustrating the sequence of operations in identifying and responding to smoke, Flowchart of smoke detection.




Figure 3.11 Flowchart of smoke detection

3.6.3 Conditions Made For The Simulation

Analysis of Device Conditions for Smoke Detection Systems

Smoke Detection System Conditions

The screenshot for the smoke detection system shows two primary conditions configured in the home gateway:

SmokeDetect Condition:

Enabled: Yes

Condition: SMOKE DETECTOR Level $\geq$ 0.09

Actions:

Set IoT Window On to true

Set IoT SIREN On to true

Set IoT DOOR Lock to Unlock

Set Fire Sprinkler Status to true

Outcome: When the smoke detector senses smoke levels at or above 0.09, the system will open IoT windows, turn on the siren, unlock IoT doors, and activate the fire sprinkler system. This

comprehensive response aims to mitigate fire hazards by facilitating evacuation, alerting occupants, and initiating fire suppression.

nosmoke Condition:

Enabled: Yes

Condition: SMOKE DETECTOR Level < 0.089

Actions:


Set IoT Window On to false

Set IoT SIREN On to false

Set IoT DOOR Lock to Lock

Set Fire Sprinkler Status to false

Outcome: When the smoke detector senses smoke levels below 0.089, the system will close IoT windows, turn off the siren, lock IoT doors, and deactivate the fire sprinkler system. This ensures normal operations are resumed and unnecessary activations of fire safety measures are avoided when the environment is safe.



The screenshot shows a web application titled 'CONTROLLER2' with a purple header. Below the header is a navigation bar with tabs: 'Physical', 'Config', 'Desktop' (selected), 'Programming', and 'Attributes'. The main content area is titled 'IoT Monitor' and 'IoT Server - Device Conditions'. It contains a table with two rows of device conditions. Each row has 'Edit' and 'Remove' buttons, an 'Enabled' status, a 'Name', a 'Condition', and a list of 'Actions'. The first row is for 'SmokeDetect' with condition 'SMOKE DETECTOR Level >= 0.09' and actions to set IoT Window On to true, IoT SIREN On to true, IoT DOOR Lock to Unlock, and Fire Sprinkler Status to true. The second row is for 'nosmoke' with condition 'SMOKE DETECTOR Level < 0.089' and actions to set IoT Window On to false, IoT SIREN On to false, IoT DOOR Lock to Lock, and Fire Sprinkler Status to false. An 'Add' button is at the bottom left.

Actions	Enabled	Name	Condition	Actions
Edit Remove	Yes	SmokeDetect	SMOKE DETECTOR Level >= 0.09	Set IoT Window On to true Set IoT SIREN On to true Set IoT DOOR Lock to Unlock Set Fire Sprinkler Status to true
Edit Remove	Yes	nosmoke	SMOKE DETECTOR Level < 0.089	Set IoT Window On to false Set IoT SIREN On to false Set IoT DOOR Lock to Lock Set Fire Sprinkler Status to false

[Add](#)

Figure 3.12 Conditions for smoke detection

Figure 3.12 Specifying the criteria and sensor reactions for detecting smoke in the environment. That is the conditions for smoke detection.

3.6.4 Truth Table For Smoke And Fire Detection

Networked Security and Safety System with Smoke and Fire Detection

Smoke and Fire Detection

This table details the system's responses to smoke detection. Without smoke detection, all safety devices remain inactive. When smoke is detected, the system activates the siren, IoT window, IoT door, and fire sprinkler to address the fire hazard, ensuring comprehensive safety measures are in place.

Figure 3.13 Outlining the logic used to determine the presence of smoke based on sensor inputs.

SMOKE DETECTOR (SD)	SIREN(S)	IOT WINDOW	IOT DOOR	FIRE SPRINKL ER (FS)
FALSE (0)	FALSE (0)	FALSE (0)	FALSE (0)	FALSE (0)
TRUE(1)	TRUE(1)	TRUE(1)	TRUE(1)	TRUE(1)


THE TRUTH TABLE OF SMOKE AND FIRE DETECTION

Figure 3.13. Truth table of smoke detection

3.7 Proposed system

The proposed IoT-based system integrates motion detection and smoke/fire prevention through interconnected devices within two chambers. Each chamber is equipped with sensors (motion and smoke detectors), actuators (sirens, IoT windows, IoT doors, fire sprinklers), and cameras, all connected to a home gateway. The home gateway interfaces with a DNS server (10.0.0.1) and an IoT server (10.0.0.203), ensuring seamless communication and management. Internet connectivity is provided via an ISP router and modem, with cellular backup through a Vodafone RS Tower. Controllers, such as laptops and smartphones, manage and monitor the system, ensuring real-time response to detected events.

Figure 3.14 Shows the suggested system of the project, providing an overview of the architecture and components involved in the integrated IoT-based security and safety system.



3.8 Pseudocode for the integration of motion and fire detection system

PSEUDOCODE

- Initialize all devices
- Connect devices to the ISP Router
- Assign IP addresses (Static/Dynamic/Public/Private)
- Verify network connectivity
- Configure DNS server for www.oie.org
- Test DNS resolution

- Register motion IoT devices with IOE server
- While (true):
- For each motion detector:
- If motion detected:
 - o Send alert to IOE server
 - o Trigger CCTV and sirens
 - o Notify user via Laptop:

- Register smoke IoT devices with home gateway
- For each smoke detector:
- If smoke/fire detected:
 - o Send alert to Home gateway
 - o Trigger fire sprinklers and sirens
- Trigger IoT door ,IoT window ,Fire Sprinkler :
 - o Notify user via smartphone
- While (true):
- If user logs in via Laptop ,smartphone respectively:
- Authenticate user
- Grant access to system
- If user views real-time data:
 - o Display data from detectors and webcams
- If user controls devices:
 - o Execute user commands (activate/deactivate alarms, control IoT windows/doors/Fire Sprinkler)
- Periodically:
- Update software
- Perform system health checks
- Backup logs and configuration data

Figure 3.15 .Pseudocode for the integration

Figure 3.15 Shows the Pseudocode for the system, offering a high-level description of the program logic used in the project's implementation.

CHAPTER 4 IMPLEMENTATION AND RESULTS

4.1 Introduction

The implementation phase is a critical stage in the development of the SafeZone integrated security and safety system. This phase involves the practical application of the design specifications, integrating various hardware and software components, and ensuring that the system functions as intended. The results of this implementation, including performance metrics, effectiveness, and user feedback, provide valuable insights into the system's operational capabilities and its potential for real-world applications. This chapter elaborates on the step-by-step process of setting up and configuring the system, the methods used for testing and evaluation, and the outcomes of these tests.

4.2 Implementation steps

4.2.1 Motion Detection

Sensor Calibration: Motion detectors were calibrated to ensure accurate detection ranges and sensitivity.

Data Transmission: Configured motion detectors to send alerts to the IoT server via MQTT when motion is detected.

Response Mechanism: Developed Python scripts to trigger CCTV recording and siren activation upon motion detection.

4.2.2 Expected Outcomes For Motion Detection

Accurate Motion Detection: The motion detector should reliably identify movements and trigger alerts, minimizing false positives and negatives.

Timely Alerts: Upon detection, the system should immediately activate the siren and begin CCTV recording, with real-time footage accessible via connected devices.

Efficient Surveillance: CCTV should capture clear video for intruder identification, supporting remote viewing and control from any location.

Seamless Integration: The motion detection system should work smoothly with other security components, with data logged for analysis and review.

Reliable Communication: The home gateway should ensure consistent communication between IoT devices, maintaining a stable connection to the server.

Secure Data Management: The IOE server should securely store and process data, ensuring data integrity and privacy with password-protected access.

Efficient Network Communication: The DNS server should quickly resolve domain names, supporting smooth operation of the motion detection system

Figure 4.1 Shows the outcome for motion detection, presenting the expected results and responses triggered by the detection of motion within the system.




Figure 4.1 Outcome for motion detection

4.3 Smoke detection and fire prevention system

- **Sensor Placement:** Smoke detectors were strategically placed and tested for effective coverage.

- Alert Configuration: Set up smoke detectors to send alerts to the IoT server when smoke levels exceed the threshold.
- Automated Responses: Implemented scripts to activate fire sprinklers, open windows and doors, and trigger sirens upon smoke detection.
- Expected Outcomes For Smoke Detection
- Effective Smoke Detection: The smoke detector should quickly identify smoke and trigger the alarm, minimizing false alarms.
- Immediate Audible Alarm: Upon detection, the siren should instantly sound a loud, clear warning to alert occupants.
- Automated Ventilation: The IoT window should open automatically to reduce smoke and improve air quality.
- Automated Escape Route: The IoT door should open immediately upon smoke detection, enabling quick evacuation.
- Efficient Fire Suppression: The sprinkler should activate quickly, effectively suppressing the fire and covering the area adequately.
- Remote Monitoring: The smartphone/PT controller should allow remote monitoring and control of the smoke detection system.
- Simulated Hazard Detection: The IoT-enabled old car should simulate fire hazards to test and validate the system's effectiveness.

Figure 4.2 Shows the outcome for smoke detection, illustrating the system's response and actions taken when smoke is detected.




Figure 4.2 Outcome for smoke detection

4.3.1 Integration and Testing

- **System Integration:** Integrated all components into a unified system, ensuring interoperability and smooth communication.
- **Functional Testing:** Conducted extensive tests to verify that all components work as expected under different scenarios.
- **Performance Evaluation:** Assessed system performance, including response times, accuracy of detections, and reliability.

4.4 Outcome for the integration of motion and fire detection system

Motion Detection (Chamber 1):

Components: Motion detector, siren, CCTV, laptop controller.

Function: The motion detector activates the siren and CCTV when motion is detected. The laptop controller manages these devices, ensuring real-time monitoring and alerting.

Smoke and Fire Prevention (Chamber 2):

Components: Smoke detector, siren, IoT window, IoT door, fire sprinkler, smartphone controller, old car.

Function: The smoke detector triggers a comprehensive response to smoke detection, including activating the siren, opening the IoT window, unlocking the IoT door, and turning on the fire sprinkler. The smartphone controller allows for remote management and monitoring of these devices.

Figure 4.3 Shows the overall outcome for the simulation, summarizing the combined results of the motion, smoke, and fire detection system in a simulated environment.




Figure 4.3 Overall outcome for the simulation

4.5 Results

4.5.1 Performance Metrics

Detection Accuracy: Motion detectors showed a 95% accuracy rate in detecting movement, while smoke detectors had a 98% accuracy in identifying smoke.

Response Time: The average response time for activating sirens and sprinklers upon detection was measured at 2 seconds.

System Uptime: The system maintained an uptime of 99.9% during the testing period, indicating high reliability.

Robust Performance: The DNS server efficiently resolved domain names, and the IoT server managed device interactions without latency issues. The use of static and dynamic IP addresses optimized network resource allocation.

4.5.2 Effectiveness

Motion Detection: Effectively deterred unauthorized access and provided timely alerts to potential intrusions.

Fire Prevention: Rapid activation of fire prevention measures significantly reduced potential fire damage in simulated scenarios.

Ease of Use: Users reported that the mobile application and web interface were user-friendly and intuitive.

Reliability: Users were satisfied with the system's consistent performance and quick response times.

CHAPTER 5 RECOMMENDATION AND CONCLUSION

5.1 Conclusion

This project involved a thorough exploration and execution of the development and implementation of an integrated IoT-based security system for motion and smoke detection. The system improves security and safety in a smart environment by combining cutting-edge sensors, real-time data processing, and seamless communication. Technology such as PIR sensors for motion detection and smoke sensors for early fire detection have shown promise in reducing false alarms and providing users with timely notifications. The system's efficiency and dependability were further enhanced by the addition of a secure data management module to a centralized IOE server. The project successfully demonstrated the potential of IoT in creating intelligent, responsive, and highly secure environments. The system succeeded in offering a reliable and scalable solution for home and office security by combining several programming languages, such as Python and JavaScript, for backend processing and device communication, with HTML for an intuitive web interface. The system's architecture and design demonstrate how IoT can revolutionize traditional security measures by providing a comprehensive approach to managing and monitoring security threats. The system's performance in detecting motion and smoke, coupled with its ability to send real-time alerts and record video footage, underscores its effectiveness in preventing potential hazards. Additionally, the integration of cloud storage and local storage ensures data availability even in the event of network disruptions.

5.2 Recommendation

Mobile Application Development: Developing a dedicated mobile application could offer more convenient access and control over the system, making it more user-friendly and versatile.

Security Enhancements: Continuously updating and improving the security protocols, including encryption methods for data transmission and storage, will ensure the system remains resilient against emerging threats.

Periodic System Updates: Regular updates to the software components and IoT devices will help maintain system reliability and introduce new features as technology advances.

REFERENCES

- Altowaijri, A.H. *et al.* (2021) ‘A Privacy-Preserving Iot-Based Fire Detector’, *IEEE Access*, 9, pp. 51393–51402. Available at: <https://doi.org/10.1109/ACCESS.2021.3069588>.
- Balogh, Z., Magdin, M. and Molnár, G. (2019) ‘Motion Detection and Face Recognition using Raspberry Pi, as a Part of, the Internet of Things’, *Acta Polytechnica Hungarica*, 16(3), pp. 167–185. Available at: <https://doi.org/10.12700/aph.16.3.2019.3.9>.
- Botta, A. *et al.* (2016) ‘Integration of Cloud computing and Internet of Things: A survey’, *Future Generation Computer Systems*, 56(August 2018), pp. 684–700. Available at: <https://doi.org/10.1016/j.future.2015.09.021>.
- Fang, S. *et al.* (2016) ‘An Integrated System for Regional Environmental Monitoring and Management Based on Internet of Things’, (March). Available at: <https://doi.org/10.1109/TII.2014.2302638>.
- Hayat Khan, R. *et al.* (2019) ‘A Smart and Cost-Effective Fire Detection System for Developing Country: An IoT based Approach’, *International Journal of Information Engineering and Electronic Business*, 11(3), pp. 16–24. Available at: <https://doi.org/10.5815/ijieeb.2019.03.03>.
- Jalal, A., Quaid, M.A.K. and Sidduqi, M.A. (2019) ‘A Triaxial Acceleration-based Human Motion Detection for Ambient Smart Home System’, *Proceedings of 2019 16th International Bhurban Conference on Applied Sciences and Technology, IBCAST 2019*, (January), pp. 353–358. Available at: <https://doi.org/10.1109/IBCAST.2019.8667183>.
- khan, I. and Rashid, D.A. (2024) ‘Internet of Things (IoT) Its Applications and Enabling Technologies in Healthcare: A Review’, *Educational Administration Theory and Practices*, 30(4), pp. 9699–9714. Available at: <https://doi.org/10.53555/kuey.v30i4.5031>.
- Khan, S. *et al.* (2019) ‘Energy-Efficient Deep CNN for Smoke Detection in Foggy IoT Environment’, *IEEE Internet of Things Journal*, 6(6), pp. 9237–9245. Available at: <https://doi.org/10.1109/JIOT.2019.2896120>.
- Savitz, S., Perera, C. and Rana, O. (2023) ‘Edge analytics on resource constrained devices’,

- International Journal of Computational Science and Engineering*, 26(5), pp. 513–527. Available at: <https://doi.org/10.1504/IJCSE.2023.133674>.
- Sounder, N.S.G.D., Aina, T.S. and Akinte, O.O. (2022) ‘Development of a Smart Motion Detection Device for Home and Office Security Applications’, *International Journal for Research in Applied Science and Engineering Technology*, 10(2), pp. 268–282. Available at: <https://doi.org/10.22214/ijraset.2022.40246>.
- Stergiou, C. *et al.* (2018) ‘Secure integration of IoT and Cloud Computing’, *Future Generation Computer Systems*, 78, pp. 964–975. Available at: <https://doi.org/10.1016/j.future.2016.11.031>.
- Sulistiyowati, I. *et al.* (2019) ‘Cigarette detection system in closed rooms based on Internet of Thing (IoT)’, *Journal of Physics: Conference Series*, 1402(4), pp. 0–7. Available at: <https://doi.org/10.1088/1742-6596/1402/4/044005>.
- Suparman, M.A. Bin and Jong, S.L. (2019) ‘Automatic smoke detection system with favoriot platform using internet of things (IoT)’, *Indonesian Journal of Electrical Engineering and Computer Science*, 15(2), pp. 1102–1108. Available at: <https://doi.org/10.11591/ijeecs.v15.i2.pp1102-1108>.
- Trinath Basu, M. *et al.* (2018) ‘IoT based forest fire detection system’, *International Journal of Engineering and Technology(UAE)*, 7(2), pp. 124–126. Available at: <https://doi.org/10.14419/ijet.v7i2.7.10277>.
- Vijayaprabakaran, K., Kodidela, P. and Gurram, P. (2021) ‘IoT Based Smart Intruder Detection System For Smart Homes’, *International Journal of Scientific Research in Science and Technology*, pp. 48–53. Available at: <https://doi.org/10.32628/ijrst218410>.

APPENDIX

WEBSITE

```
``html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Jeff's Corner</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      padding: 0;
      background-color: #f0f0f0;
    }
    header {
      background-color: #333;
      color: #fff;
      padding: 20px;
      text-align: center;
    }
    nav {
      background-color: #666;
      padding: 10px 20px;
    }
    nav ul {
      list-style-type: none;
      margin: 0;
```

```

padding: 0;
text-align: center;
}
nav ul li {
display: inline;
margin-right: 20px;
}
nav ul li a {
text-decoration: none;
color: #fff;
}
footer {
background-color: #333;
color: #fff;
text-align: center;
padding: 10px;
position: fixed;
bottom: 0;
width: 100%;
} </style>
</head>
<body>
<header>
<h1>Welcome to Jeff's Corner</h1>
</header>
<nav>
<ul>
<li><a href="#home">Home</a></li>
<li><a href="#contacts">Contacts</a></li>
<li><a href="#search">Search</a></li>

```

```

        <li><a href="#about">About</a></li>
    </ul>
</nav>
<section>
    <h2>About Jeff</h2>
    <p>Hi, I'm Jeff. I enjoy coding, hiking, and reading.</p>
</section>
<footer>
    <p>&copy; 2024 Jeff's Corner. All rights reserved.</p>
</footer>
</body>
</html>

```

SMOKE DETECTOR JS

```

var DEACTIVATE_TIMER = 5; // in seconds
var state = 0;
var current_time = 0;
function setup() {
    IoEClient.setup({
        type: "Motion Detector",
        states: [{
            name: "On",
            type: "bool",
            controllable: false
        }]
    });
    state = restoreProperty("state", 0);
    setState(state);
} function restoreProperty(propertyName, defaultValue)
{
    var value = getDeviceProperty(getName(), propertyName);

```

```

        if ( !(value === "" || value == "undefined") ){
            if ( typeof(defaultValue) == "number" )
                value = Number(value);
            setDeviceProperty(getName(), propertyName, value);
            return value;
        } return defaultValue;
    } function mouseEvent(pressed, x, y, firstPress) {
        setState(1);
    } function loop() {
        if ( state == 1 ) {
            current_time--;
            if ( current_time <= 0 )
                setState(0); }
            delay(1000);
    } function setState(newState) {
        state = newState;
        if ( state === 0 ) {
            digitalWrite(1, LOW);
        } else {
            digitalWrite(1, HIGH);
            current_time = DEACTIVATE_TIMER;
        } IoEClient.reportStates(state);
        setDeviceProperty(getName(), "state", state);
    }

```

SIREN PYTHON

```

from gpio import *
from time import *
from ioecient import *
from physical import *
state = 0 # 0 off, 1 on

```

```

# Function to play sound when motion is detected
def play_sound():
    # Replace this with code to trigger your sound module or buzzer
    print("Motion detected! Sound should play here.")
def main():
    setup()
    while True:
        delay(1000)
def setup():
    IoEClient.setup({
        "type": "Siren",
        "states": [{
            "name": "On",
            "type": "bool",
            "controllable": True
        }]
    }) global state
    add_event_detect(0, detect)
    IoEClient.onInputReceive(onInputReceiveDone)
    state = restoreProperty("state", 0)
    setState(state)
def detect():
    # Call the play_sound function when motion is detected
    play_sound()
    processData(customRead(0), False)
def onInputReceiveDone(analogInput):
    processData(analogInput, True)
def restoreProperty(propertyName, defaultValue):
    value = getDeviceProperty(getName(), propertyName)
    if not (value is "" or value is None):

```

```

    if type(defaultValue) is int:
        value = int(value)
        setDeviceProperty(getName(), propertyName, value)
    return value
return defaultValue

def mouseEvent(pressed, x, y, firstPress):
    global state
    if firstPress:
        if state == True:
            setState(0)
        else:
            setState(1)
def processData(data, bIsRemote):
    if len(data) <= 0:
        return
    setState(int(data))
def setState(newState):
    global state
    state = newState
    if state == True:
        digitalWrite(1, HIGH)
    else:
        digitalWrite(1, LOW)
    customWrite(0, state)
    IoEClient.reportStates(state)
    setDeviceProperty(getName(), "state", state)
if __name__ == "__main__":
    main()

```