



Relational Databases with MySQL Week 12 Coding Assignment

URL to GitHub Repository: <https://github.com/Jeffrweinstein/week12>

URL to Public Link of your Video: <https://www.youtube.com/watch?v=dpLNtLJ8PIQ>

Instructions :

1. Follow the **Coding Steps** below to complete this assignment.

- In Eclipse, or an IDE of your choice, write the code that accomplishes the objectives listed below. Ensure that the code compiles and runs as directed.
- Create a new repository on GitHub for this week's assignment and push your completed code to this dedicated repo.
- Create a video showcasing your work:
 - In this video: record and present your project verbally while showing the results of the working project.
 - Easy way to Create a video: Start a meeting in Zoom, share your screen, open Eclipse with the code and your Console window, start recording & record yourself describing and running the program showing the results.
 - Your video should be a maximum of 5-minutes.
 - Upload your video with a public link.
 - Easy way to Create a Public Video Link: Upload your video recording to YouTube with a public link.

2. In addition, please include the following in your Coding Assignment Document:

- The URL for this week's GitHub repository.
- The URL of the public link of your video.

3. Save the Coding Assignment Document as a .pdf and do the following:

- Push the .pdf to the GitHub repo for this week.
 - Upload the .pdf to the LMS in your Coding Assignment Submission.
-




Relational Databases with MySQL Week 12 Coding Assignment

Coding Steps:

1. Create a new Maven project. In Eclipse...
 - a. Right-click in Project Explorer, select "New / Project". Expand "Maven". Select "Maven Project". Click "Next".



- b. Check "Create a simple project (skip archetype selection)". Click "Next".





Relational Databases with MySQL Week 12 Coding Assignment

- c. Enter the Group Id: "my.unit.test". Enter the Artifact Id: "unit-test-assignment". Click "Finish".

New Maven project

Configure project

Artifact	
Group Id:	my.unit.test
Artifact Id:	unit-test-assignment
Version:	0.0.1-SNAPSHOT

- d. The project "unit-test-assignment" should appear in the Package Explorer. Click the down arrow next to "unit-test-assignment" to expand it. Double-click on "pom.xml" to open it in the editor.



- e. Put a couple of blank lines between `<version>0.0.1-SNAPSHOT</version>` and `</project>`.

```
1 <project xmlns="http://maven.apache.org/POM/4.0.0" >
2   <modelVersion>4.0.0</modelVersion>
3   <groupId>my.unit.test</groupId>
4   <artifactId>unit-test-assignment</artifactId>
5   <version>0.0.1-SNAPSHOT</version>
6
7   |
8
9 </project>
```



Relational Databases with MySQL Week 12 Coding Assignment

f. Copy and paste the following code into the blank area you just created.

```
<properties>
  <java.version>11</java.version>
  <project.build.sourceEncoding>utf-8</project.build.sourceEncoding>
</properties>

<dependencies>
  <dependency>
    <groupId>com.google.guava</groupId>
    <artifactId>guava</artifactId>
    <version>30.1.1-jre</version>
  </dependency>

  <dependency>
    <groupId>org.junit.jupiter</groupId>
    <artifactId>junit-jupiter</artifactId>
    <version>5.7.2</version>
    <scope>test</scope>
  </dependency>

  <dependency>
    <groupId>org.assertj</groupId>
    <artifactId>assertj-core</artifactId>
    <version>3.20.2</version>
    <scope>test</scope>
  </dependency>
```



Relational Databases with MySQL Week 12 Coding Assignment


```
<dependency>
  <groupId>org.mockito</groupId>
  <artifactId>mockito-junit-jupiter</artifactId>
  <version>3.11.2</version>
  <scope>test</scope>
</dependency>
</dependencies>


<build>
  <plugins>
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-compiler-plugin</artifactId>
      <version>3.8.1</version>
      <configuration>
        <source>${java.version}</source>
        <target>${java.version}</target>
      </configuration>
    </plugin>
  </plugins>
</build>
```

- g. Save the file.
- h. For Eclipse only: right-click on "unit-test-assignment" in the Project Explorer. Click on "Properties". Click "Java Compiler". Make sure "Enable project specific settings" is checked. Uncheck "Use compliance from execution environment 'J2SE-1.5' on the 'Java Build Path'". Set "Compiler compliance level" to 11. Click "Apply and Close".



Relational Databases with MySQL Week 12 Coding Assignment



- i. If asked to rebuild the project, click "Yes".
 2. Create a class named "TestDemo" under src/main/java in the default package. (In Package Explorer, expand "unit-test-assignment". Right-click on "src/main/java" and select "New / Class". Enter "TestDemo" in the "Name" field and click "Finish".)
- 
- a. Create an instance method (not static) named addPositive. It should take two int parameters and return an int.

```
public int addPositive(int a, int b) {}
```
 - b. If both parameters are positive (greater than zero) return the sum of the parameters. If either parameter is zero or negative, throw an IllegalArgumentException with the message "Both parameters must be positive!". IllegalArgumentException is in the java.lang package so you won't need an import statement.
 - c. Save the file.
 3. In Package Explorer, find "src/test/java" and right-click on it. Select "New / JUnit Test Case". In the "Name" field, enter "TestDemoTest". Make sure that "New JUnit Jupiter test" is selected. Make sure that "@BeforeEach setUp()" is checked. Click "Finish".



Relational Databases with MySQL Week 12 Coding Assignment

☐ New JUnit 3 test ☐ New JUnit 4 test ☒ New JUnit Jupiter test

Source folder:

Package:

Name:

Superclass:

Which method stubs would you like to create?

☐ @BeforeAll setUpBeforeClass() ☐ @AfterAll tearDownAfterClass()

☒ @BeforeEach setUp() ☐ @AfterEach tearDown()

☐ constructor

4. In `TestDemoTest.java`, add a private instance variable of type `TestDemo` named `testDemo`.
 - a. In the `setUp` method, create the `TestDemo` object. This will ensure that a new `TestDemo` object is created before each test.
 - b. Change `"@Test"` to `"@ParameterizedTest"`. Add the import statement for `org.junit.jupiter.params.ParameterizedTest`.
 - c. Change the name of method `"test"` to `"assertThatTwoPositiveNumbersAreAddedCorrectly"`.
 - d. Add four parameters to `assertThatTwoPositiveNumbersAreAddedCorrectly` as shown:

Type	Name
int	a
int	b
int	expected
Boolean	expectException

e.



Relational Databases with MySQL Week 12 Coding Assignment

- f. Write the test. Remove the "fail" line. Test the value of `expectException`. If it is false, assert that when `TestDemo.addPositive` is called with values `a` and `b`, that the result is the same as the parameter `expected`. The assertion should look like this:

```
if(!expectException) {  
    assertThat(testDemo.addPositive(a, b)).isEqualTo(expected);  
}
```

- g. Add the test for the thrown exception in an else clause. Use

```
assertThatThrownBy for this. Add the static import  
org.assertj.core.api.Assertions.assertThatThrownBy;
```

- h. As a parameter to `assertThatThrownBy`, add a Lambda expression with no parameters. The Lambda body should be the method call to `testDemo.addPositive`.

- i. Use the assertion `assertInstanceOf(IllegalArgumentException.class)` to ensure that the correct exception is thrown.

- j. If this is too confusing, you can "cheat" and copy this:

```
assertThatThrownBy(() ->  
    testDemo.addPositive(a, b))  
    .assertInstanceOf(IllegalArgumentException.class);
```

- k. Add the parameter source method.

- i. Create a static method named `argumentsForAddPositive`. It should not have any parameters and it should return a `Stream` of `Arguments`. The imports are: `java.util.stream.Stream` and `org.junit.jupiter.params.provider.Arguments`.

- ii. The method should return a `Stream` as in `Stream.of()`;

- iii. Each parameter set should be wrapped in an `arguments()` method call.

Add the static import for `arguments`:

```
org.junit.jupiter.params.provider.Arguments.arguments.
```




Relational Databases with MySQL Week 12 Coding Assignment

- iv. So, if you are adding 2 and 4 to get the value of 6 and are not expecting an exception, you need to do:

```
arguments(2, 4, 6, false)
```

- v. Add as many arguments lines as needed to test the `addPositive` method thoroughly. Make sure to add some zero or negative arguments.

- 1. Just below the `@ParameterizedTest` annotation, add the annotation `@MethodSource`. Pass a single parameter to `@MethodSource`. It must be the fully-qualified (includes package) class name of the test followed by a `#` sign followed by the name of the method that supplies the parameters. Since the test is in the default package, there is no package in the fully-qualified class name. So,

```
@MethodSource("TestDemoTest#argumentsForAddPositive")
```

- 5. In `TestDemo.java`, add another method named `randomNumberSquared`. This method obtains a random int between 1 and 10 and then returns the square of the number.

- a. `randomNumberSquared` should return an int and not take any parameters.
- b. It should call another method in the same class named `getRandomInt`. This method takes no parameters and must be package visibility so that the test can see it. `getRandomInt` should look like this:

```
int getRandomInt() {  
    Random random = new Random();  
    return random.nextInt(10) + 1;  
}
```

The `Random` class is in the `java.util` package.

- c. `randomNumberSquared` should return the value obtained from `getRandomInt` multiplied by itself.
- 6. Write a test for `randomNumberSquared` in `TestDemoTest.java`. Since you don't know what `getRandomInt` will return (that's the point of random, after all), you will need to mock it out and supply a known value.
 - a. Create a method annotated with `@Test` named `assertThatNumberSquaredIsCorrect`. The method must have package visibility (not public!) or JUnit won't find it. The annotation `@Test` is in the `org.junit.jupiter.api` package.



Relational Databases with MySQL Week 12 Coding Assignment

- b. To mock the `TestDemo` class, use `Mockito.spy`. The `spy` method can be imported with a static import of `org.mockito.Mockito.spy`.

```
TestDemo mockDemo = spy(testDemo);
```

- c. Program the mocked `TestDemo` object to return 5 when the `getRandomInt` method is called. Remember to use the form:

```
doReturn(aValue).when(mockedObject).methodCall(). You can use a static
import for doReturn: import static org.mockito.Mockito.doReturn;

doReturn(5).when(mockDemo).getRandomInt();
```

- d. Call the method `randomNumberSquared` on the mocked `TestDemo` object. This will call the stubbed out (mocked) method `getRandomInt`, which now should return the value 5.

```
int fiveSquared = mockDemo.randomNumberSquared();
```

- e. Use `assertThat` to test that the value returned from `randomNumberSquared` is equal to 5 squared.

```
assertThat(fiveSquared).isEqualTo(25);
```

- f. You don't need to verify the mocked method call – you know it was called since the return value is correct.



Relational Databases with MySQL Week 12 Coding Assignment

```

1 import java.util.Random;
2
3
4
5
6 public class TestDemo {
7
8     public int addPositive(int a, int b) {
9         int sum;
10        if(a>0 && b>0) {
11            sum = a + b;
12        }
13
14
15        else {
16            throw new IllegalArgumentException("Both parameters must be positive!");
17        }
18        return sum;
19    }
20
21    public int randomNumberSquared() {
22
23        int randomNumber = getRandomInt();
24        return randomNumber*randomNumber;
25    }
26
27    int getRandomInt() {
28        Random random = new Random();
29        return random.nextInt(10) + 1;
30    }
31
32
33 }
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015

```



Relational Databases with MySQL Week 12 Coding Assignment

```
38
39
40 }
41
42 // @formatter:off
43 static Stream<Arguments> argumentsForAddPositive() {
44     return Stream.of(
45         arguments(2, 4, 6, false),
46         arguments(13, -5, 8, true),
47         arguments(-1, 2, 1, true),
48         arguments(0, 5, 5, true),
49         arguments(11, 0, 11, true),
50         arguments(0, 0, 0, true)
51     );
52 // @formatter:on
53 }
54
55 @Test
56
57 void assertThatNumberSquaredIsCorrect() {
58     TestDemo mockDemo = spy(testDemo);
59     doReturn(5).when(mockDemo).getRandomInt();
60     int fiveSquared = mockDemo.randomNumberSquared();
61     assertThat(fiveSquared).isEqualTo(25);
62 }
63
64 }
```

JUnit

Finished after 0.8 seconds

Runs: 7/7 Errors: 0 Failures: 0

TestDemoTest [Runner: JUnit 5] (0.675 s)

Failure Trace

- assertThatTwoPositiveNumbersAreAddedCorrectly(int, int, Boolean) (0.104 s)
 - [1] 2, 4, 6, false (0.104 s)
 - [2] 13, -5, 8, true (0.005 s)
 - [3] -1, 2, 1, true (0.000 s)
 - [4] 0, 5, 5, true (0.002 s)
 - [5] 11, 0, 11, true (0.001 s)
 - [6] 0, 0, 0, true (0.001 s)
- assertThatNumberSquaredIsCorrect() (0.551 s)