

# Writing a Java Program (1/2)



covering

- \*\* using our new programming skills to write a real program (and **learning some new ones on the way!**)
- \*\* arrays
- \*\* enhanced `for` loop



**Chapter 5 (\*)** – “Head First Java” book



Some slides contain lots of animation.

# A Battleship Style Game: “Sink a Dot Com” (1/2)

## Your Task:

- Build a game like the battleship guessing game.
- The basic idea of battleship is a number of ships are placed on a grid world board.
- In the board game version, there are 2 players who each have their own board.



# A Battleship Style Game: “Sink a Dot Com” (2/2)


- Here, we will sink "Dot Coms", instead of Battleships
- Just play against the computer's battleships, i.e. no board of your own to put "Dot Coms" on.

## GOAL

- Sink all the computer's “Dot Coms” in the **fewest number of steps/guesses**.
- You are given a **rating**, based on how well you perform.

## SETUP

- A **virtual 7x7 board** with **3 randomly placed “Dot Coms”**.
- After that, the player should be prompted to enter their first guess.



**Dot Com** = Company that conducts its business on the internet

# “Sink a Dot Com” game: how to play and sample interaction

## How to play:

- No GUI yet, as we do not know how to do that.
- Use the command line.
- Computer should prompt for a guess, and the player should enter a cell, e.g. A3, C5, etc.
- The computer should respond with hit or miss.
- After all 3 “Dot Coms” have been sunk, the game ends by printing out your rating.

```
>java DotComBust
Enter a guess  A3
miss
Enter a guess  D2
hit
Enter a guess  D3
hit
Enter a guess  D4
Ouch! You sunk Pets.com : (
kill
...
...
```

7 x 7 grid


A							
B							
C							
D							
E							
F							
G							
	0	1	2	3	4	5	6

# Program's high level design & Conversion to Flowchart


First ...

- Work out the **program interactions**.
- **Write** everything in **English**, i.e. **do not write Java code** (**for now**).
- Define the **general flow of the game**, from the specification.

Then ...




A **circle** means **start or finish**.



A **diamond** represents a **decision point**.



A **rectangle** represents an **action point**.



# Game Sequence

User starts  
the Game


1

Game Play  
begins

2

7 x 7 grid

A							
B							
C	Go2.com						
D			Pets.com				
E							
F							
G				AskMe.com			
	0	1	2	3	4	5	6




Game finishes

3

# Developing the classes for the “Sink a Dot Com” game

- Always try to make things simpler on the first iteration of your programs!
  - You can go back and improve what you know works ...
- An even simpler "Sink a Dot Com":
  - Only 1 “Dot Com” on the board, instead of 3.
  - No 2D grid; put the “Dot Com” just in a row.
  - The goal is still the same.



- We are going to need 2 classes (at least – see later):
  - **Game** Class
  - **DotCom** Class
- Simple version:
  - The **Game** class has no instance variables and all the "coding stuff" is in **main()**.
  - When launched, it will create 1 instance of a **DotCom** class and choose a location for it.
    - in 3 consecutive array cell locations
  - After that, play the game!

# UML & Example Game Interaction

## SimpleDotCom

```
int[] locationCells;  
int numberOfHits;
```

```
String checkYourself(String guess);  
void setLocationCells(int[] loc)
```

## SimpleDotComGame

```
void main(String[] args)
```

A complete game interaction:

```
>java SimpleDotComGame  
enter a number    3  
hit  
enter a number    4  
hit  
enter a number    2  
miss  
enter a number    5  
kill  
You took 4 guesses
```



# Steps to develop a Java class (Revision)

1. Decide what the class is supposed to do.
2. List the **instance variables** and **methods**.
3. Write “**prep code**” for the methods.
4. Write **test code** for the methods.
5. **Implement** the class.
6. **Test** the methods.
7. **Debug and re-implement**, as necessary.

# “Prep code” for SimpleDotCom

- A **form of pseudocode**, to help focus on the logic without the worry of syntax.

SimpleDotCom
<b>int[] locationCells;</b> <b>int numberOfHits;</b>
<b>String checkYourself(String guess);</b> <b>void setLocationCells(int[] loc)</b>

**DECLARE** an **int** array for location cells. Call it **locationCells**.

**DECLARE** an **int** to hold the number of hits. Call it **numberOfHits** and **SET** it to 0.

---

**DECLARE** a **checkYourself()** method that takes a **String** for the user's guess ("1", "3", etc), checks it, and returns a result representing a "hit", "miss", or "kill".

**DECLARE** a **setLocationCells()** setter method that takes an **int** array (which has the three cell locations as **int** values (2, 3, 4, etc.).

# Methods `checkYourself()` and `setLocationCells()`

**METHOD:** `String checkYourself(String userGuess)`

**GET** the user guess as a `String` parameter

**CONVERT** the user guess to an `int`

**REPEAT** with each of the location cells in the `int` array

// **COMPARE** the user guess to the location cell

**IF** the user guess matches

**INCREMENT** the number of hits

// **FIND OUT** if it was the final location cell

**IF** number of hits is 3, **RETURN** "kill"

**ELSE** if it was not a kill, **RETURN** "hit"

**ELSE** the user guess did not match, so **RETURN** "miss"

**END IF**

**END REPEAT**

**END METHOD**

**METHOD:** `void setLocationCells(int[] cellLocations)`

**GET** the cell locations as an `int` array parameter

**ASSIGN** cell locations parameter to the cell location instance variable

**END METHOD**

# Time to start coding!

- We have our `SimpleDotCom` class; shouldn't we just write it up and create our game?
  - No!
- We need to test it!
  - How do you test it? What would prove that it works?
  - Writing test code helps clarify what it is we want the method to do.
- The main thing we want to test is the `checkYourself()` method.
  - Basic idea of this method: check to see if the `DotCom` object has been hit.
  - To test it, we could:
    1. Instantiate a `SimpleDotCom` object.
    2. Assign it a location (i.e. an array of 3 `int` values, like `{2, 3, 4}`).
    3. Create a `String` to represent a user guess (e.g. `"2"`, `"0"`, etc).
    4. Invoke the `checkYourself()` method, passing it a fake guess.
    5. Print out the result and see if it is what we expected.

# Test Code for SimpleDotCom class (version 1)

```
public class SimpleDotComTest {  
    public static void main(String[] args) {  
        SimpleDotCom dot = new SimpleDotCom();  
        int[] locations = {2, 3, 4};  
        dot.setLocationCells(locations);  
  
        String userGuess = "2"; // result should be "hit" or "kill"  
        String result = dot.checkYourself(userGuess);  
        String testResult = "failed"; // default value  
        if (result.equals("hit") || result.equals("kill")) {  
            testResult = "passed";  
        }  
        System.out.println(testResult);  
    }  
}
```

# First version of SimpleDotCom class

```
public class SimpleDotCom {
    private int[] locationCells;
    private int numberOfHits = 0;

    public void setLocationCells(int[] loc) { locationCells = loc; }

    public String checkYourself(String stringGuess) {
        int guess = Integer.parseInt(stringGuess);
        String result = "miss"; // default value
        for (int i : this.locationCells) {
            if (guess == i) {
                result = "hit";
                this.numberOfHits++;
                break;
            }
        }
        if (this.numberOfHits == this.locationCells.length) { result = "kill"; }
        System.out.println(result);
        return result;
    }
} // end of SimpleDotCom
```

equivalent to

```
for (int i=0; i<locationCells.length; i++) {
    if (guess == locationCells[i]) {
        // rest of the code as before
    }
}
```

# The main () method in the SimpleDotComGame class

**DECLARE** an **int** variable to hold the number of user guesses, named **numOfGuesses**; **SET** it to 0

**MAKE** a new **SimpleDotCom** instance

**COMPUTE** a random number between 0 and 4 that will be the starting location cell position

**MAKE** an **int** array with 3 **int** values using the randomly-generated number incremented by 1, and that number incremented by 2 (e.g. 3, 4, 5)

**INVOKE** the **setLocationCells ()** method on the **SimpleDotCom** instance

**DECLARE** a **boolean** variable representing the state of the game, named **isAlive**; **SET** it to **true**

**WHILE** dot com is alive  
(**isAlive == true**)

**GET** user input from command line

// **CHECK** the user guess

**INVOKE** the **checkYourself ()** method on the **SimpleDotCom** instance

**INCREMENT** **numberOfGuesses** variable

// **CHECK** for dot com death

**IF** result is “kill”

**SET** **isAlive** to **false**  
(no more looping)


**PRINT** the number of guesses

**END IF**

**END WHILE**

# Test code for SimpleDotCom class (version 2)

```
public static void main(String[] args) {  
    int numOfGuesses = 0;  
    GameHelper helper = new GameHelper();  
    SimpleDotCom dot = new SimpleDotCom();  
    int randomNum = (int) (Math.random() * 5);  
    int[] locations = {randomNum, randomNum + 1,  
                       randomNum + 2};  
    dot.setLocationCells(locations);  
    boolean isAlive = true;  
  
    while (isAlive == true) {  
        String guess = helper.getUserInput("Enter a number ");  
        String result = dot.checkYourself(guess);  
        numOfGuesses++;  
        if (result.equals("kill")) {  
            isAlive = false;  
            System.out.println("You took " + numOfGuesses + " guesses");  
        }  
    }  
}
```



**GameHelper** = pre-written "ready baked" class.

- We are **not** going to worry about how it works!
- It **gets the input from the user**; that is all we need to know (**for now**).



# Testing the first version of the game ...

A complete game interaction:

```
>java SimpleDotComGame
enter a number    3
hit
enter a number    4
hit
enter a number    2
miss
enter a number    5
kill
You took 4 guesses
```



This may be different, depending on **`Math.random()`**.

Another complete game interaction:

```
>java SimpleDotComGame
enter a number    3
hit
enter a number    3
hit
enter a number    3
kill
You took 3 guesses
```



Bug!



... and things for you to try out!