

Reset answer

```
1 #include <stdio.h>
2
3 int main()
4 {
5     printf("I love Mangoes");
6     return 0;
7 }
```

	Expected	Got	
✓	I love Mangoes	I love Mangoes	✓

Passed all tests! ✓

```
1 #include <stdio.h>
2
3 int main()
4 {
5     printf("Hello C");
6     return 0;
7 }
```

	Expected	Got	
✓	Hello C	Hello C	✓

Passed all tests! ✓

```
1 #include<stdio.h>
2 int main(){
3 printf("Hello, World!");
4 return 0;
5 }
6
```

	Expected	Got	
✓	Hello, World!	Hello, World!	✓

Passed all tests! ✓

```

1 #include<stdio.h>
2 int main(){
3     char ch;
4     scanf("%c",&ch);
5     printf("%c",ch);
6     return 0;
7 }
8

```

	Input	Expected	Got	
✓	C	C	C	✓

Passed all tests! ✓

```

1 #include<stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d %d\n",&a,&b);
5     float c,d;
6     scanf("%f %f",&c,&d);
7     printf("%d %d\n",a+b,a-b);
8     printf("%.1f %.1f",c+d,c-d);
9     return 0;
10 }

```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	✓