HealthTwin AI: patient app and hospital portal

Integration notes for Puneet (from Jehal), update after Phase 7. Simulated prototype, not a medical device.

We ran your real portal (**origin/Puneet**, commit 37964c8, built with VITE_USE_MOCK=false, unedited) together with the patient app and our mock server in one browser. **17 of 17 checks passed.** Nothing was merged. A correction to our earlier notes: the portal *does* tolerate alerts that arrive before SOS_SENT (early-state notice), so our "false-alarm flash" worry was overstated; sending the alert at SOS is still the cleaner behaviour and is what the mock does now.

1. What changed on our side (already in branch Jehal)

Topic	Now
emergency.created	Sent at SOS with state SOS_SENT, then emergency.sos_sent, then hospital.alerted. Nothing is broadcast before the SOS; cancelling inside the 10 s countdown sends the hospital nothing. Payload: patient_id, type, severity, symptoms (readable labels), symptom_ids, source, reasons, patient_summary and patient {id, name, age, sex}, created_at, hospital {id, name, distance_km, rank}, simulated. vitals {heart_rate, spo2, bp, bp_sys, bp_dia, glucose, resp_rate} and location {lat, lng, accuracy} only with the patient's consent: left out, never null
hospital.alerted	payload.hospital_id and payload.rank next to the old hospital object
Hospitals	Five Ahmedabad hospitals copied from your seed (coordinates, capability and availability objects). GET /hospitals returns them sorted by distance with distance_km. Ranking: needed unit present and ready first, then nearest
Ambulances	GET /ambulances (your unit positions and crew, fictional names). POST /ambulances/{id}/location is accepted and relayed as ambulance.location
Manual hospital mode	Start the mock with HOSPITAL_MODE=manual: your Acknowledge, Dispatch and En route / Arrived / Handed over buttons drive the emergency (POST /emergencies/{id}/ack, /dispatch {ambulance_id}, /status {state}). Staff or admin token only (patient token: 403); invalid move: 409 { detail: "Invalid transition", from, to }
Lists and logins	GET /emergencies?status=active and ?status=finished. Logins staff@demo / admin@demo with password demo123 (role staff / admin and hospital_id in the answer), plus staff1 / demo-password
Location	Demo location is Ahmedabad 23.0225, 72.5714 in the patient app and the mock, same as your geo.js
IDs and names	Realistic-looking but fictional: patient PT-2026-0417, emergency EM-YYYYMMDD-nnnn, hospitals HSP-AMD-001..005, ambulances AMB-AMD-01..05. Your H1..H5 and AMB-1..5 are kept in each record as portal_id. The portal worked unchanged with these IDs

2. What the rehearsal showed (details in docs/JOINT_REHEARSAL.md)

Scenario	Result
Patient sends SOS	Card shows type, severity, patient id, readable symptoms, HR / SpO2 / BP, coordinates. PASS
Acknowledge, dispatch, arrive, handover	Patient timeline follows each step; patient app says "Alert sent" until Dispatch. PASS
Cancel inside the countdown	Portal never shows a card. PASS
Cancel after SOS	Card turns CANCELLED and every action button is disabled. PASS
Consent off (vitals, location)	Card shows dashes and "Location not shared". PASS
Safety check-in, no answer	Card appears as "Safety check-in (no symptoms)". PASS (your label already exists)
Console	No errors in either app. PASS

3. Small things for you

• The detail panel shows "(±0 m)" when the patient app reports accuracy 0. Please hide accuracy when it is 0 or missing (real phones report a real value).

• Availability key names differ: yours are beds_free, icu_free, cath_lab_ready, stroke_unit_ready; Daksh v0.6.1 has icu_beds, cath_lab_open, stroke_unit_open. You read both; one set has to win.

• Endpoints in your integration.json that the mock does not implement (you keep them local): notes, chat, checklist ticks, hospital onboarding and edits, availability updates, responders, AED. Daksh's v0.6 contract does not have them

either, so please send him your list.

• Cancel after dispatch: Daksh's transition table forbids it and the mock enforces that only in manual mode. We have not rehearsed it.

4. Still open (Puneet, Daksh, Jehal)

• **Who moves EMERGENCY_DETECTED to SOS_SENT?** Daksh proposes the backend does it when the countdown ends. The patient app calls POST /emergencies/{id}/sos today and the mock now has the same effect for you. Decision still open.

• **Who moves the ambulance in the real system?** Your browser simulator posts positions; if the desk is closed nobody does.

• **Readable symptom labels** are made in the mock (mock-server/adapters.js); the real backend needs the same table.

• **Honest wording** stays: "notification sent" until the operator confirms dispatch; the Simulated label stays visible.

5. Run it yourself

Branch Jehal: `npm install`, then `HOSPITAL_MODE=manual DEMO_SPEED=5 CORS_ORIGINS=http://localhost:5173,http://localhost:5174 npm run mock` (port 4000). In your portal set VITE_USE_MOCK=false, VITE_API_BASE_URL=http://localhost:4000, VITE_WS_URL=ws://localhost:4000/ws and sign in staff@demo / demo123. Or run everything with one command: `node scripts/joint-rehearsal.mjs` (needs git fetch origin and Chrome).