```sql
-- Colocar la base de datos en modo FULL
ALTER DATABASE BusRD SET RECOVERY FULL;
GO

-- Dirección de guardado para BD
BACKUP DATABASE BusRD
TO DISK = 'C:\Backups\BusRD_Full.bak'
WITH INIT,
     NAME = 'BusRD-Full Database Backup';
GO
```

```sql
-- Respaldo diferencial
BACKUP LOG BusRD
TO DISK = 'C:\Backups\BusRD_Log1.trn'
WITH INIT;
GO
```

```sql
-- Insertar datos a la tabla
INSERT INTO dbo.Boletos (ViajeID, NumeroAsiento, ClienteID, FechaVenta, Canal, Precio, Estado)
SELECT TOP 8 @ViajePruebal, NumeroAsiento, 1, GETDATE(), 'Web', 500.00, 'Activo'
FROM dbo.Asientos
WHERE AutobusID = (SELECT AutobusID FROM dbo.Viajes WHERE ViajeID = @ViajePruebal)
  AND NumeroAsiento NOT IN (SELECT NumeroAsiento FROM dbo.Boletos WHERE ViajeID = @ViajePruebal);
GO
```

```sql
-- Eliminar boletos de viaje para restaurarción
DECLARE @ViajeDesastre INT = 7;

DELETE FROM dbo.Pagos
WHERE BoletoID IN (SELECT BoletoID FROM dbo.Boletos WHERE ViajeID = @ViajeDesastre);

DELETE FROM dbo.Boletos
WHERE ViajeID = @ViajeDesastre;
GO

-- Verificación de borrado
SELECT COUNT(*) AS BoletosDespuesDelDesastre
FROM dbo.Boletos
WHERE ViajeID = 7;
GO
```

	BoletosDespuesDelDesastre
1	0

```
-- Restaurar
BACKUP LOG BusRD
TO DISK = 'C:\Backups\BusRD_Log2.trn'
WITH INIT, NO_TRUNCATE;
GO

-- Restauración a estado anterior
USE master;
GO

-- Forzar acceso (eliminación de bloqueo)
ALTER DATABASE BusRD SET SINGLE_USER WITH ROLLBACK IMMEDIATE;
GO

-- Restone el Respaldo full
RESTORE DATABASE BusRD
FROM DISK = 'C:\Backups\BusRD_Full.bak'
WITH NORECOVERY, REPLACE;
GO

-- Restone respaldo diferencial
RESTORE LOG BusRD
FROM DISK = 'C:\Backups\BusRD_Log1.trn'
WITH NORECOVERY;
GO

-- Restauración de LOG
RESTORE LOG BusRD
FROM DISK = 'C:\Backups\BusRD_Log2.trn'
WITH RECOVERY,
     STOPAT = '2026-10-28 23:41:28.417';
GO
```

	BoletosRecuperados_STOPAT
1	8