# CharacterGPT: A Persona Reconstruction Framework for Role-Playing Agents





Jeiyoon Park<sup>1</sup>, Chanjun Park<sup>2</sup>, Heuiseok Lim<sup>2</sup> naruto@sooplive.com {bcj1210, limhseok}@korea.ac.kr









# SCOP

#### **Motivations**


- Maintaining consistent character personas remains a challenge due to variability in information extraction, which frequently omits critical elements such as backstory or interpersonal relationships.
- ◆ We address the primary research question (RQ) in two key tasks: 1) How to better exploit character persona, and 2) How to encourage characters to use imagination for generating new ideas.





#### **CharacterGPT**


◆ We propose a novel framework called CharacterGPT, which includes a persona rebuilding process called Character Persona Training (CPT).



- Based on character analysis literature, CPT operates by identifying eight essential traits: Internal attributes (Personality, Physical Description, and Motivation) and external attributes (Backstory, Emotions, Relationships, Growth and Change, and Conflict).
- ◆ CPT updates the character persona at each epoch by extracting rolespecific traits from chapter summaries.
- ◆ For Internal attributes (Type A), LLM-based generalization function refines extracted traits, while external attributes (Type B) are simply appended to each persona document.

## **Experimental Results**

◆ Task for RQ1: Persona Evaluation. For persona evaluation, we compare the personality traits analyzed by human.






Table 2: Differences between Megumin's personalities analyzed by humans and LLMs in the BFI test.

Figure 4: Total sum of |d| for each character in ChatGPT and GPT-4 settings  $(\Sigma \Sigma |d|)$ . The smaller value, the better.


◆ Task for RQ2: Story Generation. The story generation task is evaluated based on common aspects in generated story assessment.

Model	Grammar	Coherence	Likability	Relevance	Complexity	Creativity
Megumin	3.79	3.82	3.11	4.21	2.46	2.86
Megumin + Ours	4.11	4.00	3.71	4.11	3.46	3.29
Anya	4.29	3.82	3.39	3.86	3.61	3.68
Anya + Ours	4.25	4.00	3.79	4.00	3.43	3.89
Frieren	4.29	3.89	3.50	3.86	3.93	3.79
Frieren + Ours	4.32	3.96	3.71	4.21	4.04	3.86
Hitori	4.36	4.04	3.57	4.18	3.43	3.50
Hitori + Ours	4.36	4.39	3.82	4.18	3.96	3.93
GPT-4 (avg)	4.18	3.89	3.39	4.03	3.36	3.46
GPT-4 + Ours (avg)	4.26	4.09	3.76	4.13	3.72	3.74

Table 6: Human evaluation of generated stories. The backbone model is the same as GPT-4, and four stories for each setting, a total of 32 stories are generated and evaluated by 7 crowd-workers using a 5-point Likert scale.

### **Key Advantages**

◆ CharacterGPT minimizes information loss by aligning persona accumulation with narrative progression, and is the first to store and update a protagonist's persona at each epoch, allowing users to engage with characters at specific narrative points.






Figure 9: Case study of the evolution of Hitori's relationships (left) and Frieren's personality (right) through Character Persona Training (CPT). These results demonstrate how the method captures shifts in both external

relationships and internal character development