


5. 데이터분석 실습(항공운항데이터)

가. 분석용 데이터 다운로드

<http://stat-computing.org/dataexpo/2009>

1987~2008 21년간 미국 항공 운항 데이터를 활용하여 항공기 출발 지연, 도착 지연, 결항 등의 통계를 분석 

전체자료는 11GB이며 전체 자료를 모두 분석하려면 많은 시간이 소요되므로 2006~2008 3년간의 자료만 다운로드하여 실습

다운로드받은 파일의 압축을 해제한 후 /home/centos/data/airline 디렉토리에 복사(2006.csv , 2007.csv , 2008.csv 3개의 파일)

<http://stat-computing.org/dataexpo/2009/>



ASA Sections on:

[Statistical Computing](#)
[Statistical Graphics](#)

[[Computing, Graphics](#)]
[[Awards, Data expo, Video library](#)]
[[Events, News, Newsletter](#)]

[Data expo](#)

Airline on-time performance

Have you ever been stuck in an airport because your flight was delayed or cancelled and wondered if you could have predicted it if you'd had more data? This is your chance to find out.

The results

We had a total of [nine entries](#), and turn out at the poster session at the JSM was great, with plenty of people stopping by to find out why their flights were delayed.

The data

[The data](#) consists of flight arrival and departure details for all commercial flights within the USA, from October 1987 to April 2008. This is a large dataset: there are nearly 120 million records in total, and takes up 1.6 gigabytes of space compressed and 12 gigabytes when uncompressed. To make sure that you're not overwhelmed by the size of the data, we've provide two brief introductions to some useful tools: [linux command line tools](#) and [sqlite](#), a simple sql database.

The challenge

The aim of the data expo is to provide a **graphical** summary of important features of the data set. This is intentionally vague in order to allow different entries to focus on different aspects of the data, but here are a few ideas to get you started:

- When is the best time of day/day of week/time of year to fly to minimise delays?
- Do older planes suffer more delays?
- How does the number of people flying between different locations change over time?
- How well does weather predict plane delays?
- Can you detect cascading failures as delays in one airport create delays in others? Are there critical links in the system?

You are also welcome to work with interesting subsets: you might want to compare flight patterns before and after 9/11, or between the pair of cities that you fly between most often, or all flights to and from a major airport like Chicago (ORD). Smaller subsets may also help you to match up the data to [other interesting datasets](#).

[Data expo '09](#)

Get the data

The data comes originally from [RITA](#) where it is [described in detail](#). You can download the data there, or from the bziped csv files listed below. These files have derivable variables removed, are packaged in yearly chunks and have been more heavily compressed than the originals.

Download individual years:


[1987](#), [1988](#), [1989](#), [1990](#), [1991](#), [1992](#), [1993](#), [1994](#), [1995](#), [1996](#), [1997](#), [1998](#), [1999](#), [2000](#), [2001](#),
[2002](#), [2003](#), [2004](#), [2005](#), [2006](#), [2007](#), [2008](#)

1987~2008까지 출발 시간 및 도착 시간이 얼마나 지연되었는지에 대한 데이터이다.

총 합치면 11GB이기 때문에, 2006~2008까지의 데이터로만 실습하도록 한다.

Data expo 09

- [Posters & results](#)
- [Competition description](#)
- [Download the data](#)
- [Supplemental data sources](#)
- [Using a database](#)
- [Intro to command line tools](#)



하둡분석시간과 mysql을 통한 DBMS의 분석시간의 차이를 분석해보려고한다.

나. mysql 설치(윈도우즈에서 작업)

HDFS에서 분석하는 방법과 비교하기 위하여 다운로드받은 csv 파일을 mysql 데이터베이스 테이블로 import

[mysql 설치 방법은 Java 21강 - 데이터베이스프로그래밍 참조](#)

csv 파일을 mysql 테이블로 import하기 위하여 cmd에서 아래와 같이 mysql에 접속

```
mysql --local-infile -u root -p
```

자. mysql 설치

1) mysql 공식 사이트

<http://mysql.com>

2) mysql community edition - MySQL Installer for Windows 버전 다운로드

가) mysql community edition - 개인 개발용 무료 버전

나) GPL(General Public License, 일반 공중 사용 허가서)

1. 컴퓨터 프로그램을 어떠한 목적으로든지 사용할 수 있다. 다만 법으로 제한하는 행위는 할 수 없다.
2. 컴퓨터 프로그램의 실행 복사본은 언제나 프로그램의 소스 코드와 함께 판매하거나 소스코드를 무료로 배포해야 한다.
3. 컴퓨터 프로그램의 소스 코드를 용도에 따라 변경할 수 있다.
4. 변경된 컴퓨터 프로그램 역시 프로그램의 소스 코드를 반드시 공개 배포해야 한다.
5. 변경된 컴퓨터 프로그램 역시 반드시 똑같은 라이선스를 취해야 한다. 즉 GPL 라이선스를 적용해야 한다.

3) mysql 설치

"msvcp120.dll이 없어 프로그램을 시작할 수 없습니다." 라는 에러가 발생할 경우
Microsoft .NET Framework 프로그램을 설치해야 함

다운로드 주소 :

<https://www.microsoft.com/ko-KR/download/details.aspx?id=42642>

<https://www.mysql.com/>



- MySQL Enterprise Monitor
- MySQL Enterprise HA
- MySQL Enterprise Security
- MySQL Enterprise Transparent Data Encryption (TDE)
- MySQL Enterprise Firewall
- MySQL Enterprise Encryption
- MySQL Enterprise Audit

[Learn More »](#)

[Customer Download »](#) (Select Patches & Updates Tab, Product Search)

[Trial Download »](#) (Note - Select Product Pack: MySQL Database)

MySQL Cluster CGE (commercial)

MySQL Cluster is a real-time open source transactional database designed for fast, always-on access to data under high throughput conditions.

- MySQL Cluster
- MySQL Cluster Manager
- Plus, everything in MySQL Enterprise Edition

[Learn More »](#)

[Customer Download »](#) (Select Patches & Updates Tab, Product Search)

[Trial Download »](#) (Note - Select Product Pack: MySQL Database)

MySQL Community Edition (GPL)

[Community \(GPL\) Downloads »](#)

MySQL Community Downloads

MySQL Community Server (GPL)

(Current Generally Available Release: 8.0.16)

MySQL Community Server is the world's most popular open source database.

[DOWNLOAD](#)

MySQL Cluster (GPL)

(Current Generally Available Release: 7.6.10)

MySQL Cluster is a real-time, open source transactional database.

[DOWNLOAD](#)

MySQL Community Server 8.0.16

Select Operating System:

Microsoft Windows

[Looking for previous GA versions?](#)

Recommended Download:

MySQL Installer for Windows

All MySQL Products. For All Windows Platforms.
In One Package.

Starting with MySQL 5.6 the MySQL Installer package replaces the standalone MSI packages.

Windows (x86, 32 & 64-bit), MySQL Installer MSI



[Go to Download Page >](#)

Other Downloads:

Windows (x86, 64-bit), ZIP Archive (mysql-8.0.16-winx64.zip)	8.0.16	228.9M	Download
		MD5: 1a6646b047425cc1150b8a88751e721b Signature	
Windows (x86, 64-bit), ZIP Archive Debug Binaries & Test Suite (mysql-8.0.16-winx64-debug-test.zip)	8.0.16	336.2M	Download
		MD5: 854c5f5b21c01434e3a4c371bf a63d58 Signature	

Generally Available (GA) Releases

MySQL Installer 8.0.16

Select Operating System:

Microsoft Windows ▼

[Looking for previous GA versions?](#)

Windows (x86, 32-bit), MSI Installer (mysql-installer-web-community-8.0.16.0.msi)	8.0.16	20.0M	Download
Windows (x86, 32-bit), MSI Installer (mysql-installer-community-8.0.16.0.msi)	8.0.16	373.4M	Download



We suggest that you use the MD5 checksums and GnuPG signatures to verify the integrity of the packages you download.

- [Report and track bugs in the MySQL bug system](#)

Login »

using my Oracle Web account

Sign Up »

for an Oracle Web account

MySQL.com is using Oracle SSO for authentication. If you already have an Oracle Web account, click the Login link. If you don't, you can sign up for a free account by clicking the Sign Up link and following the instructions.

[No thanks, just start my download.](#)

☐ Developer Default



Installs all products needed for MySQL development purposes.

☒ Server only

Installs only the MySQL Server product.

☐ Client only

Installs only the MySQL Client products, without a server.



MySQL Installer

MySQL. Installer

MySQL Server 8.0.16

- High Availability
- Type and Networking
- Authentication Method
- Accounts and Roles**
- Windows Service
- Apply Configuration

Accounts and Roles

Root Account Password
Enter the password for the root account. Please remember to store this password in a secure place.

MySQL Root Password:

Repeat Password:

Password strength: **Weak**

MySQL User Accounts
Create MySQL user accounts for your users and applications. Assign a role to the user that consists of a set of privileges.

MySQL User Name	Host	User Role

1234로 설정하자.

(cmd 접속방법)

```
C:\Users\user>cd C:\Program Files\MySQL\MySQL Server 8.0\bin
C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql
ERROR 1045 (28000): Access denied for user 'ODBC'@'localhost' (using password: NO)
C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql -u root -p1234
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 13
Server version: 8.0.16 MySQL Community Server - GPL

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.


Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```


(프로그램으로 DB접속)



4) mysql 서비스 확인



5) HeidiSQL 설치

<http://heidisql.com>

6) Heidi SQL에서 사용자 계정 생성



도구 - 사용자관리자 메뉴에서 사용자 추가


아이디 : java

비번 : java1234

호스트 : localhost

전체권한에 체크






기본값으로 설치


=>실행

mysql에 접속해야한다.






저장을 누르면 다시 비밀번호를 묻지 않는다.



root이외에 사용자 계정을 하나 만든다.



id:user

pw:user

, id:java

pw:java1234

csv 파일을 mysql 테이블로 import하기 위하여 cmd에서 아래와 같이 mysql에 접속

```
mysql --local-infile -u root -p
```

```
create database airline;
use airline;
create table ontime (
  Year int,
  Month int,
  DayofMonth int,
  DayOfWeek int,
  DepTime int,
  CRSDepTime int,
  ArrTime int,
  CRSArrTime int,
  UniqueCarrier varchar(5),
  FlightNum int,
  TailNum varchar(8).
```

cmd 명령 프롬프트 - mysql --local-infile -u root -p

```
Microsoft Windows [Version 10.0.17134.765]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\chlwo>mysql --local-infile -u root -p
'mysql'은(는) 내부 또는 외부 명령, 실행할 수 있는 프로그램, 또는
배치 파일이 아닙니다.

C:\Users\chlwo>cd C:\Program Files\MySQL\MySQL Server 8.0\bin

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql
ERROR 1045 (28000): Access denied for user 'ODBC'@'localhost' (using password: NO)

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql --local-infile -u root -p
Enter password: ****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 18
Server version: 8.0.16 MySQL Community Server - GPL

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

```
create database airline;
```

```
use airline;
```

```
create table ontime (
```

```
    Year int,
```

```
    Month int,
```

```
    DayofMonth int,
```

```
    DayOfWeek int,
```

```
    DepTime int,
```

```
    CRSDepTime int,
```

```
    ArrTime int,
```

```
    CRSArrTime int,
```

```
    UniqueCarrier varchar(5),
```

```
    FlightNum int,
```

```
    TailNum varchar(8),
```

```
    ActualElapsedTime int,
```

```
    CRSElapsedTime int,
```

```
    AirTime int,
```

```
    ArrDelay int,
```

```
    DepDelay int,
```

```
    Origin varchar(3),
```

```
    Dest varchar(3),
```

```
    Distance int,
```

```
    TaxiIn int,
```

```
    TaxiOut int,
```

```
    Cancelled int,
```

```
create table ontime(
```

```
Year int,
```

```
Month int,
```

```
DayofMonth int,
```

```
DayOfWeek int,
```

```
DepTime int,
```

```
CRSDepTime int,
```

```
ArrTime int,
```

```
CRSArrTime int,
```

```
UniqueCarrier varchar(5),
```

```
FlightNum int,
```

```
TailNum varchar(8),
```

```
ActualElapsedTime int,
```

```
CRSElapsedTime int,
```

```
AirTime int,
```

```
ArrDelay int,
```

```
DepDelay int,  
Origin varchar(3),  
Dest varchar(3),  
Distance int,  
TaxiIn int,  
TaxiOut int,  
Cancelled int,  
CancellationCode varchar(1),  
Diverted varchar(1),  
CarrierDelay int,  
WeatherDelay int,  
NASDelay int,  
SecurityDelay int,  
LateAircraftDelay int  
);
```


이 페이지를
까?

If you download the data, please also subscribe to the data expo mailing list, so we can keep you up to date with any changes to the data:

Email:

Variable descriptions

Name	Description
1 Year	1987-2008
2 Month	1-12
3 DayofMonth	1-31
4 DayOfWeek	1 (Monday) - 7 (Sunday)
5 DepTime	actual departure time (local, hhmm)
6 CRSDepTime	scheduled departure time (local, hhmm)
7 ArrTime	actual arrival time (local, hhmm)
8 CRSArrTime	scheduled arrival time (local, hhmm)
9 UniqueCarrier	unique carrier code
10 FlightNum	flight number
11 TailNum	plane tail number
12 ActualElapsedTime	in minutes
13 CRSElapsedTime	in minutes
14 AirTime	in minutes
15 ArrDelay	arrival delay, in minutes
16 DepDelay	departure delay, in minutes
17 Origin	origin IATA airport code
18 Dest	destination IATA airport code
19 Distance	in miles
20 TaxiIn	taxi in time, in minutes
21 TaxiOut	taxi out time in minutes
22 Cancelled	was the flight cancelled?
23 CancellationCode	reason for cancellation (A = carrier, B = weather, C = NAS, D = security)
24 Diverted	1 = yes, 0 = no
25 CarrierDelay	in minutes
26 WeatherDelay	in minutes
27 NASDelay	in minutes
28 SecurityDelay	in minutes
29 LateAircraftDelay	in minutes

사이트에 나와있는 다음 필드명들을 가져온것이다.

```

mysql> use airline;
Database changed
mysql> create table ontime(
    -> Year int,
    -> Month int,
    -> DayofMonth int,
    -> DayOfWeek int,
    -> DepTime int,
    -> CRSDepTime int,
    -> ArrTime int,
    -> CRSArrTime int,
    -> UniqueCarrier varchar(5),
    -> FlightNum int,
    -> TailNum varchar(8),
    -> ActualElapsedTime int,
    -> CRSElapsedTime int,
    -> AirTime int,
    -> ArrDelay int,
    -> DepDelay int,
    -> Origin varchar(3),
    -> Dest varchar(3),
    -> Distance int,
    -> TaxiIn int,
    -> TaxiOut int,
    -> Cancelled int,
    -> CancellationCode varchar(1),
    -> Diverted varchar(1),
    -> CarrierDelay int,
    -> WeatherDelay int,
    -> NASDelay int,
    -> SecurityDelay int,
    -> LateAircraftDelay int
    -> );
Query OK, 0 rows affected (0.08 sec)

mysql>

```

```

mysql> show tables
    -> ;
+-----+
| Tables_in_airline |
+-----+
| ontime             |
+-----+
1 row in set (0.02 sec)

mysql>

```

```
mysql> desc ontime;
```

Field	Type	Null	Key	Default	Extra
Year	int(11)	YES		NULL	
Month	int(11)	YES		NULL	
DayofMonth	int(11)	YES		NULL	
DayOfWeek	int(11)	YES		NULL	
DepTime	int(11)	YES		NULL	
CRSDepTime	int(11)	YES		NULL	
ArrTime	int(11)	YES		NULL	
CRSArrTime	int(11)	YES		NULL	
UniqueCarrier	varchar(5)	YES		NULL	
FlightNum	int(11)	YES		NULL	
TailNum	varchar(8)	YES		NULL	
ActualElapsedTime	int(11)	YES		NULL	
CRSElapsedTime	int(11)	YES		NULL	
AirTime	int(11)	YES		NULL	
ArrDelay	int(11)	YES		NULL	
DepDelay	int(11)	YES		NULL	
Origin	varchar(3)	YES		NULL	
Dest	varchar(3)	YES		NULL	
Distance	int(11)	YES		NULL	
TaxiIn	int(11)	YES		NULL	
TaxiOut	int(11)	YES		NULL	
Cancelled	int(11)	YES		NULL	
CancellationCode	varchar(1)	YES		NULL	
Diverted	varchar(1)	YES		NULL	
CarrierDelay	int(11)	YES		NULL	
WeatherDelay	int(11)	YES		NULL	
NASDelay	int(11)	YES		NULL	
SecurityDelay	int(11)	YES		NULL	
LateAircraftDelay	int(11)	YES		NULL	

```
29 rows in set (0.01 sec)
```

```
mysql>
```

--데이터를 로딩하는데 각각 2분 정도씩 소요됨(CPU i5, RAM 16GB)

--2006년 7141922건

--2007년 7453215건

--2008년 7009728건

--총 21604865건

--로컬 텍스트 파일에서 import 할 수 있도록 옵션을 활성화시켜야 함

SET GLOBAL local_infile = true;

LOAD DATA LOCAL INFILE 'd:/data/airline/2006.csv' INTO TABLE ontime FIELDS
TERMINATED BY ',' LINES TERMINATED BY '\n';

LOAD DATA LOCAL INFILE 'd:/data/airline/2007.csv' INTO TABLE ontime FIELDS
TERMINATED BY ',' LINES TERMINATED BY '\n';

LOAD DATA LOCAL INFILE 'd:/data/airline/2008.csv' INTO TABLE ontime FIELDS
TERMINATED BY ',' LINES TERMINATED BY '\n';

--첫 라인 3개행 삭제

select * from ontime where year=0;

--3건 조회됨(40초 정도 소요되었음)

--레코드 갯수가 많아 에러가 발생할 경우 limit 절을 추가

delete from ontime where year=0 limit 3;

set global local_infile =true;

load data local infile 'D:\2006.csv' into table ontime fields terminated by ',' lines terminated by
'\n';

load data local infile 'D:\2007.csv' into table ontime fields terminated by ',' lines terminated by
'\n';

load data local infile 'D:\2008.csv' into table ontime fields terminated by ',' lines terminated by
'\n';


```
mysql> load data local infile 'd:/data/airline/2006.csv' into table ontime fields terminated by ',' lines terminated by '\n';
ERROR 2 (HY000): File 'd:\data\airline\2006.csv' not found (OS errno 2 - No such file or directory)
mysql> load data local infile 'D:\2006.csv' into table ontime fields terminated by ',' lines terminated by '\n';
Query OK, 7141923 rows affected, 65535 warnings (4 min 52.58 sec)
Records: 7141923 Deleted: 0 Skipped: 0 Warnings: 796380

mysql> load data local infile 'D:\2007.csv' into table ontime fields terminated by ',' lines terminated by '\n';
Query OK, 7453216 rows affected, 65535 warnings (5 min 1.37 sec)
Records: 7453216 Deleted: 0 Skipped: 0 Warnings: 1034226

mysql>
mysql>
mysql>
mysql> load data local infile 'D:\2008.csv' into table ontime fields terminated by ',' lines terminated by '\n';
Query OK, 7009729 rows affected, 65535 warnings (5 min 45.81 sec)
Records: 7009729 Deleted: 0 Skipped: 0 Warnings: 28602782

mysql>
```

The screenshot shows the HeidiSQL interface. The SQL editor contains the following query:

```
1 USE airline;
2 SELECT * FROM ontime WHERE YEAR=0;
3 DELETE FROM ontime WHERE YEAR=0 LIMIT 3;
```

The results pane shows the output of the SELECT query, displaying columns: Year, Month, DayOfMonth, DayOfWeek, DepTime, CRSDepTime, ArrTime, CRSArrTime, and UniqueCarrier. The data shows three rows with Year=0, Month=0, DayOfMonth=0, DayOfWeek=0, DepTime=0, CRSDepTime=0, ArrTime=0, CRSArrTime=0, and UniqueCarrier=Uniqu.

The status bar at the bottom shows the execution of the DELETE query, indicating that 3 rows were deleted.

delete를 할때 limit 3을 넣어줘도 메모리 초과가 뜬다.

따라서 너무 데이터가 크면, 연산이 불가능한 상황이 발생할 수 있는 것이다.

따라서 hadoop을 이용해서 처리를 해보려고한다.

다. HDFS에 데이터 업로드

/home/centos/data/airline 디렉토리의 csv 파일들을 하둡시스템의 input 디렉토리에 업로드

```
hdfs dfs -mkdir input
```

```
hdfs dfs -put /home/centos/data/airline input
```

```
[root@master ~]# hdfs dfs -ls input
Found 1 items
drwxr-xr-x - root supergroup          0 2019-06-10 17:14 input/airline
[root@master ~]# hdfs dfs -ls input/airline
Found 3 items
-rw-r--r--  2 root supergroup 672068096 2019-06-10 17:14 input/airline/2006.csv
-rw-r--r--  2 root supergroup 702878193 2019-06-10 17:14 input/airline/2007.csv
-rw-r--r--  2 root supergroup 689413344 2019-06-10 17:14 input/airline/2008.csv
[root@master ~]#
```

올라간것 확인

월별로 지연된 건수를 연도별 또는 월별로 값을 알고 싶다.

만약에 DBMS로 분석을 한다면,

select year, month, count(*)

from ontime

where depdelay > 0

group by year, month

order by year, month;

라. 실습예제(출발 지연 데이터 분석)

1) airline.AirlinePerformanceParser.java

```
package airline;

import org.apache.hadoop.io.Text;

public class AirlinePerformanceParser {

    private int year;
    private int month;

    private int arriveDelayTime = 0;
    private int departureDelayTime = 0;
    private int distance = 0;

    private boolean arriveDelayAvailable = true;
    private boolean departureDelayAvailable = true;

    private boolean distanceAvailable = true;

    private String uniqueCarrier;

    public AirlinePerformanceParser(Text text) {
        try {
            String[] columns = text.toString().split(",");

            // 운항 연도 설정
            year = Integer.parseInt(columns[0]);

            // 운항 월 설정
            month = Integer.parseInt(columns[1]);

            // 항공사 코드 설정
            uniqueCarrier = columns[8];
```

```

// 항공기 출발 지연 시간 설정
if (!columns[15].equals("NA")) {
    departureDelayTime = Integer.parseInt(columns[15]);
} else {
    departureDelayAvailable = false;
}

// 항공기 도착 지연 시간 설정
if (!columns[14].equals("NA")) {
    arriveDelayTime = Integer.parseInt(columns[14]);
} else {
    arriveDelayAvailable = false;
}

// 운항 거리 설정
if (!columns[18].equals("NA")) {
    distance = Integer.parseInt(columns[18]);
} else {
    distanceAvailable = false;
}
} catch (Exception e) {
    System.out.println("Error parsing a record ." + e.getMessage());
}
}

```

```

public int getYear() { return year; }
public int getMonth() { return month; }
public int getArriveDelayTime() { return arriveDelayTime; }
public int getDepartureDelayTime() { return departureDelayTime; }
public boolean isArriveDelayAvailable() { return arriveDelayAvailable; }
public boolean isDepartureDelayAvailable() { return departureDelayAvailable; }
public String getUniqueCarrier() { return uniqueCarrier; }
public int getDistance() { return distance; }
public boolean isDistanceAvailable() { return distanceAvailable; }
}

```

2) airline.DepartureDelayCountMapper.java

```
package airline;

import java.io.IOException;

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Mapper;

public class DepartureDelayCountMapper extends Mapper<LongWritable, Text,
Text, IntWritable> {

    // map 출력값
    private final static IntWritable outputValue = new IntWritable(1);
    // map 출력키

    private Text outputKey = new Text();

    public void map(LongWritable key, Text value, Context context) throws
IOException, InterruptedException {

        AirlinePerformanceParser parser = new AirlinePerformanceParser(value);

        // 출력키 설정
        outputKey.set(parser.getYear() + "," + parser.getMonth());

        if (parser.getDepartureDelayTime() > 0) {
            // 출력 데이터 생성
            context.write(outputKey, outputValue);
        }
    }
}
```


3) airline.DelayCountReducer.java

```
package airline;

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Reducer;

import java.io.IOException;

public class DelayCountReducer extends Reducer<Text, IntWritable, Text,
IntWritable> {

    private IntWritable result = new IntWritable();

    public void reduce(Text key, Iterable<IntWritable> values, Context context)
throws IOException, InterruptedException {

        int sum = 0;
        for (IntWritable value : values)
            sum += value.get();
        result.set(sum);
        context.write(key, result);
    }
}
```

4) DepartureDelayCount.java

```
package airline;

import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.input.TextInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
import org.apache.hadoop.mapreduce.lib.output.TextOutputFormat;

public class DepartureDelayCount {
    public static void main(String[] args) throws Exception {
        Configuration conf = new Configuration();

        // 입출력 데이터 경로 확인
        if (args.length != 2) {
            System.err.println("Usage: DepartureDelayCount <input> <output>");
            System.exit(2);
        }
        // Job 이름 설정
        Job job = Job.getInstance(conf, "DepartureDelayCount");
        // 입출력 데이터 경로 설정
        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));

        // Job 클래스 설정
        job.setJarByClass(DepartureDelayCount.class);
        // Mapper 클래스 설정
        job.setMapperClass(DepartureDelayCountMapper.class);
        // Reducer 클래스 설정
        job.setReducerClass(DelayCountReducer.class);
    }
}
```

```

// 입출력 데이터 포맷 설정
job.setInputFormatClass(TextInputFormat.class);
job.setOutputFormatClass(TextOutputFormat.class);

// 출력키 및 출력값 유형 설정
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);

job.waitForCompletion(true);
}
}

```

5) Hadoop.jar 파일로 export

6) 분석 작업 실행

args[0] input/airline args[1] dep_delay_count
hadoop jar jar파일 클래스이름 입력데이터폴더 출력결과폴더
실행 시간이 아주 오래 걸림

```
hadoop jar /home/centos/source/Hadoop.jar airline.DepartureDelayCount
input/airline dep_delay_count
```

결과 확인

```
hdfs dfs -cat dep_delay_count/part-r-00000
```

다시 분석 작업을 할 경우 출력 디렉토리 삭제 후 실행

```
hdfs dfs -rm -r dep_delay_count
```

하지만, sql을 통해서 한줄이면 되는 것을 자바 코딩으로 가져온다는 것이 굉장히 비효율적이라는 생각이 든다.

따라서, hive라는 기술을 사용하면, 분산처리시스템을 sql문을 사용하여 결과값을 갖고올 수 있다.

22분까지 들었음.