

# KUBERNETES

## CLOUD OPERATING SYSTEM




## K8 Secrets

Instructor: Magdy Salem



# Agenda

- What is a Secret?
- Use Cases
- Types of Secrets
- Creating Secrets
- Consuming Secrets in Pods
- Security Considerations



# What is a Secret?

---

- A Kubernetes object used to store sensitive information
- Data is base64 encoded
- Used to avoid embedding credentials in container images or YAML files
- Typical use: passwords, API keys, certificates



# Use Cases

---

- • Storing database credentials
- • TLS certificates for HTTPS communication
- • API tokens or OAuth credentials
- • SSH keys and Git credentials



# Types of Secrets

---

- Opaque (default): generic key-value pairs
- `kubernetes.io/dockerconfigjson`: for registry credentials
- `kubernetes.io/tls`: for TLS cert/key
- `bootstrap.kubernetes.io/token`: bootstrap tokens for cluster join



# Creating Secrets

---

- From literals:

```
kubectl create secret generic db-secret --from-literal=username=admin --from-literal=password=secret123
```

- From files:

```
kubectl create secret generic app-secret --from-file=config.json
```

- Declarative (YAML): base64 encode values manually



# Consuming Secrets in Pods

---

- As environment variables:
- As mounted files (volumes):
- Containers can read secrets securely at runtime



# Security Considerations

---

- Secrets are base64 encoded, not encrypted by default
- Enable encryption at rest using Kubernetes configuration
- Apply strict RBAC policies to restrict access
- Use read-only mounts and limit container privilege





Demo



Lab

