

Far Eastern University

THESIS TITLE

By

Elisha Sophia S. Borromeo,

Jan Edward F. Macagba,

Consuelo B. Mercado,

May Anne C. Tirado, Ph.D.

Adviser

An undergraduate thesis submitted to the

Department of Mathematics

Institute of Arts and Sciences

Far Eastern University

Sampaloc, Manila

In partial fulfillment of the requirements for the degree of

Bachelor of Science in Applied Mathematics

(Information Technology Track)

May 2022

Declaration of Authorship

We, Elisha Sophia S. Borromeo, , Jan Edward F. Macagba, , and Consuelo B. Mercado, , declare that this thesis titled, Thesis Title, and the work present in it are our own. We confirm that:

- This work was done wholly or mainly while in candidature for an undergraduate degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where we have consulted the published work of others, this is always clearly attributed.
- Where we have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely our work.
- We have acknowledged all main sources of help.
- Where the thesis is based on work done by ourselves jointly with others, we have made clear exactly what was done by others and what we have contributed ourselves.

Signed: _____

Date: _____

Endorsement

This is to certify that this undergraduate thesis titled, Thesis Title, prepared and submitted by Elisha Sophia S. Borromeo, , Jan Edward F. Macagba, , and Consuelo B. Mercado, , in partial fulfillment of the requirements for the degree of Bachelor of Science in Applied Mathematics (Information Technology Track) is hereby accepted.

May Anne C. Tirado, Ph.D.
Thesis Adviser

The Department of Mathematics endorses the acceptance of this undergraduate thesis in fulfillment of the requirements for the degree of Bachelor of Science in Applied Mathematics (Information Technology Track).

Genesis John G. Borja
Chair, Department of Mathematics

APPROVAL SHEET

This is to certify that this undergraduate thesis entitled **"Thesis Title"**, prepared and submitted by **Elisha Sophia S. Borromeo, Jan Edward F. Macagba,** and **Consuelo B. Mercado,** in partial fulfillment of the requirements for the degree of **Bachelor of Science in Applied Mathematics (Information Technology Track)** has been examined and was successfully defended on **May 12, 2022**.

May Anne C. Tirado, Ph.D.
Thesis Adviser

May Anne C. Tirado, Ph.D.
Research Course Instructor

Panel, Ph.D.
Thesis Examiner

Panel, Ph.D.
Thesis Examiner

Panel, Ph.D.
Thesis Examiner

Approved in partial fulfillment of the requirements for the degree of **Bachelor of Science in Applied Mathematics (Information Technology Track)**

Genesis John G. Borja
Chair, Department of Mathematics

Rowena Capulong Reyes, Ph.D.
Dean, Institute of Arts and Sciences

Far Eastern University
Institute of Arts and Sciences
Department of Mathematics

Bachelor of Science in Applied Mathematics
(Information Technology Track)

Abstract

Thesis Title

by
Elisha Sophia S. Borromeo,
Jan Edward F. Macagba,
Consuelo B. Mercado,

Type your abstract here. Your abstract should have a minimum of 150 words and a maximum of 300 words.

Acknowledgments

Type your acknowledgements here. It is customary to acknowledge special assistance from extramural agencies. There is no obligation that assistance received from members of the dissertation or thesis committee be acknowledged.
Acknowledgments should be couched in terms consistent with the scholarly nature of the work. Your name and the date should not appear on this page.

Contents

Abstract v

Acknowledgments vi

List of Tables xi

List of Figures xii

Chapter 1. The Problem and Its Background 1

1.1 Background of the Study 1

1.2 Statement of the Problem 3

1.3 General and Specific Objectives 3

1.3.1 General Objective 3

1.3.2 Specific Objectives 3

1.4 Conceptual Framework 4

1.5 Significance of the Study 5

1.5.1 Local Government Units 6

1.5.2 Disaster Risk Reduction and Management Offices 6

1.5.3 Researchers and the Academic Community 6

1.5.4 Future Researchers and Students 6

1.6 Scope and Limitations 7

1.7 Definition of Terms 8

Chapter 2. Review of Related Literature and Studies 10

2.1 Preliminaries 10

2.1.1 Fundamental Concepts of Flooding 10

2.1.2 Hydrodynamic Modeling 11

2.1.3 Artificial Neural Networks 12
2.1.4 Physics-Informed Neural Networks 13
2.2 Theoretical Background 14
2.2.1 Shallow Water Equations 14
2.2.2 Conservation of Mass 14
2.2.3 Conservation of Momentum 15
2.2.4 Governing Equations for Flood Flow 16
2.2.5 Physics-Informed Neural Network Framework 17
2.2.6 Loss Function of a PINN 18
2.3 Review of Related Literature 19
2.3.1 Flood Prediction and Modeling 20
2.3.2 Flood Modeling in Urban Areas 20
2.3.3 Shallow Water Equation Applications 21
2.3.4 Physics-Informed Neural Networks in Hydrology 22
2.3.5 Machine Learning for Flood Prediction 22
2.3.6 Flood Risk in Pasig City and Metro Manila 23
2.4 Review of Related Studies 24
2.4.1 SWE-Based Flood Prediction Studies 24
2.4.2 PINN-Based Flood Prediction Studies 25
2.4.3 PINN Applications in Hydrodynamics 25
2.4.4 Flood Prediction Studies in the Philippines 26
2.5 Synthesis of Literature 26
2.6 Research Gap 27
2.7 Relevance to the Present Study 28
2.8 Chapter Summary 29

Chapter 3. Research Methodology 30
3.1 Research Methodology 30
3.2 Research Design 30

3.3 Research Locale and Period . . . 31
3.4 Sources of Data . . . 31
3.5 Model Parameters, Variables, and Initial/Boundary Conditions . . . 32
3.6 Mathematical Model Formulation . . . 33
3.6.1 Governing Shallow Water Equations . . . 33
3.6.2 Conservation of Mass . . . 33
3.6.3 Conservation of Momentum . . . 33
3.6.4 Initial Conditions . . . 33
3.6.5 Boundary Conditions . . . 33
3.7 PINN Model Architecture . . . 34
3.7.1 Neural Network Structure . . . 34
3.7.2 Input and Output Variables . . . 34
3.7.3 Physics-Based Constraints . . . 34
3.7.4 Loss Function Formulation . . . 34
3.8 Data Preprocessing . . . 34
3.9 Model Training Procedure . . . 35
3.10 Model Validation and Evaluation . . . 35
3.11 Data Analysis Procedure . . . 36

Chapter 4. How to Cite References . . . 38

Appendix A.ThesisMain.tex File . . . 41
A.1 Preamble . . . 41
A.2 Basic Information . . . 42
A.3 Abstract and Acknowledgements . . . 44
A.4 Chapters and Appendix . . . 44
A.5 Document Outline . . . 44
A.6 Bibliography . . . 46
A.7 Folder Contents . . . 46

Appendix B.feumathstyle.sty file 48

Bibliography 49

List of Tables

List of Figures

1.1 Conceptual Framework of the SWE-Based Physics-Informed Neural Network for Flood Modeling in Pasig City 4

Chapter 1

The Problem and Its Background

1.1 Background of the Study

Flooding remains one of the major environmental challenges in the Philippines, particularly in highly urbanized areas where heavy rainfall, limited drainage capacity, and changes in land use contribute to the accumulation of surface water. In Metro Manila, flooding continues to affect residential communities, transportation systems, commercial establishments, and public infrastructure. Pasig City, which is situated near major waterways such as the Pasig River and is surrounded by densely developed urban areas, is among the locations that may experience flooding during periods of intense rainfall. These conditions highlight the importance of mathematical and computational approaches that can help predict flood behavior and improve the understanding of water movement in urban environments.

Flood prediction plays an important role in disaster risk reduction and urban planning. Accurate estimates of water depth and flow velocity can provide valuable information for identifying flood-prone areas and understanding the possible progression of inundation. Traditional hydrodynamic models simulate water movement by numerically solving governing mathematical equations. However, Guo, Guan, and Yu (2021) noted in their review of urban surface water flood modeling that computational efficiency, model complexity, and the availability of high-quality input data are important challenges, particularly in complex urban settings. Meanwhile, data-driven machine learning models can provide efficient predictions but may not fully incorporate the physical laws governing water flow.

The Shallow Water Equations (SWE) provide a mathematical representation of water

movement by describing the conservation of mass and momentum in depth-averaged flow. These equations are widely used in flood modeling because they account for changes in water depth and horizontal velocity over space and time (Guo et al., 2021). However, solving the SWE numerically may involve computational challenges, especially when dealing with complex terrain and spatially varying conditions.

Physics-Informed Neural Networks (PINNs) offer an alternative computational approach. Introduced by Raissi, Perdikaris, and Karniadakis (2019), PINNs incorporate governing differential equations into the loss function of a neural network, so that the residuals of the equations are minimized together with the data error. This allows the model to learn predictions while considering physical constraints. Recent studies have applied this idea to flooding. Liu et al. (2026) developed a PINN framework for urban flood depth prediction in Hongshan District, Wuhan, China, and Tian, Ding, Su, Huang, and Chen (2025) investigated PINNs for solving the two-dimensional SWE with terrain topography and rainfall source terms.

Despite these developments, the results of these studies were obtained using their own study areas, datasets, and model configurations, and they do not automatically establish how a SWE-based PINN performs in Pasig City. The accuracy and physical consistency of such a model must therefore be evaluated rather than assumed.

In this study, a Shallow Water Equation-based Physics-Informed Neural Network will be developed and implemented in a selected area of Pasig City. The proposed model will be evaluated in terms of its convergence, approximation error, and ability to satisfy physical constraints. Its performance will also be compared with a classical numerical method to determine its effectiveness in solving the Shallow Water Equations for flood modeling.

1.2 Statement of the Problem

Flooding remains a significant concern in urban areas such as Pasig City, where rainfall, terrain elevation, and water flow conditions influence flood behavior. Predicting the movement and depth of floodwater requires a mathematical model capable of representing the physical processes governing water flow. Although classical numerical methods can solve the Shallow Water Equations, their computational requirements may pose challenges. Meanwhile, data-driven approaches may not fully account for the physical laws governing water movement.

This study aims to develop and evaluate a Shallow Water Equation-based Physics-Informed Neural Network (PINN) for flood modeling in Pasig City. Specifically, it seeks to determine the capability of the proposed model to approximate the solutions of the Shallow Water Equations while satisfying the physical constraints of water flow.

The study will seek to answer the following research question:

> How can a Shallow Water Equation-based Physics-Informed Neural Network be developed and evaluated for predicting flood behavior in Pasig City?

1.3 General and Specific Objectives

1.3.1 General Objective

The general objective of this study is to develop and evaluate a Shallow Water Equation-based Physics-Informed Neural Network for predicting flood behavior in Pasig City.

1.3.2 Specific Objectives

Specifically, this study aims to:

1. Formulate the Shallow Water Equations as the governing mathematical model for flood and water flow behavior in Pasig City.

2. Develop a Physics-Informed Neural Network that incorporates the Shallow Water Equations into its training process.

3. Evaluate the convergence and approximation error of the proposed PINN in solving the Shallow Water Equations.

4. Compare the performance of the PINN with a classical numerical method using appropriate error metrics.

5. Assess the model's ability to satisfy physical constraints, particularly the conservation of water mass and momentum.

1.4 Conceptual Framework




Figure 1.1: Conceptual Framework of the SWE-Based Physics-Informed Neural Network for Flood Modeling in Pasig City

The conceptual framework of the study follows an Input-Process-Output (IPO) model. It illustrates how the input data are processed through a Physics-Informed Neural Network incorporating the Shallow Water Equations to generate predictions of water depth, horizontal water velocity, and flood behavior. The resulting predictions will be evaluated by comparing the PINN with a classical numerical method.

1. **Input Data:** The input data consist of rainfall data, terrain elevation, initial conditions, and boundary conditions. These inputs provide the environmental and mathematical information required for the flood modeling process.

2. **Process:** The input data will be processed using a SWE-based Physics-Informed Neural Network. The governing Shallow Water Equations will be incorporated into the model's loss function as physical constraints. The network will be trained to minimize the data error and the residuals of the governing equations while satisfying the specified initial and boundary conditions.

3. **Output:** The model will generate predictions of water depth, horizontal water velocity, and flood behavior across the selected study area in Pasig City.

4. **Evaluation:** The PINN predictions will be compared with the solutions generated by a classical numerical method. The evaluation will consider convergence, approximation error, and physical consistency, particularly the conservation of mass and momentum.

1.5 Significance of the Study

This study aims to contribute to the development and evaluation of physics-informed computational approaches for flood modeling. By integrating the Shallow Water Equations into a neural network, the research will examine how physical constraints can be incorporated into flood prediction and how the resulting model performs compared with a classical numerical method.

1.5.1 Local Government Units

The findings of the study may provide useful information to local government units, particularly Pasig City, regarding the potential application of physics-informed neural networks in flood modeling. The predicted water depth and velocity may help improve the understanding of flood behavior in selected areas. However, the model is intended as a research-based computational approach and will not replace official flood forecasting systems.

1.5.2 Disaster Risk Reduction and Management Offices

The study may contribute to the development of computational approaches that can support flood assessment and disaster risk reduction. The results may provide additional insights into the movement and accumulation of water during flooding, which could be useful in understanding flood-prone areas.

1.5.3 Researchers and the Academic Community

This study may serve as a reference for researchers interested in mathematical modeling, numerical solutions of partial differential equations, and Physics-Informed Neural Networks. The comparison between the PINN and a classical numerical method may contribute to further investigations into the accuracy, convergence, and physical consistency of physics-informed models.

1.5.4 Future Researchers and Students

The study may serve as a foundation for future research involving PINNs and the Shallow Water Equations. Future researchers may extend the model by incorporating more detailed terrain data, additional hydrological variables, or more complex representations of urban drainage systems.

1.6 Scope and Limitations

This study will focus on the development and evaluation of a Shallow Water Equation-based Physics-Informed Neural Network for flood modeling in Pasig City, Philippines. The research will utilize the Shallow Water Equations as the governing mathematical model to represent the conservation of mass and momentum in water flow. The PINN will be developed to predict water depth and horizontal water velocity based on the available rainfall data, terrain elevation, initial conditions, and boundary conditions.

The study will evaluate the performance of the proposed PINN by comparing its numerical predictions with those obtained from a classical numerical method. The comparison will focus on convergence, approximation error, and physical consistency. Appropriate error metrics will be used to assess the differences between the two methods.

The scope of the study is limited to the selected study area within Pasig City and the available datasets. The accuracy of the model may be affected by the quality, completeness, and spatial and temporal resolution of the rainfall and terrain data. The availability of observed flood depth and water velocity measurements may also limit the extent of model validation.

Furthermore, the mathematical model will rely on the assumptions associated with the Shallow Water Equations, including the representation of water flow as a depth-averaged process. The study will not fully represent every physical factor that may influence urban flooding, such as highly detailed drainage network behavior, localized obstructions, or complex interactions between surface water and underground infrastructure. The model's computational performance may also depend on the available hardware and training configuration.

The study will primarily assess the PINN as a mathematical and computational approach to solving the Shallow Water Equations. Therefore, the findings will not necessarily establish the model's readiness for real-time operational flood forecasting or its applicability to all flood-prone areas in the Philippines.

1.7 Definition of Terms

The following terms are defined conceptually and operationally to provide a clearer understanding of the concepts used in this study.

- **Shallow Water Equations (SWE).** The Shallow Water Equations are a system of partial differential equations derived from the principles of conservation of mass and momentum. In this study, they serve as the governing mathematical model for representing water flow and flood behavior in Pasig City.
- **Physics-Informed Neural Network (PINN).** A Physics-Informed Neural Network is a neural network that incorporates governing physical equations into its training process through a loss function. In this study, the PINN will use the Shallow Water Equations as physical constraints to predict water depth and horizontal water velocity.
- **Flood Modeling.** Flood modeling refers to the mathematical and computational representation of flood behavior. In this study, it involves simulating water movement and estimating water depth and velocity within the selected study area.
- **Water Depth.** Water depth refers to the vertical distance between the ground surface and the water surface. In this study, it is one of the primary variables predicted by the SWE-based PINN.
- **Horizontal Water Velocity.** Horizontal water velocity refers to the rate and direction of water movement along the horizontal plane. In this study, it is represented by the velocity components in the x- and y-directions.
- **Initial Conditions.** Initial conditions specify the state of the modeled water system at the beginning of the simulation. In this study, they define the initial water depth and velocity values used in solving the Shallow Water Equations.
- **Boundary Conditions.** Boundary conditions describe the behavior of water flow along the boundaries of the computational domain. In this study, they

define the constraints applied at the edges of the selected flood modeling area.

- **Approximation Error.** Approximation error refers to the difference between the solution produced by a computational method and a reference solution. In this study, it will be used to evaluate the accuracy of the PINN in comparison with the classical numerical method.
- **Convergence.** Convergence refers to the tendency of a numerical or computational solution to approach a stable or reference solution as the relevant approximation or training process progresses. In this study, it will be evaluated to examine the behavior of the PINN and the classical numerical method in solving the Shallow Water Equations.
- **Conservation of Mass.** Conservation of mass is the physical principle stating that mass is neither created nor destroyed within a system, although it may enter or leave through the system boundaries. In this study, it is represented by the continuity equation of the Shallow Water Equations.
- **Conservation of Momentum.** Conservation of momentum is the physical principle describing how the momentum of water changes due to forces such as gravity, friction, and flow interactions. In this study, it is represented by the momentum equations of the Shallow Water Equations.

Chapter 2

Review of Related Literature and Studies

This chapter presents the concepts, theories, literature, and previous studies relevant to the development of a Shallow Water Equation-based Physics-Informed Neural Network (PINN) for flood prediction in Pasig City. The discussion establishes the mathematical and computational foundation of the proposed model by examining flooding, hydrodynamic modeling, artificial neural networks, Physics-Informed Neural Networks, and the Shallow Water Equations. It also reviews previous applications of these approaches in flood modeling and identifies the research gap addressed by the present study.

2.1 Preliminaries

This section introduces the fundamental concepts necessary for understanding the proposed study. It discusses the characteristics of flooding, hydrodynamic modeling, artificial neural networks, and Physics-Informed Neural Networks. These concepts provide the foundation for understanding how the governing equations of water flow can be incorporated into a neural network for flood prediction.

2.1.1 Fundamental Concepts of Flooding

Flooding occurs when water accumulates in an area beyond its normal capacity to contain or drain it. It may result from heavy rainfall, overflowing rivers, inadequate drainage capacity, and changes in land use. In urban areas, the presence of buildings, roads, and other impermeable surfaces can reduce the infiltration of water into the ground, resulting in increased surface runoff. When the amount of runoff exceeds the capacity of the surrounding drainage system, water may accumulate on streets and other low-lying

areas.

Flood behavior is influenced by several hydrological and physical variables. Rainfall refers to the amount of water supplied to the ground through precipitation. Surface runoff is the portion of rainfall that flows over the ground instead of infiltrating into the soil. Terrain elevation influences the direction and distribution of water flow, while drainage systems provide pathways for collecting and removing excess water.

Water depth and flow velocity are important variables in flood modeling. Water depth refers to the vertical distance between the ground surface and the water surface. Flow velocity describes the speed and direction of water movement. In a two-dimensional flood model, velocity is commonly represented by two components, namely the velocity in the x-direction and the velocity in the y-direction.

These variables are important in understanding the development and movement of floodwater. In the present study, water depth and horizontal water velocity will be the primary variables predicted by the proposed SWE-based PINN.

2.1.2 Hydrodynamic Modeling

Hydrodynamic modeling refers to the mathematical and computational representation of water movement. It uses governing equations derived from physical principles to describe how water changes in depth, velocity, and distribution over space and time. Hydrodynamic models are commonly used in flood simulation, river flow analysis, coastal processes, and water resource management.

The movement of water can be described using mathematical equations such as the Navier-Stokes equations. However, these equations may be simplified under certain assumptions to represent shallow water flow. One commonly used formulation is the Shallow Water Equations, which describe the conservation of mass and momentum in depth-averaged water flow.

Traditional hydrodynamic models solve governing equations using numerical methods. Common approaches include finite difference, finite volume, and finite element methods.

These methods approximate the mathematical solution over a computational domain divided into discrete spatial and temporal points.

Although numerical methods are widely used in flood modeling, their computational requirements may increase when the study area is large or when detailed terrain and flow conditions are considered. Urban flood modeling may also require detailed information regarding terrain elevation, rainfall, and drainage systems. These requirements motivate the investigation of alternative computational approaches, including Physics-Informed Neural Networks.

2.1.3 Artificial Neural Networks

Artificial Neural Networks (ANNs) are computational models inspired by the structure of biological neural networks. They consist of interconnected processing units called neurons, which are organized into input, hidden, and output layers. Each neuron receives information, applies weights and biases, and passes the result through an activation function.

A general mathematical representation of a neural network is given by

$$\mathbf{y} = f_\theta(\mathbf{x}),$$

where $\mathbf{x}$ represents the input variables, $\mathbf{y}$ represents the predicted output, f_θ denotes the neural network function, and θ represents the trainable parameters of the network.

During training, the network adjusts its parameters to minimize a loss function that measures the difference between predicted and reference values. Optimization algorithms such as gradient descent and its variants are commonly used to update the network parameters.

ANNs can approximate complex nonlinear relationships between input and output variables. In flood prediction, they may be trained using rainfall, water level, terrain, or historical flood observations to estimate flood-related variables.

However, a purely data-driven ANN depends heavily on the quality and quantity of its training data. Its predictions may not automatically satisfy the physical laws governing water flow. This limitation provides the motivation for incorporating physical equations into the neural network training process.

2.1.4 Physics-Informed Neural Networks

Physics-Informed Neural Networks (PINNs) are neural networks that incorporate governing physical equations into their training process. Rather than relying exclusively on observed data, PINNs use mathematical equations to impose physical constraints on the predicted solutions.

Raissi, Perdikaris, and Karniadakis (2019) introduced a framework in which differential equations are incorporated into neural network loss functions. Through this approach, the network is trained to approximate solutions that are consistent with both available data and the governing physical laws.

A PINN generally consists of a neural network that approximates the solution of a physical system and a loss function that includes the residuals of the governing equations. The residuals measure how closely the predicted values satisfy the mathematical equations.

For flood modeling, the Shallow Water Equations can be incorporated into the PINN loss function. The network can then be trained to predict water depth and velocity while minimizing the residuals of the equations describing the conservation of mass and momentum.

One potential advantage of PINNs is their ability to combine observational data with physical constraints. This may be useful when available flood observations are limited. However, PINNs also have limitations, including training difficulties, sensitivity to loss weighting, and challenges in approximating discontinuous flow behavior. Therefore, their accuracy and physical consistency must be evaluated rather than assumed.

2.2 Theoretical Background

This section presents the mathematical and computational theories that serve as the foundation of the proposed SWE-based PINN. It discusses the governing equations of shallow water flow, the principles of conservation of mass and momentum, and the mathematical structure of the PINN.

2.2.1 Shallow Water Equations

The Shallow Water Equations (SWE) are a system of partial differential equations used to describe the movement of water with a relatively small depth compared with its horizontal dimensions. They are derived from the principles of conservation of mass and momentum and are commonly used in flood modeling.

The two-dimensional SWE represent water flow through the horizontal directions while accounting for changes in water depth, terrain elevation, rainfall, and friction. The equations are commonly derived from the Navier-Stokes equations under assumptions such as hydrostatic pressure distribution and depth-averaged horizontal velocity.

In the present study, the SWE will serve as the governing mathematical model for describing flood behavior in the selected study area of Pasig City. The equations will be incorporated into the Physics-Informed Neural Network to constrain its predictions.

2.2.2 Conservation of Mass

The principle of conservation of mass states that mass cannot be created or destroyed within a system, although it may enter or leave the system through external sources or boundaries.

For shallow water flow, conservation of mass is represented by the continuity equation. In two dimensions, the equation may be expressed as

$$\frac{\partial h}{\partial t} + \frac{\partial (hu)}{\partial x} + \frac{\partial (hv)}{\partial y} = R - D,$$

where h is the water depth, u and v are the horizontal velocity components, R is the rainfall input, and D is a simplified drainage-removal rate.

The term $\frac{\partial h}{\partial t}$ represents the rate of change of water depth over time. The terms $\frac{\partial (hu)}{\partial x}$ and $\frac{\partial (hv)}{\partial y}$ represent the changes in water flux in the horizontal directions.

The rainfall term R accounts for the addition of water to the surface. The drainage term D represents the removal of water from the modeled surface domain. For consistency, R and D must use compatible units, such as meters per second.

In this study, drainage will be represented through a simplified removal term when sufficient data are available. This representation does not constitute a complete simulation of an underground drainage network. Detailed pipe flow, manhole interactions, and surface-to-sewer exchange may require a separate coupled drainage model.

2.2.3 Conservation of Momentum

The principle of conservation of momentum describes how the movement of water changes due to forces acting on the flow. These forces include gravity, pressure gradients, terrain slope, and friction.

The two-dimensional momentum equations for shallow water flow may be expressed in conservative form as

$$\frac{\partial (hu)}{\partial t} + \frac{\partial}{\partial x}\left(hu^2 + \frac{1}{2}gh^2\right) + \frac{\partial (huv)}{\partial y} = -gh\frac{\partial z}{\partial x} + S_{fx},$$

and

$$\frac{\partial (hv)}{\partial t} + \frac{\partial (huv)}{\partial x} + \frac{\partial}{\partial y}\left(hv^2 + \frac{1}{2}gh^2\right) = -gh\frac{\partial z}{\partial y} + S_{fy},$$

where g is the gravitational acceleration, z is the terrain elevation, and S_{fx} and S_{fy} are the friction source terms in the respective directions.

The left-hand side of each equation describes the temporal and spatial changes in momentum. The right-hand side represents the forces acting on the water.

The terrain slope terms describe the influence of ground elevation on water movement. The friction source terms represent resistance caused by the ground surface. Friction may be represented using an appropriate formulation, such as Manning's equation, depending on the model configuration and the availability of surface roughness data.

In the proposed study, these equations will provide the physical constraints for the prediction of horizontal water velocity and flood behavior.

2.2.4 Governing Equations for Flood Flow

The governing equations of the proposed model consist of the continuity equation and the two momentum equations. Together, they represent the conservation of mass and momentum in two-dimensional shallow water flow.

The system may be written as

$$\begin{cases} \dfrac{\partial h}{\partial t} + \dfrac{\partial (hu)}{\partial x} + \dfrac{\partial (hv)}{\partial y} = R - D, \\ \dfrac{\partial (hu)}{\partial t} + \dfrac{\partial}{\partial x}\left(hu^2 + \dfrac{1}{2}gh^2\right) + \dfrac{\partial (huv)}{\partial y} = -gh\dfrac{\partial z}{\partial x} + S_{fx}, \\ \dfrac{\partial (hv)}{\partial t} + \dfrac{\partial (huv)}{\partial x} + \dfrac{\partial}{\partial y}\left(hv^2 + \dfrac{1}{2}gh^2\right) = -gh\dfrac{\partial z}{\partial y} + S_{fy}. \end{cases}$$

The system describes the changes in water depth and horizontal velocity over the computational domain.

The terrain elevation function $z(x, y)$ provides information about the ground surface. Rainfall $R(x, y, t)$ represents the water input, while $D(x, y, t)$ may be used to represent a simplified drainage-removal rate. Initial and boundary conditions are also necessary to define the state of the water system at the beginning of the simulation and along the boundaries of the modeled area.

The governing equations will be used to construct the physics-based residuals of the proposed PINN.

2.2.5 Physics-Informed Neural Network Framework

The proposed PINN will approximate the solution of the governing equations using a neural network. The network will receive spatial, temporal, and environmental variables as inputs and generate estimates of water depth and horizontal water velocity.

The proposed input and output variables are represented as

$$\mathbf{X} = (x, y, t, R, z, D),$$

and

$$\mathbf{Y}_\theta = (h_\theta, u_\theta, v_\theta),$$

where θ represents the trainable parameters of the neural network.

The input variables describe the location, time, rainfall, terrain elevation, and simplified drainage representation. The output variables represent the predicted water depth and the horizontal velocity components.

The network may be expressed as

$$\mathbf{Y}_\theta = f_\theta(x, y, t, R, z, D).$$

The governing equations are incorporated into the training process through their residuals. These residuals are calculated using automatic differentiation, which allows the neural network to compute the required derivatives of its predicted outputs with respect to spatial and temporal coordinates.

The continuity residual may be defined as

$$r_c = \frac{\partial h_\theta}{\partial t} + \frac{\partial (h_\theta u_\theta)}{\partial x} + \frac{\partial (h_\theta v_\theta)}{\partial y} - R + D.$$

The momentum residuals may be defined as

$$r_x = \frac{\partial(h_\theta u_\theta)}{\partial t} + \frac{\partial}{\partial x}\left(h_\theta u_\theta^2 + \frac{1}{2}gh_\theta^2\right) + \frac{\partial(h_\theta u_\theta v_\theta)}{\partial y} + gh_\theta\frac{\partial z}{\partial x} - S_{fx},$$

and

$$r_y = \frac{\partial(h_\theta v_\theta)}{\partial t} + \frac{\partial(h_\theta u_\theta v_\theta)}{\partial x} + \frac{\partial}{\partial y}\left(h_\theta v_\theta^2 + \frac{1}{2}gh_\theta^2\right) + gh_\theta\frac{\partial z}{\partial y} - S_{fy}.$$

The residuals measure the extent to which the network's predictions satisfy the governing equations. Ideally, the residuals approach zero at the sampled points within the computational domain.

2.2.6 Loss Function of a PINN

The loss function is an essential component of the PINN because it determines how the network parameters are updated during training. The proposed model will use a composite loss function that combines data-based and physics-based constraints.

The total loss function may be expressed as

$$\mathcal{L}(\theta) = \mathcal{L}_{data} + \lambda_{PDE}\mathcal{L}_{PDE} + \lambda_{BC}\mathcal{L}_{BC} + \lambda_{IC}\mathcal{L}_{IC},$$

where $\mathcal{L}_{data}$ is the data loss, $\mathcal{L}_{PDE}$ is the governing-equation residual loss, $\mathcal{L}_{BC}$ is the boundary condition loss, $\mathcal{L}_{IC}$ is the initial condition loss, and the λ terms are weighting parameters.

The data loss measures the difference between the predicted values and the available reference observations. It may be represented using the mean squared error:

$$\mathcal{L}_{data} = \frac{1}{N_d}\sum_{i=1}^{N_d}\left\|\mathbf{Y}_\theta^{(i)} - \mathbf{Y}_{ref}^{(i)}\right\|^2,$$

where N_d is the number of reference data points and $\mathbf{Y}_{ref}$ represents the observed or reference solution.

The physics-based loss measures the residuals of the governing equations:

$$\mathcal{L}_{PDE} = \frac{1}{N_f} \sum_{i=1}^{N_f} \left[(r_c^{(i)})^2 + (r_x^{(i)})^2 + (r_y^{(i)})^2 \right],$$

where N_f is the number of collocation points sampled within the computational domain.

The boundary condition loss measures the difference between the network predictions and the prescribed boundary values:

$$\mathcal{L}_{BC} = \frac{1}{N_b} \sum_{i=1}^{N_b} \left\| \mathbf{Y}_\theta^{(i)} - \mathbf{Y}_{BC}^{(i)} \right\|^2.$$

The initial condition loss measures the difference between the predicted and prescribed initial states:

$$\mathcal{L}_{IC} = \frac{1}{N_i} \sum_{i=1}^{N_i} \left\| \mathbf{Y}_\theta(x_i, y_i, 0) - \mathbf{Y}_{IC}^{(i)} \right\|^2.$$

The weighting parameters determine the relative importance of the individual loss components. Appropriate weighting is necessary because the terms may have different numerical scales. The loss function will guide the network toward approximating the reference solution while satisfying the physical constraints of water flow.

2.3 Review of Related Literature

This section discusses existing literature and theoretical discussions related to flood prediction, hydrodynamic modeling, the Shallow Water Equations, and the application of machine learning and Physics-Informed Neural Networks.

2.3.1 Flood Prediction and Modeling

Flood prediction and modeling involve estimating the behavior of floodwater under specified environmental and hydrological conditions. These approaches may be used to estimate water depth, flow velocity, inundation extent, and the temporal development of flooding.

Traditional flood modeling commonly relies on hydrological and hydrodynamic methods. Hydrological models describe the transformation of rainfall into runoff, while hydrodynamic models represent the movement of water through rivers, channels, and surface areas. The selection of a modeling approach depends on the purpose of the study, the available data, and the level of detail required.

Guo, Guan, and Yu (2021) reviewed urban surface water flood modeling approaches and discussed the use of drainage network models, shallow-water-based models, hydrogeomorphic approaches, and other methods. Their review emphasized the importance of considering computational efficiency, model complexity, and data availability when selecting a flood modeling approach.

The literature indicates that flood prediction requires a balance between computational efficiency and the ability to represent physical processes. This consideration is relevant to the present study, which investigates the use of a PINN as an alternative computational approach for solving the governing equations of flood flow.

2.3.2 Flood Modeling in Urban Areas

Urban flood modeling presents additional challenges because of the complex characteristics of developed environments. Buildings, roads, drainage networks, and variations in terrain elevation influence the direction and accumulation of water. Impermeable surfaces may also increase surface runoff during rainfall events.

Guo et al. (2021) explained that urban surface water flood models may use simplified or full forms of the Shallow Water Equations. The complexity of the model affects the required input data, computational cost, and the amount of flood information that can

be represented.

Urban flood models may also consider the interaction between surface water and underground drainage systems. However, detailed representations of drainage networks require information about pipes, inlets, outlets, and other infrastructure. The availability of these data may affect the complexity and reliability of the model.

For the present study, urban flood modeling will focus on the selected area of Pasig City. Terrain elevation and rainfall will be considered as important inputs. Drainage may be represented through a simplified removal term, subject to the availability of suitable data. The study will not attempt to fully simulate every component of the underground drainage infrastructure.

2.3.3 Shallow Water Equation Applications

The Shallow Water Equations are widely applied in flood modeling because they describe the conservation of mass and momentum in depth-averaged water flow. They can be used to estimate the movement and distribution of water over terrain.

SWE-based models may be implemented using different numerical methods, including finite difference, finite volume, and finite element approaches. These methods approximate the governing equations using discrete computational representations.

Guo et al. (2021) discussed the application of shallow-water-based models to urban surface flooding and noted their ability to provide spatially distributed information about floodwater depth and velocity. The review also highlighted that the computational cost and data requirements of such models may increase when detailed urban features are considered.

The SWE are relevant to the present study because they provide the physical basis for the proposed PINN. By incorporating the equations into the neural network loss function, the model will be trained to approximate flood behavior while considering the governing principles of water flow.

2.3.4 Physics-Informed Neural Networks in Hydrology

Physics-Informed Neural Networks have been investigated as a computational approach for solving differential equations and incorporating physical knowledge into machine learning models. The framework introduced by Raissi et al. (2019) combines neural network approximation with governing differential equations through a composite loss function.

In hydrological applications, PINNs may be used to represent processes governed by mathematical equations, such as water flow, groundwater movement, and rainfall-related processes. Their ability to combine physical constraints and available observations makes them relevant to problems in which data may be limited or incomplete.

However, the use of PINNs in hydrological modeling also presents challenges. The optimization process may be affected by the nonlinear behavior of the governing equations, differences in the scales of loss components, and the distribution of training points. Therefore, the performance of a PINN depends not only on the physical equations but also on its architecture, training configuration, and evaluation process.

The present study applies this framework to the two-dimensional Shallow Water Equations. The governing equations will be incorporated into the PINN loss function to constrain the predicted water depth and horizontal velocity.

2.3.5 Machine Learning for Flood Prediction

Machine learning approaches have been used in flood prediction to identify relationships between rainfall, water levels, and flood-related variables. Artificial Neural Networks and Long Short-Term Memory (LSTM) networks are examples of approaches that can learn patterns from historical or simulated data.

LSTM networks are designed to process sequential information. Their structure allows them to learn temporal relationships in data, making them suitable for tasks involving rainfall sequences, water-level records, and time-dependent flood behavior.

Data-driven approaches may provide efficient predictions when sufficient training data

are available. However, their predictions depend on the patterns learned from the training data. They do not automatically satisfy the governing equations of water flow unless physical constraints are explicitly incorporated.

PINNs differ from purely data-driven models because they include physical equations as part of the training objective. This distinction is important in the present study, where the proposed model will be evaluated based on both approximation error and physical consistency.

A classical numerical method will be used as the primary comparison method for assessing the PINN's approximation of the Shallow Water Equations. If an LSTM model is included as an additional baseline, its prediction accuracy may be evaluated using the same reference dataset and error metrics. The LSTM comparison will be treated as a separate data-driven evaluation.

2.3.6 Flood Risk in Pasig City and Metro Manila

Metro Manila is a highly urbanized region where flood behavior may be influenced by rainfall, river systems, terrain, and urban infrastructure. Flood modeling in the region requires consideration of both the hydrological conditions and the characteristics of the built environment.

The Marikina-Pasig River Basin has been the subject of flood modeling research. A study published in the Journal of Hydrology: Regional Studies in 2022 developed an integrated multiscale rainfall-runoff and inundation model for an extreme rainfall event in the Marikina-Pasig River Basin. The study examined floodwater accumulation, depth, and flow source, demonstrating the relevance of integrated modeling approaches in the Philippine setting.

The study provides regional context for the present research because Pasig City is located within the broader Metro Manila urban environment associated with the Pasig River system. However, the results of a basin-level study cannot automatically be applied to every location within Pasig City. Local terrain, rainfall conditions, and available flood

observations must be considered.

The present study will focus on the development and evaluation of a SWE-based PINN within a selected study area in Pasig City. Its findings will be limited to the modeled area and the datasets used in the implementation.

2.4 Review of Related Studies

This section presents previous research studies directly related to the proposed study. The discussion focuses on the methods, governing equations, datasets, findings, and limitations of the selected studies.

2.4.1 SWE-Based Flood Prediction Studies

SWE-based flood prediction studies commonly use numerical methods to solve the governing equations of water flow. These methods include finite difference, finite volume, and finite element approaches. They are used to approximate water depth and velocity over a computational domain.

Guo et al. (2021) conducted a comprehensive review of urban surface water flood modeling approaches. Their study discussed the application of full and simplified Shallow Water Equations in urban flood simulation. It also identified computational efficiency, model complexity, and the availability of high-quality input data as important challenges in urban flood modeling.

The review provides a foundation for the present study because it establishes the relevance of SWE-based approaches in representing urban surface water flooding. However, the review primarily examines existing modeling approaches rather than developing a PINN specifically for Pasig City.

The present study builds on the use of SWE as the governing mathematical model and investigates whether a neural network can approximate its solutions while maintaining physical consistency.

2.4.2 PINN-Based Flood Prediction Studies

Liu et al. (2026) developed a PINN framework for urban flood depth prediction that integrates data-driven information with physical constraints. The study used the Shallow Water Equations to incorporate physical principles into the neural network and examined the use of feature selection to improve the efficiency of urban waterlogging prediction.

The study is particularly relevant to the present research because it directly applies PINNs to urban flood depth prediction. It demonstrates the use of physical constraints within a neural network framework and highlights the potential of combining data-driven information with governing equations.

However, the study was conducted in Hongshan District, Wuhan, China. Its findings and model configuration may not directly represent the conditions of Pasig City. Differences in terrain, rainfall patterns, drainage infrastructure, and available observations may affect model performance.

The present study will investigate the application of a SWE-based PINN to a selected area of Pasig City. It will focus on the convergence and approximation error of the model and its ability to satisfy the conservation laws of water flow. The PINN will also be compared with a classical numerical method using an appropriate reference solution.

2.4.3 PINN Applications in Hydrodynamics

Tian et al. (2025) investigated the use of Physics-Informed Neural Networks for solving the two-dimensional Shallow Water Equations with terrain topography and rainfall source terms. Their study examined different equation formulations and techniques for improving PINN performance.

The researchers evaluated PINNs through a series of static and dynamic flow cases involving terrain and rainfall. Their findings indicated that the formulation of the governing equations can influence the performance of the PINN. The study also discussed challenges related to training convergence and the approximation of shallow water flow.

This study is directly relevant to the present research because it investigates the same

governing mathematical system. It provides a basis for incorporating terrain and rainfall into the proposed PINN framework.

However, the cases considered by Tian et al. (2025) were designed for evaluating the mathematical capability of PINNs to solve the SWE. Their study does not establish the performance of a model implemented in Pasig City. The present research will extend the investigation to a selected urban study area using the available local data.

2.4.4 Flood Prediction Studies in the Philippines

Flood prediction studies in the Philippines have investigated rainfall-runoff modeling, flood inundation simulation, and the application of hydrodynamic models to river basins and urban environments.

A study published in the Journal of Hydrology: Regional Studies in 2022 developed an integrated multiscale rainfall-runoff and inundation model for an extreme rainfall event in the Marikina-Pasig River Basin. The model was designed to simulate floodwater accumulation, depth, and flow source using variable grid sizes.

The study is relevant because it demonstrates the application of computational flood modeling within a Philippine river basin. It also provides a regional reference for the present research, which focuses on flood modeling in Pasig City.

Nevertheless, the study used a different modeling framework from the proposed SWE-based PINN. It did not specifically investigate the convergence, approximation error, and physical residuals of a PINN implemented in Pasig City. This difference supports the need to evaluate the proposed approach within the selected study area.

2.5 Synthesis of Literature

The reviewed literature establishes that flood prediction requires the representation of physical processes that govern the movement and accumulation of water. Traditional hydrodynamic models use mathematical equations and numerical methods to simulate

water flow. Among these, the Shallow Water Equations are widely used because they describe the conservation of mass and momentum in depth-averaged water flow.

The literature also shows that urban flood modeling presents challenges related to complex terrain, drainage systems, input data availability, and computational efficiency. These challenges are particularly relevant when modeling flood behavior in highly developed areas.

Artificial Neural Networks and other machine learning approaches provide an alternative means of estimating flood-related variables from data. However, purely data-driven models may not automatically satisfy the physical laws governing water flow. Physics-Informed Neural Networks address this limitation by incorporating governing equations into the training process.

Previous studies by Raissi et al. (2019), Liu et al. (2026), and Tian et al. (2025) establish the theoretical and computational basis for using PINNs to solve differential equations and model flood behavior. Meanwhile, the Marikina-Pasig River Basin study provides a regional reference for flood modeling in the Philippines.

Despite these contributions, the performance of a SWE-based PINN depends on the study area, available data, governing equation formulation, training process, and evaluation method. Therefore, the present study will develop and evaluate a PINN for a selected area of Pasig City and compare its predictions with a classical numerical method.

2.6 Research Gap

Existing studies have demonstrated the use of the Shallow Water Equations in flood modeling and the potential of Physics-Informed Neural Networks in solving nonlinear partial differential equations. Liu et al. (2026) investigated a PINN framework for urban flood depth prediction, while Tian et al. (2025) examined the use of PINNs for solving the two-dimensional SWE with terrain topography and rainfall source terms.

However, the results of these studies were obtained using their respective study areas,

datasets, and model configurations. Their findings cannot automatically establish the performance of a SWE-based PINN when implemented in Pasig City.

The present study addresses this gap by developing and evaluating a SWE-based PINN for flood modeling in a selected area of Pasig City. It will examine the model's convergence, approximation error, and physical consistency, particularly its ability to satisfy the conservation of mass and momentum.

The study will also compare the PINN with a classical numerical method using appropriate error metrics. This comparison will provide an assessment of how closely the PINN approximates the reference solution and whether its predictions satisfy the governing equations.

The research gap is therefore centered on the evaluation of the proposed SWE-based PINN within the selected Pasig City study area, particularly in terms of convergence, approximation error, and physical constraint satisfaction.

2.7 Relevance to the Present Study

The reviewed literature and studies provide the mathematical, computational, and scientific foundation for the present research.

The Shallow Water Equations provide the governing mathematical model for describing water depth and horizontal velocity. The principles of conservation of mass and momentum establish the physical constraints that the proposed PINN must satisfy.

The work of Raissi et al. (2019) provides the theoretical foundation for incorporating differential equations into neural network training. The study of Liu et al. (2026) provides a direct reference for applying PINNs to urban flood depth prediction. Meanwhile, Tian et al. (2025) provides a relevant mathematical and computational reference for solving the two-dimensional SWE with terrain topography and rainfall source terms.

The reviewed urban flood modeling literature also establishes the importance of considering terrain, rainfall, drainage representation, and data availability. These considerations will guide the selection and preparation of the input data for the Pasig City implementation.

The present study will use these foundations to develop a PINN that predicts water depth and horizontal velocity. Its performance will be evaluated through convergence, approximation error, and physical consistency, and compared with a classical numerical method. Through this evaluation, the study aims to examine the applicability of a physics-informed computational approach to flood modeling in the selected study area.

2.8 Chapter Summary

This chapter presented the fundamental concepts, mathematical theories, related literature, and previous studies relevant to the development of a Shallow Water Equation-based Physics-Informed Neural Network for flood modeling in Pasig City.

The discussion introduced flooding, hydrodynamic modeling, artificial neural networks, and Physics-Informed Neural Networks. It also presented the Shallow Water Equations, including the principles of conservation of mass and momentum, and explained how the governing equations can be incorporated into the PINN loss function.

The reviewed literature and studies established the relevance of SWE-based flood modeling and the use of PINNs in solving differential equations. They also identified challenges associated with urban flood modeling, including data availability, computational requirements, and the complexity of representing physical processes.

The research gap identified in this chapter concerns the development and evaluation of a SWE-based PINN for a selected area of Pasig City, particularly in terms of convergence, approximation error, and physical constraint satisfaction. These concepts and findings provide the foundation for the research methodology, model development, and evaluation procedures presented in the succeeding chapter.

Chapter 3

Research Methodology

This chapter presents the research methodology that will be followed in developing and evaluating the Shallow Water Equation-based Physics-Informed Neural Network (SWE-based PINN) for flood prediction in a selected study area in the Philippines. It discusses the research design, study location, data sources, model parameters, mathematical formulation, neural network architecture, data preprocessing, training procedure, validation methods, and data analysis procedures.

3.1 Research Methodology

This study will employ a computational and mathematical modeling approach to develop a Physics-Informed Neural Network based on the Shallow Water Equations. The proposed model will incorporate physical laws governing water flow into the neural network training process to predict water depth and horizontal water velocity.

The developed model will be evaluated by examining its convergence, approximation error, and consistency with the governing physical equations. Its performance will also be compared with a classical numerical method for solving the Shallow Water Equations.

3.2 Research Design

This study will utilize a quantitative, computational, and model-development research design. It will involve the mathematical formulation of the Shallow Water Equations, implementation of a Physics-Informed Neural Network, and numerical experiments to assess the model's performance.

The study will use quantitative evaluation metrics to measure prediction accuracy, convergence behavior, and physical consistency. Comparisons with a classical numerical method will be conducted to determine the performance of the proposed model.

3.3 Research Locale and Period

The study will focus on selected flood-prone areas in Pasig City, Philippines, particularly areas associated with the Pasig River and its relevant waterways.

The research will cover the period from [Start Date] to [End Date]. The selected study area and simulation domain will be determined based on the availability of geographical, rainfall, and hydrological datasets required for the mathematical model.

3.4 Sources of Data

The study will utilize secondary data obtained from relevant government agencies, public databases, and other reliable sources. These datasets will provide the necessary information for developing, training, and evaluating the proposed model.

The potential data requirements include:

- **Rainfall Data:** Historical rainfall measurements from relevant meteorological monitoring stations.
- **Water-Level Data:** Historical water-level measurements from the Pasig River and other relevant waterways.
- **River Flow and Discharge Data:** Available measurements describing the movement and volume of water within the selected waterways.
- **Geographic and Elevation Data:** Digital Elevation Models (DEM) and other geographical information describing the terrain of the study area.
- **Historical Flood Observations:** Available records of flood occurrences, water depths, durations, and affected locations.

- **Initial and Boundary Conditions:** Data required to establish the initial state of the water system and the conditions along the boundaries of the simulation domain.

The final selection of datasets will depend on their availability, accessibility, completeness, and suitability for the proposed mathematical model.

3.5 Model Parameters, Variables, and Initial/Boundary Conditions

This section identifies the variables and parameters used in formulating and implementing the SWE-based PINN.

The model will consider the following variables:

- **Spatial Coordinates:** The horizontal coordinates representing the position within the study area.
- **Time:** The temporal variable representing the progression of the flood simulation.
- **Water Depth:** The depth of water at a given spatial location and time.
- **Horizontal Water Velocity:** The velocity components describing water movement in the horizontal directions.
- **Rainfall:** Precipitation data that may contribute to the source terms of the governing equations.

The model parameters will include relevant physical quantities and numerical settings, such as gravitational acceleration, terrain elevation, friction coefficients, and other parameters required by the governing equations.

Initial and boundary conditions will be established using available hydrological and geographical information to define the behavior of the water system within the simulation domain.

3.6 Mathematical Model Formulation

This section presents the mathematical foundation of the proposed model using the Shallow Water Equations.

3.6.1 Governing Shallow Water Equations

Present the system of partial differential equations describing the movement of water across the selected study area.

3.6.2 Conservation of Mass

Discuss the continuity equation governing the conservation of water mass within the simulation domain.

3.6.3 Conservation of Momentum

Present the momentum equations describing changes in water velocity due to gravitational forces, terrain slope, and friction.

3.6.4 Initial Conditions

Define the initial water depth and horizontal velocity conditions at the beginning of the simulation.

3.6.5 Boundary Conditions

Specify the conditions imposed along the boundaries of the computational domain, including relevant inflow, outflow, or other boundary constraints.

3.7 PINN Model Architecture

This section describes the architecture and mathematical structure of the Physics-Informed Neural Network used to approximate the solutions of the Shallow Water Equations.

3.7.1 Neural Network Structure

Describe the neural network architecture, including its input layer, hidden layers, activation functions, and output layer.

3.7.2 Input and Output Variables

Identify the spatial coordinates and time as the primary network inputs. The outputs will represent the predicted water depth and horizontal water velocity components.

3.7.3 Physics-Based Constraints

Explain how the Shallow Water Equations are incorporated into the network using automatic differentiation to calculate the partial derivatives required for the governing equations.

3.7.4 Loss Function Formulation

Present the composite loss function, including the data loss, initial condition loss, boundary condition loss, and physics-based residual loss.

Explain how the different loss components are combined and minimized during training to obtain physically consistent predictions.

3.8 Data Preprocessing

This section discusses the procedures applied to the collected datasets before they are used in model development and training.

The preprocessing procedures may include:

- Data cleaning and removal of invalid observations.
- Normalization or scaling of numerical variables.
- Identification and handling of missing data.
- Spatial and temporal alignment of datasets.
- Preparation of training, validation, and testing datasets.

These procedures will ensure that the collected data are suitable for numerical computation and neural network training.

3.9 Model Training Procedure

This section explains the process of training the SWE-based PINN.

The training procedure will involve defining the network architecture, initializing its parameters, calculating the composite loss function, and updating the network weights through an optimization algorithm.

The following aspects will be discussed:

- Training and validation data preparation.
- Selection of optimization algorithms.
- Configuration of learning rates and training iterations.
- Selection of collocation points for evaluating the governing equations.
- Monitoring and minimization of the composite loss function.
- Evaluation of convergence during training.

3.10 Model Validation and Evaluation

The developed SWE-based PINN will be evaluated to determine its accuracy, convergence behavior, and physical consistency.

The evaluation will consider the following metrics:

- **Root Mean Square Error (RMSE):** Measures the average magnitude of prediction errors while giving greater weight to larger errors.
- **Mean Absolute Error (MAE):** Measures the average absolute difference between predicted and reference values.
- **Coefficient of Determination (R^2):** Measures how well the model explains the variation in the reference data, where appropriate.
- **Physics-Based Residual Error:** Measures the extent to which the predicted solutions satisfy the governing Shallow Water Equations.
- **Convergence Analysis:** Examines the behavior of the model's loss function and approximation error throughout the training process.

The PINN predictions will be compared with available measured observations or numerical solutions obtained using a classical method for solving the Shallow Water Equations.

3.11 Data Analysis Procedure

The results generated by the proposed model will be analyzed using quantitative and numerical methods.

The analysis will focus on the following:

1. Examining the convergence behavior of the PINN during training.
2. Measuring the approximation error between the predicted and reference solutions.
3. Evaluating the physical consistency of the predicted water depth and velocity using the governing equations.
4. Comparing the performance of the PINN with a classical numerical method.
5. Interpreting the results to determine the effectiveness and limitations of the proposed model for flood prediction.

The findings will be presented using appropriate tables, graphs, and other visual representations to support the interpretation of the model's performance.

Chapter 4

How to Cite References

First edit the file `bibliog.bib` by adding an entry for each reference used in your thesis. Follow the format in the sample file.

```
@BOOK{bsw,
  author={H. T. Banks and R. C. Smith and Y. Wang},
  title={Smart Material Structures: Modeling Estimation
         and Control},
  year=1996,
  publisher={Masson/John Wiley},
  address={Paris/Chichester}
}

@ARTICLE{BanksIto1,
  author={H. T. Banks and K. Ito},
  year=1997,
  title={Approximation in {LQR} Problems for Infinite Dimensional
    Systems with Unbounded Input Operators},
  journal={Journal of Mathematical Systems, Estimation, and Control},
  volume=7,
  pages={1-34},
  publisher={Birkh\"{a}user Boston}
}

@PHDTHESIS{Ric,
```

```
  author = {R. C. H. del Rosario },
  year = 1998,
  title = {Computational Methods for Feedback Control in
        Structural Systems},
  school = {N. C. State University}
}

@techreport{RalphRic3a,
  author = {R. C. H. del Rosario and R. C. Smith},
  year = 1997,
  title = {{LQR} Control of Thin Shell Dynamics: Formulation and
           Numerical Implementation},
  institution = {Institute for Computer Applications in Science
    and Engineering},
  number={ICASE Report 97-59},
  address={NASA Langley Research Center, Hampton},
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%   %MISC   %%%%%%%%%%%%%%%%%%%%%%%%%%%%

@BOOKLET{Le,
  author={A. W. Leissa},
  title={Vibrations of Shells},
  year=1973,
  publisher={NASA SP-288},
  howpublished={Reprinted by the Acoustical Society of America
   through the American Institute of Physics}
}
```

```
@manual{d31ref,
  organization = {{Institute} of Electrical and
   Electronics Engineers},
  year = 1978,
  title = {IEEE Standard on Piezoelectricity},
  address={New York}
}

@manual{pside,
  title = {Specification of PSIDE},
  author={Jacques J.B. de Swart and Walter M. Lioen and
   Wolter A. van der Veen},
  year=1998,
  note={Avalable at http://www.cwi.nl/cwi/projects/PSIDE/}
}
```

Click from the BibTex icon (if you are using WinEdit Program) or use the BibTex command if you are in command line mode. It is suggested that you do this twice. Then compile the main tex file using the LaTeX command.

Use the `cite` command to cite a reference. For example, `\cite{bsw}` cites the book labeled "bsw". This will give us (Banks, Smith, & Wang, 1996).

Appendix A

ThesisMain.tex File

The ThesisMain.tex file contains the basic information about your thesis while the chapter files are just called in the code. This is the only file you need to compile. Do not run the chapter files.

A.1 Preamble

```
\documentclass[12pt]{report}
\usepackage{feumathstyle}
\usepackage{amssymb, graphicx, amsmath}
\usepackage{hyperref}
\usepackage{apacite}
\bibliographystyle{apacite}

\usepackage{lscape}

\newtheorem{definition}{Definition}[chapter]
\newtheorem{theorem}{Theorem}[chapter]
\newtheorem{lemma}[theorem]{Lemma}
\newtheorem{corollary}[theorem]{Corollary}
\newtheorem{proposition}[theorem]{Proposition}
```

you may add additional packages but do not remove the prelisted packages especially the feumathstyle package. You may add other new formats here too

A.2 Basic Information

```
 \title{Thesis Title} %do not capitalize all


\authorfirst{Juan L.}
\authorlast{Dela Cruz}
\authorext{Jr.}
\authorexttrue %make this a comment if you do not have an extension name e.g. Jr.,

\secondauthorfirst{Juan L.}
\secondauthorlast{Dela Cruz}
\secondauthorext{Jr.}
\secondauthorexttrue %make this a comment if you do not have an extension name e.g

\thirdauthorfirst{Juan L.}
\thirdauthorlast{Dela Cruz}
\thirdauthorext{Jr.}
\thirdauthorexttrue %make this a comment if you do not have an extension name e.g.

\degree{Bachelor of Science in Applied Mathematics } %enter the specific degree
\thesistype{thesis}
\thesisdocument{undergraduate thesis}

\specialization{with Information Technology} \specializetrue

\defensedate{May 12, 2022} %indicate the month, day and year the research was defe
\submitmonth{May} %indicate the month the manuscript was submitted
\submityear{2022} %indicate the year the manuscript was submitted
```

```
\adviser{Adviser, Ph.D.}%main adviser
\panel{Panel, Ph.D.}
\secondpanel{Panel, Ph.D.}
\thirdpanel{Panel, Ph.D.}


\thesisinstructor{May Anne C. Tirado, Ph.D.}


%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% highlight \bothabsenttrue if the student has only one adviser and one reader
%% otherwise comment \bothabsenttrue and highlight \coadviser or \coreader which
%% ever is applicable. In this case, the package assumes either you have 1 Adviser
%% and 2 Readers, or 2 Advisers and 1 Reader.

\bothabsenttrue

%\coadviser{co-Adviser, Ph.D.}
%\coadvisetrue
% Make the \coadvisetrue as a comment if there is no adviser
%%%%%%%%%%%%%%%%%%%%%%%%%%%


\deptchair{Genesis John G. Borja}
\dean{Dean Name}
```

input the names and information about your thesis, authors, adviser, panel, dean.

A.3 Abstract and Acknowledgements

```
\abs{Type your abstract here.  Your abstract should have a minimum
 of 150 words and a maximum of 300 words.}

\acknowledge{Type your acknowledgements here. It is customary to acknowledge spec
 Acknowledgments should be couched in terms consistent with the
 scholarly nature of the work. Your name and the date should not appear on this p
```

type your abstract and acknowledgements here

A.4 Chapters and Appendix

Type your chapters and appendix in separate tex files. This is so it will be easier to edit a shorter code than the full manuscript.

The chapter files starts with

```
\chapter{How to Wrtie Text and Type Equations}
\label{chap:typing}
```

The label is optional. This part is when you want to cite this chapter in other chapters. This file just ends with the last line of your chapter content.

A.5 Document Outline

```
\beforepreface
\abstractpage

\acknowledgetrue
\acknowledgepage
```

```
\tableofcontents

\newpage


\listoftables
\listoffigures

\afterpreface

\include{1typing}
\include{2compiling}
\include{3figures}
\include{4citing}
%%%%% edit the chapter files. no more preamble. start directly on \chapter{}. add r

\appendix
\input{appendixA}
\input{appendixB}
%%%%% edit appendix files. no more preamble. start directly on \chapter. you may re

\nocite*
\bibliography{BIBLIOG.bib}
%to edit your bibliography, open the BIBLIOG.BIB file.
```

The first set of commands will create beforepreface using the information you inputed at the start of ThesisMain.tex. Include the chapters in order and input the appendices in order too. The chapter file names are used in the arguments. It is best to not use

space in the chapter file names.

A.6 Bibliography

Input your references in the Bibliography.bib file

```
@article{Datta-Figueira-2013,
 author = {Dilip Datta and Jos\'e Rui Figueira},
 title = {{A real-integer-discrete-coded differential evolution}},
 journal = {Applied Soft Computing},
 volume = {13},
 number = {9},
 pages = {3884--3893},
 year = {2013}
}
@book{Deb-2001,
 author = {Kalyanmoy Deb},
 title = {{Multi-Objective Optimization using Evolutionary Algorithms}},
 publisher = {John Wiley \& Sons Ltd.},
 address = {Chichester, England},
 year = {2001}
}
```

A.7 Folder Contents

All your thesis files must be in one folder before you compile/run ThesisMain.tex

1. ThesisMain.tex
2. feumathstyle.sty

3. FEUlogo.png
4. IASlogo.png
5. BIBLIOG.bib
6. chapter tex files
7. appendix tex files

See the sample compiled ThesisMain.pdf to see the intended output.

Appendix B

feumathstyle.sty file

DO NOT EDIT feumathstyle.sty unless necessary. If you want to edit beforepreface contents that are not on the main tex file, and other formats, do it on feumathstyle.sty file. Be careful in editing this file. You may create a copy first and edit the copy.

feumathstyle.sty contains the text format and layout of the beforepreface pages, chapter pages, appendices, table of contents and other lists.

the definition of some commands are also on this file.

Bibliography

Banks, H. T., Smith, R. C., & Wang, Y. (1996). *Smart material structures: Modeling estimation and control*. Paris/Chichester: Masson/John Wiley.

Burke, E., Elliman, D., & Weare, P. F. R. (1996). Examination Timetabling in British Universities - A Survey. In E. K. Burke & P. Ross (Eds.), *Proceedings of practice and theory of automated timetabling* (Vol. 1153, pp. 76–90). Springer.

Colorni, A., Dorigo, M., & Maniezzo, V. (1992). *A Genetic Algorithm to Solve the Timetable Problem* (Tech. Rep. No. 90-060 revised). Politecnico di Milano, Italy.

Datta, D. (1998). *Optimal Shape Design System for Plates under Dynamic Loads* (Unpublished master's thesis). Indian Institute of Technology, Delhi. (Master thesis)

Datta, D., & Figueira, J. R. (2013). A real-integer-discrete-coded differential evolution. *Applied Soft Computing*, *13*(9), 3884–3893.

Deb, K. (2001). *Multi-Objective Optimization using Evolutionary Algorithms*. Chichester, England: John Wiley & Sons Ltd.

Guo, K., Guan, M., & Yu, D. (2021). Urban surface water flood modelling – a comprehensive review of current models and future challenges. *Hydrology and Earth System Sciences*, *25*(5), 2843–2860. doi: 10.5194/hess-25-2843-2021

Liu, W., Wu, Q., Liu, Z., Zheng, X., Liu, T., & Gao, H. (2026). PINN framework for urban flood depth prediction: integrating data-driven insights with physical constraints. *Journal of Hydrology*, *665*, 134693. doi: 10.1016/j.jhydrol.2025.134693

Raissi, M., Perdikaris, P., & Karniadakis, G. E. (2019). Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, *378*, 686–707. doi: 10.1016/j.jcp.2018.10.045

Tian, Y., Ding, S., Su, G., Huang, L., & Chen, J. (2025). *Physics-informed neural networks for solving the two-dimensional shallow water equations with terrain*

topography and rainfall source terms. Retrieved from `https://arxiv.org/abs/2501.11372`