
 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Aim: Practical based on Pandas Data Structures

IDE:

What is Python Pandas?

Pandas is a powerful, open-source data analysis and manipulation package for Python. It provides data structures and functions needed to work on structured data seamlessly and efficiently.

What Is Pandas Used For?

Pandas is extensively used for:

- Data Cleaning: Handling missing values, duplications, and incorrect data formats.
- Data Manipulation: Filtering, transforming, and merging datasets.
- Data Analysis: Performing statistical analysis and aggregations.
- Data Visualization: Creating plots and charts to visualize data trends and patterns.
- Time Series Analysis: Handling and manipulating time series data.

Run the following command to install Pandas:

```
pip install pandas
```

```
import pandas as pd
```

```
print(pd._version_)
```



Pandas Series

A Pandas Series is a one-dimensional labeled array capable of holding any data type. It is similar to a column in a spreadsheet or a SQL table.

Example:

```
import pandas as pd
# Creating a Series
data = [1, 2, 3, 4, 5]
series = pd.Series(data)
print(series)
```

Output:

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [2]: import pandas as pd
...: # Creating a Series
...: data = [1, 2, 3, 4, 5]
...: series = pd.Series(data)
...: print(series)
0    1
1    2
2    3
3    4
4    5
dtype: int64
```

Basic Operations on Series

Perform various operations on Series, such as arithmetic operations, filtering, and statistical calculations.


Example:

```
# Arithmetic Operations
series2 = series + 10
print(series2)

# Filtering
filtered_series = series[series > 2]
print(filtered_series)

# Statistical Calculations
mean_value = series.mean()
print(mean_value)
```

Output

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025


```

In [3]:
....: series2 = series + 10
....: print(series2)
....: # Filtering
....: filtered_series = series[series > 2]
....: print(filtered_series)
....: # Statistical Calculations
....: mean_value = series.mean()
....: print(mean_value)
0    11
1    12
2    13
3    14
4    15
dtype: int64
2     3
3     4
4     5
dtype: int64
3.0

```



Pandas Dataframe

Pandas DataFrame is two-dimensional size-mutable, potentially heterogeneous tabular data structure with labeled axes (rows and columns). A Data frame is a two-dimensional data structure, i.e., data is aligned in a tabular fashion in rows and columns. Pandas DataFrame consists of three principal components, the data, rows, and columns.



The diagram illustrates a Pandas DataFrame with three principal components: Rows, Columns, and Data. The DataFrame is represented as a table with 7 rows and 6 columns. The columns are labeled Name, Team, Number, Position, and Age. The rows are indexed from 0 to 6. The data is highlighted in green cells. The label 'Columns' points to the column headers. The label 'Rows' points to the row indices. The label 'Data' points to the data cells.

	Name	Team	Number	Position	Age
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Creating a DataFrame

```
data = {
    'Name': ['Alice', 'Bob', 'Charlie'],
    'Age': [25, 30, 35],
    'City': ['New York', 'Los Angeles', 'Chicago']
}
```

```
df = pd.DataFrame(data)
```

```
print(df)
```

Output

```
In [4]:
....: data = {
....:     'Name': ['Alice', 'Bob', 'Charlie'],
....:     'Age': [25, 30, 35],
....:     'City': ['New York', 'Los Angeles', 'Chicago']
....: }
....: df = pd.DataFrame(data)
....: print(df)
      Name  Age      City
0   Alice   25  New York
1    Bob   30  Los Angeles
2  Charlie   35   Chicago
```



Basic Operations on Dataframes

DataFrames support a wide range of operations for data manipulation and analysis.

Accessing Columns (# select one column)

```
print(df[['Name']])
```

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [60]:
...: print(df[['Name']])
Name
0    John
1  Emily
2    Mike
3    Lisa
```

Adding a New Column

```
df['Salary'] = [70000, 80000, 90000]
```

```
print(df)
```

Output



```
In [64]: d['Salary'] = [70000, 80000, 90000]
...: print(d)
0          1
1          2
2          3
3          4
Salary    [70000, 80000, 90000]
dtype: object
```

Dropping a Column

```
df = df.drop('City', axis=1)
```

```
print(df)
```

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [11]: data = {
...:     'Name': ['Alice', 'Bob', 'Charlie'],
...:     'Age': [25, 30, 35],
...:     'City': ['New York', 'Los Angeles', 'Chicago']
...: }
...: df = pd.DataFrame(data)
...: print(df)
...:
...: df1 = df.drop('City', axis=1)
...: print(df1)
```

	Name	Age	City
0	Alice	25	New York
1	Bob	30	Los Angeles
2	Charlie	35	Chicago

	Name	Age
0	Alice	25
1	Bob	30
2	Charlie	35



The DataFrame is like a table with rows and columns.

Pandas use the loc attribute to return one or more specified row(s)

Return row 0:

```
print(df.loc[[0]])
```

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [68]: d['Salary'] = [70000, 80000, 90000]
...: print(d)
...: # Return row 0:
...: print(d.loc[[0]])
```

```
0      1
1      2
2      3
3      4
Salary  [70000, 80000, 90000]
dtype: object
0      1
dtype: object
```

#Return row 0 and 1:

#use a list of indexes:

```
print(df.loc[[0, 1]])
```

Output



```
In [69]: d['Salary'] = [70000, 80000, 90000]
...: print(d)
...: print(df.loc[[0, 1]])
```

```
0      1
1      2
2      3
3      4
Salary  [70000, 80000, 90000]
dtype: object
   Name  Age  Gender
0  John   28      M
1  Emily  23      F
```

Named Indexes

With the index argument, you can name your own indexes.

Example:

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Add a list of names to give each row a name:

```
import pandas as pd
data = {
    "calories": [420, 380, 390],
    "duration": [50, 40, 45]
}
df = pd.DataFrame(data, index = ["day1", "day2", "day3"])
print(df)
Output
```

```
In [70]: import pandas as pd
...: data = {
...:     "calories": [420, 380, 390],
...:     "duration": [50, 40, 45]
...: }
...: df = pd.DataFrame(data, index = ["day1", "day2", "day3"])
...: print(df)
      calories  duration
day1         420         50
day2         380         40
day3         390         45
```



Explanation of Key Pandas Functions

Reading and Writing Data:

Reading Data: Read a CSV file into a DataFrame.

Example:

```
s = pd.read_csv(r"C:\Users\ambat\Downloads\data.csv")
print(s)
Output
```


 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [71]: s = pd.read_csv(r"C:\Users\ambat\Downloads\data.csv")
....: print(s)
```

	Name	City	Number
0	A	M	1
1	B	N	4
2	C	V	5
3	D	B	7
4	E	J	8
5	F	G	9
6	G	F	7
7	H	D	5
8	I	C	6
9	J	X	7
10	K	Z	3
11	L	S	4
12	M	R	6

Writing Data: Write a DataFrame to a CSV file.



Note: Other Ways to Save Pandas DataFrames (to_excel(), to_json(), to_hdf(), to_sql(), to_pickle())

Example:

```
Biodata = {'Name': ['John', 'Emily', 'Mike', 'Lisa'],
           'Age': [28, 23, 35, 31],
           'Gender': ['M', 'F', 'M', 'F']}
}
```

```
df = pd.DataFrame(Biodata)
# Save the dataframe to a CSV file
df.to_csv('Biodata.csv', index=False)
```

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

A1					
Name					
	A	B	C	D	
1	Name	age	Gender		
2	John	28	M		
3	Emily	33	F		
4	Mike	25	M		
5	Lisa	17	F		
6					

Data Inspection:

`df.head()`: Display the first few rows of the DataFrame.

`df.tail()`: Display the last few rows of the DataFrame.

`df.info()`: Display a summary of the DataFrame.

`df.describe()`: Provide descriptive statistics for numerical columns. (count: the number of non-null entries, mean: the mean value, std: the standard deviation, min: the minimum value, 25%, 50%, 75%: the lower, median, and upper quartiles, max: the maximum value)

Example:

```
dat = pd.read_csv("data.csv")
print(dat.info())
# shows first and last five rows
print(dat.head())
print(dat.tail())
print(dat.describe())
```

Output

Subject: Programming With Python (01CT1309)



Aim: Practical based on Pandas Data Structures

Experiment No: 09

Date:

Enrollment No:92510133025

```
In [75]: s = pd.read_csv(r"C:\Users\ambat\Downloads\data.csv")
...: print(s)
...: print(s.info())
...: # shows first and last five rows
...: print(s.head())
...: print(s.tail())
...: print(s.describe())
Name City Number
0      A      M      1
1      B      N      4
2      C      V      5
3      D      B      7
4      E      J      8
5      F      G      9
6      G      F      7
7      H      D      5
8      I      C      6
9      J      X      7
10     K      Z      3
11     L      S      4
12     M      R      6
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 13 entries, 0 to 12
Data columns (total 3 columns):
#   Column  Non-Null Count  Dtype
---  -
0   Name    13 non-null      object
1   City    13 non-null      object
2   Number  13 non-null      int64
```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
Data columns (total 3 columns):
#   Column  Non-Null Count  Dtype
---  -
0   Name    13 non-null    object
1   City     13 non-null    object
2   Number   13 non-null    int64
dtypes: int64(1), object(2)
memory usage: 440.0+ bytes
None
   Name City  Number
0     A    M        1
1     B    N        4
2     C    V        5
3     D    B        7
4     E    J        8
   Name City  Number
8     I    C        6
9     J    X        7
10    K    Z        3
11    L    S        4
12    M    R        6
      Number
count  13.000000
mean    5.538462
std     2.183857
min     1.000000
25%     4.000000
50%     6.000000
75%     7.000000
max     9.000000
```





Data Selection and Indexing:

`dat[['A']]:` Select a column.

`dat[['A', 'B']]:` Select multiple columns.

`dat.loc[[0]]:` Select a row by label.



 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Example:

```
print(dat[['Name']])
print(dat[['Name','Number']])
print(dat.loc[[1]])
```

Output

```
In [76]: print(dat[['Name']])
...: print(dat[['Name','Number']])
...: print(dat.loc[[1]])
Name
0      A
1      B
2      C
3      D
4      E
5      F
6      G
7      H
8      I
9      J
10     K
11     L
12     M
```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

	Name	Number
0	A	1
1	B	4
2	C	5
3	D	7
4	E	8
5	F	9
6	G	7
7	H	5
8	I	6
9	J	7
10	K	3
11	L	4
12	M	6

	Name	City	Number
1	B	N	4

Data Manipulation:

`dat['A'] = dat['A'] * 2:` Modify a column.

`dat['F'] = dat['A'] + dat['B']:` Create a new column based on existing columns.

`dat.drop(columns=['A']):` Drop a column.

`dat.drop(index=[0]):` Drop a row.



Task

Create a DataFrame with 5 numeric columns

```
data = {
    'A': [np.nan, 2, 3, 4, 5, 6, 7, 8, 9, 10],
    'B': np.random.normal(50, 15, 10),
    'C': np.random.rand(10) * 100,
    'D': np.linspace(1, 10, 10),
    'E': np.logspace(1, 2, 10)
}
```



```
df = pd.DataFrame(data)
```

Output

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```
In [4]: import numpy as np
...: import pandas as pd
...: data = {
...:     'A': [np.nan, 2, 3, 4, 5, 6, 7, 8, 9, 10],
...:     'B': np.random.normal(50, 15, 10),
...:     'C': np.random.rand(10) * 100,
...:     'D': np.linspace(1, 10, 10),
...:     'E': np.logspace(1, 2, 10)
...: }
...: df = pd.DataFrame(data)
...:
...:
...: print(df)
```

	A	B	C	D	E
0	NaN	30.408184	99.211477	1.0	10.000000
1	2.0	33.142956	28.074403	2.0	12.915497
2	3.0	59.663260	44.702550	3.0	16.681005
3	4.0	45.668449	27.580080	4.0	21.544347
4	5.0	32.276692	6.939616	5.0	27.825594
5	6.0	51.849172	98.071691	6.0	35.938137
6	7.0	70.651190	97.168423	7.0	46.415888
7	8.0	42.500231	72.229654	8.0	59.948425
8	9.0	50.584567	3.029188	9.0	77.426368
9	10.0	57.954979	25.595063	10.0	100.000000

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Post Lab Exercise:

- a. Write a Pandas program to add, subtract, multiple and divide two Pandas Series.

```
import pandas as pd
```



```
series1 = pd.Series([10, 20, 30, 40, 50])
series2 = pd.Series([1, 2, 3, 4, 5])
```

```
addition = series1 + series2
print("Addition:\n", addition)
```

```
subtraction = series1 - series2
print("Subtraction:\n", subtraction)
```

```
multiplication = series1 * series2
print("Multiplication:\n", multiplication)
```

```
division = series1 / series2
print("Division:\n", division)
```


 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

Addition:

```
0    11
1    22
2    33
3    44
4    55
```

dtype: int64

Subtraction:

```
0     9
1    18
2    27
3    36
4    45
```

dtype: int64

Multiplication:

```
0     10
1     40
2     90
3    160
4    250
```

dtype: int64

Division:

```
0    10.0
1    10.0
2    10.0
3    10.0
4    10.0
```



dtype: float64

b. Write a Pandas program to convert a dictionary to a Pandas series.

```
dict_data = {'a': 1, 'b': 2, 'c': 3, 'd': 4, 'e': 5}
```

```
series = pd.Series(dict_data)
```

```
print("Pandas Series:\n", series)
```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

In [79]:

```
....: dict_data = {'a': 1, 'b': 2, 'c': 3, 'd': 4, 'e': 5}
....:
....: # Convert the dictionary to a Pandas Series
....: series = pd.Series(dict_data)
....: print("Pandas Series:\n", series)
```

Pandas Series:

```
a    1
b    2
c    3
d    4
e    5
dtype: int64
```

- c. Write a Pandas program to create a series from a list, numpy array and dict

```
import numpy as np
```



```
list_data = [10, 20, 30, 40, 50]
np_array = np.array([1, 2, 3, 4, 5])
```

```
dict_data = {'a': 100, 'b': 200, 'c': 300, 'd': 400, 'e': 500}
```

```
series_from_list = pd.Series(list_data)
print("Series from list:\n", series_from_list)
```

```
series_from_array = pd.Series(np_array)
print("Series from numpy array:\n", series_from_array)
```

```
series_from_dict = pd.Series(dict_data)
print("Series from dictionary:\n", series_from_dict)
```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```

Series from list:
0    10
1    20
2    30
3    40
4    50
dtype: int64
Series from numpy array:
0    1
1    2
2    3
3    4
4    5
dtype: int32
Series from dictionary:
a    100
b    200
c    300
d    400
e    500
dtype: int64

In [81]:

```

d. Write a Pandas program to stack two series vertically and horizontally

```



import pandas as pd

series1 = pd.Series([10, 20, 30, 40, 50])
series2 = pd.Series([60, 70, 80, 90, 100])

vertical_stack = pd.concat([series1, series2], ignore_index=True)
print("Vertical Stack:\n", vertical_stack)

horizontal_stack = pd.concat([series1, series2], axis=1)
print("Horizontal Stack:\n", horizontal_stack)

```

 Marwadi University Marwadi Chandarana Group 	Marwadi University Faculty of Engineering & Technology Department of Information and Communication Technology	
Subject: Programming With Python (01CT1309)	Aim: Practical based on Pandas Data Structures	
Experiment No: 09	Date:	Enrollment No:92510133025

```

...: print("Horizontal Stack:\n", horizontal
Vertical Stack:
  0      10
  1      20
  2      30
  3      40
  4      50
  5      60
  6      70
  7      80
  8      90
  9     100
dtype: int64
Horizontal Stack:
      0      1
0  10   60
1  20   70
2  30   80
3  40   90
4  50  100

```

Github link: https://github.com/JenishDesai5115/PWP_postlabs