



Rapido

Data Analysis Using MySQL



Prepared by Jenishragavan . s



MySQL Requirement For Rapido Data analysis

- Identify the city with the highest ride demand
- Find the most common ride start and end locations.
- Identify the Total rides completed per driver
- Find the longest ride distance recorded
- Calculate total revenue generated per month
- Identify the top 5 cities by revenue
- Identify drivers who earned the highest revenue
- Analyze the most common reasons for ride cancellations
- Customers with the Highest Ride Frequency & Spending
- Find the top 5 customers who took the most rides
- Get the percentage of canceled rides
- Find customer satisfaction score per city.



MySQL Requirement For Rapido Data analysis

- Find the most profitable payment method.
- Find drivers with the highest customer ratings.
- How many rides were completed without customer ratings
- Which vehicle type is used the most for Rapido rides .
- Which customers have spent the most money on Rapido .
- Which time slot has the highest demand for Rapido rides
- What is the total revenue generate from Night-time rides .
- How many customers have used Rapido in Multiple cities .
- Average Ride Frequency per Month by Gender .
- Find Highest Spending Age Group .
- Calculate Cancellation rate by Gender



1 . Identify the city with the highest ride demand .

```
select city , sum(total_rides) as Total_Rides from city_wise_demand  
group by city order by Total_Rides desc ;
```

2. Find the most common ride start and end locations.

```
select pickup_location , drop_location , count(*) as Most_rides from rides  
group by pickup_location , drop_location  
order by Most_rides desc limit 5 ;
```

3. Identify the Total rides completed per driver .

```
select driver_name , sum(total_rides_completed) as Completed_rides  
from drivers group by driver_name  
order by Completed_rides desc limit 5 ;
```



4. Find the longest ride distance recorded.

```
select ride_id , pickup_location , drop_location , max(ride_distance_km) as Longest_ride  
from rides group by ride_id order by Longest_ride desc limit 5 ;
```

5. Calculate total revenue generated per month.

```
select date_format(transaction_date , '%Y-%m') as Month ,  
sum(amount_paid) as Total_revenue from ride_payments  
group by Month  
order by Total_revenue desc ;
```

6. Identify the top 5 cities by revenue.

```
select r.city , sum(rp.amount_paid) as Total_revenue from rides as r  
join ride_payments as rp  
on r.ride_id = rp.ride_id  
group by r.city  
order by Total_revenue desc limit 5 ;
```



7. Customers with the Highest Ride Frequency & Spending

```
select c.customer_id , c.customer_name , count(r.ride_id) as Total_rides ,  
coalesce(sum(rp.amount_paid),0) as total_spent  
from customers as c inner join rides as r on c.customer_id = r.customer_id  
inner join ride_payments as rp on r.ride_id = rp.ride_id  
where r.ride_date >= date_sub(curdate(), interval 3 month ) -- last 3 month  
group by c.customer_id , c.customer_name  
order by total_spent desc , total_rides desc limit 10 ;  
limit 10 ;
```

8. Identify drivers who earned the highest revenue.

```
select driver_name , sum(earnings) as highest_revenue from drivers  
group by driver_name order by highest_revenue desc limit 5 ;
```

9 . Analyze the most common reasons for ride cancellations.

```
select cancellation_reason , count(*) as Cancel_reason  
from ride_cancel group by cancellation_reason order by  
Cancel_reason desc ;
```



10. Find the top 5 customers who took the most rides .

```
SELECT customer_id , COUNT(*) AS ride_count FROM Rides  
GROUP BY customer_id ORDER BY ride_count DESC LIMIT 5;
```

11 . Get the percentage of canceled rides

```
SELECT  
(SELECT COUNT(*) FROM Ride_Cancel) / COUNT(*) * 100 AS cancel_rate  
FROM Rides;
```

12. Find customer satisfaction score per city.

```
SELECT r.city, AVG(cf.rating) AS avg_rating  
FROM rides as r join customer_feedback as cf on r.ride_id = cf.ride_id  
GROUP BY r.city  
ORDER BY avg_rating DESC;
```



13 . Find the most profitable payment method.

```
SELECT payment_method, SUM(amount_paid) AS total_revenue  
FROM Ride_Payments GROUP BY payment_method  
ORDER BY total_revenue DESC LIMIT 1;
```

14 . Find drivers with the highest customer ratings.

```
SELECT driver_id, driver_name ,round(AVG(driver_rating),1) AS avg_rating  
FROM drivers GROUP BY driver_id ORDER BY avg_rating DESC LIMIT 5;
```

15 . HOW MANY RIDES WERE COMPLETED WITHOUT CUSTOMER RATINGS?

```
SELECT COUNT(*) AS no_rating_rides FROM Rides r  
LEFT JOIN Customer_Feedback cf ON r.ride_id = cf.ride_id  
WHERE cf.rating IS NULL;
```



16. Which vehicle type is used the most for Rapido rides .

```
SELECT d.vehicle_type, COUNT(r.ride_id) AS ride_count  
FROM Rides r  
JOIN Drivers d ON r.driver_id = d.driver_id  
GROUP BY d.vehicle_type  
ORDER BY ride_count DESC;
```

17. Which customers have spent the most money on Rapido .

```
SELECT c.customer_id, c.customer_name, SUM(rp.amount_paid) AS total_spent  
FROM Customers c  
JOIN Rides r ON c.customer_id = r.customer_id  
JOIN Ride_Payments rp ON r.ride_id = rp.ride_id  
GROUP BY c.customer_id, c.customer_name  
ORDER BY total_spent DESC  
LIMIT 10 ;
```



18. Which time slot has the highest demand for rapido rides .

SELECT CASE

WHEN HOUR(ride_time) BETWEEN 6 AND 10 THEN 'Morning (6AM-10AM)'

WHEN HOUR(ride_time) BETWEEN 11 AND 16 THEN 'Afternoon (11AM-4PM)'

WHEN HOUR(ride_time) BETWEEN 17 AND 21 THEN 'Evening (5PM-9PM)'

ELSE 'Night (10PM-5AM)'

END AS time_slot, COUNT(*) AS ride_count

FROM Rides

GROUP BY time_slot

ORDER BY ride_count DESC;

19 .What is the total revenue generate from Night-time rides .

SELECT SUM(rp.amount_paid) AS total_night_revenue

FROM Rides r

JOIN Ride_Payments rp ON r.ride_id = rp.ride_id

WHERE HOUR(r.ride_time) BETWEEN 22 AND 5;



20. How many customers have used Rapido in Multiple cities .

```
SELECT r.city, COUNT(DISTINCT c.customer_name) AS customer_count  
FROM Rides as r join customers as c on r.customer_id = c.customer_id  
GROUP BY r.city  
HAVING customer_count > 1  
ORDER BY customer_count DESC;
```

21.Average Ride Frequency per Month by Gender .

```
SELECT  c.gender,  round(COUNT(r.ride_id) /  COUNT(DISTINCT  
DATE_FORMAT(r.ride_date, '%Y-%m')),1)  
AS avg_rides_per_month FROM Rides as r  
JOIN Customers as c ON r.customer_id = c.customer_id  
GROUP BY c.gender;
```



22. Find Highest Spending Age Group .

```
SELECT
  CASE
    WHEN c.age BETWEEN 18 AND 25 THEN 'Adult'
    WHEN c.age BETWEEN 26 AND 35 THEN 'Teenage'
    WHEN c.age BETWEEN 36 AND 50 THEN 'Middle-Aged'
    ELSE 'Senior'
  END AS age_group,
  SUM(rp.amount_paid) AS total_spent
FROM Ride_Payments rp
JOIN Rides r ON rp.ride_id = r.ride_id
JOIN Customers c ON r.customer_id = c.customer_id
GROUP BY age_group
ORDER BY total_spent DESC;
```



23. Calculate Cancellation rate by Gender .

```
SELECT c.gender,  
       COUNT(rc.ride_id) / (SELECT COUNT(*) FROM Rides) * 100 AS cancellation_rate  
FROM Ride_Cancel as rc  
JOIN Customers as c ON rc.customer_id = c.customer_id  
GROUP BY c.gender;
```

