

WearLoc

Midterm presentation

L. Gemein, D. Speck, A. Biedenkapp, R. Gelhausen, J. Nist

June 6, 2016

Simultaneous Localization and Mapping (SLAM)



Figure: SLAM: <http://ais.informatik.uni-freiburg.de/teaching/ss15/robotics/slides/16-graph-slam.pdf>

- **04.05.2016: Group presentations**
- 2 weeks: installing ROS + connecting Sensor
- 2 weeks: prepearing data (calibrations) + writing interface
- 1 week: time buffer
- **08.06.2016: Mid-Term Presentations**
 - ⇒ all necessary data available/accessible in ROS
- 2 weeks: first SLAM + calibrations
- 2 weeks: refinements + design
- 2 weeks: time buffer
- **20.07.2016: Final Presentations**
 - ⇒ working WearLoc version + (live presentation)

- Notebook running ROS kinetic

- Notebook running ROS kinetic
- Raspberry Pi running ROS indigo


- Notebook running ROS kinetic
- Raspberry Pi running ROS indigo
- Working Wi-Fi connection Pi \Leftrightarrow Notebook

- Notebook running ROS kinetic
- Raspberry Pi running ROS indigo
- Working Wi-Fi connection Pi \Leftrightarrow Notebook
- 360° Laser Scanner Rplidar attached to Pi

- Notebook running ROS kinetic
- Raspberry Pi running ROS indigo
- Working Wi-Fi connection Pi \Leftrightarrow Notebook
- 360° Laser Scanner Rplidar attached to Pi
- Grove IMU 9DOF attached to Pi

- Notebook running ROS kinetic
- Raspberry Pi running ROS indigo
- Working Wi-Fi connection Pi \Leftrightarrow Notebook
- 360° Laser Scanner Rplidar attached to Pi
- Grove IMU 9DOF attached to Pi
- Adapted version of Hector Slam ROS package

IMU demonstration



Prototype demonstration

Yet to come...

- Improve map quality: better IMU calibration, different laser scanner
- Scale it down: Intel Edison instead of Pi, smaller power bank
- Increase operating range: eduroam instead of notebook hotspot
- Make it acutally wearable: one-handed / no-handed design

Yet to come...?

- Include odometry information
- 3D mapping
- Highlight interesting map locations