Aims of today's session

- To explain how the laboratory portion of the Science A module works and how it is assessed.
- To provide you with a general overview of performing a scientific investigation.
- To introduce the concept of uncertainty and how to compare results correctly
- To show you where to go for more information and resources for report writing.



Science A Introduction to Labs and Report Writing

Assessment

 There are 2 laboratory sessions this semester. During each lab sessions, you will perform 3 experiments.

Experiments 1 & 2 are assessed via an online quiz (5%)

• Experiment 3 is assessed via a written report (20%)

 The report is group assessed (so you only submit one report for your lab group), whilst the online quiz is individually assessed.

Purpose of a Report

 In order to write a good scientific report we first need to understand the purpose of a report.



- Why do scientists write reports?
- A scientific report is a way for scientists to share the findings of an investigation with scientific community.
- A report should contain enough information that the reader can understand exactly what was done during an investigation and how the evidence obtained leads to the conclusion(s) of the report.

Evidence

- All scientific discoveries are based upon evidence, in order to claim something as a 'scientific truth' we must have evidence to back it up.
- So how do scientists gather this evidence?
- By performing an investigation (usually involving an experiment) and gathering data.
- So what are the steps involved in performing an investigation?



Performing an Investigation

 Question: We start with a question, why do objects fall towards the ground? Is the earth round?





 Hypothesis: We then create a hypothesis – an initial idea or belief of how an aspect of the universe works, which must be further investigated to prove its validity.



Performing an Investigation

- Choose an Experiment: We then choose an experiment to test our hypothesis
- Make Predictions: We make predictions about what we will observe in the experiment if our hypothesis is correct.
- Perform the Experiment: Now we can carry out our experiment



Performing an Investigation


 Compare Results: Compare the predicted results with the actual results from the experiment.

 Draw Conclusions: Draw conclusions based on evidence from the experiment. Decide if the results support (prove) or refute (disprove) the hypothesis.



Example

 Let's examine a specific experiment and see how this works in practice.



Hypothesis

 For each experiment in this module there is a specific hypothesis we are aiming to test; which is written on the instructions for the experiment.


In the case of this experiment;
 "The acceleration of a vehicle can be accurately modelled using Newton's second law of motion".




Make predictions

 How do we make meaningful predictions about what we will observe in the experiment?


 We need to create an equation which links the control variable (independent variable) with the measured variable (dependent), this is called a mathematical model.




Let's start with a simple diagram



- What are the main forces involved in this experiment?
 - Weight (mass multiplied by acceleration due to gravity)
 - The force from the string (called tension)
- Let's add these to the diagram.



- Now we can use Newton's second law (F = ma) to create our equation linking the independent variable (mass 2) with the dependent variable (acceleration).
- We can then use this equation to predict the value of the dependent variable for different values of the independent variable.



Using Newton's second law on the vehicle we find that

$$T = m_1 a$$

 And using Newton's second law on the mass hanger we find that

$$m_2g - T = m_2a$$

Now we can replace T in our second equation to obtain

$$m_2g - m_1a = m_2a$$

Now we can replace T in our second equation to obtain

$$m_2g - m_1a = m_2a$$

 Now we can rearrange the equation to make acceleration, a, the subject.

$$m_2g = m_2a + m_1a$$

$$m_2g = (m_1 + m_2)a$$

$$a = \frac{m_2 g}{(m_1 + m_2)}$$

Note what he have just done is known as deriving the equation.

- A mathematical model is simply a tool to represent the real world in the form of one or more equations.
- A mathematical model is usually a simplification of the real world; as it does not include all of the possible factors that can affect the results.
- What factors have we ignored when we made our model?
- Discuss with the people around you and try to come up with 3 such factors.

Assumptions

- Discuss with the people around you and try to come up with 3 such factors.
- Friction and air resistance have a negligible effect.
- The track is perfectly horizontal.
- The string has no mass and is inextensible.
- The acceleration due to gravity is constant at $9.81~\mathrm{m}\cdot\mathrm{s}^{-2}$

 We hope that all of our assumptions are close to being true, then our predictions will be accurate!

Assumptions

- We call these factors modelling assumptions, as we are assuming they will have no affect on the results.
- This is obviously not true, but if the effect they
 have is small enough then it is okay to assume they
 have no affect.
- When writing a report the assumptions are very important as often if the results do not match the predictions it is because we have a bad assumption, not because the hypothesis is wrong!

Perform the Experiment

 Now that we can make our predictions, we can perform the experiment and gather our results.

Table 1: Mass of the vehicle.

$m{m_1} \ (\mathbf{g})$	
100	

Table 2. Measurements and predicted values.

Measurement no.	m ₂ (g)	$\frac{m_2}{m_1+m_2}$	Measured acceleration (ms ⁻²)			Predicted acceleration a_p	
			a_1	a_2	a_3	a_m	(ms^{-2})
1	50.1	0.334	3.26	3.28	3.29	3.28	3.27
2	60.1	0.375	3.71	3.67	3.69	3.69	3.68
3	70.1	0.412	4.06	4.06	4.04	4.05	4.04
4	80.1	0.445	4.52	4.49	4.50	4.50	4.36
5	90.1	0.474	4.82	4.81	4.79	4.81	4.65
6	100.1	0.500	5.12	5.13	5.11	5.12	4.91

Perform the Experiment

Table 2. Measurements and predicted values.

Measurement no.	m_2 (g)	$\frac{m_2}{m_1+m_2}$	Measured acceleration (ms ⁻²)			Predicted acceleration a_p	
	(8)	1101 1 1102	a_1	a_2	a_3	a_m	(ms^{-2})
1	50.1	0.334	3.26	3.28	3.29	3.28	3.27
2	60.1	0.375	3.71	3.67	3.69	3.69	3.68
3	70.1	0.412	4.06	4.06	4.04	4.05	4.04
4	80.1	0.445	4.52	4.49	4.50	4.50	4.36
5	90.1	0.474	4.82	4.81	4.79	4.81	4.65
6	100.1	0.500	5.12	5.13	5.11	5.12	4.91

- You may have noticed that the measured and predicted values in the table are not the same, does this mean that the results do not support the hypothesis?
- How do we decide how close the predicted and measured results need to be?

- First of all we need to realise that there is no such thing as a perfect measurement, every measurement we make has uncertainty.
- The uncertainty in a measurement represents the range of statistically likely values that true value of the measurement could take.

 $Measurement = value \pm uncertainty$

 This plus/minus uncertainty tells us how much bigger or smaller than the value we have measured our measurement could be.

- Whenever we measure something we are approximating the true value to a certain number of decimal places, there is always uncertainty since we don't know the value of the decimal places we can't measure!
- For example a measurement of length as 20.8 cm could actually be 20.8237... we don't know the value of the additional decimal places since our ruler can only measure to 1 decimal place.

$$l = 20.8 \pm uncertainty$$
 cm

• The uncertainty in a measurement is **denoted by the Greek letter delta** δ . For example if we have a measurement of x then the symbol for the **uncertainty** in the measurement is δx .

$$x = value \pm \delta x$$

 For each lab session there is an uncertainty guide available on Moodle which gives you all the equations you will need. For this module you will not be asked to create your own uncertainty equations.

Table 3: Mass of the vehicle.

δm_1
(g)
0.29

Table 4. Uncertainties associated with the measured and predicted values.

Measurement no.	$\delta m_2 \ ({f g})$	$\delta\left(\frac{m_2}{m_1+m_2}\right)$	$\delta a_m \ (\mathbf{m} \cdot \mathbf{s}^{-2})$	$\delta a_p \ (\mathbf{m} \cdot \mathbf{s}^{-2})$
1	0.29	0.03	0.07	0.01
2	0.29	0.04	0.07	0.01
3	0.29	0.04	0.08	0.01
4	0.29	0.04	0.09	0.01
5	0.29	0.04	0.10	0.01
6	0.29	0.04	0.10	0.01

 So we can use the formulae provided to calculate the uncertainty in the measured and predicted values.

 For two values to agree they need to have possible values in common when we consider the uncertainty.

Value

For example

$$x_m = 20.8 \pm 0.2$$

$$20.6 \le x_m \le 21.0$$

Uncertainty

$$x_p = 20.7 \pm 0.4$$

$$20.3 \le x_p \le 21.1$$

• The predicted value, x_p , agrees with the measured value, x_m , since there are values they have in common when we consider the uncertainty.

- Normally at this point we would also plot a graph of our results and analyse the values from the graph as additional sources of evidence.
- However for this example we will leave this step out as producing the graph and analysing it is a significant amount of work.
- There is a training PPT and exercise available on Moodle in the report writing section and you should work your way through it in your own time to make sure you can do this for your own reports.

To analyse a set of results we should ask ourselves 4 simple questions.

- 1) How many of the measured results agreed with the predicted results?
- 2) Is there an observable pattern to how the measured and predicted results differ?
- 3) What are most likely sources of any discrepancies between our measured and predicted results?
- 4) Overall, do the measured results support your hypothesis or not?

1) How many of the measured results agreed with the predicted results?

Measurement	a_m	δa_m	a_p	δa_p
no.	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$
1	3.28	0.07	3.27	0.01
2	3.69	0.07	3.68	0.01
3	4.05	0.08	4.04	0.01
4	4.50	0.09	4.36	0.01
5	4.81	0.10	4.65	0.01
6	5.12	0.10	4.91	0.01

 So 3 out of 6 of the measured values agree with the predicted values.

2) Is there an observable pattern to how the measured and predicted results differ?

Measurement	a_m	δa_m	a_p	δa_p
no.	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$
1	3.28	0.07	3.27	0.01
2	3.69	0.07	3.68	0.01
3	4.05	0.08	4.04	0.01
4	4.50	0.09	4.36	0.01
5	4.81	0.10	4.65	0.01
6	5.12	0.10	4.91	0.01

• The results all agree for small values of mass, m_2 , as m_2 gets larger our measurements get further away from the predictions.

2) Is there an observable pattern to how the measured and predicted results differ?

Measurement	a_m	δa_m	a_p	δa_p
no.	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$	$(\mathbf{m} \cdot \mathbf{s}^{-2})$
1	3.28	0.07	3.27	0.01
2	3.69	0.07	3.68	0.01
3	4.05	0.08	4.04	0.01
4	4.50	0.09	4.36	0.01
5	4.81	0.10	4.65	0.01
6	5.12	0.10	4.91	0.01

 Also all of the measured values which disagree are larger than the predicted value.

- 3) What are most likely sources of any discrepancies between our measured and predicted results?
- A good answer to this question is to consider the modelling assumptions, this demonstrates we are thinking about a scientific explanation for the results.
- A poor answer to this question is to claim that results are an error or caused by faulty equipment



- 3) What are most likely sources of any discrepancies between our measured and predicted results?
- There are 3 values that don't match the predictions and they are all larger than we predicted. Why that might be the case?
- Lets review the assumptions and think about which might have affected the results in this manner.
 - The string has no mass and is inextensible. X
 - Friction and air resistance have a negligible effect. X
 - The track is perfectly horizontal.
 - The acceleration due to gravity is constant at $9.81 \text{ m} \cdot \text{s}^{-2}$

Discussion

- 4) Overall, do the measured results support your hypothesis or not?
- To support a hypothesis we need the majority (more than half) of the measured values to agree with the predicted values.
- Since only half of the results agree with the predicted values there is not enough evidence to support the hypothesis.



Draw Conclusions

- The conclusion is where we pull together everything we have talked about when comparing the results and come to an overall conclusion about the experiment.
- Did the experiment support your initial hypothesis or not?
- It is worth mentioning that it doesn't matter if the
 experiment supports the hypothesis or not. What matters is
 that you base your conclusion on the evidence you have
 collected.
- If the results don't support the hypothesis but your conclusion states that they do, then you will score poorly on a report.

Draw Conclusions

- To write a good conclusion we should ask ourselves
 3 simple questions.
- 1) Based on the results does our experiment demonstrate the validity of the hypothesis or not?
- 2) Which of the factors we have discussed is the main source of any measured results differing from predicted results?
- 3) What improved experimental techniques or mathematical models could account for these discrepancies in future investigations?


Conclusion

- 1) Based on the results does our experiment demonstrate the validity of the hypothesis or not?
- Half of the results obtained were found to be within the corresponding predicted acceleration value ranges, while for the other half, this was not the case. This evidence was insufficient to support the hypothesis.



Conclusion

- 2) Which of the factors we have discussed is the main source of any measured results differing from predicted results?
- The main factor which affected the results was most likely to be the apparatus not having been setup perfectly horizontal, this would have caused a component of the vehicles weight to increase the acceleration and would explain why the values that differed were larger than predicted.



Conclusion

3) What improved experimental techniques or mathematical models could account for these discrepancies in future investigations?

This experiment could be further improved by;

- using a spirit level to ensure that the air track was perfectly horizontal
- obtaining an accurate value for the local acceleration due to gravity
- taking in to account the effect of air resistance in the mathematical model.

Writing a Report

- A Scientific Report can be broadly broken down in to the following sections:
 - Abstract
 - Objective & Introduction
 - Apparatus & Procedure
 - Results & Uncertainty analysis
 - Discussion
 - Conclusion

