



We are hiring

HOME

TUTORIALS LIBRARY ▾

CODING GROUND

TUTOR CONNECT

SEND18

TOOLS Q Search



C Programming Tutorial

C - Home

C - Overview

C - Environment Setup

C - Program Structure

C - Basic Syntax

C - Data Types

C - Variables

C - Constants

C - Storage Classes

C - Operators

C - Decision Making

C - Loops

C - Functions

C - Scope Rules

C - Arrays

C - Pointers

C - Strings

C - Structures

C - Unions

C - Bit Fields

C - Typedef

C - Input & Output

C - File I/O

C - Preprocessors

C - Header Files

C - Type Casting

C - Error Handling

C - Recursion

C - Variable Arguments


C - Memory Management

C - Command Line Arguments

C Programming Resources

C - Pointer arithmetic

Advertisements



Previous Page

Next Page

A pointer in c is an address, which is a numeric value. Therefore, you can perform arithmetic operations on a pointer just as you can on a numeric value. There are four arithmetic operators that can be used on pointers: ++, --, +, and -

To understand pointer arithmetic, let us consider that **ptr** is an integer pointer which points to the address 1000. Assuming 32-bit integers, let us perform the following arithmetic operation on the pointer –

ptr++

After the above operation, the **ptr** will point to the location 1004 because each time ptr is incremented, it will point to the next integer location which is 4 bytes next to the current location. This operation will move the pointer to the next memory location without impacting the actual value at the memory location. If **ptr** points to a character whose address is 1000, then the above operation will point to the location 1001 because the next character will be available at 1001.

Incrementing a Pointer

We prefer using a pointer in our program instead of an array because the variable pointer can be incremented, unlike the array name which cannot be incremented because it is a constant pointer. The following program increments the variable pointer to access each succeeding element of the array –

```
#include <stdio.h>

const int MAX = 3;

int main () {

    int var[] = {10, 100, 200};
    int i, *ptr;

    /* let us have array address in pointer */
    ptr = var;

    for ( i = 0; i < MAX; i++) {

        printf("Address of var[%d] = %x\n", i, ptr );
        printf("Value of var[%d] = %d\n", i, *ptr );

        /* move to the next location */
        ptr++;
    }

    return 0;
}
```

When the above code is compiled and executed, it produces the following result –



MongoLab is now **mLab**
MongoDB-as-a-Service

TRY NOW



Work at a startup

No resumes,
just show us you can code

[C - Questions & Answers](#)[C - Quick Guide](#)[C - Useful Resources](#)[C - Discussion](#)[Selected Reading](#)[Developer's Best Practices](#)[Questions and Answers](#)[Effective Resume Writing](#)[HR Interview Questions](#)[Computer Glossary](#)[Who is Who](#)

```
Address of var[0] = bf882b30
Value of var[0] = 10
Address of var[1] = bf882b34
Value of var[1] = 100
Address of var[2] = bf882b38
Value of var[2] = 200
```

Decrementing a Pointer

The same considerations apply to decrementing a pointer, which decreases its value by the number of bytes of its data type as shown below –

```
#include <stdio.h>

const int MAX = 3;

int main () {

    int var[] = {10, 100, 200};
    int i, *ptr;

    /* let us have array address in pointer */
    ptr = &var[MAX-1];

    for ( i = MAX; i > 0; i--) {

        printf("Address of var[%d] = %x\n", i, ptr );
        printf("Value of var[%d] = %d\n", i, *ptr );

        /* move to the previous location */
        ptr--;

    }

    return 0;
}
```

When the above code is compiled and executed, it produces the following result –

```
Address of var[3] = bfeedbcd8
Value of var[3] = 200
Address of var[2] = bfeedbcd4
Value of var[2] = 100
Address of var[1] = bfeedbcd0
Value of var[1] = 10
```

Pointer Comparisons

Pointers may be compared by using relational operators, such as ==, <, and >. If p1 and p2 point to variables that are related to each other, such as elements of the same array, then p1 and p2 can be meaningfully compared.

The following program modifies the previous example – one by incrementing the variable pointer so long as the address to which it points is either less than or equal to the address of the last element of the array, which is &var[MAX - 1] –

```
#include <stdio.h>

const int MAX = 3;

int main () {

    int var[] = {10, 100, 200};
    int i, *ptr;

    /* let us have address of the first element in pointer */
    ptr = var;
    i = 0;

    while ( ptr <= &var[MAX - 1] ) {

        printf("Address of var[%d] = %x\n", i, ptr );
        printf("Value of var[%d] = %d\n", i, *ptr );

        /* point to the previous location */
        ptr++;
        i++;
    }

    return 0;
}
```

When the above code is compiled and executed, it produces the following result –

```
Address of var[0] = bfdbcb20
Value of var[0] = 10
Address of var[1] = bfdbcb24
Value of var[1] = 100
Address of var[2] = bfdbcb28
Value of var[2] = 200
```

[Previous Page](#)[Print](#)[Next Page](#)

Advertisements

[Write for us](#) [FAQ's](#) [Helping](#) [Contact](#)

© Copyright 2016. All Rights Reserved.

[go](#)