# **Performance Optimization** for Stampede

Jim Browne, Leo Fialho and Ashay Rane

# **XSEDE 2013**





## Agenda

- Why another performance tool?
- What is MACPO?
- What does MACPO tell you?
- ▶ How to use MACPO?
- Details of MACPO metrics

#### State of the art

- ▶ Modern processors can record performance events
- ▶ Performance events provide accurate view of CPU execution
- ▶ Various tools exist to correlate perormance events to user code
- Ex: PerfExpert, TAU, HPCToolkit, VTune, Scalasca, etc.

## But memory is a bigger problem than CPU




Figure 2.2 Starting with 1980 performance as a baseline, the gap in performance, measured as the difference in the time between processor memory requests (for a single processor or core) and the latency of a DRAM access, is plotted over time.

Source: Computer Architecture: A Quantitative Approach, 4th Edition by Hennessy and Patterson

## But memory is a bigger problem than CPU




Figure 2.2 Starting with 1980 performance as a baseline, the gap in performance, measured as the difference in the time between processor memory requests (for a single processor or core) and the latency of a DRAM access, is plotted over time.

Source: Computer Architecture: A Quantitative Approach, 4th Edition by Hennessy and Patterson

- For data-intensive applications, application performance usually dependent on memory and not the processor.
- Performance events provide a CPU-centric, not a memory-centric view.



## Limitations for performance events:

## #1: Fine-grain measurements

- Performance events are measured on execution of each instruction
- ▶ mov ah, [1234h] causes cache miss,
  ⇒ increment cache miss counter
- But memory is optimized for stream traffic and regular accesses (locality, bandwidth, reuse)
- Hence gap between measurements and optimization techniques



## Limitations for performance events:

## #2: Ambiguous interpretation

- ▶ Same symptoms but different root causes
- ► For instance, L3 cache misses could mean any of the following:
  - Capacity misses (cold cache)
  - ▶ Poor locality (less reuse of data structures)
  - ► False sharing (two processors writing to same cache line)

## Limitations for performance events:


## #3: Little or no scoping

- ▶ Performance events are triggered for all instructions
- ▶ Hence all memory accesses are profiled
- ▶ But information about only specific data structures is desirable
- Can greatly speed up problem resolution

# Hence, MACPO Memory Access Centric Performance Optimization

- Analyzes access patterns to find sources of inefficiency
- Used as part of the compilation process
- Tracks accesses to arrays and structures within a function
- ► Tags each such access with source code location
- Analyzes accesses to see if access patterns can be improved
- ▶ Works with C, C++ and Fortran code [+ Pthreads, OpenMP]

#### MACPO workflow



Combines information from compiler, architecture and simulation



## What does MACPO tell you?

For each important variable, MACPO shows:

- Access strides and the frequency of occurence
- Presence or absence of cache thrashing and the frequency
- NUMA misses
- Reuse factors for data caches

## Sample output

Var "counts", seen 1668 times, estimated to cost 147.12 cycles on every access Stride of 0 cache lines was observed 1585 times (100.00%).

#### How to use MACPO?

- ► Compile application using macpo.sh
- Run application as usual
- ► Analyze macpo logs using macpo-analyze

#### How to use MACPO?

- # Compile the application using macpo.sh
- # Specify code section using --macpo:function or --macpo:loop
- \$ macpo.sh --macpo:function=thread\_func -o mcpi mcpi.cc -lpthread -lrt
- # Run the application as usual
- \$ ./mcpi
- # Post-process logs to get analysis output
- \$ macpo-analyze macpo.out

## Understanding MACPO metrics

- Access strides
- Cache conflicts
- NUMA misses
- Reuse factor for data caches

## Metric #1: Cycles per access

#### Example:

Var "counts", seen 1073 times, estimated to cost 8.98 cycles on every access

- ▶ Provides esimate of performance impact of accesses to variable
- ▶ Can be used to rule-out variables from further consideration

### Metric #2: Access strides

#### Example:

Stride of 0 cache lines was observed 983 times (97.62%). Stride of 2 cache lines was observed 24 times (2.38%).

- Programs that have unit strides or small regular stride values generally execute fast
- ► If stide value is high, look for inverted loops affecting the row-major or column-major ordering

## Metric #3: Cache conflicts

#### Example:

```
Level 1 data cache conflicts = 78.22%
Level 2 data cache conflicts = 63.37%
```

- Indicates multiple cores writing to the same cache line
- ► Add dummy bytes to the array so that each processor writes to a different cache line

## Metric #4: NUMA misses

#### Example:

NUMA data conflicts = 43.56%

- ► NUMA misses generally arise from one processor initializing all of the shared memory
- ► To eliminate NUMA misses, have each processor initialize it's portion of shared memory

## Metric #5: Reuse factors

#### Example:

```
Level 1 data cache reuse factor = 94.1%
Level 2 data cache reuse factor = 5.9%
Level 3 data cache reuse factor = 0.0%
```

- Reuse factor indicates the number of times a cache was reused before it was evicted
- ▶ Improve reuse factors by using techniques to improve locality

## Summary

- ► MACPO is a tool to analyze memory access patterns
- NOT a replacement for PerfExpert. Instead, complements PerfExpert's diagnosis.
- Allows collection of memory traces for arrays and structures
- Analyzes traces offline to calculate performance metrics
- ▶ This is an early release, please help us squash the bugs! :)

## Sample application

- Monte-Carlo computation of Pi
- ▶ Source code online at: http://goo.gl/uEVrh or at ~train300/sample-programs.tar.gz
- ▶ Uses basic C++, parallelized using Pthreads
- Tasks performed by each thread:
  - Generates a buffer of random numbers
  - For each pair of random numbers, calculates z
  - Checks a condition on z, based on the result increments a counter

#### Thread function

```
int t;
float x, y, z;
thread info t* thread info = (thread info t*) arg;
for (int repeat=0; repeat<REPEAT_COUNT; repeat++)</pre>
{
  for (int i=0; i<ITERATIONS; i++)</pre>
    t = i+thread info->tid;
    x = random_numbers[t%RANDOM_BUFFER_SIZE];
    v = random numbers[(1+t)%RANDOM BUFFER SIZE];
    z = x*x + y*y;
    if (z < 1) counts[thread info->tid]++;
```

## Commands for sample code

- # Extract the source code into the local directory
- \$ tar -xzf /home1/0003/train300/sample-programs.tar.gz
- # Switch to the directory that contains the Monte-Carlo Pi code cd sample-programs/monte-carlo/
- # Compile the application using macpo.sh
- # Specify code section using --macpo:function or --macpo:loop
- # Run the application as usual
- \$ ./mm
- # Post-process logs to get analysis output
- \$ macpo-analyze macpo.out



## MACPO analysis output (truncated)

```
$ macpo-analyze macpo.out
```

```
Var "counts", seen 1668 times, estimated to cost 147.12 cycles on every access
```

Stride of 0 cache lines was observed 1585 times (100.00%).

```
Level 1 data cache conflicts = 78.22%
Level 2 data cache conflicts = 63.37%
NUMA data conflicts = 43.56%
```

```
Level 1 data cache reuse factor = 97.0%
Level 2 data cache reuse factor = 3.0%
Level 3 data cache reuse factor = 0.0%
```



#### Problem resolution

- ► MACPO shows cache thrashing for **counts** variable.
- Solution: Add dummy bytes, thus all processors write to different cache lines
- Optimized code in monte-carlo-v2.cc

## MACPO analysis output for optimized code (truncated)

```
$ macpo-analyze macpo.out
```

```
Var "counts", seen 1073 times, estimated to cost 8.98 cycles on every access
```

Stride of 0 cache lines was observed 983 times (97.62%). Stride of 2 cache lines was observed 24 times (2.38%).

```
Level 1 data cache conflicts = 0.00%
Level 2 data cache conflicts = 0.00%
NUMA data conflicts = 0.00%
```

Level 1 data cache reuse factor = 94.1% Level 2 data cache reuse factor = 5.9% Level 3 data cache reuse factor = 0.0%





#### Review

- ► Compiled application using macpo.sh
- Discovered cache thrashing for the counts array
- ▶ Padding the array reduced cache conflicts from 70% to 0%
- ► Execution time: 9.14s to 3.17s (65% improvement)

## Summary of MACPO instructions

- # Extract the source code into the local directory
- \$ tar -xzf /home1/0003/train300/sample-programs.tar.gz
- # Switch to the directory that contains the Monte-Carlo Pi code cd sample-programs/monte-carlo/
- # Compile the application using macpo.sh
- # Specify code section using --macpo:function or --macpo:loop
- $\verb§ macpo.sh --macpo:function=thread_func monte-carlo.cc -o mm -lpthread$
- # Run the application as usual
- \$ ./mm
- # Post-process logs to get analysis output
- \$ macpo-analyze macpo.out

