



# HTML Input Types

[< Previous](#)[Next >](#)

This chapter describes the different types for the HTML `<input>` element.

## HTML Input Types

Here are the different input types you can use in HTML:

- `<input type="button">`
- `<input type="checkbox">`
- `<input type="color">`
- `<input type="date">`
- `<input type="datetime-local">`
- `<input type="email">`
- `<input type="file">`
- `<input type="hidden">`
- `<input type="image">`
- `<input type="month">`
- `<input type="number">`
- `<input type="password">`
- `<input type="radio">`
- `<input type="range">`
- `<input type="reset">`
- `<input type="search">`
- `<input type="submit">`
- `<input type="tel">`
- `<input type="text">`
- `<input type="time">`
- `<input type="url">`
- `<input type="week">`

**Tip:** The default value of the `type` attribute is "text".

---

# Input Type Text

`<input type="text">` defines a **single-line text input field**:

## Example

```
<form>
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname">
</form>
```

[Try it Yourself »](#)

This is how the HTML code above will be displayed in a browser:

First name:

Last name:

---

# Input Type Password

`<input type="password">` defines a **password field**:

## Example

```
<form>
  <label for="username">Username:</label><br>
  <input type="text" id="username" name="username"><br>
  <label for="pwd">Password:</label><br>
  <input type="password" id="pwd" name="pwd">
</form>
```

[Try it Yourself »](#)

This is how the HTML code above will be displayed in a browser:

Username:

Password:

The characters in a password field are masked (shown as asterisks or circles).

---

## Input Type Submit

`<input type="submit">` defines a button for **submitting** form data to a **form-handler**.

The form-handler is typically a server page with a script for processing input data.

The form-handler is specified in the form's `action` attribute:

## Example

```
<form action="/action_page.php">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname" value="John"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname" value="Doe"><br><br>
  <input type="submit" value="Submit">
</form>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

First name:

Last name:

If you omit the submit button's value attribute, the button will get a default text:

## Example

```
<form action="/action_page.php">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname" value="John"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname" value="Doe"><br><br>
  <input type="submit">
</form>
```

Try it Yourself »

## Input Type Reset

`<input type="reset">` defines a **reset button** that will reset all form values to their default values:

## Example

```
<form action="/action_page.php">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname" value="John"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname" value="Doe"><br><br>
  <input type="submit" value="Submit">
  <input type="reset">
</form>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

First name:

Last name:

If you change the input values and then click the "Reset" button, the form-data will be reset to the default values.

---

## Input Type Radio

`<input type="radio">` defines a **radio button**.

Radio buttons let a user select ONLY ONE of a limited number of choices:

### Example

```
<p>Choose your favorite Web language:</p>

<form>
  <input type="radio" id="html" name="fav_language" value="HTML">
  <label for="html">HTML</label><br>
  <input type="radio" id="css" name="fav_language" value="CSS">
  <label for="css">CSS</label><br>
  <input type="radio" id="javascript" name="fav_language" value="JavaScript">
  <label for="javascript">JavaScript</label>
</form>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

- ☐ HTML
  - ☐ CSS
  - ☐ JavaScript
- 

## Input Type Checkbox

`<input type="checkbox">` defines a **checkbox**.

Checkboxes let a user select ZERO or MORE options of a limited number of choices.

### Example

```
<form>
  <input type="checkbox" id="vehicle1" name="vehicle1" value="Bike">
```

```
<label for="vehicle1"> I have a bike</label><br>
<input type="checkbox" id="vehicle2" name="vehicle2" value="Car">
<label for="vehicle2"> I have a car</label><br>
<input type="checkbox" id="vehicle3" name="vehicle3" value="Boat">
<label for="vehicle3"> I have a boat</label>
</form>
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

- ☐ I have a bike
  - ☐ I have a car
  - ☐ I have a boat
- 

## Input Type Button

`<input type="button">` defines a **button**:

### Example

```
<input type="button" onclick="alert('Hello World!')" value="Click Me!">
```

Try it Yourself »

This is how the HTML code above will be displayed in a browser:

Click Me!

---

## Input Type Color

The `<input type="color">` is used for input fields that should contain a color.

Depending on browser support, a color picker can show up in the input field.

### Example

```
<form>
  <label for="favcolor">Select your favorite color:</label>
```

```
<input type="color" id="favcolor" name="favcolor">
</form>
```

[Try it Yourself »](#)

---

## Input Type Date

The `<input type="date">` is used for input fields that should contain a date.

Depending on browser support, a date picker can show up in the input field.

### Example

```
<form>
  <label for="birthday">Birthday:</label>
  <input type="date" id="birthday" name="birthday">
</form>
```

[Try it Yourself »](#)

You can also use the `min` and `max` attributes to add restrictions to dates:

### Example

```
<form>
  <label for="datemax">Enter a date before 1980-01-01:</label>
  <input type="date" id="datemax" name="datemax" max="1979-12-31"><br><br>
  <label for="datemin">Enter a date after 2000-01-01:</label>
  <input type="date" id="datemin" name="datemin" min="2000-01-02">
</form>
```

[Try it Yourself »](#)

---

## Input Type Datetime-local

The `<input type="datetime-local">` specifies a date and time input field, with no time zone.

Depending on browser support, a date picker can show up in the input field.

## Example

```
<form>
  <label for="birthdaytime">Birthday (date and time):</label>
  <input type="datetime-local" id="birthdaytime" name="birthdaytime">
</form>
```

[Try it Yourself »](#)

---

## Input Type Email

The `<input type="email">` is used for input fields that should contain an e-mail address.

Depending on browser support, the e-mail address can be automatically validated when submitted.

Some smartphones recognize the email type, and add ".com" to the keyboard to match email input.

## Example

```
<form>
  <label for="email">Enter your email:</label>
  <input type="email" id="email" name="email">
</form>
```

[Try it Yourself »](#)

---

## Input Type Image

The `<input type="image">` defines an image as a submit button.

The path to the image is specified in the `src` attribute.

## Example



```
<form>
<input type="image" src="img_submit.gif" alt="Submit" width="48" height="48">
</form>
```

Try it Yourself »

---

## Input Type File

The `<input type="file">` defines a file-select field and a "Browse" button for file uploads.

### Example

```
<form>
  <label for="myfile">Select a file:</label>
  <input type="file" id="myfile" name="myfile">
</form>
```

Try it Yourself »

---

## Input Type Hidden

The `<input type="hidden">` defines a hidden input field (not visible to a user).

A hidden field lets web developers include data that cannot be seen or modified by users when a form is submitted.

A hidden field often stores what database record that needs to be updated when the form is submitted.

**Note:** While the value is not displayed to the user in the page's content, it is visible (and can be edited) using any browser's developer tools or "View Source" functionality. Do not use hidden inputs as a form of security!

### Example

```
<form>
  <label for="fname">First name:</label>
  <input type="text" id="fname" name="fname"><br><br>
  <input type="hidden" id="custId" name="custId" value="3487">
```

```
<input type="submit" value="Submit">
</form>
```

[Try it Yourself »](#)

---

## Input Type Month

The `<input type="month">` allows the user to select a month and year.

Depending on browser support, a date picker can show up in the input field.

### Example

```
<form>
  <label for="bdaymonth">Birthday (month and year):</label>
  <input type="month" id="bdaymonth" name="bdaymonth">
</form>
```

[Try it Yourself »](#)

---

## Input Type Number

The `<input type="number">` defines a **numeric** input field.

You can also set restrictions on what numbers are accepted.

The following example displays a numeric input field, where you can enter a value from 1 to 5:

### Example

```
<form>
  <label for="quantity">Quantity (between 1 and 5):</label>
  <input type="number" id="quantity" name="quantity" min="1" max="5">
</form>
```

[Try it Yourself »](#)

---

# Input Restrictions

Here is a list of some common input restrictions:

Attribute	Description
checked	Specifies that an input field should be pre-selected when the page loads (for type="checkbox" or type="radio")
disabled	Specifies that an input field should be disabled
max	Specifies the maximum value for an input field
maxlength	Specifies the maximum number of character for an input field
min	Specifies the minimum value for an input field
pattern	Specifies a regular expression to check the input value against
readonly	Specifies that an input field is read only (cannot be changed)
required	Specifies that an input field is required (must be filled out)
size	Specifies the width (in characters) of an input field
step	Specifies the legal number intervals for an input field
value	Specifies the default value for an input field

You will learn more about input restrictions in the next chapter.

The following example displays a numeric input field, where you can enter a value from 0 to 100, in steps of 10. The default value is 30:

## Example

```
<form>
  <label for="quantity">Quantity:</label>
  <input type="number" id="quantity" name="quantity" min="0" max="100" step="10"
value="30">
</form>
```

[Try it Yourself »](#)

## Input Type Range

The `<input type="range">` defines a control for entering a number whose exact value is not important (like a slider control). Default range is 0 to 100. However, you can set restrictions on what numbers are accepted with the `min`, `max`, and `step` attributes:

## Example

```
<form>
  <label for="vol">Volume (between 0 and 50):</label>
  <input type="range" id="vol" name="vol" min="0" max="50">
</form>
```

Try it Yourself »

---

## Input Type Search

The `<input type="search">` is used for search fields (a search field behaves like a regular text field).

## Example

```
<form>
  <label for="gsearch">Search Google:</label>
  <input type="search" id="gsearch" name="gsearch">
</form>
```

Try it Yourself »

---

## Input Type Tel

The `<input type="tel">` is used for input fields that should contain a telephone number.

## Example

```
<form>
  <label for="phone">Enter your phone number:</label>
  <input type="tel" id="phone" name="phone" pattern="[0-9]{3}-[0-9]{2}-[0-9]{3}">
</form>
```

# Input Type Time

The `<input type="time">` allows the user to select a time (no time zone).

Depending on browser support, a time picker can show up in the input field.

## Example

```
<form>
  <label for="appt">Select a time:</label>
  <input type="time" id="appt" name="appt">
</form>
```

Try it Yourself »

---

# Input Type Url

The `<input type="url">` is used for input fields that should contain a URL address.

Depending on browser support, the url field can be automatically validated when submitted.

Some smartphones recognize the url type, and adds ".com" to the keyboard to match url input.

## Example

```
<form>
  <label for="homepage">Add your homepage:</label>
  <input type="url" id="homepage" name="homepage">
</form>
```

Try it Yourself »

---

# Input Type Week

The `<input type="week">` allows the user to select a week and year.

Depending on browser support, a date picker can show up in the input field.

## Example

```
<form>
  <label for="week">Select a week:</label>
  <input type="week" id="week" name="week">
</form>
```

[Try it Yourself »](#)

---

## HTML Exercises

### Test Yourself With Exercises

#### Exercise:

In the form below, add an input field for text, with the name "username" .

```
<form action="/action_page.php">
<                                     >
</form>
```


[Submit Answer »](#)

[Start the Exercise](#)

---

## HTML Input Type Attribute

Tag	Description
<code>&lt;input type=""&gt;</code>	Specifies the input type to display

[< Previous](#)
[Next >](#)



COLOR PICKER



Get certified  
by completing  
a HTML  
course today!



Get started



---

Report Error

Spaces

Upgrade

Newsletter

Get Certified

---

## Top Tutorials

HTML Tutorial  
CSS Tutorial  
JavaScript Tutorial  
How To Tutorial  
SQL Tutorial  
Python Tutorial  
W3.CSS Tutorial  
Bootstrap Tutorial  
PHP Tutorial  
Java Tutorial  
C++ Tutorial  
jQuery Tutorial

## Top References

HTML Reference  
CSS Reference



[JavaScript Reference](#)  
[SQL Reference](#)  
[Python Reference](#)  
[W3.CSS Reference](#)  
[Bootstrap Reference](#)  
[PHP Reference](#)  
[HTML Colors](#)  
[Java Reference](#)  
[Angular Reference](#)  
[jQuery Reference](#)

## Top Examples

[HTML Examples](#)  
[CSS Examples](#)  
[JavaScript Examples](#)  
[How To Examples](#)  
[SQL Examples](#)  
[Python Examples](#)  
[W3.CSS Examples](#)  
[Bootstrap Examples](#)  
[PHP Examples](#)  
[Java Examples](#)  
[XML Examples](#)  
[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)  
[CSS Certificate](#)  
[JavaScript Certificate](#)  
[Front End Certificate](#)  
[SQL Certificate](#)  
[Python Certificate](#)  
[PHP Certificate](#)  
[jQuery Certificate](#)  
[Java Certificate](#)  
[C++ Certificate](#)  
[C# Certificate](#)  
[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

