

ANDROID STATIC ANALYSIS REPORT



♠ My Scan APP (2.0)

File Name:	sample.apk		
Package Name:	com.ldjSxw.heBbQd		
Scan Date:	Nov. 19, 2024, 12:38 p.m.		
App Security Score:	37/100 (HIGH RISK)		
Grade:	C		

G FINDINGS SEVERITY

☆ HIGH	▲ MEDIUM	i INFO	✓ SECURE	Q НОТЅРОТ
5	8	0	1	1

FILE INFORMATION

File Name: sample.apk

Size: 33.5MB

MD5: f90f81f7b47ca73de0e5aa5aaeba6735

SHA1: f5c894ac5aeb6f23953b0dad7ff57dc937d95149

SHA256 : 82 d 64 4 a 1 f 3 b b a 120327 e 7 e b 6029 f 6 b 986 c 95 c 35 f 0 c 40 c d 43001 f 2 d b e de e 2 e e 6 f

i APP INFORMATION

App Name: My Scan APP

Package Name: com.ldjSxw.heBbQd

Main Activity: com.ldjSxw.heBbQd.IntroActivity

Target SDK: 28 Min SDK: 23 Max SDK:

Android Version Name: 2.0 Android Version Code: 20

EXAMPLE APP COMPONENTS

Activities: 4 Services: 5 Receivers: 3 Providers: 2

Exported Activities: 2
Exported Services: 2
Exported Receivers: 2
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed v1 signature: True v2 signature: True v3 signature: False v4 signature: False

X.509 Subject: C=CN, ST=Shanghai, L=ZB, O=Shanghai University, OU=NC, CN=tmp

Signature Algorithm: rsassa_pkcs1v15 Valid From: 2023-10-16 12:18:00+00:00 Valid To: 2123-09-22 12:18:00+00:00

Issuer: C=CN, ST=Shanghai, L=ZB, O=Shanghai University, OU=NC, CN=tmp

Serial Number: 0xa2cda5f Hash Algorithm: sha256

md5: 7eb61921f7d6a137681b91903163044f

sha1: 85e7916ac9aa2a5700f73140a9e40fa4ac0abab1

sha256: 006a72fa8f6dc3e38ebe32189d2101c191671bef63ed9eb919ccab20080bded3

PublicKey Algorithm: rsa

Bit Size: 2048

Fingerprint: dd8f6a3567c31bb2e77b04e031044b734f0b13e1b68832daed4e36bf43615304

Found 1 unique certificates

E APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.REQUEST_DELETE_PACKAGES	normal	enables an app to request package deletions.	Allows an application to request deleting packages.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.DISABLE_KEYGUARD	normal	disable keyguard	Allows applications to disable the keyguard if it is not secure.
android.permission.BOOT_COMPLETED	unknown	Unknown permission	Unknown permission from android reference

PERMISSION	STATUS	INFO	DESCRIPTION
1 EKWI 5516 K	317(103	11110	BESCHII TION

android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.GET_TASKS	dangerous	retrieve running applications	Allows application to retrieve information about currently and recently running tasks. May allow malicious applications to discover private information about other applications.
android.permission.BROADCAST_STICKY	normal	send sticky broadcast	Allows an application to send sticky broadcasts, which remain after the broadcast ends. Malicious applications can make the phone slow or unstable by causing it to use too much memory.
android.permission.CHANGE_WIFI_STATE	normal	change Wi-Fi status	Allows an application to connect to and disconnect from Wi-Fi access points and to make changes to configured Wi-Fi networks.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.RECEIVE_USER_PRESENT	unknown	Unknown permission	Unknown permission from android reference
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.ldjSxw.heBbQd.permission.C2D_MESSAGE	unknown	Unknown permission	Unknown permission from android reference
android.permission.READ_PHONE_STATE	dangerous	read phone state and identity	Allows the application to access the phone features of the device. An application with this permission can determine the phone number and serial number of this phone, whether a call is active, the number that call is connected to and so on.

APKID ANALYSIS

FILE	DETAILS		
assets/pgsHZz.apk!classes.dex	FINDINGS	DETAILS	
assets/ pgst tzz.apt.ctasses.aex	Compiler	dx	
classes.dex	FINDINGS	DETAILS	
Classes.aeA	Compiler	dx	



ACTIVITY	INTENT
com.ldjSxw.heBbQd.ScanActivity	Schemes: openscan://,

A NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

Q MANIFEST ANALYSIS

HIGH: 5 | WARNING: 7 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable upatched Android version Android 6.0-6.0.1, [minSdk=23]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Clear text traffic is Enabled For App [android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.
3	Debug Enabled For App [android:debuggable=true]	high	Debugging was enabled on the app which makes it easier for reverse engineers to hook a debugger to it. This allows dumping a stack trace and accessing debugging helper classes.
4	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

NO	ISSUE	SEVERITY	DESCRIPTION
5	Activity (com.ldjSxw.heBbQd.ResultActivity) is vulnerable to StrandHogg 2.0	high	Activity is found to be vulnerable to StrandHogg 2.0 task hijacking vulnerability. When vulnerable, it is possible for other applications to place a malicious activity on top of the activity stack of the vulnerable application. This makes the application an easy target for phishing attacks. The vulnerability can be remediated by setting the launch mode attribute to "singleInstance" and by setting an empty taskAffinity (taskAffinity=""). You can also update the target SDK version (28) of the app to 29 or higher to fix this issue at platform level.
6	Activity (com.ldjSxw.heBbQd.ResultActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity (com.ldjSxw.heBbQd.ScanActivity) is vulnerable to StrandHogg 2.0	high	Activity is found to be vulnerable to StrandHogg 2.0 task hijacking vulnerability. When vulnerable, it is possible for other applications to place a malicious activity on top of the activity stack of the vulnerable application. This makes the application an easy target for phishing attacks. The vulnerability can be remediated by setting the launch mode attribute to "singleInstance" and by setting an empty taskAffinity (taskAffinity=""). You can also update the target SDK version (28) of the app to 29 or higher to fix this issue at platform level.
8	Activity (com.ldjSxw.heBbQd.ScanActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
9	Service (com.ldjSxw.heBbQd.iservice.TaskService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_ACCESSIBILITY_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
10	Broadcast Receiver (com.google.android.gms.measurement.AppMeasurementInstallReferrerReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.INSTALL_PACKAGES [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
11	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
12	Service (com.google.firebase.iid.FirebaseInstanceIdService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES	
				1	

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED	
----	------------------	----	-----	-----------------	-------	-------	---------	---------	---------------------	--

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	armeabi- v7a/libset.so	True info The binary has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	Dynamic Shared Object (DSO) info The shared object is build with - fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run- time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi- v7a/libset.so	True info The binary has NX bit set. This marks a memory page non- executable making attacker injected shellcode non- executable.	Dynamic Shared Object (DSO) info The shared object is build with - fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run- time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option - D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

■ NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	com/lzsEsq/dykSgp/jhvqZx/pupsPVlBod.java
00121	Create a directory	file command	com/lzsEsq/dykSgp/jhvqZx/pupsPVlBod.java
00125	Check if the given file path exist	file	com/lzsEsq/dykSgp/jhvqZx/pupsPVlBod.java
00104	Check if the given path is directory	file	com/lzsEsq/dykSgp/jhvqZx/pupsPVlBod.java

***: ::** ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	12/25	android.permission.INTERNET, android.permission.ACCESS_WIFI_STATE, android.permission.ACCESS_NETWORK_STATE, android.permission.REQUEST_INSTALL_PACKAGES, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.READ_EXTERNAL_STORAGE, android.permission.WAKE_LOCK, android.permission.GET_TASKS, android.permission.VIBRATE, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.READ_PHONE_STATE
Other Common Permissions	5/44	android.permission.FOREGROUND_SERVICE, android.permission.BROADCAST_STICKY, android.permission.CHANGE_WIFI_STATE, android.permission.MODIFY_AUDIO_SETTINGS, com.google.android.c2dm.permission.RECEIVE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

• OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

Q DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.openssl.org	ok	IP: 34.49.79.89 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map

∷ SCAN LOGS

Timestamp	Event	Error
2024-11-19 12:38:48	Generating Hashes	ОК

2024-11-19 12:38:49	Extracting APK	ОК
2024-11-19 12:38:49	Unzipping	ОК
2024-11-19 12:38:49	Getting Hardcoded Certificates/Keystores	ОК
2024-11-19 12:38:49	Parsing APK with androguard	ОК
2024-11-19 12:38:50	Parsing AndroidManifest.xml	ОК
2024-11-19 12:38:50	Extracting Manifest Data	ОК
2024-11-19 12:38:50	Performing Static Analysis on: My Scan APP (com.ldjSxw.heBbQd)	ОК
2024-11-19 12:38:50	Fetching Details from Play Store: com.ldjSxw.heBbQd	ОК
2024-11-19 12:38:51	Manifest Analysis Started	ОК
2024-11-19 12:38:51	Checking for Malware Permissions	ОК

2024-11-19 12:38:51	Fetching icon path	ОК
2024-11-19 12:38:51	Library Binary Analysis Started	ОК
2024-11-19 12:38:51	Analyzing apktool_out/lib/armeabi-v7a/libset.so	ОК
2024-11-19 12:38:51	Analyzing lib/armeabi-v7a/libset.so	ОК
2024-11-19 12:38:51	Reading Code Signing Certificate	ОК
2024-11-19 12:38:51	Running APKiD 2.1.5	ОК
2024-11-19 12:38:54	Detecting Trackers	ОК
2024-11-19 12:38:54	Decompiling APK to Java with JADX	ОК
2024-11-19 12:38:57	Converting DEX to Smali	ОК
2024-11-19 12:38:57	Code Analysis Started on - java_source	ОК

2024-11-19 12:38:57	Android SAST Completed	ОК
2024-11-19 12:38:57	Android API Analysis Started	ОК
2024-11-19 12:38:58	Android API Analysis Completed	ОК
2024-11-19 12:38:58	Android Permission Mapping Started	OK
2024-11-19 12:38:58	Android Permission Mapping Completed	OK
2024-11-19 12:38:58	Email and URL Extraction Completed	OK
2024-11-19 12:38:58	Android Behaviour Analysis Started	ОК
2024-11-19 12:38:59	Android Behaviour Analysis Completed	ОК
2024-11-19 12:38:59	Extracting String data from APK	OK
2024-11-19 12:38:59	Extracting String data from SO	OK
2024-11-19 12:38:59	Extracting String data from Code	OK

2024-11-19 12:38:59	Extracting String values and entropies from Code	ОК
2024-11-19 12:38:59	Performing Malware check on extracted domains	ОК
2024-11-19 12:39:00	Saving to Database	ОК
2024-11-19 12:49:15	Performing Malware check on extracted domains	ОК
2024-11-19 12:49:19	Detecting Trackers from Domains	OK

Report Generated by - MobSF v4.1.9

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2024 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.