

Project: PTF Series  
Status: Production  
Date: August 9th 2013  
Rev 1

| PTF Series                 |                         |                |                |
|----------------------------|-------------------------|----------------|----------------|
| Characteristic             | OPTF0075P / OPTF0075PXL | OPTF0077P      | OPTF0078P      |
| Fuse Link                  | 5X20                    | 5X20           | 5X20           |
| Mounting                   | PCB                     | PCB            | PCB            |
| Rated Current              | 6.3 Amp.                | 6.3 Amp.       | 6.3 Amp.       |
| Rated Voltage              | 250 VAC                 | 250 VAC        | 250 VAC        |
| Rated Power Acceptance     | 1.6 W                   | 1.6 W          | 1.6 W          |
| Housing                    | PA UL-94 V0             | PA UL-94 V0    | PA UL-94 V0    |
| Admissible Air Temperature | -30° C to 85°C          | -30° C to 85°C | -30° C to 85°C |
| Schoksafe Catgory          | PC1                     | PC1            | PC1            |
| Degree of Protection       | IP00                    | IP00           | IP00           |
| Contact Resistance         | < 5.0 mΩ                | < 5.0 mΩ       | < 5.0 mΩ       |
| VDE Rated Current          | 6.3 Amp.                | 6.3 Amp.       | 6.3 Amp.       |
| VDE Rated Voltage          | 250 VAC                 | 250 VAC        | 250 VAC        |
| VDE Rated Power Acceptance | 1.6 W                   | 1.6 W          | 1.6 W          |
| UR Rated Current           | 10 Amp.                 | 10 Amp.        | 10 Amp.        |
| UR Rated Voltage           | 250 VDC                 | 250 VDC        | 250 VDC        |
| UR Rated Power Acceptance  | -                       | -              | -              |

