Model 1:N relationships with foreign keys


INTRODUCTION TO RELATIONAL DATABASES IN SQL

SQL


Timo GrossenbacherData Journalist



The current database model



The next database model



Implementing relationships with foreign keys

- A foreign key (FK) points to the primary key (PK) of another table
- Domain of FK must be equal to domain of PK
- Each value of FK must exist in PK of the other table (FK constraint or "referential integrity")
- FKs are not actual keys

A query

```
SELECT * FROM professors LIMIT 8;
```

```
| university_s...
id |
        firstname
                       lastname
    Karl
                     | Aberer
                                    EPF
    Reza Shokrollah | Abhari
                                    ETH
    Georges
                     | Abou Jaoudé | EPF
    Hugues
                     Abriel
                                   UBE
    Daniel
                     | Aebersold
                                   I UBE
    Marcelo
                     Aebi
                                   ULA
    Christoph
                     Aebi
                                   UBE
8 | Patrick
                     l Aebischer
                                   l EPF
```

```
SELECT * FROM universities;
```

```
university_city
       university
id
     ETH Lausanne
                      Lausanne
     ETH Zürich
                      Zurich
     Uni Basel
                      Basel
                      Bern
     Uni Bern
     Uni Freiburg
                      Fribourg
     Uni Genf
                      Geneva
     Uni Lausanne
                      Lausanne
     Uni Neuenburg
                      Neuchâtel
     Uni St. Gallen | Saint Gallen
     USI Lugano
USI
                      Lugano
     Uni Zürich
                      Zurich
```

Specifying foreign keys

```
CREATE TABLE manufacturers (
name varchar(255) PRIMARY KEY);
INSERT INTO manufacturers
VALUES ('Ford'), ('VW'), ('GM');
CREATE TABLE cars (
model varchar(255) PRIMARY KEY,
manufacturer_name integer REFERENCES manufacturers (name));
INSERT INTO cars
VALUES ('Ranger', 'Ford'), ('Beetle', 'VW');
-- Throws an error!
INSERT INTO cars
VALUES ('Tundra', 'Toyota');
```



Specifying foreign keys to existing tables

```
ALTER TABLE a

ADD CONSTRAINT a_fkey FOREIGN KEY (b_id) REFERENCES b (id);
```



Let's implement this!

INTRODUCTION TO RELATIONAL DATABASES IN SQL



Model more complex relationships


INTRODUCTION TO RELATIONAL DATABASES IN SQL

SQL


Timo GrossenbacherData Journalist



The current database model



The final database model





How to implement N:M-relationships

- Create a table
- Add foreign keys for every connected table
- Add additional attributes

```
CREATE TABLE affiliations (
  professor_id integer REFERENCES professors (id),
  organization_id varchar(256) REFERENCES organizations (id),
  function varchar(256)
);
```

- No primary key!
- Possible PK = {professor_id, organization_id, function}

Time to implement this!

INTRODUCTION TO RELATIONAL DATABASES IN SQL



Referential integrity

INTRODUCTION TO RELATIONAL DATABASES IN SQL



Timo GrossenbacherData Journalist



Referential integrity

- A record referencing another table must refer to an existing record in that table
- Specified between two tables
- Enforced through foreign keys



Referential integrity violations

Referential integrity from table A to table B is violated...

- ...if a record in table B that is referenced from a record in table A is deleted.
- ...if a record in table A referencing a non-existing record from table B is inserted.
- Foreign keys prevent violations!

Dealing with violations

```
CREATE TABLE a (
  id integer PRIMARY KEY,
  column_a varchar(64),
  ...,
  b_id integer REFERENCES b (id) ON DELETE NO ACTION
);
```

```
create Table a (
  id integer PRIMARY KEY,
  column_a varchar(64),
  ...,
  b_id integer REFERENCES b (id) ON DELETE CASCADE
);
```

Dealing with violations, contd.

ON DELETE...

- ...NO ACTION: Throw an error
- ...CASCADE: Delete all referencing records
- ...RESTRICT: Throw an error
- ...SET NULL: Set the referencing column to NULL
- ...SET DEFAULT: Set the referencing column to its default value



Let's look at some examples!

INTRODUCTION TO RELATIONAL DATABASES IN SQL



Roundup


INTRODUCTION TO RELATIONAL DATABASES IN SQL




Timo GrossenbacherData Journalist



How you've transformed the database







- Column data types
- Key constraints
- Relationships between tables



The database ecosystem



The database ecosystem



Thank you!

INTRODUCTION TO RELATIONAL DATABASES IN SQL

