

Lecture 3: Informed Search

Shuai Li

John Hopcroft Center, Shanghai Jiao Tong University

<https://shuaili8.github.io>

<https://shuaili8.github.io/Teaching/CS410/index.html>

Part of slide credits: CMU AI & <http://ai.berkeley.edu>

Informed Search

- Uninformed Search


- DFS
- BFS
- UCS



www.shutterstock.com · 149559782




- Informed Search

- Heuristics
- Greedy Search
- A* Search
- Graph Search




Search Heuristics

- A heuristic is:
 - A function that estimates how close a state is to a goal
 - Designed for a particular search problem
 - **Pathing?**
 - Examples: Manhattan distance, Euclidean distance for pathing



Example: Heuristic Function (Euclidean distance to Bucharest)




Straight-line distance to Bucharest	
Arad	366
Bucharest	0
Craiova	160
Dobreta	242
Eforie	161
Fagaras	178
Giurgiu	77
Hirsova	151
Iasi	226
Lugoj	244
Mehadia	241
Neamt	234
Oradea	380
Pitesti	98
Rimnicu Vilcea	193
Sibiu	253
Timisoara	329
Urziceni	80
Vaslui	199
Zerind	374


$h(\text{state}) \rightarrow \text{value}$

Effect of heuristics

- Guide search *towards the goal* instead of *all over the place*




Informed



Uninformed

Example: Heuristic Function 2

- Heuristic?
- E.g. the index of the largest pancake that is still out of place






Greedy Search



Greedy Search



- Expand the node that seems closest to the goal



- Is it optimal?
 - No. Resulting path to Bucharest is not the shortest!
 - Why?
 - Heuristics might be wrong

Greedy Search 2

- Strategy: expand a node that **you think** is closest to a goal state
 - Heuristic: estimate of distance to nearest goal for each state
- A common case:
 - Best-first takes you straight to the (wrong) goal
 - (It chooses a node even if it's at the end of a very long and winding road)
- Worst-case: like a badly-guided DFS
 - (It takes h literally even if it's completely wrong)





[Demo: contours greedy empty (L3D1)]


[Demo: contours greedy pacman small maze (L3D4)]

Greedy Search 3


- Each time it visit or expand the point with least $h(n)$ value
 - $h(n)$ is the distance from point n to end point. It works fine when there is no obstacles.
- The cost doubles when there is obstacles




Video of Demo Contours Greedy (Empty)



Video of Demo Contours Greedy (Pacman Small Maze)




A* Search




A* Search

Combining UCS and Greedy

- **Uniform-cost** orders by path cost, or *backward cost* $g(n)$
- **Greedy** orders by goal proximity, or *forward cost* $h(n)$




- **A* Search** orders by the sum: $f(n) = g(n) + h(n)$



When should A* terminate?

- Should we stop when we enqueue a goal?




- No: only stop when we dequeue a goal

	g	h	+
S	0	3	3
S->A	2	2	4
S->B	2	1	3
S->B->G	5	0	5
S->A->G	4	0	4

A* Search

```
function A-STAR-SEARCH(problem) returns a solution, or failure
  initialize the frontier as a priority queue using  $f(n)=g(n)+h(n)$  as the priority
  add initial state of problem to frontier with priority  $f(S)=0+h(S)$ 
  loop do
    if the frontier is empty then
      return failure
    choose a node and remove it from the frontier
    if the node contains a goal state then
      return the corresponding solution
    for each resulting child from node
      add child to the frontier with  $f(n)=g(n)+h(n)$ 
```


(a) The initial state




(b) After expanding Arad




(c) After expanding Sibiu





(d) After expanding Rimnicu Vilcea



(e) After expanding Fagaras




(f) After expanding Pitesti



Arad	366	Mehadia	241
Bucharest	0	Neamt	234
Craiova	160	Oradea	380
Drobeta	242	Pitesti	100
Eforie	161	Rimnicu Vilcea	193
Fagaras	176	Sibiu	253
Giurgiu	77	Timisoara	329
Hirsova	151	Urziceni	80
Iasi	226	Vaslui	199
Lugoj	244	Zerind	374

Is A* Optimal?



g h +		
S	0	7
S->A	1	6
S->G	5	0


- What went wrong?
- **Actual** bad goal cost < **estimated** good goal cost
- We need estimates to be less than actual costs!

The Price is Wrong...


- Closest bid without going over...



Admissible Heuristics: Ideas





Inadmissible (pessimistic) heuristics
break optimality by trapping
good plans on the fringe



Admissible (optimistic) heuristics
slow down bad plans but
never outweigh true costs

Admissible Heuristics

- A heuristic h is *admissible* (optimistic) if
$$0 \leq h(n) \leq h^*(n)$$
where $h^*(n)$ is the true cost to a nearest goal
- Examples:




0.0

- Coming up with admissible heuristics is most of what's involved in using A^* in practice


Optimality of A* Tree Search

- Assume:
 - A is an optimal goal node
 - B is a suboptimal goal node
 - h is admissible
- Claim:
 - A will exit the fringe before B



Optimality of A* Tree Search: Blocking

- Proof:
 - Imagine B is on the fringe
 - Some ancestor n of A is on the fringe, too (maybe A!)
 - Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$



$$f(n) = g(n) + h(n)$$

Definition of f-cost

$$f(n) \leq g(A)$$


Admissibility of h

$$g(A) = f(A)$$

$h = 0$ at a goal

Optimality of A* Tree Search: Blocking 2

- Proof:
 - Imagine B is on the fringe
 - Some ancestor n of A is on the fringe, too (maybe A!)
 - Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$
 2. $f(A)$ is less than $f(B)$



$$g(A) < g(B)$$


$$f(A) < f(B)$$

B is suboptimal


$h = 0$ at a goal

Optimality of A* Tree Search: Blocking 3

- Proof:
 - Imagine B is on the fringe
 - Some ancestor n of A is on the fringe, too (maybe A!)
 - Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$
 2. $f(A)$ is less than $f(B)$
 3. n expands before B
 - All ancestors of A expand before B
 - A expands before B
 - A* search is optimal





$$f(n) \leq f(A) < f(B)$$





UCS vs A*

- Uniform-cost expands equally in all “directions”




- A* expands mainly toward the goal, but does hedge its bets to ensure optimality




[Demo: contours UCS / greedy / A* empty (L3D1)]

[Demo: contours A* pacman small maze (L3D5)]


Video of Demo Contours (Empty) -- UCS



Video of Demo Contours (Empty) -- Greedy




Video of Demo Contours (Empty) – A^*




Video of Demo Contours (Pacman Small Maze)


– A^*




Comparison



Greedy



Uniform Cost




A*

A* Applications




A* Applications 2


- Video games
- Pathing / routing problems
- Resource planning problems
- Robot motion planning
- Language analysis
- Machine translation
- Speech recognition
- ...



Video of Demo Pacman (Tiny Maze) – UCS / A*






Video of Demo Empty Water Shallow/Deep – Guess Algorithm



Creating Heuristics

- Most of the work in solving hard search problems optimally is in coming up with admissible heuristics
- Often, admissible heuristics are solutions to **relaxed problems**, where new actions are available




- Inadmissible heuristics are often useful too

Example: 8 Puzzle

7	2	4
5		6
8	3	1

Start State



3	7	1
2	4	5
	8	6

Actions

	1	2
3	4	5
6	7	8


Goal State

- What are the states?
- How many states?
- What are the actions?
- How many successors from the start state?
- What should the costs be?


Admissible
heuristics?

Example: 8 Puzzle 2


- Heuristic: Number of tiles misplaced
- Why is it admissible?
- $h(\text{start}) = 8$
- This is a relaxed-problem heuristic



Start State




Goal State




Average nodes expanded when the optimal path has...			
	...4 steps	...8 steps	...12 steps
UCS	112	6,300	3.6×10^6
TILES	13	39	227

Example: 8 Puzzle 3

- What if we had an easier 8-puzzle where any tile could slide any direction at any time, ignoring other tiles?



Start State





Goal State

- Total Manhattan distance
- Why is it admissible?
- $h(\text{start}) = 3 + 1 + 2 + \dots = 18$

Average nodes expanded when the optimal path has...			
	...4 steps	...8 steps	...12 steps
TILES	13	39	227
MANHATTAN	12	25	73

Example: 8 Puzzle 4


- How about using the actual cost as a heuristic?
 - Would it be admissible?
 - Would we save on nodes expanded?
 - What's wrong with it?




- With A*: a trade-off between quality of estimate and work per node
 - As heuristics get closer to the true cost, you will expand fewer nodes but usually do more work per node to compute the heuristic itself

Combining Heuristics, Dominance

- Dominance: $h_a \geq h_c$ if
$$\forall n : h_a(n) \geq h_c(n)$$
 - Roughly speaking, larger is better as long as both are admissible
- Heuristics form a **semi-lattice**:
 - Max of admissible heuristics is admissible
$$h(n) = \max(h_a(n), h_b(n))$$
- Trivial heuristics
 - Bottom of lattice is the zero heuristic (what does this give us?)
 - Top of lattice is the exact heuristic, but usually too expensive







Graph Search


Tree Search: Extra Work!

- Failure to detect repeated states can cause exponentially more work



Graph Search

- In BFS, for example, we shouldn't bother expanding the circled nodes (why?)




Graph Search 2

- Idea: never **expand** a state twice
- How to implement:
 - Tree search + set of expanded states (“closed set”, “explored set”)
 - Expand the search tree node-by-node, but...
 - Before expanding a node, check to make sure its state has never been expanded before
 - If not new, skip it, if new add to closed set
- Important: **store the closed set as a set**, not a list
- Can graph search wreck completeness? Why/why not?
- How about optimality?




Graph Search 3

- This graph search algorithm overlays a tree on a graph
- The **frontier** states separate the **explored** states from **never seen** states



Quiz

- What is the relationship between these sets of states after each loop iteration in **GRAPH_SEARCH**?
- (Loop invariants!!!)



function GRAPH_SEARCH(**problem**) **returns** a solution, or failure

initialize the explored set to be empty

initialize the **frontier** as a specific work list (stack, queue, priority queue)

add initial state of **problem** to **frontier**

loop do

if the **frontier** is empty **then**

return failure

choose a **node** and remove it from the **frontier**

if the **node** contains a goal state **then**

return the corresponding solution

add the node state to the explored set

for each resulting **child** from node

if the **child** state is not already in the **frontier** or **explored set** **then**

add **child** to the **frontier**

```
function UNIFORM-COST-GRAPH-SEARCH(problem) returns a solution, or failure
    initialize the explored set to be empty
    initialize the frontier as a priority queue using node's path_cost as the priority
    add initial state of problem to frontier with path_cost = 0
    loop do
        if the frontier is empty then
            return failure
        choose a node and remove it from the frontier
        if the node contains a goal state then
            return the corresponding solution
        add the node state to the explored set
        for each resulting child from node
            if the child state is not already in the frontier or explored set then
                add child to the frontier
            else if the child is already in the frontier with higher path_cost then
                replace that frontier node with child
```

function A-STAR-GRAPH-SEARCH(**problem**) **returns** a solution, or failure

initialize the **explored set** to be empty

initialize the **frontier** as a priority queue using $f(n) = g(n) + h(n)$ as the priority

add initial state of **problem** to **frontier** with priority $f(S) = 0 + h(S)$

loop do

if the **frontier** is empty **then**

return failure

 choose a **node** and remove it from the **frontier**

if the **node** contains a goal state **then**

return the corresponding solution

 add the **node** state to the **explored set**

 for each resulting **child** from node

if the **child** state is not already in the **frontier** or **explored set** **then**


 add **child** to the **frontier**

else if the **child** is already in the **frontier** with higher $f(n)$ **then**


 replace that **frontier** node with **child**

A* Tree Search

State space graph




Search tree



Quiz: A* Graph Search


- What paths does A* graph search consider during its search?




- A) ~~S~~, ~~S-A~~, ~~S-C~~, S-C-G
- B) ~~S~~, ~~S-A~~, S-C, ~~S-A-C~~, S-C-G
- C) ~~S~~, ~~S-A~~, ~~S-A-C~~, S-A-C-G
- D) ~~S~~, ~~S-A~~, ~~S-C~~, ~~S-A-C~~, S-A-C-G

Quiz: A* Graph Search 2


- What does the resulting graph tree look like?




A)



B)




C & D)




A* Graph Search Gone Wrong?

State space graph



Search tree




- Simple check against explored set blocks C
- Fancy check allows new C if cheaper than old $h=0$ but requires recalculating C's descendants

Explored Set: S B C A


Consistency of Heuristics

- Main idea: estimated heuristic costs \leq actual costs
 - Admissibility: heuristic cost \leq actual cost to goal
 - $h(A) \leq$ actual cost from A to G
 - Consistency: heuristic “arc” cost \leq actual cost for each arc
 - $h(A) - h(C) \leq \text{cost}(A \text{ to } C)$
 - triangle inequality: $h(A) \leq c(A-C) + h(C)$
- Consequences of consistency:
 - The f value along a path never decreases
 - $h(A) \leq \text{cost}(A \text{ to } C) + h(C)$
 - A* graph search is optimal




Optimality of A* Graph Search

- Sketch: consider what A* does with a consistent heuristic:
 - Fact 1: In tree search, A* expands nodes in increasing total f value (f-contours)
 - Fact 2: For every state s, nodes that reach s optimally are expanded before nodes that reach s suboptimally
 - Result: A* graph search is optimal




Optimality of A* Graph Search: Proof

- New possible problem: some n on path to G^* isn't in queue when we need it, because some worse n' for the same state dequeued and expanded first (disaster!)
- Take the highest such n in tree
- Let p be the ancestor of n that was on the queue when n' was popped
- $f(p) < f(n)$ because of **consistency**
- $f(n) < f(n')$ because n' is suboptimal
- p would have been expanded before n'
- Contradiction!




Optimality of A* Search

- Tree search:
 - A* is optimal if heuristic is **admissible**
 - UCS is a special case ($h = 0$)
- Graph search:
 - A* optimal if heuristic is **consistent**
 - UCS optimal ($h = 0$ is consistent)
- Consistency implies admissibility
- In general, most natural admissible heuristics tend to be consistent, especially if from relaxed problems



Summary of A*

- A* uses both backward costs and (estimates of) forward costs
- A* is optimal with admissible / consistent heuristics
- Heuristic design is key: often use relaxed problems



Summary

- Informed Search Methods
 - Heuristics
 - Greedy Search
 - A* Search
 - Graph Search

Shuai Li

<https://shuaili8.github.io>

Questions?