

C.

Version 2.X BNF Message Descriptions

Editor: Karen Van Hentenryck
Health Level Seven International

Donald Lloyd
Health Level Seven International

C.1 APPENDIX C CONTENTS

C.1	APPENDIX C CONTENTS.....	C-1
C.2	BNF DESCRIPTIONS OF HL7 VERSION 2.X ABSTRACT MESSAGES.....	C-1
C.2.1	OVERVIEW.....	C-1
C.2.2	TOKENS	C-2
C.2.2.1	Terminators	C-2
C.2.2.2	Segments	C-2
C.2.2.2.1	Control/query.....	C-2
C.2.2.2.2	Master files.....	C-2
C.2.2.2.3	Patient administration	C-2
C.2.2.2.4	Financial information	C-2
C.2.2.2.5	Orders/Observations	C-2
C.2.3	BNF MESSAGE DEFINITIONS	C-3

C.2 BNF DESCRIPTIONS OF HL7 VERSION 2.X ABSTRACT MESSAGES

C.2.1 Overview

This appendix gives examples of BNF representations of abstract message definitions at the segment level for HL7, version 2.x. Please note, however, that this appendix is only current up to version 2.4, and that the examples provided herein are only provided to illustrate how the message definitions MIGHT be represented in BNF. Should an organization wish to undertake updating the BNF descriptions to the current standard, HL7 would be glad to use this material to update this appendix. In addition, users should note that the examples in this appendix do not specify the field-level or data-type definitions nor do they define the message exchange protocol. These are not the only possible set of BNF productions capable of describing these messages, since the choice of tokens for certain segments and messages is to some extent

arbitrary (e.g., should the EVN segment have a single token, or many?), as are the forms used to define recursion.

In the definitions that follow an attempt has been made both to follow the general use of message definitions given in the various chapters and to resolve questions of ambiguity.

For more information on BNF, see *Compiler Design in C ; Allen I. Holub; Prentice Hall; Englewood Cliffs, New Jersey; 1990.*

C.2.2 Tokens

C.2.2.1 Terminators

EOM End of message. Not formally part of HL7 abstract message definition, nor of the encoding rules: hence optional from the point of view of the abstract message definitions and encoding rules. Included here to add to clarity and add to the usefulness of the BNF descriptions in generating HL7 parsers.

ST Segment terminator.

SOM Start of Message. Not formally part of HL7 abstract message definition, nor of the encoding rules: hence optional from the point of view of the abstract message definitions and encoding rules. Included here to add to clarity and to the usefulness of the BNF descriptions in generating HL7 parsers.

C.2.2.2 Segments

C.2.2.2.1 Control/query

MSH MSA ERR NTE QRD QRF DSC URS URD DSP MSHmcf

C.2.2.2.2 Master files

MFE MFI MFA

C.2.2.2.3 Patient administration

EVN EVNA01 EVNA02 EVNA03 EVNA04 EVNA05 EVNA06 EVNA07 EVNA08 EVNA09 EVNA10
EVNA11 EVNA12 EVNA13 EVNA14 EVNA15 EVNA16 EVNA17 EVNA18 EVNA19 EVNA20
EVNA21 EVNA22 EVNA23 EVNA24 EVNA25 EVNA26 EVNA27 EVNA28 EVNA29 EVNA30
EVNA31 EVNA32 EVNA33 EVNA34 EVNA35 EVNA36 EVNA37 PID PV1 DG1 PR1 NK1 PV2 ACC
AL1 IN1 IN2 IN3 UB1 UB2 NPU MRG

C.2.2.2.4 Financial information

GT1 FT1 BLG EVNP01 EVNP02 EVNP03

C.2.2.2.5 Orders/Observations

ORC OBR OBX RXA RXC RXO RXR RXG RXD RXE ODS ODT RQ1 RQD MSHorr1 MSHorr2

C.2.3 BNF Message Definitions

The following is a listing of the BNF message descriptions, using the tokens defined above. It includes the accompanying segment groups used in producing the messages. Comments within the file are delimited by "/" (comment start) and "/" (comment end).

```
hl7Msgs: ack      /* General acknowledgment      */

|   mcf          /* Delayed acknowledgment message. */

|   qry          /* Query message.                */

|   dsr          /* Display response message.    */

|   udm          /* Unsolicited display message. */

|   adt          /* Admissions, discharge, transfer. */

|   orm          /* Order message.                */

|   orr          /* Order message response.      */

|   rxo          /* Pharmacy order.              */

|   rde          /* Pharmacy order information.   */

|   rds          /* Pharmacy dispense information. */

|   rgv          /* Pharmacy dose information.    */

|   ras          /* Pharmacy administration information. */

|   rre          /* Pharmacy encoded order history report. */

|   rrd          /* Pharmacy dispense history report. */

|   rrg          /* Pharmacy give history report. */

|   rra          /* Pharmacy administration report. */

|   orrRxo       /* Pharmacy order message response. */

|   orrRde       /* Pharmacy encoded order message response. */

|   orrRds       /* Pharmacy dispense message response. */

|   orrRgv       /* Pharmacy give message response. */

|   orrRas       /* Pharmacy administer message response. */

|   bar          /* Add or change billing account. */

|   dft          /* Detail financial transaction. */

|   oru          /* Observation result - unsolicited. */

|   orf          /* Observation result - solicited. */

|   mfn          /* Master Files Notification */

|   mfk          /* Master Files Acknowledgement */

|   mfd          /* Master File Update Delayed Application Acknowledgement */
```

Appendix C: BNF Message Descriptions

```
|      mfq      /* Master Files Query */

|      mfr      /* Master Files Query Response */

;

/* Chapter II - Control Section */

/* ACK - General synchronous acknowledgement.                                     */

ack:      SOM MSH ST MSA ST ERROpt EOM ;

/* Delayed Acknowledgement */

mcf:      SOM MSHmcf ST MSA ST EOM

|      SOM MSHmcf ST MSA ST ERROpt EOM ;

NoteOptGrp:

|      NoteGrp ;

NoteGrp: NTE ST

|      NTE ST NoteGrp ;

/* Chapter II - Query Section */

QueryHdr: QRD ST QRFOpt PIDOpt ;

qry:      SOM MSH ST QRD ST QRFOpt DSCOpt EOM ;

dsr:      SOM MSH ST MSA ST ERROpt QRD ST QRFOpt DisplayGrp DSCOpt EOM

|      SOM MSH ST QRD ST QRFOpt DisplayGrp DSCOpt EOM ;

udm:      SOM MSH ST URD ST URSOpt DisplayGrp DSCOpt EOM ;

DisplayGrp: DSP ST

|      DSP ST DisplayGrp ;

/* Chapter III - ADT Messages: note that the EVNxxx tokens stand for identical segments except for
the event type code values. This allows the BNF description for each ADT message to be unique,
although the actual segment level definitions are non-unique. Thus the BNF is parallel to that
used in the ADT chapter. */

adt:      a01 /* Admit a patient. */

|      a02 /* Transfer a patient. */

|      a03 /* Discharge a patient. */

|      a04 /* Register a patient. */

|      a05 /* Pre-admit a patient. */

|      a06 /* Transfer an outpatient to inpatient. */
```

Appendix C: BNF Message Descriptions

```
| a07 /* Transfer an inpatient to outpatient. */
| a08 /* Update patient information. */
| a09 /* Patient departing. */
| a10 /* Patient arriving. */
| a11 /* Cancel admit. */
| a12 /* Cancel transfer. */
| a13 /* Cancel discharge. */
| a14 /* Pending admit. */
| a15 /* Pending transfer. */
| a16 /* Pending discharge. */
| a17 /* Swap a patient. */
| a18 /* Merge patient information. */
| a19 /* Patient query. */
| a20 /* Nursing - census application updates. */
| a21 /* Leave of absence - out (leaving). */
| a22 /* Leave of absence - in (returning). */
| a23 /* Delete a patient record. */
| a24 /* Link patient information. */
| a25 /* Cancel pending discharge. */
| a26 /* Cancel pending transfer. */
| a27 /* Cancel pending admit. */
| a28 /* Add person information. */
| a29 /* Delete person information. */
| a30 /* Merge person information. */
| a31 /* Update person information. */
| a32 /* Cancel patient arriving. */
| a33 /* Cancel patient departing. */
| a34 /* Merge patient information (PID only). */
| a35 /* Merge patient information (Account # only). */
| a36 /* Merge patient information (PID & Account #). */
| a37 ; /* Unlink patient information. */

a01: SOM MSH ST EVNA01 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
      AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
```

Appendix C: BNF Message Descriptions

```
        ACCOpt UB1Opt UB2Opt EOM ;

a02:    SOM MSH ST EVNA02 ST PidGrp EOM ;

a03:    SOM MSH ST EVNA03 ST PidGrp EOM ;

a04:    SOM MSH ST EVNA04 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a05:    SOM MSH ST EVNA05 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a06:    SOM MSH ST EVNA06 ST PID ST MRGOpt NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a07:    SOM MSH ST EVNA07 ST PID ST MRGOpt NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a08:    SOM MSH ST EVNA08 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a09:    SOM MSH ST EVNA09 ST PidGrp DG1OptGrp EOM ;

a10:    SOM MSH ST EVNA10 ST PidGrp DG1OptGrp EOM ;

a11:    SOM MSH ST EVNA11 ST PidGrp DG1OptGrp EOM ;

a12:    SOM MSH ST EVNA12 ST PidGrp DG1OptGrp EOM ;

a13:    SOM MSH ST EVNA13 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a14:    SOM MSH ST EVNA14 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp
        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
        ACCOpt UB1Opt UB2Opt EOM ;

a15:    SOM MSH ST EVNA15 ST PidGrp DG1OptGrp EOM ;

a16:    SOM MSH ST EVNA16 ST PidGrp DG1OptGrp EOM ;

a17:    SOM MSH ST EVNA17 ST PidGrp PidGrp EOM ;

a18:    SOM MSH ST EVNA18 ST PID ST MRG ST PV1Opt EOM ;

a19:    SOM MSH ST MSA ST ERROpt QRD ST InfGrp DSCOpt EOM ;
```

```

a20:  SOM MSH ST EVNA20 ST NPU ST EOM  ;

a21:  SOM MSH ST EVNA21 ST PidGrp EOM  ;

a22:  SOM MSH ST EVNA22 ST PidGrp EOM  ;

a23:  SOM MSH ST EVNA23 ST PidGrp EOM  ;

a24:  SOM MSH ST EVNA24 ST PID ST PV1Opt PID ST EOM  ;

a25:  SOM MSH ST EVNA25 ST PidGrp EOM  ;

a26:  SOM MSH ST EVNA26 ST PidGrp EOM  ;

a27:  SOM MSH ST EVNA27 ST PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp EOM  ;

a28:  SOM MSH ST EVNA28 ST PID ST NK1OptGrp PV1Opt PV2Opt OBXOptGrp
      AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
      ACCOpt UB1Opt UB2Opt EOM  ;

a29:  SOM MSH ST EVNA29 ST PID ST PV1Opt PV2Opt OBXOptGrp EOM  ;

a30:  SOM MSH ST EVNA30 ST PID ST MRG ST EOM  ;

a31:  SOM MSH ST EVNA31 ST PID ST NK1OptGrp PV1Opt PV2Opt OBXOptGrp
      AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1
      ACCOpt UB1Opt UB2Opt EOM  ;

a32:  SOM MSH ST EVNA32 ST PidGrp EOM  ;

a33:  SOM MSH ST EVNA33 ST PidGrp EOM  ;

a34:  SOM MSH ST EVNA34 ST PID ST MRG ST EOM  ;

a35:  SOM MSH ST EVNA35 ST PID ST MRG ST EOM  ;

a36:  SOM MSH ST EVNA36 ST PID ST MRG ST EOM  ;

a37:  SOM MSH ST EVNA37 ST PID ST PV1Opt PID ST PV1Opt EOM  ;

/* Insurance group 1 requires an IN1 segment within a repeating insurance */
/* group while Insurance group 2 allows a repeating IN3 within the group */
/* of a single IN1-IN2 pair */

InsOptGrp1:
    |  InsGrp1  ;

InsGrp1: Ins1
    |  Ins1 InsGrp1  ;

Ins1:  IN1 ST IN2Opt IN3Opt  ;

InsOptGrp2:
    |  InsGrp2  ;

```

Appendix C: BNF Message Descriptions

```
InsGrp2:  Ins2

|      Ins2 InsGrp2 ;

Ins2:     IN1 ST IN2Opt IN3OptGrp ;

/* Inf is the patient information data that forms each member */

/* of a list of patient information segments in response to a query */

InfGrp: Inf

| Inf InfGrp ;

Inf:      EVNA19Opt PID ST NK1OptGrp PV1 ST PV2Opt OBXOptGrp

        AL1OptGrp DG1OptGrp PR1OptGrp GT1OptGrp InsOptGrp1

        ACCOpt UB1Opt UB2Opt;

PidGrp:   PID ST PV1 ST PV2Opt OBXOptGrp ;

/* Chapter IV - ORDERS */

/* ORM - Order message. */

orm:      SOM MSH ST NoteOptGrp PidOptClause1 ORCGrp EOM ;

PidOptClause1:

|      PID ST NoteOptGrp AL1OptGrp PV1Opt ;

ORCGrp:   ORC ST DetailOptClause

|      ORC ST DetailOptClause ORCGrp ;

DetailOptClause:

|      OrderSeg OBXDOptGrp BLGOpt ;

OBXDOptGrp:

|      OBXDGrp ;

OBXDGrp:  OBX ST NoteOptGrp

|      OBX ST NoteOptGrp OBXDGrp ;

OrderSeg: OBR ST NoteOptGrp

|      Supplies NoteOptGrp

|      ODSGrp NoteOptGrp

|      ODTGrp NoteOptGrp ;

Supplies: RQD ST

|      RQD ST RQ1 ST ;

/* ORR - Response message. */

orr:      Orr1

|      Orr2 ;
```



```

Orr1:      SOM MSHorr1 ST MSA ST ERROpt NoteOptGrp PidOptClause2 EOM ;

Orr2:      SOM MSHorr2 ST MSA ST ERROpt NoteOptGrp RxOptResponse EOM ;

RxOptResponse:

    |      RxResponse ;

RxResponse: PIDOpt PrescriptionGrp ;

PrescriptionGrp:  ORC ST PrescriptionOpt

    |      ORC ST PrescriptionOpt PrescriptionGrp ;

PrescriptionOpt:

    |      Prescription;

Prescription:  RXO ST NoteOptGrp RXRGrp ST  RXCNOptGrp ;

PidOptClause2:

    |      PIDOpt ORCGrp1 ;

ORCGrp1:  ORC ST OrderSegOpt

    |      ORC ST OrderSegOpt ORCGrp1 ;

OrderSegOpt:

    |      OrderSeg ;

/* Pharmacy.                                     */

rxo:      SOM MSH ST NoteOptGrp PidOptClause1 RxOrderGrp EOM ;

rde:      SOM MSH ST NoteOptGrp PidOptClause1 RxEncOrdGrp EOM ;

rds:      SOM MSH ST NoteOptGrp PidOptClause1 DispenseGrp EOM ;

rgv:      SOM MSH ST NoteOptGrp PidOptClause1 RxGiveGrp EOM ;

ras:      SOM MSH ST NoteOptGrp PidOptClause1 RxAdminGrp EOM ;

rra:      SOM MSH ST MSA ST ERROpt AdminRptGrp DSCOpt EOM ;

rrd:      SOM MSH ST MSA ST ERROpt DispenseRptGrp DSCOpt EOM ;

rre:      SOM MSH ST MSA ST ERROpt RxOrderRptGrp DSCOpt EOM ;

rrg:      SOM MSH ST MSA ST ERROpt GiveRptGrp DSCOpt EOM ;

orrRxo:   SOM MSH ST MSA ST ERROpt NoteOptGrp PidOptClause2 PrescriptionGrp EOM ;

orrRde:   SOM MSH ST MSA ST ERROpt NoteOptGrp PidOptClause2 RxOrdGrp2Opt EOM ;

orrRds:   SOM MSH ST MSA ST ERROpt NoteOptGrp PidOptClause2 RxdGrpOpt EOM ;

orrRgv:   SOM MSH ST MSA ST ERROpt NoteOptGrp PidOptClause2 RxgGrpOpt EOM ;

orrRas:   SOM MSH ST MSA ST ERROpt NoteOptGrp PidOptClause2 RxaGrpOpt EOM ;

RxAdmin:  ORC ST PrescriptionOpt RxEncOrdOpt RXAGrp RXR ST ;

```

Appendix C: BNF Message Descriptions

```
RxGive:      ORC ST PrescriptionOpt RxEncOrdOpt RXG ST RXRGrp ST RXCOptGrp ;

RxEncOrd:    ORC ST PrescriptionOpt RXE ST RXRGrp ST RXCOptGrp ;

Dispense:    ORC ST PrescriptionOpt RxEncOrdOpt RxD ST RXRGrp ST RXCOptGrp ;

GiveRpt:     QueryHdr RxOrdGrp4 ;

AdminRpt:    QueryHdr RxOrdGrp1 ;

DispenseRpt: QueryHdr RxOrdGrp3 ;

RxOrderRptGrp: RxOrderRpt

    |      RxOrderRpt RxOrderRptGrp ;

RxOrderRpt:  QueryHdr RxOrdGrp2 ;

RxOrdGrp1:   RxOrd1

    |      RxOrd1 RxOrdGrp1 ;

RxOrd1:      ORC ST RXE ST RXRGrp ST RXCOptGrp RXAGrp RXR ST;

RxOrdGrp2:   RxOrd2

    |      RxOrd2 RxOrdGrp2 ;

RxOrd2:      ORC ST RXE ST RXRGrp ST RXCOptGrp ;

RxOrdGrp2Opt:

    | RxOrdGrp2 RxOrdGrp2Opt ;

RxOrdGrp3:   RxOrd3

    |      RxOrd3 RxOrdGrp3 ;

RxOrd3:      ORC ST RXE ST RXRGrp ST RXCOptGrp RxDGrp RXRGrp ST ;

RxOrdGrp4:   RxOrd4

    |      RxOrd4 RxOrdGrp4 ;

RxOrd4:      RXE St RXRGrp ST RXCOptGrp RXGGrp RXRGrp ST ;

RxdGrpOpt:

    | OrcRxdGrp RxdGrpOpt ;

OrcRxdGrp:

    | ORC ST RxdDsGrp OrcRxdGrp ;

RxdDsGrp:

    | RxD RXRGrp RXCOptGrp RxdDsGrp ;

RxgGrpOpt:

    | OrcRxgGrp RxgGrpOpt ;

OrcRxgGrp:

    | ORC ST RxgGvGrp OrcRxgGrp ;
```

```

RxgGvGrp:
    | RXG RXRGrp RXCOptGrp RxgGvGrp ;

RxaGrpOpt:
    | OrcRxaGrp RxaGrpOpt ;

OrcRxaGrp:
    | ORC ST RxaRaGrp OrcRxaGrp ;

RxaRaGrp:
    | RXA RXR RxaRaGrp ;

GiveRptGrp:    GiveRpt
    |    GiveRpt GiveRptGrp ;

AdminRptGrp:    AdminRpt
    |    AdminRpt AdminRptGrp ;

DispenseRptGrp:    DispenseRpt
    |    DispenseRpt DispenseRptGrp ;

DispenseGrp:    Dispense
    |    Dispense DispenseGrp ;

RxAdminGrp: RxAdmin
    |    RxAdmin RxAdminGrp ;

RxOrderGrp: RxOrder
    |    RxOrder RxOrderGrp ;

RxOrder:    ORC ST Prescription OBXDOptGrp BLGOpt ;

RxGiveGrp: RxGive
    |    RxGive RxGiveGrp ;

RxEncOrdGrp: RxEncOrd
    |    RxEncOrd RxEncOrdGrp ;

RxEncOrdOpt:
    |    RxEncOrd ;

/* Chapter VI - Finance */

/* Finance: Patient accounting. The triggering events that follow are */
/* served by the DFT, BAR and ACK messages.                               */

bar:    p01    /* Add and update patient account.          */
    |    p02 ; /* Purge patient account.                  */

dft:    p03 ; /* Post detail financial transaction.        */

```

Appendix C: BNF Message Descriptions

```
p01:      SOM MSH ST EVNP01 ST PID ST BillingGrp EOM ;

BillingGrp:  Billing

      |      Billing BillingGrp ;

Billing:  PV1Opt PV2Opt OBXOptGrp AL1OptGrp DG1OptGrp PR1OptGrp

      GT1OptGrp NK1OptGrp InsOptGrp2 ACCOpt UB1Opt UB2Opt ;

p02:      SOM MSH ST EVNP02 ST VisitGrp EOM ;

VisitGrp: Visit

      |      Visit VisitGrp ;

Visit:  PID ST PV1Opt PV2Opt OBXOptGrp ;

p03:      SOM MSH ST EVNP03 ST PID ST PV1Opt PV2Opt1 OBXOptGrp FT1Grp EOM ;

FT1Grp:  FT1 ST

      |      FT1 ST FT1Grp ;

/* Chapter VII - Ancillary Reporting */

/* Ancillary Data Reporting. */

oru:      SOM MSH ST  PidOptClause3 ObserveGrp DSCOpt EOM ;

orf:      SOM MSH ST MSA ST ERROpt QueryHdr ObserveGrp DSCOpt EOM ;

PidOptClause3:

      |      PID ST NoteOptGrp PV1Opt ;

ObserveGrp: Observe

      |      Observe ObserveGrp ;

Observe:  ORCOpt OBR ST NoteOptGrp OBXDGRPOpt ;

/* Master Files Messages...see note below... the segment level definition for the MFSGrp will vary
according to the master file entry being referenced in the MFI segment... hence a BNF form will
need to be generated for each master file ... */

mfn: SOM MSH ST MFI ST MFEGrp EOM ;

MFEGrp: MFE ST MFSGrpOpt

      |      MFE ST MFSGrpOpt MFEGrp ;

MFSGrpOpt:

      | MFSGrp ;

MFSGrp: XXX ST

      | XXX ST MFSGrp ;

/* XXX is then one or more HL7 and/or Z-segments carrying the data for the entry identified by the
MFI segment. */

/* Master File Delayed Acknowledgment */

mfd:      SOM MSH ST MFI ST MFAOptGrp EOM ;
```

```
MFAOptGrp:

    |      MFAGrp ;

MFAGrp: MFA ST

    |      MFA ST MFAGrp ;

/* Response to Master Files Query */

mfr:   SOM MSH ST MSA ST ERROpt QRD ST QRFOpt MFI ST MFEGrp EOM ;

/* The segment level definition for the MFSGrp will vary according to the master file being
referenced by the MFI segment... hence a BNF form will need to be generated for each master
file... */

/* This is the end of the message definition section */

/* The following are sets of segment options and groups needed above. */

ACCOpt:

    |      ACC ST ;

BLGOpt:

    |      BLG ST ;

ERROpt:

    |      ERR ST ;

AL1OptGrp:

    |      AL1 ST

    |      AL1 ST AL1Grp ;

AL1Grp: AL1 ST

    |      AL1 ST AL1Grp ;

DSCOpt:

    |      DSC ST ;

DG1Grp: DG1 ST

    |      DG1 ST DG1Grp ;

DG1OptGrp:

    |      DG1 ST

    |      DG1 ST DG1Grp ;

EVNOpt:

    |      EVN ST ;

EVNA19Opt:

    |      EVNA19 ST ;

GT1OptGrp:
```

Appendix C: BNF Message Descriptions

```
|      GT1 ST

|      GT1 ST GT1Grp ;

GT1Grp:  GT1 ST

|      GT1 ST GT1Grp ;

IN2Opt:

|      IN2 ST ;

IN3Opt:

|      IN3 ST ;

IN3OptGrp:

|      IN3Grp ;

IN3Grp:  IN3 ST

|      IN3 ST IN3Grp ;

MRGOpt:

|      MRG ST ;

NK1OptGrp:

|      NK1 ST

|      NK1 ST NK1Grp ;

NK1Grp:  NK1 ST

|      NK1 ST NK1Grp ;

OBXOptGrp:

|      OBXGrp ;

OBXGrp:  OBX ST

|      OBX ST OBXGrp ;

ODSGrp:  ODS ST

|      ODS ST ODSGrp ;

ODTGrp:  ODT ST

|      ODT ST ODTGrp ;

ORCOpt:

|      ORC ST ;

PIDOpt:

|      PID ST NoteOptGrp ;

PR1OptGrp:

|      PR1 ST
```

```

    |      PR1 ST PR1Grp ;

PR1Grp:  PR1 ST

    |      PR1 ST PR1Grp ;

PV1Opt:

    |      PV1 ST ;

PV2Opt:

    |      PV2 ST ;

UB1Opt:

    |      UB1 ST ;

UB2Opt:

    |      UB2 ST ;

QRFOpt:  QRF ST

    |      QRF ST QRFOpt ;

RXAGrp:  RXA ST

    |      RXA ST RXAGrp ;

RXDGrp:  RXD ST

    |      RXD ST RXDGrp ;

RXGGrp:  RXG ST

    |      RXG ST RXGGrp ;

RXCOpt:

    |      RXC ST ;

RXCOptGrp:

    |      RXCGrp ;

RXCGrp:  RXC ST

    |      RXC ST RXCGrp ;

RXCNOptGrp:

    |      RXCNGrp ;

RXCNGrp:  RXC ST NoteOptGrp

    |      RXC ST NoteOptGrp RXCNGrp ;

RXRGrp:  RXR ST

    |      RXR ST RXRGrp ;

URSOpt:

    |      URS ST ;

```