

Security DBS

Bit Name	IADC code	Size range, in.	Recommended WOB, lb/in. diameter	Recommended rotary speed, rpm	Special features/usage*
Surface set diamond coring bits					
CB17	M613	6-12 1/4	250-3,500	80-140	F
Medium					
Insert roller cone bits					
M84	615	11 5/8, 17, 17 1/2	3,000-7,000	300-80	X
M84F	617	43/4, 51/2, 61/4, 61/2, 63/4, 77/8, 83/8, 81/2, 83/4, 91/2, 97/8, 105/8, 12, 121/4	3,000-7,000	80-40	BX
M84FD	617	83/8, 81/2, 8 3/4, 121/4	3,000-7,000	80-40	BXW
MAF	617	77/8	3,000-7,000	80-40	AB
MM88	625	121/4	2,500-7,000	150-80	MB
M84CF	627	77/8, 83/4, 11	3,000-7,000	80-40	BY
M84CFD	627	81/2, 83/4	3,000-7,000	14824	BYW
M85F	627	61/2, 63/4, 77/8, 83/4	3,500-7,000	80-40	BX
M86CF	627	77/8	3,000-7,000	80-40	BY
M89T	627	171/2	2,500-7,000	150-80	MB
M89TF	627	57/8, 6, 61/8, 61/4, 61/2, 63/4, 77/8,	3,500-7,000	80-40	BX
M89TFD	627	81/2, 83/4, 91/2	3,500-7,000	80-40	BXW
M89F	637	77/8, 121/4	4,000-7,000	70-40	BY
M89FD	637	97/8	4,000-7,000	70-40	BYW