

Write a LEX program to print all the constants in the given C source program file.

Input Source Program: (sample.c)

```
#define P 314
#include<stdio.h>
#include<conio.h>
void main()
{
    int a,b,c = 30;
    printf("hello");
}
```

Program: (countconstants.l)

digit [0-9]

%{

int cons=0;

%}

%%

{digit}+ { cons++; printf("%s is a constant\n", yytext); }

.\n { }

%%

int yywrap(void) {

return 1; }

int main(void)

{

FILE *f;

char file[10];

printf("Enter File Name : ");

scanf("%s",file);

f = fopen(file,"r");

yyin = f;

yylex();

printf("Number of Constants : %d\n", cons);

fclose(yyin);

}

bin

C:\Windows\System32\cmd.exe

Microsoft Windows [Version 10.0.22621.2134]
(c) Microsoft Corporation. All rights reserved.
C:\lex_programs>set path=C:\Program Files (x86)\GnuWin32\bin
C:\lex_programs>flex pro1.l.txt
C:\lex_programs>set path=C:\MinGW\bin
C:\lex_programs>gcc lex.yy.c
C:\lex_programs>a.exe
Enter File Name : pro1.c
a=b*c-17
17 is a constant
^Z
Number of Constants : 1
C:\lex_programs>^S

Compiler design

This PC

Windows (C:)

autoheader	04-09-2011 23:19	File	5 KB
autoheader-2.14	24-07-2009 19:07	File	9 KB
autoheader-2.60	05-09-2011 06:06	File	9 KB
autom4te	04-09-2011 23:19	File	5 KB

140 items