

ABBREVIATIONS

FECB	FIRE PROTECTION SPECIALTIES, Fire Extinguisher/Blanket Cabinet, Type FECB-1, Unless Noted Otherwise, Provide Fire Rated Cabinet at Rated Walls, Provide Surface Mounted Cabinet at Rated Walls Where Stud Depth is Less than 6" and at Masonry Walls, See _____, Typ	A1
FEC	FIRE PROTECTION SPECIALTIES, Fire Extinguisher Cabinet, Type FEC-1, Unless Noted Otherwise, Provide Fire Rated Cabinet at Rated Walls, See _____, Typ	A1 XARGY
FF	Face of Finish	
FOC	Face of Concrete	
FD	Floor Drain	
FOM	Face of Masonry	
FOS	Face of Stud	
FS	Floor Sink	
HB	Hose Bib	
MO	Masonry Opening	
UNO	Unless Noted Otherwise	
RO	Roof Opening	
Typ	Typical	
Sim	Similar	
OH	Opposite Hand	

NOTES

1. All Exterior Walls shall be Wall Assembly Type $\frac{6R}{1M}$ Unless Noted Otherwise.
2. All Interior Walls shall be Wall Assembly Type $\frac{6E}{1M}$ Unless Noted Otherwise.
3. All Dimensions are to Face of Stud (FOS) or Center Line, Unless Noted Otherwise.
4. All Elevation Dimensions are above Finish Floor (FF) at each floor level, Unless Noted Otherwise.
5. Dimensions noted as "+/-" are nominal.
6. Floor Drains (FD) and Floor Sinks (FS) shall be set -3/4" and a min. of 3'-0" from nearest wall, Unless Noted Otherwise.
7. IDENTIFYING DEVICES: For Room Signage refer $\frac{E11}{XAG60}$ Typ to and Specifications
8. FIRE RESISTIVE ASSEMBLIES:
 - a. All Through Penetrations and Wall Membrane Penetrations through Walls of Fire Resistive Construction shall be protected in accordance with their Fire Resistive Ratings.
 - b. All Walls of Fire and/or Smoke Resistive Construction shall be Permanently Identified with Signs or Stenciling in lettering not less than 3 inches (76 mm) in height with a minimum 3/8 inch (9.5 mm) stroke in a contrasting color incorporating the following wording: FIRE AND/OR SMOKE BARRIER "R" HOUR RATED, PROTECT ALL OPENINGS, Signs or Stenciling shall be located above ceilings on both sides of the wall, located 15'-0" from ends of wall and at intervals not to exceed 30'-0" horizontally along the wall or partition. Note: "R" indicates the hourly rating of the wall or partition.

F18	Floor Plan Legend
No Scale	

OSHPD No.: _____
 OSHPD _____ Agency Approval _____

Behavioral Health Building Addition
Good Samaritan Hospital
Bakersfield, CA 93309

BUILDING A
FLOOR PLAN- FIRST FLOOR

Drawing _____


**ARCHITECTURE
PLANNING
INTERIORS**
www.dardenarchitects.com
 6790 N. West Ave. • Fresno, CA 93711 • T. 559.448.8051


No.	Revision/Submission	Date
Revision		
	Designed/Designer	Copyright 2022 Darden Architects
Scale: 1/8" = 1'-0"	Drawn By: Author	<i>A/A101</i>
Project Number: 2475	Checked I/Checker	
Date: xx/xx/xx	Review/Approver	

ABBREVIATIONS

FECB	FIRE PROTECTION SPECIALTIES, Fire Extinguisher/Blanket Cabinet, Type FECB-1, Unless Noted Otherwise, Provide Fire Rated Cabinet at Railed Walls. Provide Surface Mounted Cabinet at Railed Walls Where Stud Depth is Less than 6" and at Masonry Walls, See  Type
FEC	FIRE PROTECTION SPECIALTIES, Fire Extinguisher Cabinet, Type FEC-1, Unless Noted Otherwise, Provide Fire Rated Cabinet at Railed Walls, See  Type
FF	Face of Finish
FOC	Face of Concrete
FD	Floor Drain
FOM	Face of Masonry
FOS	Face of Stud
FS	Floor Sink
FB	Brass Bib
MO	Masonry Opening
UNO	Unless Noted Otherwise
RO	Rough Opening
Type	Typical
Sim	Similar
OH	Opposite Hand

NOTES

1. All Exterior Walls shall be Wall Assembly Type $\frac{6}{8}$ UM Unless Noted Otherwise.
2. All Interior Walls shall be Wall Assembly Type $\frac{6}{E}$ UM Unless Noted Otherwise.
3. All Dimensions are to Face of Stud (FOS) or Center Line, Unless Noted Otherwise.
4. All Elevation Dimensions are above Finish Floor (FF) at each floor level, Unless Noted Otherwise.
5. Dimensions noted as "+/-" are nominal.
6. Floor Drains (FD) and Floor Sinks (FS) shall be set -3/4" and a min. of 3'-0" from nearest wall, Unless Noted Otherwise.
7. IDENTIFYING DEVICES: For Room Signage refer $\frac{E11}{XAB07}$ Typ to and Specifications
8. FIRE RESISTIVE ASSEMBLIES:
 - a. All Through Penetrations and Wall Penetrations shall be in accordance with Fire of Fire Resistive Construction shall be protected in compliance with their Fire Resistive Ratings.
 - b. All Walls of Fire and/or Smoke Resistive Construction shall be Permanently identified with Signs or Stenciling in lettering not less than 3 inches (76 mm) in height, with a minimum 3/8 inch (3.5 mm) stroke in a contrasting color incorporating the following wording: FIRE AND/OR SMOKE BARRIER "R" HOUR RATED, PROTECT ALL OPENINGS, Signs or Stenciling shall be located above ceilings on both sides of the wall, located 15'-0" from ends of wall and at intervals not to exceed 50'-0" horizontally along the wall or partition. Note: "R" indicates the hourly rating of the wall or partition.

F18	Floor Plan Legend																											
No Scale																												
OSHPD No.: OSHPD Agency Approval Behavioral Health Building Addition Good Samaritan Hospital Bakersfield, CA 93309 Project BUILDING A FLOOR PLAN- SECOND FLOOR  ARCHITECTURE PLANNING INTERIORS www.dardenarchitects.com  6790 N. West Ave. • Fresno, CA 93711 • T. 559.448.8051 Architect <table> <tr> <th>No.</th><th>Revision/Submission</th><th>Date</th></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> Revision <table> <tr> <td></td><td>Designed/Designer</td><td>Copyright 2022 Darden Architects</td></tr> <tr> <td>Scale: 1/8" = 1'-0"</td><td>Drawn By: Author</td><td rowspan="2">A/A102</td></tr> <tr> <td>Project Number: 2475</td><td>Checked IChecker</td></tr> <tr> <td>Date: xx/xx/xx</td><td>Reviewed/Approver</td><td></td></tr> </table>			No.	Revision/Submission	Date														Designed/Designer	Copyright 2022 Darden Architects	Scale: 1/8" = 1'-0"	Drawn By: Author	A/A102	Project Number: 2475	Checked IChecker	Date: xx/xx/xx	Reviewed/Approver	
No.	Revision/Submission	Date																										
	Designed/Designer	Copyright 2022 Darden Architects																										
Scale: 1/8" = 1'-0"	Drawn By: Author	A/A102																										
Project Number: 2475	Checked IChecker																											
Date: xx/xx/xx	Reviewed/Approver																											