

Build & Automation Handoff — New Site (Same Stack as Wash Kings Rebuild)

Purpose: Paste into ChatGPT (or any AI) as reference when scaffolding a **new** website that must match this repository's **build, deploy, and automation** patterns.

Repo: Staten Island Wash Kings / Wash Kings Rebuild (staten-island-wash-kings).

Generated: April 30, 2026.

1. Master prompt (copy for the AI)

You are scaffolding a new Next.js project that must match this reference stack unless the human overrides a point.

Stack: Next.js 15 (App Router), React 18, TypeScript, Tailwind CSS 3, ESLint via `next lint`. Do not replace the bundler with Vite or CRA.

Scripts: `npm run dev` → `next dev`; `npm run build` → `next build`; `npm run start` → `next start`; `npm run lint` → `next lint`. Optional: `npm run generate-blog-draft` → `node scripts/generate-blog-draft.js` if blog tooling is copied.

Deploy: Vercel. Use `vercel.json` with `framework: "nextjs"`, `buildCommand: "next build"`, and preserve cron jobs unless the human changes paths/schedules.

Next.js config: `trailingSlash: true`; expose `NEXT_PUBLIC_SUPABASE_URL` and `NEXT_PUBLIC_SUPABASE_ANON_KEY` via `next.config.js` env if Supabase is used; keep security headers and image optimization settings aligned with the reference `next.config.js`.

Conventions: `app/` (App Router), `components/`, `lib/`, `scripts/` as in the reference repo. After env changes on Vercel, redeploy.

Windows note: Prefer `;` instead of `&&` when chaining commands in PowerShell.

Deliverables when asked to scaffold: `package.json`, `next.config.js`, `tailwind.config.js`, `postcss.config.js`, `tsconfig.json`, `vercel.json`, `.env.local.example`, and a short README with install, build, lint, and deploy steps.

2. package.json (scripts & core versions)

Script	Command
dev	next dev
build	next build
start	next start
lint	next lint
generate-blog-draft	node scripts/generate-blog-draft.js

Dependencies (representative): `next ^15.1.6`, `react ^18.2.0`, `react-dom ^18.2.0`, `typescript ^5.3.3`, `tailwindcss ^3.4.1`, `eslint ^8.56.0`, `eslint-config-next ^14.1.0`, `postcss`,

autoprefixer.

Integrations in this repo (enable only what the new site needs): @supabase/supabase-js, resend, twilio, stripe, sanity, next-sanity, @sanity/client, framer-motion, react-hook-form, @hookform/resolvers, zod, dotenv.

3. Vercel (vercel.json)

- **buildCommand:** next build
- **framework:** nextjs
- **Crons:** One job calling GET (Vercel cron) path /api/cron/generate-and-publish/ on schedule 0 13 * * 2,5 (13:00 UTC Tuesday and Friday — aligns with “2x per week” blog automation when that route exists).

If the new site does not use blog cron, remove the crons array or change path/schedule.

4. next.config.js behavior (mirror for parity)

- **trailingSlash:** true
 - **env:** Pass through NEXT_PUBLIC_SUPABASE_URL, NEXT_PUBLIC_SUPABASE_ANON_KEY when using Supabase
 - **images:** formats: ['image/avif', 'image/webp']; deviceSizes and imageSizes as in production config
 - **headers:** Global /:path* — X-DNS-Prefetch-Control, X-Frame-Options: SAMEORIGIN, X-Content-Type-Options: nosniff, X-XSS-Protection
-

5. Environment variables (from `.env.local.example` + server secrets)

Public / client-safe (examples):

- `NEXT_PUBLIC_SITE_URL` — canonical site URL
- `NEXT_PUBLIC_PHONE`, `NEXT_PUBLIC_PHONE_DISPLAY`
- `NEXT_PUBLIC_JOBBER_URL` (if used)
- `NEXT_PUBLIC_TRUSTINDEX_WIDGET_ID`
- `NEXT_PUBLIC_SANITY_PROJECT_ID`, `NEXT_PUBLIC_SANITY_DATASET`,
`NEXT_PUBLIC_SANITY_API_VERSION`

Sanity / blog automation:

- `SANITY_API_READ_TOKEN`, `SANITY_API_WRITE_TOKEN`
- `OPENAI_API_KEY`, `ANTHROPIC_API_KEY`
- `BLOG_AUTOPUBLISH_SECRET` — protect cron route
- `BLOG_AUTOPUBLISH_MODE` — publish or draft
- `BLOG_PUBLISH_SCHEDULE` — e.g. `2x_week`

Comms & payments (when CRM/booking/invoices are in scope):

- NEXT_PUBLIC_SUPABASE_URL, NEXT_PUBLIC_SUPABASE_ANON_KEY, SUPABASE_SERVICE_ROLE_KEY (server only)
- RESEND_API_KEY
- TWILIO_ACCOUNT_SID, TWILIO_AUTH_TOKEN, TWILIO_PHONE_NUMBER
- STRIPE_SECRET_KEY, STRIPE_WEBHOOK_SECRET

Rule: Set the same names in Vercel project settings; redeploy after changes.

6. Architecture snapshot (full product context)

- **Framework:** Next.js 15 App Router, TypeScript, Tailwind, Framer Motion where used
- **Data:** Supabase (Postgres); privileged server work via service role
- **Email:** Resend; **SMS:** Twilio; **Payments:** Stripe + webhook route
- **CMS:** Sanity (blog/studio), distinct from lead CRM flow
- **Cron:** Blog generate/publish via /api/cron/generate-and-publish/ (secret-gated in app code — verify route implementation when copying)

For route-level behavior, admin shell, booking funnel, migrations order, and Stripe operational notes, use the repository file **SESSION-CONTEXT-COMPLETE-PACK-MAX-2026.md** as the detailed continuation pack.

7. Verification checklist (after new project boots)

1. `npm run build` succeeds locally.
2. `npm run lint` passes (or fix only new issues).
3. Vercel preview deploy uses `next build` without custom command drift.
4. If cron exists: Vercel Cron shows the job; hitting the cron URL in production requires the expected auth/secret behavior from your API route.
5. Trailing slashes: internal Link hrefs and canonical URLs match `trailingSlash: true`.

8. Remote reference

- Example remote (from session context):
`https://github.com/Jerovyn/Wash-Kings-Rebuild.git`

9. Regenerating this handoff as PDF

From the repository root, with Python 3 and packages `markdown` and `xhtml2pdf` installed (`py -3 -m pip install markdown xhtml2pdf`):

```
py -3 scripts/generate-handoff-pdf.py
```

Output: `docs/BUILD-HANDOFF-FOR-CHATGPT.pdf` (same folder as this Markdown file).

End of handoff document.