


# Conceptual Database Design 1



# Topics List

---

- Conceptual Database Design
- Build conceptual data model

# Conceptual Database Design

---

- The process of constructing a model of the data used in an enterprise, independent of *all* physical considerations.
- The goal of this phase is to produce a conceptual schema (which includes identification of the important entity types, relationship types, and attributes) for the database that is independent of a specific DBMS.
- We will use Entity Relationship (ER) modelling during this phase.

# Conceptual Database Design

---

- Overview Database Design Methodology:

- Step 1 Build conceptual data model. Conceptual

- Step 2 Build and validate logical data model. Logical

- Step 3 Translate logical data model for target DBMS.

- Step 4 Design file organisations and indexes.

- Step 5 Design user views.

- Step 6 Design security mechanisms.

- Step 7 Consider the introduction of controlled redundancy.

- Step 8 Monitor and tune the operational system.

Physical

Maintenance

# Conceptual Database Design

## Build conceptual data model

---

- Step 1.1 Identify entity types.
- Step 1.2 Identify relationship types.
  - 1.2.1 Cardinality.
  - 1.2.2 Participation.
- Step 1.3 Identify and associate attributes with entity or relationship types.
- Step 1.4 Determine attribute domains.
- Step 1.5 Determine candidate, primary, and alternate key attributes.
- Step 1.6 Consider use of enhanced modelling concepts (optional step).
- Step 1.7 Check model for redundancy.
- Step 1.8 Validate conceptual model against user transactions.
- Step 1.9 Review conceptual data model with user.

# Topics List

---

- Conceptual Database Design
- Build conceptual data model

# Build conceptual data model

## Identify entity types

---

- Identify entity types that we need to represent in the database.
- Typical examples:
  - People: staff, clients/customers, patients, members, owners, contacts, other individuals
  - Objects: stock items, real estate, offices
  - Organisations: firms (suppliers), departments, charities, clubs, committees
  - Object classes: recordings, films, books, types of stock, biological species, work roles
  - Events: concerts, examinations, lecture courses, consultations, sales
- Document the entity types.

# Build conceptual data model

## Identify relationship types

---

- Identify the relationships between entity types that need to be recorded.
- Typical examples:
  - Ownership: person *owns* object
  - Lines of command: person *supervises* person
  - Participation: person *participates in* event
  - Part of relationship: item *is part of* order; person *belongs to* organisation
  - Location: house *is located in* region
  - Personal: person *is married to* person; person *is parent of* person



# Build conceptual data model

## Identify relationship types

---

- Use entity–relationship (ER) modelling to understand the relationship types.
- Determine the *Structural Constraints* of each relationship type.
- Document the relationship types.

# Build conceptual data model

Identify and associate attributes with entity or relationship types.

---

- Attributes can be identified where a *noun* or a *noun phrase* is a property, quality, identifier, or characteristic of one of the entity or relationship types previously found.
- Identify whether attributes are:
  - Simple/composite.
  - Single/multi-valued.
  - Derived.
- Document the attributes.

# Build conceptual data model

## Documenting attributes

---

- Record the following information for each attribute:
  - attribute name and description;
  - data type and length;
  - any aliases that the attribute is known by;
  - whether the attribute must always be specified (in other words, whether the attribute allows or disallows nulls);
  - whether the attribute is multi-valued;
  - whether the attribute is composite, and if so, which simple attributes make up the composite attribute;
  - whether the attribute is derived and, if so, how it should be computed;
  - default values for the attribute (if specified).

# Build conceptual data model

## Determine attribute domains

---

- A domain is a pool of values from which one or more attributes draw their values.
- A domain specifies:
  - allowable set of values for the attribute;
  - size and format of the attribute.
- Document the attribute domains.

# Build conceptual data model

## Guidelines for choosing a primary key

---

- Select the candidate key
  - with the minimal set of attributes;
  - that is less likely to have its values changed;
  - that is less likely to lose uniqueness in the future;
  - with fewest characters (for those with textual attribute(s));
  - with the smallest maximum value (for numerical attributes);
  - that is easiest to use from the users' point of view.