

Lab 16	
Name	Dang Hoang Nguyen
Student ID	SE171946

What is Server-Side Request Forgery (SSRF), and how does it differ from other types of web application vulnerabilities?

A online security flaw known as Server-Side Request Forgery (SSRF) enables attackers to trick a server into sending unwanted requests to other systems. It is distinct from other kinds of vulnerabilities in web applications in a few important ways:

Goal:

- SSRF: Targets the server directly by abusing server-side capability.
- Others: Frequently focus on application logic, session data, or user data.

Effect:

- SSRF: May result in data exfiltration, denial-of-service attacks, remote code execution, and exposing of internal resources.
- Others: Could result in unapproved access, account takeover, data breaches, or website vandalism.

Challenge:

- SSRF: Compared to certain other vulnerabilities, it may be more difficult to exploit and identify.
- Others: Depending on the particular vulnerability and application scenario, difficulty varies.

Describe a methodology for exploiting an SSRF vulnerability in a web application. What are the key steps and techniques involved in crafting and sending malicious requests to exploit SSRF vulnerabilities?

1. **Identify SSRF Vulnerability:** Find endpoints vulnerable to SSRF.
2. **Understand Functionality:** Know how the app processes user-supplied URLs.
3. **Craft Malicious Requests:** Manipulate URLs, abuse protocols, exploit DNS rebinding, or request smuggling.
4. **Test Payloads:** Verify crafted payloads work.
5. **Exploit Internal Services:** Access sensitive files, query metadata, or exploit intra-app communication.
6. **Exploit External Resources:** Perform port scanning, access administrative panels, or attack other targets.
7. **Cover Tracks:** Modify headers, use proxies, or delete logs.
8. **Report and Mitigation:** Report responsibly, provide details, and recommend mitigations.
9. **Continuously Monitor:** Regularly scan for SSRF vulnerabilities.
10. **Stay Updated:** Keep up with new SSRF exploitation techniques.

**Lab: Blind SSRF with out-of-band detection**

Every time a user hits a product page, this lab program uses another piece of software to automatically get the URL from the Referer header field. Thus, by entering the Referer URL field that we control, we may OOB SSRF. Put Burp Collaborator to use.

The screenshot displays a web browser window at the URL `https://0af4d005903f38d5781b4c56f00b30073.web-security-academy.net`. The page is titled "Blind SSRF with out-of-band detection" and is part of a "LAB" section. It features a "WE LIKE TO SHOP" banner and a grid of product cards. The products shown are:

- Com.Tool (4 stars, \$48.88)
- Real Life Photoshopping (4 stars, \$92.92)
- Hexbug Battleground Tarantula Double Pack (3 stars, \$8.09)
- Six Pack Beer Belt (4 stars, \$1.45)
- Wings (1 star, \$1.45)
- Paper Plane (1 star, \$1.45)
- Lightbulb (1 star, \$1.45)
- Red and White Balloon (1 star, \$1.45)

Below the browser window, the Burp Suite interface is shown. The "Request" tab is selected, displaying a request to the target URL. The "Response" tab is also selected, showing the HTML response. The response includes a section titled "Blind SSRF with out-of-band detection" which contains a link to a portswigger.net URL and a description of the challenge.

Because this time we are dealing with Blind SSRF we should setup Burp Collaborator to receive DNS response

We have successfully performed Blind SSRF attack(POC only) with the help of Burp Collaborator and we have received a DNS/HTTP Responses

Burp Suite Professional v2023.12.1.5 - Temporary Project - licensed to h3110w0r1d

Dashboard

Target

Proxy

Intruder

Repeater

Collaborator

Sequence

Decoder

Comparer

Logger

Organizer

Extensions

Learn

1 x +

Payloads to generate: 1

Copy to clipboard

☒ Include Collaborator server location

Poll now

Polling automatically

Search

#	Time	Type	Payload	Source IP address	Comment
1	2024-Feb-15 13:20:20.597 UTC	DNS	tkhs0wunogfk8cx9u3e4fc1us0joe3	3.248.180.83	
2	2024-Feb-15 13:20:20.598 UTC	DNS	tkhs0wunogfk8cx9u3e4fc1us0joe3	3.251.104.212	
3	2024-Feb-15 13:20:20.673 UTC	HTTP	tkhs0wunogfk8cx9u3e4fc1us0joe3	34.251.122.40	

Description

DNS query

The Collaborator server received a DNS lookup of type A for the domain name tkhs0wunogfk8cx9u3e4fc1us0joe3.oastify.com.  
The lookup was received from IP address 3.251.104.212:45433 at 2024-Feb-15 13:20:20.598 UTC.

Event log

All issues (16)

Memory: 185.0MB

29°C

Troil quang

Search

8:20 pm

15/02/2024



Blind SSRF with out-of-band detection

[Back to lab description >>](#)

LAB Solved

Congratulations, you solved the lab!

[Share your skills!](#) [Continue learning >>](#)

THE TUTORIALS POINT

[Home](#)