

Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	My organization recently experienced a DoS attack, which compromised and stopped the network services for about 2 hours until it was resolved. It was found out that there was an unconfigured firewall and the malicious actor used it as its way to flood the services with ICMP until it stopped working. The organization then installed and implemented several protocols including new firewall rules, network monitoring software and IDS/IPS system to filter out suspicious traffic characteristics.
Identify	The network services came to a halt after the employees were unable to use the services. It was found out that there was a gap in security because of an unconfigured firewall. With this, the malicious actor used this vulnerable surface to flood the network services with ICMP for it to stop working and halt the system.
Protect	From what happened, we can learn a lesson to regularly monitor and audit the firewall rules, inspect every data packets coming in and out for the systems and server, verify the authenticity of the connections and source IP Address verification to check spoofed IP Address on incoming ICMP packets. Installations of IDS/IPS system and network monitoring software to detect irregular traffic patterns will also help add another layer of protection to the

	system.
Detect	The use of network monitoring software to detect abnormal traffic patterns, port filtering to filter out incoming services that do not belong to the required field, and IDS/IPS system to filter out ICMP traffic based on suspicious patterns.
Respond	The first step to consider when trying to contain and respond to an event is by blocking ICMP packets so the attack can come to a halt, stopping all non-critical network services offline. Next we can isolate the case and assess the damage it took from the DoS attack. This way, we can mitigate and close all the surface attacks from further damage and are able to recover by using back ups and baseline configurations.
Recover	The organization can be able to recover from the attack of DoS by restoring critical network services and use of back up plans, so it is very important to back up regularly.

Reflections/Notes: