

2ºDAW. Despliegue de aplicaciones web.

UD 1 - Actividad 4 - Configuración DNS I (Definición de las zonas)



cat del fichero de zonas de S1-Alias

```
jcordero@s1-jcordero:/etc/bind$ cat named.conf.local
//
// Do any local configuration here
//

// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "alumno-1.ca" {
    type master;
    notify yes;
    allow-transfer { 172.16.1.2; };
    file "/etc/bind/db.alumno-1.ca";
};

zone "1.16.172.in-addr.arpa" {
    type master;
    notify yes;
    allow-transfer { 172.16.1.2; };
    file "/etc/bind/bd.alumno-1.ca.rev";
};

zone "aula-1.org" {
    type slave;
    masters { 172.16.1.2; };
    allow-notify { 172.16.1.2; };
    file "db.aula-1.org";
};

jcordero@s1-jcordero:/etc/bind$ _
```

cat del fichero de zonas de S2-Alias

```
jccordero@s2-jccordero:/etc/bind$ cat named.conf.local
//
// Do any local configuration here
//

// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "alumno-1.ca" {
    type slave;
    masters { 172.16.1.1; };
    allow-notify { 172.16.1.1; };
    file "db.alumno-1.ca";
};

zone "1.16.172.in-addr.arpa" {
    type slave;
    masters { 172.16.1.1; };
    allow-notify { 172.16.1.1; };
    file "bd.alumno-1.ca.rev";
};

zone "aula-1.org" {
    type master;
    notify yes;
    allow-transfer { 172.16.1.1; };
    file "/etc/bind/db.aula-1.org";
};

jccordero@s2-jccordero:/etc/bind$
```