

Create a MySQL table called `playlists` to store Spotify-style music playlists, with columns: `playlist_id` (primary key), `user_id` (foreign key), `name` (varchar), and `created_at` (datetime). Write the CREATE TABLE statement.

The screenshot shows the MySQL Workbench interface. On the left, the 'SCHEMAS' pane shows a tree view with 'emp' and 'instacore' schemas. Under 'instacore', there are 'Tables' (including 'cart', 'expenses', 'foodorder', 'influencers', 'movies', 'orderitems', 'orders', 'payments', 'pl', 'playlist', and 'playlists') and 'Columns' (including 'playlist_id', 'user_id', 'name', and 'created_at'). The 'playlists' table is selected. The main editor shows the following SQL code:

```
4  playlist_id INT AUTO_INCREMENT PRIMARY KEY,  
5  user_id INT NOT NULL,  
6  name VARCHAR(255) NOT NULL,  
7  created_at DATETIME DEFAULT CURRENT_TIMESTAMP,  
8  CONSTRAINT fk_playlists_user  
9      FOREIGN KEY (user_id)  
10     REFERENCES users(user_id)  
11     ON DELETE CASCADE  
12 );  
13  
14 • DESCRIBE playlists;
```

Below the SQL editor, the 'Result Grid' shows the table structure:

Field	Type	Null	Key	Default	Extra
playlist_id	int(11)	NO	PRI	NULL	auto_increment
user_id	int(11)	NO	MUL	NULL	
name	varchar(255)	NO		NULL	
created_at	datetime	YES		current_timestamp()	

The bottom of the interface shows 'Result 1' and 'Administration' tabs.