

Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.

The screenshot shows the MySQL Workbench interface. The left sidebar displays the 'SCHEMAS' tree with 'instacore' selected. The main editor shows the following SQL code:

```
4 -- id INT AUTO_INCREMENT PRIMARY KEY,
5 -- name VARCHAR(100),
6 -- cuisine VARCHAR(50),
7 -- rating DECIMAL(2,1),
8 -- city VARCHAR(50)
9 -- );
10
11 * INSERT INTO Restaurants (name, cuisine, rating, city)
12 VALUES
13 ('Spice Garden', 'Indian', 4.5, 'Ahmedabad'),
14 ('Pizza House', 'Italian', 4.2, 'Surat'),
15 ('Dragon Palace', 'Chinese', 4.3, 'Rajkot'),
```

The 'Result Grid' shows the data inserted into the 'Restaurants' table:

	id	name	cuisine	rating	city
▶	1	Spice Garden	Indian	4.5	Ahmedabad
	2	Pizza House	Italian	4.2	Surat
	3	Dragon Palace	Chinese	4.3	Rajkot
	4	Burger Point	American	4.1	Vadodra
	5	Sushi World	Japanese	4.7	Gandhinagar

The 'Output' pane at the bottom shows the execution log:

#	Time	Action	Message
✓	17 14:47:13	use instacore	0 row(s) affected
✓	18 14:47:13	CREATE TABLE Restaurants (id INT AUTO_INCREMENT PRIMARY KEY, name VARCHAR(100), cu...	0 row(s) affected
✓	19 14:47:13	select * from Restaurants LIMIT 0, 1000	0 row(s) returned
✓	20 14:49:57	use instacore	0 row(s) affected
✓	21 14:49:57	INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ('Spice Garden', 'Indian', 4.5, 'Ahmedabad'), (...	5 row(s) affected Records: 5 Duplicates: 0 Warnings: 0
✓	22 14:49:57	select * from Restaurants LIMIT 0, 1000	5 row(s) returned

SQL script saved to 'Z:\Top_Technology\Assignments\Assignment_4_sql\session_3\1_question.sql'