

INTENT: trunk_port
VENDOR: Cisco
OS: IOS-XE
VERSION: 17.15.01
FEATURE: vlan

DESCRIPTION

Configures an interface as a trunk port.

SUPPORTED PARAMETERS

Required:

interface (string)

Optional:

allowed_vlans (list)

native_vlan (integer)

PARAMETER DEFINITIONS

interface: Target switch interface.

allowed_vlans: List of VLANs permitted on the trunk.

native_vlan: Native VLAN for the trunk.

PAYLOAD CONTRACT

```
{  
  "operation": "trunk_port",  
  "payload": {  
    "interface": "",  
    "allowed_vlans": [10, 20],  
    "native_vlan": 10  
  }  
}
```

EXAMPLE INPUT

```
{  
  "intent_type": "trunk_port",  
  "parameters": {  
    "interface": "GigabitEthernet1/0/1",  
    "allowed_vlans": [10, 20],  
    "native_vlan": 10  
  }  
}
```

EXAMPLE OUTPUT

```
{  
  "operation": "trunk_port",  
  "payload": {  
    "interface": "GigabitEthernet1/0/1",  
    "allowed_vlans": [10, 20],  
    "native_vlan": 10  
  }  
}
```

RETRIEVAL KEYWORDS

trunk port switchport trunk allowed vlans native vlan

RAG METADATA

intent=trunk_port

vendor=Cisco

os=IOS-XE

version=17.15.01

feature=vlan