

DDM

2023-07-21

Lets start off making a function that simulates the weiner process:

```
set.seed(1111)

make_weiner = function(data){

  timesteps = data$max_time
  w0 = data$bias
  sd = data$sd

  bound = data$bound

  drift = data$drift
  #keeping track of position
  w = array(NA,timesteps+1)
  w[1] = 0

  for(i in 1:timesteps){
    if(w[i] > bound){
      w[i:(i+5)] = bound

      break
    }else if(w[i] < -bound){
      w[i:(i+5)] = -bound
      break
    }
    w[i+1] = w[i]+rnorm(1,0,sd)+drift
  }

  q = data.frame(x = 1:timesteps,
                y = w[1:timesteps],
                bound = bound,
                bias = bias,
                sd = sd,
                max_time = max_time,
                drift = drift,
                col = round(rnorm(1,100,1000),0)) #this is id
  q = q %>% mutate(resp = ifelse(y == bound, "upper", "lower"))

  return(list(q))
}
```

Next we then simulate 5 such process!

```

max_time = seq(500,length.out = 1)

bias = seq(0.5,length.out = 1)

sd = seq(0.1,length.out = 1)

bound = seq(1,2,length.out = 1)

drift = seq(0,length.out = 1)

replicate = 1:5

params = expand.grid(max_time = max_time,
                     bias = bias,
                     sd = sd,
                     bound = bound,
                     drift = drift,
                     replicate = replicate) %>%
  mutate(id = 1:nrow(.))

data_list <- split(params, params$id)

plan(multisession, workers = 3)
weiners = future_map(data_list, ~make_weiner(.x), .progress = TRUE, .options = furrr_options(seed = TRUE))

data = map_dfr(weiners,1)

q = na.omit(data) %>%
  ggplot(aes(x = x, y = y, color = as.factor(col)))+
  xlab("Time")+
  ylab("x")+
  coord_cartesian(ylim = c(min(na.omit(data)$y),max(na.omit(data)$y)))+
  geom_line(linewidth=1)+
  theme_classic()+
  geom_hline(yintercept = bound, linetype = 2)+
  geom_hline(yintercept = -bound, linetype = 2)+
  theme(legend.position="none")+
  theme(axis.title.x=element_blank(),
        axis.text.x=element_blank(),
        axis.ticks.x=element_blank())+
  #transition_time(x)+
  #shadow_wake(wake_length = 0.1, alpha = FALSE)+
  #shadow_mark(alpha = 0.3, size = 0.5)+
  transition_reveal(x)

q

```

```

## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?

```






































































































































































































































































































We can now play around with different drift rates and animate those!

```
max_time = seq(500,length.out = 1)

bias = seq(0.5,length.out = 1)

sd = seq(1,length.out = 1)

bound = seq(1,2,length.out = 1)

drift = seq(-1,1,length.out = 5)

replicate = 1:5

params = expand.grid(max_time = max_time,
                     bias = bias,
                     sd = sd,
                     bound = bound,
                     drift = drift,
                     replicate = replicate) %>%
  mutate(id = 1:nrow(.))

data_list <- split(params, params$id)

plan(multisession, workers = 3)
```

```

weiners = future_map(data_list, ~make_weiner(.x), .progress = TRUE, .options = furrr_options(seed = TRUE))

data = map_dfr(weiners, 1)

q = na.omit(data) %>%
  ggplot(aes(x = x, y = y, color = as.factor(col)))+
  xlab("Time")+
  ylab("x")+
  facet_wrap(~drift, nrow = 3, ncol = 2, labeller = label_both)+
  coord_cartesian(ylim = c(min(na.omit(data)$y), max(na.omit(data)$y)))+
  geom_line(linewidth=1)+
  theme_classic()+
  geom_hline(yintercept = bound, linetype = 2)+
  geom_hline(yintercept = -bound, linetype = 2)+
  theme(legend.position="none")+
  theme(axis.title.x=element_blank(),
        axis.text.x=element_blank(),
        axis.ticks.x=element_blank())+
  #transition_time(x)+
  #shadow_wake(wake_length = 0.1, alpha = FALSE)+
  #shadow_mark(alpha = 0.3, size = 0.5)+
  transition_reveal(x)


q


```

```


## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?
## 'geom_line()': Each group consists of only one observation.
## i Do you need to adjust the group aesthetic?


```








































































































































































































































































































Lastly we can look at the RT distribution for both lower and upper bound hits for different drift rates:

```
max_time = seq(500,length.out = 1)

bias = seq(0.5,length.out = 1)

sd = seq(1,length.out = 1)

bound = seq(1,2,length.out = 1)

drift = seq(-1,1,length.out = 5)

replicate = 1:100

params = expand.grid(max_time = max_time,
                    bias = bias,
                    sd = sd,
                    bound = bound,
                    drift = drift,
                    replicate = replicate) %>%
  mutate(id = 1:nrow(.))

data_list <- split(params, params$id)
```

```
plan(multisession, workers = 3)
weiners = future_map(data_list, ~make_weiner(.x), .progress = TRUE, .options = furrr_options(seed = TRUE))

data = map_dfr(weiners, 1)

data %>% na.omit(data) %>% group_by(col, drift) %>% summarize(last(resp))
```

```
## 'summarise()' has grouped output by 'col'. You can override using the '.groups'
## argument.
```

```
## # A tibble: 492 x 3
## # Groups:   col [462]
##   col drift 'last(resp)'
##   <dbl> <dbl> <chr>
## 1 -2728  -1   lower
## 2 -2359  -0.5 lower
## 3 -2218   0   lower
## 4 -2131  -1   lower
## 5 -2125  -0.5 lower
## 6 -2072   0.5 upper
## 7 -2059  -1   upper
## 8 -2010   0   lower
## 9 -2004  -0.5 upper
## 10 -1987   0   lower
## # i 482 more rows
```


```
qq = na.omit(data) %>% group_by(col, drift) %>% summarize(x = max(x), resp = last(resp)) %>% ungroup()
ggplot(aes(x = x)) +
  geom_histogram(aes(fill = resp, bins = 30), position = position_dodge()) +
  theme_classic() +
  facet_wrap(~drift, labeller = label_both)
```

```
## 'summarise()' has grouped output by 'col'. You can override using the '.groups'
## argument.
```

```
## Warning in geom_histogram(aes(fill = resp, bins = 30), position =
## position_dodge()): Ignoring unknown aesthetics: bins
```

```
qq
```

```
## 'stat_bin()' using 'bins = 30'. Pick better value with 'binwidth'.
```




```
df = data.frame()
for(d in drift){
  df = rbind(df,RWiener::rwiener(1000,alpha = bound,tau = 0.01, beta = bias, delta = d)%>% mutate(drift = d)
}
```

```
qq = na.omit(df) %>%
  mutate(upper = ifelse(resp == "upper", T,F)) %>%
  ggplot(aes(x = q)) +
  geom_histogram(aes(fill = upper,bins = 30), position = position_dodge())+
  theme_classic()+
  facet_wrap(~drift, labeller = label_both)
```

```
## Warning in geom_histogram(aes(fill = upper, bins = 30), position =
## position_dodge()): Ignoring unknown aesthetics: bins
```

```
qq
```

```
## 'stat_bin()' using 'bins = 30'. Pick better value with 'binwidth'.
```



There does seem to be a difference in how the RWeiner function uses the driftrate and how i use it? Why??