

2.5 Project: A miniature relational database with order

This project is due on Thursday Dec 5, 2019 at 4:30 PM.

Given ordered tables (array-tables) whose rows consist of strings (string constants are bracketed by single quotes) and integers, you are to write a program which will

- Perform the basic operations of relational algebra: selection, projection, join, group by, and count, sum and avg aggregates. The comparators for select and join will be $=$, $<$, $>$, \neq , \geq , \leq
- Because the array-tables are potentially ordered, you can sort an array-table by one or more columns, and running moving sums and average aggregates on a column of an array-table.
- Import a vertical bar delimited file into an array-table (in the same order), export from an array-table to a file preserving its order, and assign the result of a query to an array-table.
- Each operation will be on a single line. Each time you execute a line, you should print the time it took to execute.
- You will support in memory B-trees and hash structures. You are welcome to take those implementations from wherever you can find them, but you must say where.
- Your program should be written in python or java. You will hand in clean and well structured source code in which each function has a header that says (i) what the function does, (ii) what its inputs are and what they mean (iii) what the outputs are and mean (iv) any side effects to globals.
- You must ensure that your software runs on the Courant Institute (cims) machine `crunchy5.cims.nyu.edu`
- You may NOT use any relational algebra or SQL library or system (e.g. no SQLite, no MySQL, no other relational database system, no Pandas). Stick pretty much to the standard stuff (e.g. in Python: numpy, core language features, string manipulation, random number generators, and data structure support for in memory B-trees and hash structures). You may not use anyone else's code (other than for the

B-tree or Hash structure implementation). Doing so will constitute plagiarism.

Your program should take operations from standard input. We will run your programs on test cases of our choosing. For ease of parsing there will be one operation per line. Comments begin with `//` and go to the end of the line. For example,

```
R := inputfromfile(sales1) // import vertical bar delimited foo, first line
    // has column headers.
    // Suppose they are saleid|itemid|customerid|storeid|time|qty|pricerange
    // In general there can be more or fewer columns than this.
R1 := select(R, (time > 50) or (qty < 30))
    // select * from R where time > 50 or qty < 30
R2 := project(R1, saleid, qty, pricerange) // select saleid, qty, pricerange
    // from R1
R3 := avg(R1, qty) // select avg(qty) from R1
R4 := sumgroup(R1, time, qty) // select sum(time), qty from R1 group by qty
R5 := sumgroup(R1, qty, time, pricerange) // select sum(qty), time,
    // pricerange from R1 group by time, pricerange
R6 := avggroup(R1, qty, pricerange) // select avg(qty), pricerange
    // from R1 group by by pricerange
S := inputfromfile(sales2) // suppose column headers are
    // saleid|I|C|S|T|Q|P
T := join(R, S, R.customerid = S.C) // select * from R, S
    // where R.customerid = S.C
T1 := join(R1, S, (R1.qty > S.Q) and (R1.saleid = S.saleid)) // select * from R1, S w
T2 := sort(T1, S_C) // sort T1 by S_C
T2prime := sort(T1, R1_time, S_C) // sort T1 by R1_time, S_C (in that order)
T3 := movavg(T2prime, R1_qty, 3) // perform the three item moving average of T2prime
    // on column R_qty. This will be as long as R_qty with the three way
    // moving average of 4 8 9 7 being 4 6 7 8
T4 := movsum(T2prime, R1_qty, 5) // perform the five item moving sum of T2prime
    // on column R_qty
Q1 := select(R, qty = 5) // select * from R where qty=5
Btree(R, qty) // create an index on R based on column qty
    // Equality selections and joins on R should use the index.
    // All indexes will be on one column (both Btree and Hash)
Q2 := select(R, qty = 5) // this should use the index
```

```

Q3 := select(R, itemid = 7) // select * from R where itemid = 7
Hash(R,itemid)
Q4 := select(R, itemid = 7) // this should use the hash index
Q5 := concat(Q4, Q2) // concatenate the two tables (must have the same schema)
    // Duplicate rows may result (though not with this example).
outputtofile(Q5, Q5) // This should output the table Q5 into a file
    // with the same name and with vertical bar separators
outputtofile(T, T) // This should output the table T

```

Our tests may operate on different files with different column headers.
Our queries may use different parameter values (e.g. 14 way moving average).
Our joins may be on different fields.

Some constraints to make your life easier:

- There will be no syntax errors in our tests. However, white space may vary in the operations, e.g. `select(R, itemid = 7)`, `select(R, itemid = 7)`, `select(R,itemid=7)`, and `select(R ,itemid = 7)` all should be interpreted in the same way.
- The only aggregates are count, sum, and avg and the corresponding `countgroup`, `sumgroup`, and `avggroup`.
- The only moving aggregates are `movsum` and `movavg`. There is no group by for moving sums and averages.
- All data is in main memory.
- Within select there may be several conditions but only all ands or all ors.
- Within join there may be several conditions but only all ands.
- A join condition can be
`table.attribute [arithop constant] relop table.attribute [arithop constant]`
- A select condition can be
`attribute [arithop constant] relop constant`
or
`constant relop attribute [arithop constant]`

- If there are multiple conditions, each condition will be surrounded by parentheses.
- relop is =, !=, >, >=, <, <=
arithop is +, -, *, /
- If R is (A,B,C) and S is (B,C,D,E) then
the result of the join will have A, R_B, R_C, S_B, S_C, D, E
as column names.
You have the option to use the _ notation for every column, so
the result of the above join could be:
R_A, R_B, R_C, S_B, S_C, S_D, S_E
- All numbers should be interpreted as floating point. So $5/2 = 2.5$
- project syntax: project(TABLENAME, listofatts) listofatts is just a
comma-separated list of attributes. e.g. $R2 := \text{project}(R1, \text{saleid}, \text{qty}, \text{pricerange})$
- sum and avg take a table and a single attribute e.g. $R3 := \text{avg}(R1, \text{qty})$ // select avg(qty) from R1
- sumgroup, avggroup, countgroup take a table, a single attribute and
a list of attributes and perform the aggregate on the single attribute
grouped by the other attributes, All these primitives should be as-
sumed to execute on a multiset (i.e. duplicates are NOT removed).
e.g. $R5 := \text{sumgroup}(R1, \text{qty}, \text{time}, \text{pricerange})$ // select sum(qty),
time, // pricerange from R1 group by time, pricerange
- sort takes a table and one or more attributes and sorts by those at-
tributes in order, e.g. $T2\text{prime} := \text{sort}(T1, R1.\text{time}, S_C)$ // sort T1
by R1_time, S_C (in that order)
- movavg and movsum take a table, an, attribute and a constant k
and does the k-way moving aggregate of that attribute, e.g. $T3 := \text{movavg}(T2\text{prime}, R1.\text{qty}, 3)$ // perform the three item moving average
of T2prime
- concat takes two tables with the same schema and concatenates each
column in order e.g. $Q5 := \text{concat}(Q4, Q2)$ // concatenate the two
tables (must have the same schema)

- `count(TABNAME)` // count the number of rows in the table even if duplicate rows

Here is an example of the first few lines of the sales1 file:

```
saleid|itemid|customerid|storeid|time|qty|pricerange
45|133|2|63|49|23|outrageous
658|75|2|89|46|43|outrageous
149|103|2|23|67|2|cheap
398|82|2|41|3|27|outrageous
147|81|2|4|92|11|outrageous
778|75|160|72|67|17|supercheap
829|112|2|70|63|43|supercheap
101|105|2|9|74|28|expensive
940|62|2|90|67|39|outrageous
864|119|12|38|67|49|outrageous
288|46|2|95|67|26|outrageous
875|83|59|56|59|20|outrageous
783|86|180|29|67|46|outrageous
289|16|2|95|92|2|cheap
```

Full example files can be found here:

```
http://cs.nyu.edu/cs/faculty/shasha/papers/sales1
http://cs.nyu.edu/cs/faculty/shasha/papers/sales2
```

You will hand in your code using Reprozip inside a Docker Virtual Machine so that it is reproducible across platforms.