Nanophotonic Computational Design

Jesse Lu

February 25, 2013

Goal: Show you how to design *any* linear nanophotonic device



Goal: Show you how to design *any* linear nanophotonic device



- Device properties:
  - Full 3D
  - Compact
  - Efficient
  - Multi-mode
  - Multi-functional

- Developed by
  - applying (convex) optimization techniques (math)
  - to the area of nanophotonics (physics)
  - and implementing in software (programming)

- Developed by
  - applying (convex) optimization techniques (math)
  - to the area of nanophotonics (physics)
  - and implementing in software (programming)

- Physics Advisory:

  CONTAINS INVOLVED MATHEMATICAL CONTENT

- Developed by
  - applying (convex) optimization techniques (math)
  - to the area of nanophotonics (physics)
  - and implementing in software (programming)

- Physics Advisory:

  CONTAINS INVOLVED MATHEMATICAL CONTENT

- Math Advisory:

  CONTAINS INVOLVED NANOPHOTONIC CONTENT

Given a field, can we find its structure?



Given a field, can we find its structure?



- Equivalently, find ϵ (structure) given E (field)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$

Given a field, can we find its structure?



- Equivalently, find ϵ (structure) given E (field)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$

- If possible, we can design *any* nanophotonic/optical component!

- Answer: Yes, given E we *can* solve for ϵ (trivial!)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$

- Answer: Yes, given E we *can* solve for ϵ (trivial!)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$

$$\omega^2 \epsilon E = \nabla \times \mu_0^{-1} \nabla \times E + i\omega J$$

- Answer: Yes, given E we *can* solve for ϵ (trivial!)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$

$$\omega^2 \epsilon E = \nabla \times \mu_0^{-1} \nabla \times E + i\omega J$$

$$\omega^2 E \epsilon = \nabla \times \mu_0^{-1} \nabla \times E + i\omega J$$

- Answer: Yes, given E we *can* solve for ϵ (trivial!)

$$\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J$$
$$\omega^2 \epsilon E = \nabla \times \mu_0^{-1} \nabla \times E + i\omega J$$
$$\omega^2 E \epsilon = \nabla \times \mu_0^{-1} \nabla \times E + i\omega J$$
$$\epsilon = (\nabla \times \mu_0^{-1} \nabla \times E + i\omega J)/\omega^2 E$$

- Solving for ϵ actually way faster than simulation (solving for E)!

- Obvious and well-known from a mathematical perspective
  - Pre-requisite (200-level) class in optimization curriculum
  - Not yet taught (I think) in optics/photonics at Stanford

- Obvious and well-known from a mathematical perspective
  - Pre-requisite (200-level) class in optimization curriculum
  - Not yet taught (I think) in optics/photonics at Stanford

$$\underbrace{\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J}_{\text{physics}} \quad \longrightarrow \quad \underbrace{A(z)x = b}_{\text{linear algebra}}$$

- Obvious and well-known from a mathematical perspective
  - Pre-requisite (200-level) class in optimization curriculum
  - Not yet taught (I think) in optics/photonics at Stanford

$$\underbrace{\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J}_{\text{physics}} \quad \longrightarrow \quad \underbrace{A(z)x = b}_{\text{linear algebra}}$$

$$E \rightarrow x$$

$$\epsilon \rightarrow z$$

$$\nabla \times \mu_0^{-1} \nabla \times -\omega^2 \epsilon \rightarrow A(z)$$

$$-i\omega J \rightarrow b$$

- Obvious and well-known from a mathematical perspective
  - Pre-requisite (200-level) class in optimization curriculum
  - Not yet taught (I think) in optics/photonics at Stanford

$$\underbrace{\nabla \times \mu_0^{-1} \nabla \times E - \omega^2 \epsilon E = -i\omega J}_{\text{physics}} \quad \longrightarrow \quad \underbrace{A(z)x = b}_{\text{linear algebra}}$$

$$E \to x$$

$$\epsilon \to z$$

$$\nabla \times \mu_0^{-1} \nabla \times -\omega^2 \epsilon \to A(z)$$

$$-i\omega J \to b$$

- Key: If $A(z)$ is linear in z then $A(z)x = b$ is as well!

Direct design of structure in 1D

- Chose x (field) and solved for z (structure)



Direct design of structure in 1D

- Chose x (field) and solved for z (structure)



- Perfect performance but unmanufacturable structure


$\eta = 10^{-8}$
actual field
target field
0.5
0
-0.5
magnetic field H (a.u.)
permittivity (ϵ)
10
1
$\eta = 10^{-6}$
0.5
0
-0.5
10
1

- Regularization on z decreases performance

- We know that there exist x which produce well-behaved z
- However, choosing such x is next to impossible
- Therefore, a practical design tool must include x-search

Iterative design of structure in 1D

-
- Insight: Solving for well-behaved z requires fortuitous selection of x
- Therefore, vary x in order to allow for well-behaved z



- Variation in x allows z to be better behaved

- Alternately solve for x and z:

$$\underset{z}{\text{minimize}} \quad \|A(z)x - b\|^2 + \eta_1 \|z - z_0\|^2$$

$$\underset{x}{\text{minimize}} \quad \|A(z)x - b\|^2 + \eta_0 \|x - x_0\|^2$$