

# Title of Qualification Exam Talk

J. S. Rehak



Qualification Exam  
September 4<sup>th</sup>, 2019

2019-08-21

Qualification Exam

Title of Qualification Exam Talk

J. S. Rehak



Qualification Exam  
September 4<sup>th</sup>, 2019

Outline

① Motivation

② Background

③ Acceleration Methods

④ BART

# Motivation

2019-08-21

Qualification Exam  
└ Motivation

Motivation

## Background

2019-08-21

Qualification Exam  
└─ BACKGROUND

Background

# Steady-state Boltzman Transport Equation

Our problem of interest is the time-independent transport equation for a critical system on a domain of interest  $\mathbf{r} \in V$  [2],

$$\begin{aligned} & \left[ \hat{\Omega} \cdot \nabla + \Sigma_t(\mathbf{r}, E) \right] \psi(\mathbf{r}, E, \hat{\Omega}) \\ &= \int_0^\infty dE' \int_{4\pi} d\hat{\Omega}' \Sigma_s(\mathbf{r}, E' \rightarrow E, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi(\mathbf{r}, E', \hat{\Omega}') \\ &+ Q(\mathbf{r}, E, \hat{\Omega}) , \end{aligned}$$

with a given boundary condition,

$$\psi(\mathbf{r}, E, \hat{\Omega}) = \Gamma(\mathbf{r}, E, \hat{\Omega}), \quad \mathbf{r} \in \partial V, \quad \hat{\Omega} \cdot \hat{n} < 0$$

2019-08-21

## Qualification Exam

### BACKGROUND

### Steady-state Boltzman Transport Equation

#### Steady-state Boltzman Transport Equation

Our problem of interest is the time-independent transport equation for a critical system on a domain of interest  $\mathbf{r} \in V$  [2].

$$\begin{aligned} & \left[ \hat{\Omega} \cdot \nabla + \Sigma_t(\mathbf{r}, E) \right] \psi(\mathbf{r}, E, \hat{\Omega}) \\ &= \int_0^\infty dE' \int_{4\pi} d\hat{\Omega}' \Sigma_s(\mathbf{r}, E' \rightarrow E, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi(\mathbf{r}, E', \hat{\Omega}') \\ &+ Q(\mathbf{r}, E, \hat{\Omega}) , \end{aligned}$$

with a given boundary condition,

$$\psi(\mathbf{r}, E, \hat{\Omega}) = \Gamma(\mathbf{r}, E, \hat{\Omega}), \quad \mathbf{r} \in \partial V, \quad \hat{\Omega} \cdot \hat{n} < 0$$

# The multigroup $S_N$ equations

Apply the following discretizations:

- Apply a Petrov-Galerkin scheme in energy (multigroup method), splitting into  $G$  coupled equations.
- Apply a collocation scheme in angle, solving at angles  $\hat{\Omega}_a$ .
- Expanding scattering cross-section in Legendre Polynomials with a maximum degree  $N$  (the  $P_N$  method).

$$\Sigma_{s,g',g,\ell} = \int_{-1}^1 \Sigma_{s,g',g}(\mathbf{r}, \mu) P_\ell(\mu) d\mu, \quad \mu = \hat{\Omega}' \cdot \hat{\Omega}$$

$$\phi_{g,\ell,m} = \int_{4\pi} \phi_g(\mathbf{r}, \hat{\Omega}') Y_{\ell,m}(\hat{\Omega}') d\hat{\Omega}'$$

## Multigroup $S_N$ equations

$$\left[ \hat{\Omega}_a \cdot \nabla + \Sigma_{t,g}(\mathbf{r}) \right] \psi_g(\mathbf{r}, \hat{\Omega}_a)$$

$\underbrace{\quad}_G \quad \underbrace{\quad}_N \quad \underbrace{\quad}_\ell$

2019-08-21

## Qualification Exam

### BACKGROUND

### — The multigroup $S_N$ equations

- Multigroup method splits the equations into  $G$  coupled equations
- Collocation scheme in angle uses points for a quadrature rule for integrating angular flux to get flux moments
- Expand in Legendre polynomials, use polynomial addition theorem,

#### The multigroup $S_N$ equations

Apply the following discretizations:

- Apply a Petrov-Galerkin scheme in energy (multigroup method), splitting into  $G$  coupled equations.
- Apply a collocation scheme in angle, solving at angles  $\hat{\Omega}_a$ .
- Expanding scattering cross-section in Legendre Polynomials with a maximum degree  $N$  (the  $P_N$  method).

$$\Sigma_{s,g',g,\ell} = \int_{-1}^1 \Sigma_{s,g',g}(\mathbf{r}, \mu) P_\ell(\mu) d\mu, \quad \mu = \hat{\Omega}' \cdot \hat{\Omega}$$

$$\phi_{g,\ell,m} = \int_{4\pi} \phi_g(\mathbf{r}, \hat{\Omega}') Y_{\ell,m}(\hat{\Omega}') d\hat{\Omega}'$$

#### Multigroup $S_N$ equations

$$\left[ \hat{\Omega}_a \cdot \nabla + \Sigma_{t,g}(\mathbf{r}) \right] \psi_g(\mathbf{r}, \hat{\Omega}_a)$$

$$= \sum_{\ell=0}^N \sum_{m=-\ell}^{\ell} \Sigma_{t,g,\ell}(\mathbf{r}) Y_{\ell,m}(\hat{\Omega}_a) \psi_{g,\ell,m}(\mathbf{r})$$

# Iterative Solving Methods

Expressed in operator form, this is

$$\mathbf{L}_g \Psi_g = \mathbf{M} \sum_{g'=0}^G \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{Q}_g, \quad \Phi_g = \mathbf{D} \Psi_g .$$

Splitting the scattering source into down-scattering and up-scattering terms,

$$\mathbf{L}_g \Psi_g = \mathbf{M} \sum_{g'=0}^g \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{M} \sum_{g'=g+1}^G \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{Q}_g ,$$

And holding the source  $\mathbf{Q}$  fixed leads to a Gauss-Seidel (scattering) source iteration,

$$\mathbf{L}_g \Psi_g^{k+1} = \mathbf{M} \sum_{g'=0}^g \mathbf{S}_{g'g} \Phi_{g'}^{k+1} + \mathbf{M} \sum_{g'=g+1}^G \mathbf{S}_{g'g} \Phi_{g'}^k + \mathbf{Q}_g .$$

2019-08-21

## Qualification Exam └ BACKGROUND

### └ Iterative Solving Methods

- M is the moment-to-discrete, D is the reverse
- Important to note that the  $G$ -th energy group is the lowest.

#### Iterative Solving Methods

Expressed in operator form, this is

$$\mathbf{L}_g \Phi_g = \mathbf{M} \sum_{g'=0}^G \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{Q}_g, \quad \Phi_g = \mathbf{D} \Psi_g .$$

Splitting the scattering source into down-scattering and up-scattering terms,

$$\mathbf{L}_g \Phi_g = \mathbf{M} \sum_{g'=0}^g \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{M} \sum_{g'=g+1}^G \mathbf{S}_{g'g} \Phi_{g'} + \mathbf{Q}_g .$$

And holding the source  $\mathbf{Q}$  fixed leads to a Gauss-Seidel (scattering) source iteration,

$$\mathbf{L}_g \Phi_g^{k+1} = \mathbf{M} \sum_{g'=0}^g \mathbf{S}_{g'g} \Phi_{g'}^{k+1} + \mathbf{M} \sum_{g'=g+1}^G \mathbf{S}_{g'g} \Phi_{g'}^k + \mathbf{Q}_g .$$

# Iterative Solving Methods

For a multiplying-medium problem, the fixed source  $\mathbf{Q}$  is replaced with the fission source,

$$\mathbf{L}_g \boldsymbol{\Psi}_g = \mathbf{M} \sum_{g'=0}^G \left[ \mathbf{S}_{g'g} \boldsymbol{\Phi}_{g'} + \frac{1}{k} \mathbf{F}_{g'} \boldsymbol{\Phi}_{g'} \right] .$$

Holding the scattering source fixed leads to power iteration (fission source iteration),

$$\mathbf{L}_g \boldsymbol{\Psi}_g^{k+1} = \mathbf{M} \sum_{g'=0}^G \left[ \mathbf{S}_{g'g} \boldsymbol{\Phi}_{g'}^0 + \frac{1}{k} \mathbf{F}_{g'} \boldsymbol{\Phi}_{g'}^k \right] .$$

2019-08-21

## Qualification Exam └ BACKGROUND

### └ Iterative Solving Methods

#### Iterative Solving Methods

For a multiplying-medium problem, the fixed source  $\mathbf{Q}$  is replaced with the fission source,

$$\mathbf{L}_g \boldsymbol{\Psi}_g = \mathbf{M} \sum_{g'=0}^G \left[ \mathbf{S}_{g'g} \boldsymbol{\Phi}_{g'} + \frac{1}{k} \mathbf{F}_{g'} \boldsymbol{\Phi}_{g'} \right] .$$

Holding the scattering source fixed leads to power iteration (fission source iteration),

$$\mathbf{L}_g \boldsymbol{\Psi}_g^{k+1} = \mathbf{M} \sum_{g'=0}^G \left[ \mathbf{S}_{g'g} \boldsymbol{\Phi}_{g'}^0 + \frac{1}{k} \mathbf{F}_{g'} \boldsymbol{\Phi}_{g'}^k \right] .$$



## Fourier analysis

To see how the error in our iterative schemes evolves, we can use Fourier analysis [1]. To do so, we use a one-group, one dimension, infinite homogeneous medium with isotropic scattering.

$$\mu \frac{\partial}{\partial x} \psi(x, \mu) + \Sigma_t \psi(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 \psi(x, \mu') d\mu' + \frac{Q}{2}.$$

We define the source iteration scheme as discussed above,

$$\mu \frac{\partial}{\partial x} \psi^{k+1}(x, \mu) + \Sigma_t \psi^{k+1}(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 \psi^k(x, \mu') d\mu' + \frac{Q}{2}.$$

and subtract the two to get an equation for the error in iteration  $k$ , giving us a similar equation for the error in iteration  $k+1$  as it relates to the error in iteration  $k$ ,

$$\mu \frac{\partial}{\partial x} e^{k+1}(x, \mu) + \Sigma_t e^{k+1}(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 e^k(x, \mu') d\mu'.$$

2019-08-21

## Qualification Exam

### BACKGROUND

### Fourier analysis

#### Fourier analysis

To see how the error in our iterative schemes evolves, we can use Fourier analysis [1]. To do so, we use a one-group, one dimension, infinite homogeneous medium with isotropic scattering.

$$\mu \frac{\partial}{\partial x} \psi(x, \mu) + \Sigma_t \psi(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 \psi(x, \mu') d\mu' + \frac{Q}{2}.$$

We define the source iteration scheme as discussed above,

$$\mu \frac{\partial}{\partial x} \psi^{k+1}(x, \mu) + \Sigma_t \psi^{k+1}(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 \psi^k(x, \mu') d\mu' + \frac{Q}{2}.$$

and subtract the two to get an equation for the error in iteration  $k$ , giving us a similar equation for the error in iteration  $k+1$  as it relates to the error in iteration  $k$ ,

$$\mu \frac{\partial}{\partial x} e^{k+1}(x, \mu) + \Sigma_t e^{k+1}(x, \mu) = \frac{\Sigma_s}{2} \int_{-1}^1 e^k(x, \mu') d\mu'.$$

- How can we be sure that source iteration will converge? What controls the convergence rate? To determine this we can use a Fourier analysis.
- We need to start with a lot of assumptions to get a very simplified version of our transport equation.
- We define what we mean by error, and get an equation that relates the error in each step to the previous step. Unsurprisingly it looks like our original equation, because the evolution of the solution and the evolution of the error are related.

# Fourier Analysis

To perform an inverse Fourier transform, we need to choose a measure of spatial variation, an error “wavelength.”

$$\lambda = \frac{\ell}{n}, \quad \forall n \in \mathbb{R} \implies \tilde{\nu} = \frac{1}{\lambda} = \frac{n}{\ell} = n \cdot \Sigma_t$$

Perform an inverse Fourier transform,

$$e^k(x, \mu) = \int_{-\infty}^{\infty} \hat{e}^k(n, \mu) e^{i \Sigma_t n x} dn.$$

After plugging into our equation for error and some rearranging,

$$\int_{-1}^1 \hat{e}^{k+1}(n, \mu) d\mu = \Lambda(n) \int_{-1}^1 \hat{e}^k(n, \mu') d\mu',$$

Where

$$\Lambda(n) = \frac{\Sigma_s}{\Sigma_t} \cdot \frac{\tan^{-1}(n)}{n}.$$

2019-08-21

## Qualification Exam └ BACKGROUND

### └ Fourier Analysis

#### Fourier Analysis

To perform an inverse Fourier transform, we need to choose a measure of spatial variation, an error “wavelength.”

$$\lambda = \frac{\ell}{n}, \quad \forall n \in \mathbb{R} \implies \tilde{\nu} = \frac{1}{\lambda} = \frac{n}{\ell} = n \cdot \Sigma_t$$

Perform an inverse Fourier transform,

$$e^k(x, \mu) = \int_{-\infty}^{\infty} \hat{e}^k(n, \mu) e^{i \Sigma_t n x} dn.$$

After plugging into our equation for error and some rearranging,

$$\int_{-1}^1 \hat{e}^{k+1}(n, \mu) d\mu = \Lambda(n) \int_{-1}^1 \hat{e}^k(n, \mu') d\mu',$$

Where

$$\Lambda(n) = \frac{\Sigma_s}{\Sigma_t} \cdot \frac{\tan^{-1}(n)}{n}.$$

- We can examine the modes of the spatial error by using an inverse fourier transform. This will give us an idea of how the spatial frequencies of the error. We need to decide on an error wavelength, which gives us a linear error frequency. Higher  $n$  means higher error frequency, with  $n = 0$  being infinite wavelength, completely non-coupled error.
- If we plug this back into our previous equation and do a large amount of manipulation, we get a fairly simple relationship between the integrated error in one step to the integrated error in the previous step.
- This lambda function is maximized when  $n = 0$ . The lowest frequency error converges the slowest, and at a rate proportional to  $\Sigma_s/\Sigma_t$ .

2019-08-21

Qualification Exam  
└ Acceleration Methods

Acceleration Methods

# Acceleration Methods

# Nonlinear Diffusion Acceleration (NDA)

Start, with the single-group first-order transport equation [3], and integrate over angle:

$$\nabla \cdot J_g + (\Sigma_{t,g} - \Sigma_s^{g \rightarrow g}) \phi_g = \sum_{g' \neq g} \Sigma_s^{g' \rightarrow g} \phi_{g'} + q_g, \quad J_g \equiv \int d\hat{\Omega} \hat{\Omega} \psi_g(\hat{\Omega}).$$

As a closure to this problem, it is common to define current using *Fick's law*,

$$J_g = -D \nabla \phi_g.$$

Construct an additive correction to the current using information from an angular solve:

$$\begin{aligned} J_g &= -D \nabla \phi_g + J_g^{\text{ang}} - J_g^{\text{ang}} \\ &= -D \nabla \phi_g + \int_{4\pi} d\hat{\Omega} \hat{\Omega} \psi_g + D \nabla \phi_g \end{aligned}$$

2019-08-21

## Qualification Exam

### Acceleration Methods

### Nonlinear Diffusion Acceleration (NDA)

#### Nonlinear Diffusion Acceleration (NDA)

Start, with the single-group first-order transport equation [3], and integrate over angle:

$$\nabla \cdot J_g + (\Sigma_{t,g} - \Sigma_s^{g \rightarrow g}) \phi_g = \sum_{g' \neq g} \Sigma_s^{g' \rightarrow g} \phi_{g'} + q_g, \quad J_g \equiv \int d\hat{\Omega} \hat{\Omega} \psi_g(\hat{\Omega}).$$

As a closure to this problem, it is common to define current using *Fick's law*.

$$J_g = -D \nabla \phi_g.$$

Construct an additive correction to the current using information from an angular solve:

$$\begin{aligned} J_g &= -D \nabla \phi_g + J_g^{\text{ang}} - J_g^{\text{ang}} \\ &= -D \nabla \phi_g + \int_{4\pi} d\hat{\Omega} \hat{\Omega} \psi_g + D \nabla \phi_g \end{aligned}$$

- Uses a lower order diffusion solve to accelerate a higher order solve.
- Start with the same single-group first-order transport equation, multiply by and integrate over angle, giving the “neutron continuity equation.”
- We need closure for this problem, so often we use Fick's law, we will introduce a correction onto Fick's Law based on a higher order solve.
- We will introduce an additive correction based on our two definitions of the current.

# Nonlinear Diffusion Acceleration (NDA)

Fold the additive correction into a *drift-diffusion vector*:

$$\begin{aligned} J_g &= -D\nabla\phi_g + \int_{4\pi} d\hat{\Omega}\hat{\Omega}\psi_g + D\nabla\phi_g \\ &= -D\nabla\phi_g + \left[ \frac{\int_{4\pi} d\hat{\Omega}\hat{\Omega}\psi_g + D\nabla\phi_g}{\phi_g} \right] \phi_g \\ &= -D\nabla\phi_g + \hat{D}_g\phi_g . \end{aligned}$$

Plugging this into our integrated transport equation gives the low-order non-linear diffusion acceleration equation (LONDA),

$$\nabla \cdot \left[ -D\nabla + \hat{D}_g \right] \phi_g + (\Sigma_{t,g} - \Sigma_s^{g \rightarrow g}) \phi_g = \sum_{g' \neq g} \Sigma_s^{g' \rightarrow g} \phi_{g'} + q_g$$

2019-08-21

## Qualification Exam └ Acceleration Methods

### └ Nonlinear Diffusion Acceleration (NDA)

#### Nonlinear Diffusion Acceleration (NDA)

Fold the additive correction into a drift-diffusion vector:


$$\begin{aligned} J_g &= -D\nabla\phi_g + \int_{4\pi} d\hat{\Omega}\hat{\Omega}\psi_g + D\nabla\phi_g \\ &= -D\nabla\phi_g + \left[ \frac{\int_{4\pi} d\hat{\Omega}\hat{\Omega}\psi_g + D\nabla\phi_g}{\phi_g} \right] \phi_g \\ &= -D\nabla\phi_g + \hat{D}_g\phi_g . \end{aligned}$$

Plugging this into our integrated transport equation gives the low-order non-linear diffusion acceleration equation (LONDA).

$$\nabla \cdot \left[ -D\nabla + \hat{D}_g \right] \phi_g + (\Sigma_{t,g} - \Sigma_s^{g \rightarrow g}) \phi_g = \sum_{g' \neq g} \Sigma_s^{g' \rightarrow g} \phi_{g'} + q_g$$

- We combine these corrections into a drift diffusion vector.
- This gives us the LONDA equation, which is just the same integrated transport equation with a corrected current term.
- Presumably, the “higher order” angular solve will have better current information, so we can use it to calculate the drift diffusion vector.

# NDA algorithm



2019-08-21

## Qualification Exam

### Acceleration Methods

#### NDA algorithm

NDA algorithm




Figure 1: NDA Algorithm

- NDA algorithm showing inner low order loop, and outer high order loop.
- In general, outer loop updates both scattering and fission source, checking for  $k$  convergence. Inner loop updates fission source, also checking  $k$  convergence.

# Two-grid acceleration

2019-08-21

Qualification Exam

└ Acceleration Methods

└└ Two-grid acceleration

Two-grid acceleration

**BART**

2019-08-21

Qualification Exam  
└ BART

BART



## Transport equation second-order forms

Consider the mono-energetic form of the transport equation, using the scattering operator  $S\psi(\mathbf{r}, \hat{\Omega}) = \int_{4\pi} d\hat{\Omega}' \Sigma_s(\mathbf{r}, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi(\mathbf{r}, \hat{\Omega}')$ :

$$\left[ \hat{\Omega} \cdot \nabla + \Sigma_t(\mathbf{r}) \right] \psi(\mathbf{r}, \hat{\Omega}) = S\psi(\mathbf{r}, \hat{\Omega}) + Q \quad (1)$$

Substitute  $-\hat{\Omega}$  for  $\hat{\Omega}$ , add to Eq. (1), and divide by two to get a function of even- and odd-parity angular fluxes.

$$\hat{\Omega} \cdot \nabla \psi^- + \Sigma_t \psi^+ = S^+ \psi^+ + Q^+$$

where,

$$\begin{aligned} \psi^+ &= \frac{1}{2} \left( \psi(\hat{\Omega}) + \psi(-\hat{\Omega}) \right) \\ \psi^- &= \frac{1}{2} \left( \psi(\hat{\Omega}) - \psi(-\hat{\Omega}) \right) \end{aligned}$$

2019-08-21

## Qualification Exam

└ BART

└ Transport equation second-order forms

### Transport equation second-order forms

Consider the mono-energetic form of the transport equation, using the scattering operator  $S\psi(\mathbf{r}, \hat{\Omega}) = \int_{4\pi} d\hat{\Omega}' \Sigma_s(\mathbf{r}, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi(\mathbf{r}, \hat{\Omega}')$ .

$$\left[ \hat{\Omega} \cdot \nabla + \Sigma_t(\mathbf{r}) \right] \psi(\mathbf{r}, \hat{\Omega}) = S\psi(\mathbf{r}, \hat{\Omega}) + Q \quad (1)$$

Substitute  $-\hat{\Omega}$  for  $\hat{\Omega}$ , add to Eq. (1), and divide by two to get a function of even- and odd-parity angular fluxes.

$$\hat{\Omega} \cdot \nabla \psi^- + \Sigma_t \psi^+ = S^+ \psi^+ + Q^+$$

where,

$$\psi^+ = \frac{1}{2} \left( \psi(\hat{\Omega}) + \psi(-\hat{\Omega}) \right)$$

$$\psi^- = \frac{1}{2} \left( \psi(\hat{\Omega}) - \psi(-\hat{\Omega}) \right)$$

# Self-adjoint angular flux equation (SAAF)

Start with the single-group first-order transport equation [4]:

$$\hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q. \quad (2)$$

Solve for  $\psi$ ,

$$\psi = \frac{1}{\Sigma_t} \left[ S\psi + q - \hat{\Omega} \cdot \nabla \psi \right],$$

and plug back into the gradient term in Eq.2.

$$-\hat{\Omega} \cdot \nabla \frac{1}{\Sigma_t} \hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q - \hat{\Omega} \cdot \nabla \frac{S\psi + q}{4\pi}$$

With boundary conditions, for all  $\mathbf{r} \in \partial D$ :

$$\psi = f, \quad \hat{\Omega} \cdot \hat{n} < 0$$

$$\hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q, \quad \hat{\Omega} \cdot \hat{n} > 0$$

2019-08-21

$$\hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q. \quad (2)$$

Solve for  $\psi$ ,

$$\psi = \frac{1}{\Sigma_t} \left[ S\psi + q - \hat{\Omega} \cdot \nabla \psi \right],$$

and plug back into the gradient term in Eq.2.

$$-\hat{\Omega} \cdot \nabla \frac{1}{\Sigma_t} \hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q - \hat{\Omega} \cdot \nabla \frac{S\psi + q}{4\pi}$$

With boundary conditions, for all  $\mathbf{r} \in \partial D$ :

$$\psi = f, \quad \hat{\Omega} \cdot \hat{n} < 0$$

$$\hat{\Omega} \cdot \nabla \psi + \Sigma_t \psi = S\psi + q, \quad \hat{\Omega} \cdot \hat{n} > 0$$

The Self-adjoint angular flux equation (SAAF) is a second-order form of the transport equation introduced by Morel and McGhee in 1999. To derive, consider scattering term part of the source. Properties of SAAF

- +Can solve using standard CFEM methods, which give SPD matrices (can use CG instead of GMRES)
- +Full angular flux is obtained by solve (unlike Even/Odd parity)
- +BCs only coupled in one direction when reflective
- -General sparse matrix, not block lower-triangular (no sweeping)
- -Pure scattering causes issues like odd-parity

# References

[1] Marvin L. Adams and Edward W. Larsen.  
Fast iterative methods for discrete-ordinates particle transport calculations.  
*Progress in Nuclear Energy*, 2002.

[2] E. E. Lewis and W.F. Miller, Jr.  
*Computational Methods of Neutron Transport*.  
American Nuclear Society, 1993.

[3] Hans R Hammer, Jim E. Morel, and Yaqi Wang.  
Nonlinear Diffusion Acceleration in Voids for the Weighted Least-Square Transport Equation.  
In *Mathematics and Computation*2, 2017.

[4] J E Morel and J M Mcghee.  
A Self-Adjoint Angular Flux Equation.  
*Nuclear Science and Engineering*, 132:312–325, 1999.

2019-08-21

Qualification Exam  
└ BART

└ References

## References

[1] Marvin L. Adams and Edward W. Larsen.  
Fast iterative methods for discrete-ordinates particle transport calculations.  
*Progress in Nuclear Energy*, 2002.

[2] E. E. Lewis and W.F. Miller, Jr.  
*Computational Methods of Neutron Transport*.  
American Nuclear Society, 1993.

[3] Hans R Hammer, Jim E. Morel, and Yaqi Wang.  
Nonlinear Diffusion Acceleration in Voids for the Weighted Least-Square Transport Equation.  
In *Mathematics and Computation*2, 2017.

[4] J E Morel and J M Mcghee.  
A Self-Adjoint Angular Flux Equation.  
*Nuclear Science and Engineering*, 132:312–325, 1999.

2019-08-21

Qualification Exam  
└ Backup Slides

Backup Slides

## Backup Slides

# Energy discretization

Introduce a discretization of the energy domain  $\mathbb{E}$  into  $G$  non-overlapping elements, such that

$$E_h = \{E_1, E_2, \dots, E_G\}, \quad \mathbb{E} = \bigcup_{g=1}^G E_g$$

Assume that the energy-dependent angular flux can be separated into a group angular flux and a energy function within each of these groups

$$\psi(\mathbf{r}, E, \hat{\Omega}) \approx \psi_g(\mathbf{r}, \hat{\Omega}) f_g(E), \quad E \in E_g$$

This gives us  $G$  coupled equations for each energy group, converting the integral scattering term into a summation,

$$\left[ \hat{\Omega} \cdot \nabla + \Sigma_{t,g}(\mathbf{r}) \right] \psi_g(\mathbf{r}, \hat{\Omega}) = \sum_{g'=0}^G \Sigma_{s,g' \rightarrow g}(\mathbf{r}, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi_{g'}(\mathbf{r}, \hat{\Omega}') + Q_g(\mathbf{r}, \hat{\Omega}) .$$

2019-08-21

Qualification Exam

└ Backup Slides

└ Energy discretization

- Say that the function  $f_g$  is zero inside element, and 0 outside, Petrov-Galerkin scheme.

## Energy discretization

Introduce a discretization of the energy domain  $\mathbb{E}$  into  $G$  non-overlapping elements, such that

$$E_h = \{E_1, E_2, \dots, E_G\}, \quad \mathbb{E} = \bigcup_{g=1}^G E_g$$

Assume that the energy-dependent angular flux can be separated into a group angular flux and a energy function within each of these groups

$$\psi(\mathbf{r}, E, \hat{\Omega}) \approx \psi_g(\mathbf{r}, \hat{\Omega}) f_g(E), \quad E \in E_g$$

This gives us  $G$  coupled equations for each energy group, converting the integral scattering term into a summation,

$$\left[ \hat{\Omega} \cdot \nabla + \Sigma_{t,g}(\mathbf{r}) \right] \psi_g(\mathbf{r}, \hat{\Omega}) = \sum_{g'=0}^G \Sigma_{s,g' \rightarrow g}(\mathbf{r}, \hat{\Omega}' \rightarrow \hat{\Omega}) \psi_{g'}(\mathbf{r}, \hat{\Omega}') + Q_g(\mathbf{r}, \hat{\Omega}) .$$