



Cyberscope

# Audit Report

## **Quack Quack**

May 2023

Network    BSC

Address    0x4f2cd6e39cb3627f934f388e23ea35dc87b48b29

Audited by    © cyberscope

# Table of Contents

<b>Table of Contents</b>	<b>1</b>
<b>Review</b>	<b>2</b>
Audit Updates	2
Source Files	2
<b>Findings Breakdown</b>	<b>3</b>
<b>Analysis</b>	<b>4</b>
ST - Stops Transactions	5
Description	5
Recommendation	5
<b>Diagnostics</b>	<b>6</b>
MU - Modifiers Usage	7
Description	7
Recommendation	7
PTRP - Potential Transfer Revert Propagation	8
Description	8
Recommendation	8
PVC - Price Volatility Concern	9
Description	9
Recommendation	9
IDI - Immutable Declaration Improvement	0
Description	0
Recommendation	0
L02 - State Variables could be Declared Constant	0
Description	0
Recommendation	0
L04 - Conformance to Solidity Naming Conventions	0
Description	0
Recommendation	0
L07 - Missing Events Arithmetic	0
Description	0
Recommendation	0
L09 - Dead Code Elimination	0
Description	0
Recommendation	0
L16 - Validate Variable Setters	0
Description	0
Recommendation	0
L19 - Stable Compiler Version	0
Description	0

Recommendation	0
L20 - Succeeded Transfer Check	0
Description	0
Recommendation	0
<b>Functions Analysis</b>	<b>0</b>
<b>Inheritance Graph</b>	<b>0</b>
<b>Flow Graph</b>	<b>0</b>
<b>Summary</b>	<b>0</b>
<b>Disclaimer</b>	<b>0</b>
<b>About Cyberscope</b>	<b>0</b>

## Review

Contract Name	QUACKQUACK
Compiler Version	v0.8.18+commit.87f61d96
Optimization	200 runs
Explorer	<a href="https://bscscan.com/address/0x4f2cd6e39cb3627f934f388e23ea35dc87b48b29">https://bscscan.com/address/0x4f2cd6e39cb3627f934f388e23ea35dc87b48b29</a>
Address	0x4f2cd6e39cb3627f934f388e23ea35dc87b48b29
Network	BSC
Symbol	QUACKIN
Decimals	18
Total Supply	1,000,000,000,000


## Audit Updates

Initial Audit	20 May 2023
---------------	-------------

## Source Files

Filename	SHA256
QUACKQUACK.sol	b6fa75f8dbc369c386fc5c5a7131d42119fcc419cd7039d437b78fba55f6b13b

## Findings Breakdown



● Critical	0
● Medium	0
● Minor / Informative	12

Severity	Unresolved	Acknowledged	Resolved	Other
● Critical	0	0	0	0
● Medium	0	0	0	0
● Minor / Informative	12	0	0	0

# Analysis

● Critical ● Medium ● Minor / Informative ● Pass

Severity	Code	Description	Status
●	ST	Stops Transactions	Unresolved
●	OCTD	Transfers Contract's Tokens	Passed
●	OTUT	Transfers User's Tokens	Passed
●	ELFM	Exceeds Fees Limit	Passed
●	ULTW	Transfers Liquidity to Team Wallet	Passed
●	MT	Mints Tokens	Passed
●	BT	Burns Tokens	Passed
●	BC	Blacklists Addresses	Passed

## ST - Stops Transactions

<b>Criticality</b>	Minor / Informative
<b>Location</b>	QUACKQUACK.sol#L474
<b>Status</b>	Unresolved

### Description

The transactions are initially disabled for all users excluding the authorized addresses. The owner can enable the transactions for all users. Once the transactions are enable the owner will not be able to disable them again.

```
require(canTrading, "not finalized yet");
```

### Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

# Diagnostics

● Critical ● Medium ● Minor / Informative

Severity	Code	Description	Status
●	MU	Modifiers Usage	Unresolved
●	PTRP	Potential Transfer Revert Propagation	Unresolved
●	PVC	Price Volatility Concern	Unresolved
●	IDI	Immutable Declaration Improvement	Unresolved
●	L02	State Variables could be Declared Constant	Unresolved
●	L04	Conformance to Solidity Naming Conventions	Unresolved
●	L07	Missing Events Arithmetic	Unresolved
●	L09	Dead Code Elimination	Unresolved
●	L16	Validate Variable Setters	Unresolved
●	L19	Stable Compiler Version	Unresolved
●	L20	Succeeded Transfer Check	Unresolved



## MU - Modifiers Usage

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L462,507
Status	Unresolved

### Description

The contract is using repetitive statements on some methods to perform the lock of the swap functionality. In Solidity, the form of preconditions is usually represented by the modifiers. Modifiers allow you to define a piece of code that can be reused across multiple functions within a contract. This can be particularly useful when you have several functions that require the same checks to be performed before executing the logic within the function.

```
swapping = true;
uint256 marketingTokens = contractTokenBalance;
swapAndSendMarketing(marketingTokens);
swapping = false;
// ...
swapping = true;
swapAndSendMarketing(contractTokenBalance);
swapping = false;
```

### Recommendation

The team is advised to use modifiers since it is a useful tool for reducing code duplication and improving the readability of smart contracts. By using modifiers to perform these checks, it reduces the amount of code that is needed to write, which can make the smart contract more efficient and easier to maintain.

## PTRP - Potential Transfer Revert Propagation

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L501
Status	Unresolved

### Description

The contract sends funds to a `wallet01` as part of the transfer flow. This address can either be a wallet address or a contract. If the address belongs to a contract then it may revert from incoming payment. As a result, the error will propagate to the token's contract and revert the transfer.

```
sendBNB(payable(wallet01), newBalance);
```

### Recommendation

The contract should tolerate the potential revert from the underlying contracts when the interaction is part of the main transfer flow. This could be achieved by not allowing set contract addresses or by sending the funds in a non-revertable way.

## PVC - Price Volatility Concern

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L518
Status	Unresolved

### Description

The contract accumulates tokens from the taxes to swap them for ETH. The variable `swapTokensAtAmount` sets a threshold where the contract will trigger the swap functionality. If the variable is set to a big number, then the contract will swap a huge amount of tokens for ETH.

It is important to note that the price of the token representing it, can be highly volatile. This means that the value of a price volatility swap involving Ether could fluctuate significantly at the triggered point, potentially leading to significant price volatility for the parties involved.

```
function setSwapTokensAtAmount(uint256 newAmount) external
onlyOwner {
    require(
        newAmount > totalSupply() / 100000,
        "SwapTokensAtAmount must be greater than 0.001% of total
supply"
    );
    swapTokensAtAmount = newAmount;
}
```

### Recommendation

The contract could ensure that it will not sell more than a reasonable amount of tokens in a single transaction. A suggested implementation could check that the maximum amount should be less than a fixed percentage of the total supply. Hence, the contract will guarantee that it cannot accumulate a huge amount of tokens in order to sell them.

## IDI - Immutable Declaration Improvement

<b>Criticality</b>	Minor / Informative
<b>Location</b>	QUACKQUACK.sol#L335
<b>Status</b>	Unresolved

### Description

The contract is using variables that initialize them only in the constructor. The other functions are not mutating the variables. These variables are not defined as `immutable`.

```
ultimateAddress
```

### Recommendation

By declaring a variable as immutable, the Solidity compiler is able to make certain optimizations. This can reduce the amount of storage and computation required by the contract, and make it more gas-efficient.

## L02 - State Variables could be Declared Constant

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L322
Status	Unresolved

### Description

State variables can be declared as constant using the constant keyword. This means that the value of the state variable cannot be changed after it has been set. Additionally, the constant variables decrease gas consumption of the corresponding transaction.

```
address private DEAD = 0x0000000000000000000000000000000000000000000000000000000000000000dEaD
```

### Recommendation

Constant state variables can be useful when the contract wants to ensure that the value of a state variable cannot be changed by any function in the contract. This can be useful for storing values that are important to the contract's behavior, such as the contract's address or the maximum number of times a certain function can be called. The team is advised to add the constant keyword to state variables that never change.

## L04 - Conformance to Solidity Naming Conventions

<b>Criticality</b>	Minor / Informative
<b>Location</b>	QUACKQUACK.sol#L303,322,428,434
<b>Status</b>	Unresolved

### Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX\_VALUE, ERROR\_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```
function WETH() external pure returns (address);
address private DEAD = 0x0000000000000000000000000000000000000000000000000000000000000000dEaD
uint256 _sellFee
uint256 _buyFee
address _wallet01
```

### Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

<https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention>.

## L07 - Missing Events Arithmetic

<b>Criticality</b>	Minor / Informative
<b>Location</b>	QUACKQUACK.sol#L430,519
<b>Status</b>	Unresolved

### Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

```
buyFee = _buyFee  
swapTokensAtAmount = newAmount
```

### Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.



## L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L252
Status	Unresolved

### Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
function _burn(address account, uint256 amount) internal virtual {
    require(account != address(0), "ERC20: burn from the zero address");

    _beforeTokenTransfer(account, address(0), amount);

    uint256 accountBalance = _balances[account];
    ...
}
_totalSupply -= amount;

emit Transfer(account, address(0), amount);

_afterTokenTransfer(account, address(0), amount);
}
```

### Recommendation

To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.

## L16 - Validate Variable Setters

<b>Criticality</b>	Minor / Informative
<b>Location</b>	QUACKQUACK.sol#L390,436
<b>Status</b>	Unresolved

### Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```
uniswapV2Pair = _uniswapV2Pair  
wallet01 = address(_wallet01)
```

### Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.

## L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L2
Status	Unresolved

### Description

The `^` symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
pragma solidity ^0.8.7;
```

### Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.

## L20 - Succeeded Transfer Check

Criticality	Minor / Informative
Location	QUACKQUACK.sol#L366
Status	Unresolved

### Description

According to the ERC20 specification, the transfer methods should be checked if the result is successful. Otherwise, the contract may wrongly assume that the transfer has been established.

```
ERC20token.transfer(msg.sender,  
ERC20token.balanceOf(address(this)))
```

### Recommendation

The contract should check if the result of the transfer methods is successful. The team is advised to check the SafeERC20 library from the [Openzeppelin library](#).

## Functions Analysis

# Inheritance Graph

## Flow Graph



## Summary

Token is an interesting project that has a friendly and growing community. The Smart Contract analysis reported no compiler error or critical issues. The contract Owner can access some admin functions that can not be used in a malicious way to disturb the users' transactions. There is also a limit of max 25% fees.

There are some functions that can be abused by the owner, like manipulating fees and transferring funds to the team's wallet. The maximum fee percentage that can be set is 25%. A multi-wallet signing pattern will provide security against potential hacks. Temporarily locking the contract or renouncing ownership will eliminate all the contract threats.

The contract can be converted into a honeypot and prevent users from selling if the owner abuses the admin functions.

This audit investigates security issues, business logic concerns and potential improvements.

## Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security. Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

## About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



**The Cyberscope team**

<https://www.cyberscope.io>