

Audit Report Evolution Al

April 2023

Network BSC

Address 0xE7f21F166Fb9aD8b074E4beCFE972b26997657Bd

Audited by © cyberscope



Table of Contents

Table of Contents	1
Review	3
Audit Updates	3
Source Files	3
Findings Breakdown	4
Analysis	5
ST - Stops Transactions	6
Description	6
Recommendation	6
Diagnostics	7
RSV - Redundant State Variables	8
Description	8
Recommendation	8
DDP - Decimal Division Precision	9
Description	9
Recommendation	9
RSML - Redundant SafeMath Library	10
Description	10
Recommendation	10
IDI - Immutable Declaration Improvement	11
Description	11
Recommendation	11
L04 - Conformance to Solidity Naming Conventions	12
Description	12
Recommendation	13
L05 - Unused State Variable	14
Description	14
Recommendation	14
L07 - Missing Events Arithmetic	15
Description	15
Recommendation	15
L09 - Dead Code Elimination	16
Description	16
Recommendation	17
L13 - Divide before Multiply Operation	18
Description	18
Recommendation	18
L15 - Local Scope Variable Shadowing	19
Description	19



Recommendation	19
L16 - Validate Variable Setters	20
Description	20
Recommendation	20
Functions Analysis	
Inheritance Graph	
Flow Graph	
Summary	
Disclaimer	31
About Cyberscope	32



Review

Contract Name	EvolutionAl
Compiler Version	v0.8.9+commit.e5eed63a
Optimization	200 runs
Explorer	https://bscscan.com/address/0xe7f21f166fb9ad8b074e4becfe9 72b26997657bd
Address	0xe7f21f166fb9ad8b074e4becfe972b26997657bd
Network	BSC
Symbol	\$EAI
Decimals	18
Total Supply	100,000,000

Audit Updates

Initial Audit	20 Apr 2023
---------------	-------------

Source Files

Filename	SHA256
EvolutionAl.sol	63ec9753e986a0a5c890a0700fdc593247c02c50ffd3861a5a201547d56 bf9a0



Findings Breakdown



Sev	verity	Unresolved	Acknowledged	Resolved	Other
•	Critical	0	0	0	0
•	Medium	0	0	0	0
	Minor / Informative	12	0	0	0



Analysis

CriticalMediumMinor / InformativePass

Severity	Code	Description	Status
•	ST	Stops Transactions	Unresolved
•	OCTD	Transfers Contract's Tokens	Passed
•	OTUT	Transfers User's Tokens	Passed
•	ELFM	Exceeds Fees Limit	Passed
•	ULTW	Transfers Liquidity to Team Wallet	Passed
•	MT	Mints Tokens	Passed
•	BT	Burns Tokens	Passed
•	ВС	Blacklists Addresses	Passed



ST - Stops Transactions

Criticality	Minor / Informative
Location	EvolutionAl.sol#L1032
Status	Unresolved

Description

The contract owner has the authority to stop the transactions for all users excluding the owner. The owner may take advantage of it by setting the <code>maxBuyTransactionAmount</code> to zero.

```
if(automatedMarketMakerPairs[from] && (!_isExcludedFromFees[from]) &&
  (!_isExcludedFromFees[to])){
    require(amount <= maxBuyTransactionAmount, "Sell transfer amount
  exceeds the maxBuyTransactionAmount.");
}</pre>
```

Recommendation

The contract could embody a check for not allowing setting the
maxBuyTransactionAmount less than a reasonable amount. A suggested
implementation could check that the maximum amount should be more than a fixed
percentage of the total supply. The team should carefully manage the private keys of the
owner's account. We strongly recommend a powerful security mechanism that will prevent
a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a time-locker mechanism with a reasonable delay.
- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.
- Renouncing the ownership will eliminate the threats but it is non-reversible.



Diagnostics

CriticalMediumMinor / Informative

Severity	Code	Description	Status
•	RSV	Redundant State Variables	Unresolved
•	DDP	Decimal Division Precision	Unresolved
•	RSML	Redundant SafeMath Library	Unresolved
•	IDI	Immutable Declaration Improvement	Unresolved
•	L04	Conformance to Solidity Naming Conventions	Unresolved
•	L05	Unused State Variable	Unresolved
•	L07	Missing Events Arithmetic	Unresolved
•	L09	Dead Code Elimination	Unresolved
•	L13	Divide before Multiply Operation	Unresolved
•	L15	Local Scope Variable Shadowing	Unresolved
•	L16	Validate Variable Setters	Unresolved



RSV - Redundant State Variables

Criticality	Minor / Informative
Location	EvolutionAl.sol#L1068,1069,1070,1071,1076,1077,1078,1079
Status	Unresolved

Description

There are code segments that could be optimized. A segment may be optimized so that it becomes a smaller size, consumes less memory, executes more rapidly, or performs fewer operations.

The contract uses the global variables tokensForLiquidity, tokensForMarketing, tokensForBurn and tokensForEcoSystem as temporary variables for the amount that the corresponding address will receive on each transaction. These variables are not used anywhere else in the contract. As a result, these variables are redundant.

```
tokensForLiquidity += fees * sellLiquidityFee / sellTotalFees;
tokensForMarketing += fees * sellMarketingFee / sellTotalFees;
tokensForBurn += fees * sellBurnFee / sellTotalFees;
tokensForEcoSystem += fees * sellEcoSystemFee / sellTotalFees;
```

Recommendation

The team is advised to take these segments into consideration and rewrite them so the runtime will be more performant. That way it will improve the efficiency and performance of the source code and reduce the cost of executing it. The team should remove these variables and transfer the appropriate amount directly.



DDP - Decimal Division Precision

Criticality	Minor / Informative
Location	EvolutionAl.sol#L1068,1069,1070,1071,1076,1077,1078,1079
Status	Unresolved

Description

Division of decimal (fixed point) numbers can result in rounding errors due to the way that division is implemented in Solidity. Thus, it may produce issues with precise calculations with decimal numbers.

Solidity represents decimal numbers as integers, with the decimal point implied by the number of decimal places specified in the type (e.g. decimal with 18 decimal places). When a division is performed with decimal numbers, the result is also represented as an integer, with the decimal point implied by the number of decimal places in the type. This can lead to rounding errors, as the result may not be able to be accurately represented as an integer with the specified number of decimal places.

Hence, the splitted shares will not have the exact precision and some funds may not be calculated as expected.

```
tokensForLiquidity += fees * sellLiquidityFee / sellTotalFees;
tokensForMarketing += fees * sellMarketingFee / sellTotalFees;
tokensForBurn += fees * sellBurnFee / sellTotalFees;
tokensForEcoSystem += fees * sellEcoSystemFee / sellTotalFees;
```

Recommendation

The contract could calculate the subtraction of the divided funds in the last calculation in order to avoid the division rounding issue.



RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Location	EvolutionAl.sol
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert to underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, and overhead and increases gas consumption unnecessarily.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library. Since the version of the contract is greater than 0.8.0 then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the unchecked { ... } statement.

Read more about the breaking change at https://docs.soliditylang.org/en/v0.8.16/080-breaking-changes.html#solidity-v0-8-0-breaking-changes.



IDI - Immutable Declaration Improvement

Criticality	Minor / Informative
Location	EvolutionAl.sol#L937,940,941,942,943,944,947
Status	Unresolved

Description

The contract is using variables that initialize them only in the constructor. The other functions are not mutating the variables. These variables are not defined as <code>immutable</code>.

buyEcoSystemFee sellMarketingFee sellBurnFee sellLiquidityFee sellEcoSystemFee sellTotalFees ecoSystemWallet

Recommendation

By declaring a variable as immutable, the Solidity compiler is able to make certain optimizations. This can reduce the amount of storage and computation required by the contract, and make it more gas-efficient.



L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	EvolutionAl.sol#L31,32,49,722,860,904,906,981,1000
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

- 1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
- 2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
- 3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
- 4. Use indentation to improve readability and structure.
- 5. Use spaces between operators and after commas.
- 6. Use comments to explain the purpose and behavior of the code.
- 7. Keep lines short (around 120 characters) to improve readability.



```
function DOMAIN_SEPARATOR() external view returns (bytes32);
function PERMIT_TYPEHASH() external pure returns (bytes32);
function MINIMUM_LIQUIDITY() external pure returns (uint);
function WETH() external pure returns (address);
address public constant deadAddress = address(0xdead)
event marketingWalletUpdated(address indexed newWallet, address indexed
oldWallet);
event buyBackWalletUpdated(address indexed newWallet, address indexed
oldWallet);
uint256 _burnFee
uint256 _liquidityFee
uint256 _marketingFee
uint256 _amount
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention.



L05 - Unused State Variable

Criticality	Minor / Informative
Location	EvolutionAl.sol#L653
Status	Unresolved

Description

An unused state variable is a state variable that is declared in the contract, but is never used in any of the contract's functions. This can happen if the state variable was originally intended to be used, but was later removed or never used.

Unused state variables can create clutter in the contract and make it more difficult to understand and maintain. They can also increase the size of the contract and the cost of deploying and interacting with it.

```
int256 private constant MAX_INT256 = ~(int256(1) << 255)</pre>
```

Recommendation

To avoid creating unused state variables, it's important to carefully consider the state variables that are needed for the contract's functionality, and to remove any that are no longer needed. This can help improve the clarity and efficiency of the contract.



L07 - Missing Events Arithmetic

Criticality	Minor / Informative
Location	EvolutionAl.sol#L972,982,1001
Status	Unresolved

Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

```
swapTokensAtAmount = newAmount
buyMarketingFee = _marketingFee
maxBuyTransactionAmount = _amount
```

Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.



L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	EvolutionAl.sol#L398,699,705,712
Status	Unresolved

Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
function _burn(address account, uint256 amount) internal virtual {
    require(account != address(0), "ERC20: burn from the zero
address");

    _beforeTokenTransfer(account, address(0), amount);

    _balances[account] = _balances[account].sub(amount, "ERC20: burn
amount exceeds balance");
    _totalSupply = _totalSupply.sub(amount);
    emit Transfer(account, address(0), amount);
}

function abs(int256 a) internal pure returns (int256) {
    require(a != MIN_INT256);
    return a < 0 ? -a : a;
}
...</pre>
```



Recommendation

To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.



L13 - Divide before Multiply Operation

Criticality	Minor / Informative
Location	EvolutionAl.sol#L1067,1068,1069,1070,1071,1075,1076,1077,1078,1079
Status	Unresolved

Description

It is important to be aware of the order of operations when performing arithmetic calculations. This is especially important when working with large numbers, as the order of operations can affect the final result of the calculation. Performing divisions before multiplications may cause a loss of prediction.

```
fees = amount.mul(sellTotalFees).div(100)
tokensForLiquidity += fees * sellLiquidityFee / sellTotalFees
```

Recommendation

To avoid this issue, it is recommended to carefully consider the order of operations when performing arithmetic calculations in Solidity. It's generally a good idea to use parentheses to specify the order of operations. The basic rule is that the multiplications should be prior to the divisions.



L15 - Local Scope Variable Shadowing

Criticality	Minor / Informative
Location	EvolutionAl.sol#L930
Status	Unresolved

Description

Local scope variable shadowing occurs when a local variable with the same name as a variable in an outer scope is declared within a function or code block. When this happens, the local variable "shadows" the outer variable, meaning that it takes precedence over the outer variable within the scope in which it is declared.

```
uint256 totalSupply = 1000000000 * 1e18
```

Recommendation

It's important to be aware of shadowing when working with local variables, as it can lead to confusion and unintended consequences if not used correctly. It's generally a good idea to choose unique names for local variables to avoid shadowing outer variables and causing confusion.



L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	EvolutionAl.sol#L1012
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

marketingWallet = newMarketingWallet

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.



Functions Analysis

Contract	Туре	Bases		
	Function Name	Visibility	Mutability	Modifiers
Context	Implementation			
	_msgSender	Internal		
	_msgData	Internal		
IUniswapV2Pair	Interface			
	name	External		-
	symbol	External		-
	decimals	External		-
	totalSupply	External		-
	balanceOf	External		-
	allowance	External		-
	approve	External	✓	-
	transfer	External	1	-
	transferFrom	External	✓	-
	DOMAIN_SEPARATOR	External		-
	PERMIT_TYPEHASH	External		-
	nonces	External		-
	permit	External	✓	-



	MINIMUM_LIQUIDITY	External		-
	factory	External		-
	token0	External		-
	token1	External		-
	getReserves	External		-
	price0CumulativeLast	External		-
	price1CumulativeLast	External		-
	kLast	External		-
	mint	External	✓	-
	burn	External	✓	-
	swap	External	✓	-
	skim	External	✓	-
	sync	External	✓	-
	initialize	External	✓	-
IUniswapV2Fac tory	Interface			
	feeTo	External		-
	feeToSetter	External		-
	getPair	External		-
	allPairs	External		-
	allPairsLength	External		-
	createPair	External	✓	-
	setFeeTo	External	✓	-



	setFeeToSetter	External	✓	-
IERC20	Interface			
	totalSupply	External		-
	balanceOf	External		-
	transfer	External	✓	-
	allowance	External		-
	approve	External	✓	-
	transferFrom	External	✓	-
IERC20Metadat a	Interface	IERC20		
	name	External		-
	symbol	External		-
	decimals	External		-
ERC20	Implementation	Context, IERC20, IERC20Meta data		
		Public	1	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-



	transfer	Public	1	-
	allowance	Public		-
	approve	Public	1	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	1	-
	decreaseAllowance	Public	1	-
	_transfer	Internal	1	
	_mint	Internal	✓	
	_burn	Internal	✓	
	_approve	Internal	✓	
	_beforeTokenTransfer	Internal	1	
SafeMath	Library			
	add	Internal		
	sub	Internal		
	sub	Internal		
	mul	Internal		
	div	Internal		
	div	Internal		
	mod	Internal		
	mod	Internal		
Ownable	Implementation	Context		



		Public	✓	-
	owner	Public		-
	renounceOwnership	Public	✓	onlyOwner
	transferOwnership	Public	✓	onlyOwner
SafeMathInt	Library			
	mul	Internal		
	div	Internal		
	sub	Internal		
	add	Internal		
	abs	Internal		
	toUint256Safe	Internal		
SafeMathUint	Library			
	toInt256Safe	Internal		
IUniswapV2Rou ter01	Interface			
	factory	External		-
	WETH	External		-
	addLiquidity	External	✓	-
	addLiquidityETH	External	Payable	-
	removeLiquidity	External	✓	-
	removeLiquidityETH	External	✓	-




	removeLiquidityWithPermit	External	✓	-
	removeLiquidityETHWithPermit	External	✓	-
	swapExactTokensForTokens	External	✓	-
	swapTokensForExactTokens	External	1	-
	swapExactETHForTokens	External	Payable	-
	swapTokensForExactETH	External	✓	-
	swapExactTokensForETH	External	1	-
	swapETHForExactTokens	External	Payable	-
	quote	External		-
	getAmountOut	External		-
	getAmountIn	External		-
	getAmountsOut	External		-
	getAmountsIn	External		-
IUniswapV2Rou ter02	Interface	IUniswapV2 Router01		
	removeLiquidityETHSupportingFeeOnTr ansferTokens	External	✓	-
	removeLiquidityETHWithPermitSupportingFeeOnTransferTokens	External	1	-
	swapExactTokensForTokensSupporting FeeOnTransferTokens	External	✓	-
	swapExactETHForTokensSupportingFee OnTransferTokens	External	Payable	-
	swapExactTokensForETHSupportingFee OnTransferTokens	External	1	-
EvolutionAl	Implementation	ERC20, Ownable		



	Public	✓	ERC20
	External	Payable	-
updateSwapTokensAtAmount	External	1	onlyOwner
updateSwapEnabled	External	✓	onlyOwner
updateFees	External	✓	onlyOwner
excludeFromFees	Public	✓	onlyOwner
setAutomatedMarketMakerPair	Public	✓	onlyOwner
setMaxBuyAmount	Public	✓	onlyOwner
_setAutomatedMarketMakerPair	Private	✓	
updateMarketingWallet	External	✓	onlyOwner
isExcludedFromFees	Public		-
_transfer	Internal	✓	
swapTokensForEth	Private	✓	
addLiquidity	Private	✓	
swapAndLiquify	Private	✓	




Inheritance Graph





Flow Graph





Summary

Evolution AI contract implements a token mechanism. This audit investigates security issues, business logic concerns, and potential improvements. There are some functions that can be abused by the owner like stopping transactions. A multi-wallet signing pattern will provide security against potential hacks. Temporarily locking the contract or renouncing ownership will eliminate all the contract threats. There is also a limit of max 25% fees.



Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.



About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.

