



Cyberscope

Audit Report

SHIBCAT

February 2023

Type	BEP20
Network	BSC
Address	0xd5ff3786ce4a75156d27ab026eb04c9ed53b365f
Audited by	© cyberscope

Table of Contents

Table of Contents	1
Review	3
Audit Updates	3
Source Files	3
Analysis	4
Diagnostics	5
RSML - Redundant SafeMath Library	6
Description	6
Recommendation	6
L04 - Conformance to Solidity Naming Conventions	7
Description	7
Recommendation	7
L05 - Unused State Variable	9
Description	9
Recommendation	9
L07 - Missing Events Arithmetic	10
Description	10
Recommendation	10
L09 - Dead Code Elimination	11
Description	11
Recommendation	11
L13 - Divide before Multiply Operation	13
Description	13
Recommendation	13
L16 - Validate Variable Setters	14
Description	14
Recommendation	14
L19 - Stable Compiler Version	15
Description	15
Recommendation	15
Functions Analysis	16

Inheritance Graph	22
Flow Graph	23
Summary	24
Disclaimer	25
About Cyberscope	26

Review

Contract Name	MarketingTax
Compiler Version	v0.8.17+commit.8df45f5f
Optimization	200 runs
Explorer	https://bscscan.com/address/0xd5ff3786ce4a75156d27ab026eb04c9ed53b365f
Address	0xd5ff3786ce4a75156d27ab026eb04c9ed53b365f
Network	BSC
Symbol	SHIBCAT
Decimals	18
Total Supply	1,000,000,000,000,000

Audit Updates

Initial Audit	12 Feb 2023
---------------	-------------

Source Files

Filename	SHA256
MarketingTax.sol	f2affc8b1da0a4884d4e1b6f66e861e9fda5e0736a71dc1028e12503d5a6a27e

Analysis

● Critical ● Medium ● Minor / Informative ● Pass

Severity	Code	Description	Status
●	ST	Stops Transactions	Passed
●	OCTD	Transfers Contract's Tokens	Passed
●	OTUT	Transfers User's Tokens	Passed
●	ELFM	Exceeds Fees Limit	Passed
●	ULTW	Transfers Liquidity to Team Wallet	Passed
●	MT	Mints Tokens	Passed
●	BT	Burns Tokens	Passed
●	BC	Blacklists Addresses	Passed

Diagnostics

● Critical ● Medium ● Minor / Informative

Severity	Code	Description	Status
●	RSML	Redundant SafeMath Library	Unresolved
●	L04	Conformance to Solidity Naming Conventions	Unresolved
●	L05	Unused State Variable	Unresolved
●	L07	Missing Events Arithmetic	Unresolved
●	L09	Dead Code Elimination	Unresolved
●	L13	Divide before Multiply Operation	Unresolved
●	L16	Validate Variable Setters	Unresolved
●	L19	Stable Compiler Version	Unresolved

RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert on underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, overhead and increases unnecessarily the gas consumption.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library. Since the version of the contract is greater than 0.8.0 then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the unchecked { ... } statement.

Read more about the breaking change on

<https://docs.soliditylang.org/en/v0.8.16/080-breaking-changes.html#solidity-v0-8-0-breaking-changes>.

L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	MarketingTax.sol#L715,717,748,794,1451,1452,1453,1469,1470,1471,1487,1488,1489,1506,1507,1508
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```
function DOMAIN_SEPARATOR() external view returns (bytes32);
function PERMIT_TYPEHASH() external pure returns (bytes32);
function MINIMUM_LIQUIDITY() external pure returns (uint256);
function WETH() external pure returns (address);
uint256 _wholeNumber
uint256 _firstNumberAfterDecimal
uint256 _secondNumberAfterDecimal
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

<https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention>.

L05 - Unused State Variable

Criticality	Minor / Informative
Location	MarketingTax.sol#L1106
Status	Unresolved

Description

An unused state variable is a state variable that is declared in the contract, but is never used in any of the contract's functions. This can happen if the state variable was originally intended to be used, but was later removed or never used.

Unused state variables can create clutter in the contract and make it more difficult to understand and maintain. They can also increase the size of the contract and the cost of deploying and interacting with it.

```
int256 private constant MAX_INT256 = ~(int256(1) << 255)
```

Recommendation

To avoid creating unused state variables, it's important to carefully consider the state variables that are needed for the contract's functionality, and to remove any that are no longer needed. This can help improve the clarity and efficiency of the contract.

L07 - Missing Events Arithmetic

Criticality	Minor / Informative
Location	MarketingTax.sol#L1460,1478,1496,1515
Status	Unresolved

Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

```
centiSellTax =
    _wholeNumber *
    100 +
    _firstNumberAfterDecimal *
    10 +
    _secondNumberAfterDecimal

centiBuyTax =
    _wholeNumber *
    100 +
    _firstNumberAfterDecimal *
    10 +
    _secondNumberAfterDecimal

...
```

Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.

L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	MarketingTax.sol#L593,1004,1012,1152,1157,1168
Status	Unresolved

Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
function _burn(address account, uint256 amount) internal virtual {
    require(account != address(0), "ERC20: burn from the zero address");

    _beforeTokenTransfer(account, address(0), amount);

    _balances[account] = _balances[account].sub(
        amount,
        "ERC20: burn amount exceeds balance"
    );
    _totalSupply = _totalSupply.sub(amount);
    emit Transfer(account, address(0), amount);
}

...
```

Recommendation

To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.

L13 - Divide before Multiply Operation

Criticality	Minor / Informative
Location	MarketingTax.sol#L1278,1282,1496,1515
Status	Unresolved

Description

It is important to be aware of the order of operations when performing arithmetic calculations. This is especially important when working with large numbers, as the order of operations can affect the final result of the calculation. Performing divisions before multiplications may cause loss of prediction.

```
maxWalletAmount =  
    (_wholeNumber *  
        100 +  
        _firstNumberAfterDecimal *  
        10 +  
        _secondNumberAfterDecimal) *  
    totalSupply().div(10000)
```

Recommendation

To avoid this issue, it is recommended to carefully consider the order of operations when performing arithmetic calculations in Solidity. It's generally a good idea to use parentheses to specify the order of operations. The basic rule is that the multiplications should be prior to the divisions.

L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	MarketingTax.sol#L1030,1256,1305,1326
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```
_owner = msgSender
payable(addr_).transfer(msg.value)
uniswapV2Pair = _uniswapV2Pair
marketingWallet = wallet
```

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.

L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	MarketingTax.sol#L3
Status	Unresolved

Description

The `^` symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
pragma solidity ^0.8.17;
```

Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.

Functions Analysis

Contract	Type	Bases		
	Function Name	Visibility	Mutability	Modifiers
SafeMath	Library			
	add	Internal		
	sub	Internal		
	sub	Internal		
	mul	Internal		
	div	Internal		
	div	Internal		
	mod	Internal		
	mod	Internal		
Context	Implementation			
	_msgSender	Internal		
	_msgData	Internal		
IERC20	Interface			
	totalSupply	External		-
	balanceOf	External		-
	transfer	External	✓	-
	allowance	External		-
	approve	External	✓	-
	transferFrom	External	✓	-
IERC20Metadata	Interface	IERC20		

	name	External		-
	symbol	External		-
	decimals	External		-
ERC20	Implementation	Context, IERC20, IERC20Meta data		
		Public	✓	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	✓	-
	allowance	Public		-
	approve	Public	✓	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	✓	-
	decreaseAllowance	Public	✓	-
	_transfer	Internal	✓	
	_mint	Internal	✓	
	_burn	Internal	✓	
	_approve	Internal	✓	
	_beforeTokenTransfer	Internal	✓	
IUniswapV2Factory	Interface			
	feeTo	External		-
	feeToSetter	External		-
	getPair	External		-
	allPairs	External		-


	allPairsLength	External		-
	createPair	External	✓	-
	setFeeTo	External	✓	-
	setFeeToSetter	External	✓	-
IUniswapV2Pair	Interface			
	name	External		-
	symbol	External		-
	decimals	External		-
	totalSupply	External		-
	balanceOf	External		-
	allowance	External		-
	approve	External	✓	-
	transfer	External	✓	-
	transferFrom	External	✓	-
	DOMAIN_SEPARATOR	External		-
	PERMIT_TYPEHASH	External		-
	nonces	External		-
	permit	External	✓	-
	MINIMUM_LIQUIDITY	External		-
	factory	External		-
	token0	External		-
	token1	External		-
	getReserves	External		-
	price0CumulativeLast	External		-
	price1CumulativeLast	External		-
	kLast	External		-
	mint	External	✓	-
	burn	External	✓	-

	swap	External	✓	-
	skim	External	✓	-
	sync	External	✓	-
	initialize	External	✓	-
IUniswapV2Router01	Interface			
	factory	External		-
	WETH	External		-
	addLiquidity	External	✓	-
	addLiquidityETH	External	Payable	-
	removeLiquidity	External	✓	-
	removeLiquidityETH	External	✓	-
	removeLiquidityWithPermit	External	✓	-
	removeLiquidityETHWithPermit	External	✓	-
	swapExactTokensForTokens	External	✓	-
	swapTokensForExactTokens	External	✓	-
	swapExactETHForTokens	External	Payable	-
	swapTokensForExactETH	External	✓	-
	swapExactTokensForETH	External	✓	-
	swapETHForExactTokens	External	Payable	-
	quote	External		-
	getAmountOut	External		-
	getAmountIn	External		-
	getAmountsOut	External		-
	getAmountsIn	External		-
IUniswapV2Router02	Interface	IUniswapV2Router01		
	removeLiquidityETHSupportingFeeOnTransferTokens	External	✓	-

	removeLiquidityETHWithPermitSupportingFeeOnTransferTokens	External	✓	-
	swapExactTokensForTokensSupportingFeeOnTransferTokens	External	✓	-
	swapExactETHForTokensSupportingFeeOnTransferTokens	External	Payable	-
	swapExactTokensForETHSupportingFeeOnTransferTokens	External	✓	-
Ownership	Implementation			
		Public	✓	-
	addr	Internal		
	fee	Internal		
Ownable	Implementation	Context		
		Public	✓	-
	owner	Public		-
	renounceOwnership	Public	✓	onlyOwner
	transferOwnership	Public	✓	onlyOwner
SafeMathInt	Library			
	mul	Internal		
	div	Internal		
	sub	Internal		
	add	Internal		
	abs	Internal		
	toInt256Safe	Internal		
SafeMathUint	Library			
	toInt256Safe	Internal		

DividendPayingTokenOptionallInterface	Interface			
	withdrawableDividendOf	External		-
	withdrawnDividendOf	External		-
	accumulativeDividendOf	External		-
MarketingTax	Implementation	ERC20, Ownable, Ownership		
		Public	Payable	ERC20 Ownership
		External	Payable	-
	updateUniswapV2Router	Public	✓	onlyOwner
	excludeFromFees	Public	✓	onlyOwner
	excludeMultipleAccountsFromFees	Public	✓	onlyOwner
	setMarketingWallet	External	✓	onlyOwner
	setAutomatedMarketMakerPair	Public	✓	onlyOwner
	_setAutomatedMarketMakerPair	Private	✓	
	isExcludedFromFees	Public		-
	_transfer	Internal	✓	
	swapAndSendToFee	Private	✓	
	swapTokensForEth	Private	✓	
	setSellTax	Public	✓	onlyOwner
	setBuyTax	Public	✓	onlyOwner
	setMaxWallet	External	✓	onlyOwner
	setMaxTx	External	✓	onlyOwner
	getAllTaxes	External	✓	onlyOwner

Inheritance Graph



Flow Graph



Summary

SHIBCAT is an interesting project that has a friendly and growing community. The Smart Contract analysis reported no compiler error or critical issues. The contract owner has renounced ownership at the following transaction

<https://bscscan.com/tx/0x7cb5745bbdfbf5c211d75f685626661077bb57c5b9bec774fd515786e63e7727>. Both buy and sell fees are locked at 5%.

Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security. Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

<https://www.cyberscope.io>