

Audit Report K-World

January 2023

Type ERC20

Network ETH

Address 0x98E775F8d4F7af6ec194205d94570AEb2Cf90e75

Audited by © cyberscope



Table of Contents

Table of Contents	1
Review	2
Audit Updates	2
Source Files	3
Analysis	4
Diagnostics	5
L04 - Conformance to Solidity Naming Conventions	6
Description	6
Recommendation	7
L07 - Missing Events Arithmetic	8
Description	8
Recommendation	8
L13 - Divide before Multiply Operation	9
Description	9
Recommendation	9
L16 - Validate Variable Setters	10
Description	10
Recommendation	10
L19 - Stable Compiler Version	11
Description	11
Recommendation	11
Functions Analysis	12
Inheritance Graph	17
Flow Graph	18
Summary	19
Disclaimer	20
About Cyberscope	21



Review

Contract Name	KWorld
Compiler Version	v0.8.12+commit.f00d7308
Optimization	1 runs
Explorer	https://etherscan.io/address/0x98e775f8d4f7af6ec194205d94570aeb2cf90e75
Address	0x98e775f8d4f7af6ec194205d94570aeb2cf90e75
Network	ETH
Symbol	\$KWorld
Decimals	18
Total Supply	1,000,000,000

Audit Updates

Initial Audit	05 Jan 2023 https://github.com/cyberscope-io/audits/blob/main/1-kworld/v1/audit.p https://github.com/cyberscope-io/audits/blob/main/1-kworld/v1/audit.p
Corrected Phase 2	09 Jan 2023 https://github.com/cyberscope-io/audits/blob/main/1-kworld/v2/audit.p https://github.com/cyberscope-io/audits/blob/main/1-kworld/v2/audit.p
Corrected Phase 3	11 Jan 2023



Source Files

Filename	SHA256
@openzeppelin/contracts/access/Ownable.sol	75e3c97011e75627ffb36f4a2799a4e887 e1a3e27ed427490e82d7b6f51cc5c9
@openzeppelin/contracts/token/ERC20/ERC20.sol	3cd9bf87ad804088f574a5266771f038a2 c44b53d85f355aadb35645e497d1c2
@openzeppelin/contracts/token/ERC20/extension s/IERC20Metadata.sol	af5c8a77965cc82c33b7ff844deb982616 6689e55dc037a7f2f790d057811990
@openzeppelin/contracts/token/ERC20/IERC20.so	94f23e4af51a18c2269b355b8c7cf4db80 03d075c9c541019eb8dcf4122864d5
@openzeppelin/contracts/utils/Context.sol	1458c260d010a08e4c20a4a517882259a 23a4baa0b5bd9add9fb6d6a1549814a
contracts/Token.sol	6234b76bb5f4aa751e28999f11b41d505 92ea78c06878e917361bfcc8142461f



Analysis

CriticalMediumMinor / InformativePass

Severity	Code	Description	Status
•	ST	Stops Transactions	Passed
•	OCTD	Transfers Contract's Tokens	Passed
•	OTUT	Transfers User's Tokens	Passed
•	ELFM	Exceeds Fees Limit	Passed
•	ULTW	Transfers Liquidity to Team Wallet	Passed
•	MT	Mints Tokens	Passed
•	ВТ	Burns Tokens	Passed
•	ВС	Blacklists Addresses	Passed

5



Diagnostics

CriticalMediumMinor / Informative

Severity	Code	Description	Status
•	L04	Conformance to Solidity Naming Conventions	Unresolved
•	L07	Missing Events Arithmetic	Unresolved
•	L13	Divide before Multiply Operation	Unresolved
•	L16	Validate Variable Setters	Unresolved
•	L19	Stable Compiler Version	Unresolved



L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	contracts/Token.sol#L81,234,245,261,262,547,560,565
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

- 1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
- 2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
- 3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
- 4. Use indentation to improve readability and structure.
- 5. Use spaces between operators and after commas.
- 6. Use comments to explain the purpose and behavior of the code.
- 7. Keep lines short (around 120 characters) to improve readability.



```
function WETH() external pure returns (address);
uint256 constant public feeDivisor = 100
uint256 public LPBuyFee
event marketingWalletUpdated(address indexed newWallet, address indexed oldWallet);
event rewardWalletUpdated(address indexed newWallet, address indexed oldWallet);
uint256 _devBuyFee
uint256 _rewardSellFee
uint256 _marketingSellFee
uint256 _devSellFee
uint256 _devSellFee
uint256 _marketingBuyFee
uint256 _marketingBuyFee
uint256 _maxWalletAmount
uint256 _maxTxAmount
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention.



L07 - Missing Events Arithmetic

Criticality	Minor / Informative
Location	contracts/Token.sol#L562,567
Status	Unresolved

Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

```
maxWalletBalance = _maxWalletAmount
maxTxAmount = _maxTxAmount
```

Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.



L13 - Divide before Multiply Operation

Criticality	Minor / Informative
Location	contracts/Token.sol#L454,455,456,457,464,465,466,467
Status	Unresolved

Description

It is important to be aware of the order of operations when performing arithmetic calculations. This is especially important when working with large numbers, as the order of operations can affect the final result of the calculation. Performing divisions before multiplications may cause loss of prediction.

```
fees = amount * totalBuyFees / feeDivisor
tokensForLP += fees * LPBuyFee / totalBuyFees
```

Recommendation

To avoid this issue, it is recommended to carefully consider the order of operations when performing arithmetic calculations in Solidity. It's generally a good idea to use parentheses to specify the order of operations. The basic rule is that the multiplications should be prior to the divisions.



L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	contracts/Token.sol#L292,296,298,300
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```
marketingWallet = _marketingWallet
devWallet = _devWallet
autoLiquidityReceiver = _newOwner
rewardWallet = _rewardWallet
```

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.



L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	contracts/Token.sol#L8
Status	Unresolved

Description

The symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
pragma solidity ^0.8.12;
```

Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.

Functions Analysis

Contract	Туре	Bases		
	Function Name	Visibility	Mutability	Modifiers
Ownable	Implementation	Context		
		Public	1	-
	owner	Public		-
	renounceOwnership	Public	1	onlyOwner
	transferOwnership	Public	1	onlyOwner
	_transferOwnership	Internal	1	
ERC20	Implementation	Context, IERC20, IERC20Met adata		
		Public	1	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	1	-
	allowance	Public		-
	approve	Public	1	-
	transferFrom	Public	1	-
	increaseAllowance	Public	1	-
	decreaseAllowance	Public	1	-
	_transfer	Internal	✓	
	_mint	Internal	1	



	_burn	Internal	✓	
	_approve	Internal	✓	
	_spendAllowance	Internal	✓	
	_beforeTokenTransfer	Internal	✓	
	_afterTokenTransfer	Internal	✓	
IERC20Metad ata	Interface	IERC20		
	name	External		-
	symbol	External		-
	decimals	External		-
IERC20	Interface			
	totalSupply	External		-
	balanceOf	External		-
	transfer	External	✓	-
	allowance	External		-
	approve	External	✓	-
	transferFrom	External	✓	-
Context	Implementation			
	_msgSender	Internal		
	_msgData	Internal		
IUniswapV3Pa ir	Interface			
	name	External		-
	symbol	External		-
	decimals	External		-
	balanceOf	External		-
	allowance	External		-



approve				
transferFrom External - nonces External - permit External - factory External - token0 External - getReserves External - priceOCumulativeLast External - price1CumulativeLast External - kLast External - mint External - burn External - swap External - skim External - sync External - initialize External - feeTo External - feeTo External - getPair External - allPairs External - createPair External - external - - external - - external - - <td>approve</td> <td>External</td> <td>✓</td> <td>-</td>	approve	External	✓	-
nonces	transfer	External	✓	-
permit	transferFrom	External	✓	-
factory	nonces	External		-
token0	permit	External	1	-
token1	factory	External		-
getReserves	token0	External		-
price0CumulativeLast	token1	External		-
price1CumulativeLast External -	getReserves	External		-
KLast	price0CumulativeLast	External		-
mint	price1CumulativeLast	External		-
burn External	kLast	External		-
swap skim External y sync External y initialize External IUniswapV3Fa ctory feeTo feeTo External External External - getPair allPairs External External External - allPairs External External - External - External - allPairs External External - External - setFeeTo External - External	mint	External	1	-
skim External	burn	External	1	-
sync External	swap	External	1	-
initialize External ✓ - IUniswapV3Fa ctory feeTo External - feeToSetter External - getPair External - allPairs External - allPairsLength External - createPair External - setFeeTo External - External -	skim	External	1	-
IUniswapV3Fa ctory Interface feeTo External - feeToSetter External - getPair External - allPairs External - allPairsLength External - createPair External ✓ setFeeTo External ✓	sync	External	1	-
ctory feeTo External - feeToSetter External - getPair External - allPairs External - allPairsLength External - createPair External ✓ setFeeTo External ✓	initialize	External	✓	-
ctory feeTo External - feeToSetter External - getPair External - allPairs External - allPairsLength External - createPair External ✓ setFeeTo External ✓				
feeToSetter External - getPair External - allPairs External - allPairsLength External - createPair External - setFeeTo External ✓ -	Interface			
getPair External - allPairs External - allPairsLength External - createPair External √ - setFeeTo External √ -	feeTo	External		-
allPairs External - allPairsLength External - createPair External ✓ - setFeeTo External ✓ -	feeToSetter	External		-
allPairsLength External - createPair External ✓ - setFeeTo External ✓ -	getPair	External		-
createPair External ✓ - setFeeTo External ✓ -	allPairs	External		-
setFeeTo External ✓ -	allPairsLength	External		-
	createPair	External	1	-
setFeeToSetter External ✓ -	setFeeTo	External	✓	-
	setFeeToSetter	External	1	-




IUniswapV3Ro uter01	Interface			
	factory	External		-
	WETH	External		-
	addLiquidity	External	✓	-
	addLiquidityETH	External	Payable	-
	removeLiquidity	External	1	-
	removeLiquidityETH	External	1	-
	removeLiquidityWithPermit	External	1	-
	removeLiquidityETHWithPermit	External	1	-
	swapExactTokensForTokens	External	1	-
	swapTokensForExactTokens	External	1	-
	swapExactETHForTokens	External	Payable	-
	swapTokensForExactETH	External	1	-
	swapExactTokensForETH	External	✓	-
	swapETHForExactTokens	External	Payable	-
	quote	External		-
	getAmountOut	External		-
	getAmountIn	External		-
	getAmountsOut	External		-
	getAmountsIn	External		-
IUniswapV3Ro uter02	Interface	IUniswapV3 Router01		
	removeLiquidityETHSupportingFeeOn TransferTokens	External	✓	-
	removeLiquidityETHWithPermitSuppo rtingFeeOnTransferTokens	External	✓	-
	swapExactTokensForTokensSupporti ngFeeOnTransferTokens	External	✓	-
	swapExactETHForTokensSupporting FeeOnTransferTokens	External	Payable	-
	swapExactTokensForETHSupporting FeeOnTransferTokens	External	✓	-



KWorld	Implementation	ERC20, Ownable		
		Public	✓	ERC20
		External	Payable	-
	updateSwapTokensAtAmount	External	1	onlyOwner
	excludeFromFees	Public	1	onlyOwner
	excludeMultipleAccountsFromFees	External	1	onlyOwner
	setAutomatedMarketMakerPair	Public	✓	onlyOwner
	_setAutomatedMarketMakerPair	Private	✓	
	updateAutoLiquidityReceiver	External	✓	onlyOwner
	updateMarketingWallet	External	✓	onlyOwner
	updateRewardWallet	External	✓	onlyOwner
	updateDevWallet	External	✓	onlyOwner
	isExcludedFromFees	Public		-
	_transfer	Internal	✓	
	swapTokensForEth	Private	1	
	addLiquidity	Private	1	
	swapBack	Private	1	
	setTaxes	External	✓	onlyOwner
	setMaxWalletAmount	External	✓	onlyOwner
	setMaxTxAmount	External	1	onlyOwner




Inheritance Graph





Flow Graph





Summary

KhabyWorld is an interesting project that has a friendly and growing community. The Smart Contract analysis reported no compiler errors or critical issues. The contract Owner can access some admin functions that can not be used in a malicious way to disturb the users' transactions. There is also a limit of max 24% buy/sell fees.



Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.



About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

https://www.cyberscope.io