

Audit Report Pepes Gone Wild

May 2023

Network BSC

Address 0xb1de0971acf50bc3f1230fb923aa8b66ffc79c5e

Audited by © cyberscope



Table of Contents

Table of Contents	1
Review	2
Audit Updates	2
Source Files	2
Findings Breakdown	3
Analysis	4
ST - Stops Transactions	5
Description	5
Recommendation	5
ELFM - Exceeds Fees Limit	6
Description	6
Recommendation	6
BC - Blacklists Addresses	7
Description	7
Recommendation	7
Diagnostics	8
PTRP - Potential Transfer Revert Propagation	9
Description	9
Recommendation	9
RSML - Redundant SafeMath Library	10
Description	10
Recommendation	10
IDI - Immutable Declaration Improvement	11
Description	11
Recommendation	11
L04 - Conformance to Solidity Naming Conventions	12
Description	12
Recommendation	13
L07 - Missing Events Arithmetic	14
Description	14
Recommendation	14
L09 - Dead Code Elimination	15
Description	15
Recommendation	15
L16 - Validate Variable Setters	17
Description	17
Recommendation	17
L19 - Stable Compiler Version	18
Description	18

Recommendation	18
Functions Analysis	19
nheritance Graph	22
Flow Graph	23
Summary	24
Disclaimer	25
About Cyberscope	26



Review

Contract Name	PepesGoneWild
Compiler Version	v0.8.18+commit.87f61d96
Optimization	200 runs
Explorer	https://bscscan.com/address/0xb1de0971acf50bc3f1230fb923a a8b66ffc79c5e
Address	0xb1de0971acf50bc3f1230fb923aa8b66ffc79c5e
Network	BSC
Symbol	\$PGW
Decimals	18
Total Supply	1,000,000,000


Audit Updates

Source Files

Filename	SHA256
PepesGoneWild.sol	2cf789a89f08a69dcace5f630288ba457e3ee0e1ea29faaec6fd6aa10abd 0df5



Findings Breakdown



Sev	erity	Unresolved	Acknowledged	Resolved	Other
•	Critical	2	0	0	0
•	Medium	1	0	0	0
	Minor / Informative	8	0	0	0



Analysis

CriticalMediumMinor / InformativePass

Severity	Code	Description	Status
•	ST	Stops Transactions	Unresolved
•	OCTD	Transfers Contract's Tokens	Passed
•	OTUT	Transfers User's Tokens	Passed
•	ELFM	Exceeds Fees Limit	Unresolved
•	ULTW	Transfers Liquidity to Team Wallet	Passed
•	MT	Mints Tokens	Passed
•	ВТ	Burns Tokens	Passed
•	ВС	Blacklists Addresses	Unresolved



ST - Stops Transactions

Criticality	Critical
Location	PepesGoneWild.sol#L708
Status	Unresolved

Description

The contract owner has the authority to stop the sales for all users excluding the owner. The owner may take advantage of it by setting the sell_Fee to a high value. As a result, the contract may operate as a honeypot.

```
} else if (to == PancakeswapV2Pair){
   fee = sell_Fee;
}
```

Additionally, the contract owner can universally stop the trades by disabling the flag variable.

```
require (flag, "_");
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a time-locker mechanism with a reasonable delay.
- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.
- Renouncing the ownership will eliminate the threats but it is non-reversible.



ELFM - Exceeds Fees Limit

Criticality	Critical
Location	PepesGoneWild.sol#L785
Status	Unresolved

Description

The contract owner has the authority to increase over the allowed limit of 25%. The owner may take advantage of it by calling the setBuyTax or setSellTax function with a high percentage value.

```
function setBuyTax (uint8 _newBuyTax) external onlyOwner {
   buy_Fee = _newBuyTax;
}

function setSellTax (uint8 _newSellTax) external onlyOwner {
   sell_Fee = _newSellTax;
}
```

Recommendation

The contract could embody a check for the maximum acceptable value. The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a time-locker mechanism with a reasonable delay.
- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.
- Renouncing the ownership will eliminate the threats but it is non-reversible.



BC - Blacklists Addresses

Criticality	Medium
Location	PepesGoneWild.sol#L710
Status	Unresolved

Description

The contract owner has the authority to stop addresses from transactions. The owner may take advantage of it by calling the setBlacklist function.

```
require(!_isBlacklisted[from] && !_isBlacklisted[to], "To or From
address is blacklisted.");
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a time-locker mechanism with a reasonable delay.
- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.
- Renouncing the ownership will eliminate the threats but it is non-reversible.



Diagnostics

CriticalMediumMinor / Informative

Severity	Code	Description	Status
•	PTRP	Potential Transfer Revert Propagation	Unresolved
•	RSML	Redundant SafeMath Library	Unresolved
•	IDI	Immutable Declaration Improvement	Unresolved
•	L04	Conformance to Solidity Naming Conventions	Unresolved
•	L07	Missing Events Arithmetic	Unresolved
•	L09	Dead Code Elimination	Unresolved
•	L16	Validate Variable Setters	Unresolved
•	L19	Stable Compiler Version	Unresolved



PTRP - Potential Transfer Revert Propagation

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L761
Status	Unresolved

Description

The contract sends funds to a marketingWallet as part of the transfer flow. This address can either be a wallet address or a contract. If the address belongs to a contract then it may revert from incoming payment. As a result, the error will propagate to the token's contract and revert the transfer.

```
payable(marketingWallet).transfer(ethBalance);
```

Recommendation

The contract should tolerate the potential revert from the underlying contracts when the interaction is part of the main transfer flow. This could be achieved by not allowing set contract addresses or by sending the funds in a non-revertable way.



RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Location	PepesGoneWild.sol
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert to underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, overhead and increases gas consumption unnecessarily.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library. Since the version of the contract is greater than 0.8.0 then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the unchecked { ... } statement.

Read more about the breaking change on https://docs.soliditylang.org/en/v0.8.16/080-breaking-changes.html#solidity-v0-8-0-breaking-changes.



IDI - Immutable Declaration Improvement

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L692,693
Status	Unresolved

Description

The contract is using variables that initialize them only in the constructor. The other functions are not mutating the variables. These variables are not defined as <code>immutable</code>.

PancakeswapV2Router PancakeswapV2Pair

Recommendation

By declaring a variable as immutable, the Solidity compiler is able to make certain optimizations. This can reduce the amount of storage and computation required by the contract, and make it more gas-efficient.



L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L113,114,131,167,672,673,677,678,681,765,771,777,781,785,789
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

- 1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
- 2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
- 3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
- 4. Use indentation to improve readability and structure.
- 5. Use spaces between operators and after commas.
- 6. Use comments to explain the purpose and behavior of the code.
- 7. Keep lines short (around 120 characters) to improve readability.



Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention.



L07 - Missing Events Arithmetic

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L782,786
Status	Unresolved

Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.



L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L613
Status	Unresolved

Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
sing Hooks].
    */
    function _beforeTokenTransfer(
        address from,
        address to,
        uint256 amount
...
    using SafeMath for uint256;

IPancakeswapV2Router02 public PancakeswapV2Router;
    address public PancakeswapV2Pair;
    bool private swapping;

address public marketingWallet = 0x0CD42C8
```

Recommendation



To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.



L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L767
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.



L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	PepesGoneWild.sol#L23
Status	Unresolved

Description

The ^ symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
msgSender();
```

Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.



Functions Analysis

Contract	Туре	Bases		
	Function Name	Visibility	Mutability	Modifiers
SafeMath	Library			
	add	Internal		
	sub	Internal		
	sub	Internal		
	mul	Internal		
	div	Internal		
	div	Internal		
	mod	Internal		
	mod	Internal		
Context	Implementation			
	_msgSender	Internal		
Ownable	Implementation	Context		
		Public	✓	-
	owner	Public		-
	renounceOwnership	Public	✓	onlyOwner
	transferOwnership	Public	✓	onlyOwner




ERC20	Implementation	Context, IERC20, IERC20Meta data		
		Public	✓	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	✓	-
	allowance	Public		-
	approve	Public	✓	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	✓	-
	decreaseAllowance	Public	✓	-
	_transfer	Internal	✓	
	_mint	Internal	✓	
	_burn	Internal	✓	
	_approve	Internal	✓	
	_beforeTokenTransfer	Internal	✓	
PepesGoneWild	Implementation	ERC20, Ownable		
		Public	✓	ERC20



	External	Payable	-
_transfer	Internal	✓	
swapTokensForEth	Private	1	
swapAndSendDividends	Private	1	
setBlacklist	External	1	onlyOwner
setmarketingWallet	External	1	onlyOwner
changeOwner	External	1	onlyOwner
setExcludeWallet	External	1	onlyOwner
setBuyTax	External	✓	onlyOwner
setSellTax	External	✓	onlyOwner
start	External	✓	onlyOwner




Inheritance Graph





Flow Graph





Summary

Pepes Gone Wild contract implements a token mechanism. This audit investigates security issues, business logic concerns and potential improvements. There are some functions that can be abused by the owner like stop transactions, manipulate the fees and blacklist addresses. The contract can be converted into a honeypot and prevent users from selling if the owner abuses the admin functions. A multi-wallet signing pattern will provide security against potential hacks. Temporarily locking the contract or renouncing ownership will eliminate all the contract threats.



Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.



About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.

