

Finger Pose Classification — Run Report

Generated 2026-05-19 15:58:21

Data paths

Data root	/home/jestin/ThesisRepo/ML/NewTrainingData/Finger_MCP_PIP · 121 trials total
Class folders	curl_curl, straight_straight
Report output dir	/home/jestin/ThesisRepo/ML/NewReports/FingerPoseReports/Binary
Trials · curl_curl	61
Trials · straight_straight	60

Sensor selection

Hands	left, right
Segments	palm_mid, thumb, index, middle, ring, pinky
Modalities	YPR, Flex
Sensor columns	92 channels
Fingers	thumb, index, middle, ring, pinky
Classes	2: curl_curl, straight_straight

Preprocessing, features & split

Resample steps	90
Butterworth	on · cutoff 10.0 Hz · order 4 · fs 30.0 Hz
Normalisation	standard
Feature mode	stats+fft → feature dim 594
Split / seed / CV	test_size=0.2 · random_state=42 · CV folds=5
Trials per finger dataset	409 (train+test, post-aug train)

Augmentation (training only)

Copies per train trial	3
Gaussian noise	on · sigma=0.02 (per-channel std-scaled)
Time warp	on · max_scale=0.1
Amplitude scaling	off · range=(0.9, 1.1)

Active classifiers

Algorithm	Class
SVM (RBF)	SVC
SVM (Linear)	SVC
Random Forest	RandomForestClassifier
KNN	KNeighborsClassifier
Logistic Regression	LogisticRegression
LDA	LinearDiscriminantAnalysis
Voting Soft (SVM+RF+KNN+LogReg)	VotingClassifier
Voting Soft (SVM+RF)	VotingClassifier
Stacking (SVM+RF+KNN+LogReg)	StackingClassifier

Classifier hyperparameters

SVM (RBF)	C=10 · break_ties=False · cache_size=200 · class_weight=None · coef0=0.0 · decision_function_shape=ovr · degree=3 · gamma=scale · kernel=rbf · max_iter=-1 · probability=True · random_state=42 · shrinking=True · tol=0.001 · verbose=False
SVM (Linear)	C=1 · break_ties=False · cache_size=200 · class_weight=None · coef0=0.0 · decision_function_shape=ovr · degree=3 · gamma=scale · kernel=linear · max_iter=-1 · probability=True · random_state=42 · shrinking=True · tol=0.001 · verbose=False
Random Forest	bootstrap=True · ccp_alpha=0.0 · class_weight=None · criterion=gini · max_depth=None · max_features=sqrt · max_leaf_nodes=None · max_samples=None · min_impurity_decrease=0.0 · min_samples_leaf=1 · min_samples_split=2 · min_weight_fraction_leaf=0.0 · monotonic_cst=None · n_jobs=-1 · oob_score=False · random_state=42 · verbose=0 · warm_start=False
KNN	algorithm=auto · leaf_size=30 · metric=euclidean · metric_params=None · n_jobs=None · n_neighbors=5 · p=2 · weights=uniform
Logistic Regression	C=1.0 · class_weight=None · dual=False · fit_intercept=True · intercept_scaling=1 · l1_ratio=0.0 · max_iter=1000 · n_jobs=None · penalty=deprecated · random_state=42 · solver=lbfgs · tol=0.0001 · verbose=0 · warm_start=False
LDA	covariance_estimator=None · n_components=None · priors=None · shrinkage=None · solver=svd · store_covariance=False · tol=0.0001
Voting Soft (SVM+RF+KNN+LogReg)	flatten_transform=True · n_jobs=-1 · verbose=False · voting=soft · weights=None
Voting Soft (SVM+RF)	flatten_transform=True · n_jobs=-1 · verbose=False · voting=soft · weights=None
Stacking (SVM+RF+KNN+LogReg)	cv=5 · final_estimator=LogisticRegression(max_iter=1000, random_state=42) · n_jobs=-1 · passthrough=False · stack_method=auto · verbose=0

Per-dataset test accuracy

Rows = (hand, finger) dataset. Columns = classifier. Last row = mean across datasets.

Dataset	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
left · thumb	0.840	0.840	0.920	0.920	0.880	0.800	0.920	0.920	0.880
left · index	0.960	0.920	0.960	0.920	0.920	0.880	0.920	0.920	0.880
left · middle	0.920	0.960	1.000	0.960	0.960	0.880	0.960	0.960	0.960
left · ring	0.960	0.880	0.960	0.960	0.880	0.880	1.000	1.000	1.000
left · pinky	0.920	0.840	0.960	0.920	0.800	0.920	0.920	0.920	0.920
right · thumb	0.920	0.960	0.960	0.920	0.960	0.960	0.960	0.960	0.960
right · index	0.960	0.960	0.960	0.920	0.960	0.960	0.960	0.960	0.960
right · middle	0.960	0.880	0.960	0.960	0.880	0.880	0.960	0.960	0.960
right · ring	0.960	0.960	1.000	0.960	0.960	0.880	0.960	0.960	0.960
right · pinky	0.840	0.880	0.960	0.920	0.880	0.920	0.880	0.880	0.880
Mean	0.924	0.908	0.964	0.936	0.908	0.896	0.944	0.944	0.936

Per-class accuracy by dataset

Each table: rows = class, columns = classifier. Values are per-class accuracy on the test set.

left · thumb

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.692	0.769	0.923	0.923	0.769	0.846	0.846	0.846	0.769
straight_straight	1.000	0.917	0.917	0.917	1.000	0.750	1.000	1.000	1.000

left · index

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	1.000	0.923	1.000	1.000	0.923	1.000	1.000	1.000	0.923
straight_straight	0.917	0.917	0.917	0.833	0.917	0.750	0.833	0.833	0.833

left · middle

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	1.000	1.000	1.000	0.923	1.000	0.846	1.000	1.000	1.000
straight_straight	0.833	0.917	1.000	1.000	0.917	0.917	0.917	0.917	0.917

left · ring

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	1.000	0.923	1.000	0.923	0.923	0.923	1.000	1.000	1.000
straight_straight	0.917	0.833	0.917	1.000	0.833	0.833	1.000	1.000	1.000

left · pinky

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.923	0.769	1.000	0.846	0.692	0.923	0.923	0.923	0.923
straight_straight	0.917	0.917	0.917	1.000	0.917	0.917	0.917	0.917	0.917

right · thumb

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.846	0.923	0.923	0.846	0.923	0.923	0.923	0.923	0.923
straight_straight	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000

right · index

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.923	0.923	0.923	0.923	0.923	0.923	0.923	0.923	0.923
straight_straight	1.000	1.000	1.000	0.917	1.000	1.000	1.000	1.000	1.000

right · middle

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.923	0.923	0.923	0.923	0.923	0.846	0.923	0.923	0.923
straight_straight	1.000	0.833	1.000	1.000	0.833	0.917	1.000	1.000	1.000

right · ring

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.923	0.923	1.000	0.923	0.923	0.846	0.923	0.923	0.923
straight_straight	1.000	1.000	1.000	1.000	1.000	0.917	1.000	1.000	1.000

right · pinky

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regress ion	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stackin g (SVM+ RF+KN N+LogR eg)
curl_curl	0.923	0.923	0.923	0.923	0.923	0.846	0.923	0.923	0.923
straight_straight	0.750	0.833	1.000	0.917	0.833	1.000	0.833	0.833	0.833