

Finger Pose Classification — Run Report

Generated 2026-05-19 14:43:46

Data paths

Data root	/home/jestin/ThesisRepo/ML/NewTrainingData/Finger_MCP_PIP · 241 trials total
Class folders	curl_curl, curl_straight, straight_curl, straight_straight
Report output dir	/home/jestin/ThesisRepo/ML/NewReports/FingerPoseReports
Trials · curl_curl	61
Trials · curl_straight	60
Trials · straight_curl	60
Trials · straight_straight	60

Sensor selection

Hands	left, right
Segments	palm_mid, thumb, index, middle, ring, pinky
Modalities	Accel
Sensor columns	72 channels
Fingers	thumb, index, middle, ring, pinky
Classes	4: curl_curl, curl_straight, straight_curl, straight_straight

Preprocessing, features & split

Resample steps	90
Butterworth	on · cutoff 10.0 Hz · order 4 · fs 30.0 Hz
Normalisation	standard
Feature mode	stats+fft → feature dim 486
Split / seed / CV	test_size=0.2 · random_state=42 · CV folds=5
Trials per finger dataset	817 (train+test, post-aug train)

Augmentation (training only)

Copies per train trial	3
Gaussian noise	on · sigma=0.02 (per-channel std-scaled)
Time warp	on · max_scale=0.1
Amplitude scaling	off · range=(0.9, 1.1)

Active classifiers

Algorithm	Class
SVM (RBF)	SVC
SVM (Linear)	SVC
Random Forest	RandomForestClassifier
KNN	KNeighborsClassifier
Logistic Regression	LogisticRegression
LDA	LinearDiscriminantAnalysis
Voting Soft (SVM+RF+KNN+LogReg)	VotingClassifier
Voting Soft (SVM+RF)	VotingClassifier

Algorithm	Class
Stacking (SVM+RF+KNN+LogReg)	StackingClassifier

Classifier hyperparameters

SVM (RBF)	C=10 · break_ties=False · cache_size=200 · class_weight=None · coef0=0.0 · decision_function_shape=ovr · degree=3 · gamma=scale · kernel=rbf · max_iter=-1 · probability=True · random_state=42 · shrinking=True · tol=0.001 · verbose=False
SVM (Linear)	C=1 · break_ties=False · cache_size=200 · class_weight=None · coef0=0.0 · decision_function_shape=ovr · degree=3 · gamma=scale · kernel=linear · max_iter=-1 · probability=True · random_state=42 · shrinking=True · tol=0.001 · verbose=False
Random Forest	bootstrap=True · ccp_alpha=0.0 · class_weight=None · criterion=gini · max_depth=None · max_features=sqrt · max_leaf_nodes=None · max_samples=None · min_impurity_decrease=0.0 · min_samples_leaf=1 · min_samples_split=2 · min_weight_fraction_leaf=0.0 · monotonic_cst=None · n_jobs=-1 · oob_score=False · random_state=42 · verbose=0 · warm_start=False
KNN	algorithm=auto · leaf_size=30 · metric=euclidean · metric_params=None · n_jobs=None · n_neighbors=5 · p=2 · weights=uniform
Logistic Regression	C=1.0 · class_weight=None · dual=False · fit_intercept=True · intercept_scaling=1 · l1_ratio=0.0 · max_iter=1000 · n_jobs=None · penalty=deprecated · random_state=42 · solver=lbfgs · tol=0.0001 · verbose=0 · warm_start=False
LDA	covariance_estimator=None · n_components=None · priors=None · shrinkage=None · solver=svd · store_covariance=False · tol=0.0001
Voting Soft (SVM+RF+KNN+LogReg)	flatten_transform=True · n_jobs=-1 · verbose=False · voting=soft · weights=None
Voting Soft (SVM+RF)	flatten_transform=True · n_jobs=-1 · verbose=False · voting=soft · weights=None
Stacking (SVM+RF+KNN+LogReg)	cv=5 · final_estimator=LogisticRegression(max_iter=1000, random_state=42) · n_jobs=-1 · passthrough=False · stack_method=auto · verbose=0

Per-dataset test accuracy

Rows = (hand, finger) dataset. Columns = classifier. Last row = mean across datasets.

Dataset	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
left · thumb	0.469	0.408	0.429	0.327	0.510	0.306	0.490	0.490	0.510
left · index	0.735	0.510	0.551	0.551	0.551	0.469	0.633	0.633	0.592
left · middle	0.673	0.531	0.612	0.571	0.653	0.592	0.633	0.633	0.673
left · ring	0.694	0.612	0.776	0.633	0.633	0.633	0.714	0.714	0.714
left · pinky	0.429	0.531	0.571	0.510	0.510	0.388	0.510	0.510	0.592
right · thumb	0.449	0.408	0.347	0.469	0.429	0.286	0.469	0.469	0.449
right · index	0.612	0.592	0.694	0.571	0.653	0.429	0.673	0.673	0.694
right · middle	0.469	0.510	0.469	0.490	0.469	0.327	0.429	0.429	0.449
right · ring	0.469	0.408	0.612	0.531	0.449	0.265	0.592	0.592	0.510
right · pinky	0.531	0.531	0.551	0.429	0.510	0.327	0.510	0.510	0.469
Mean	0.553	0.504	0.561	0.508	0.537	0.402	0.565	0.565	0.565

Per-class accuracy by dataset

Each table: rows = class, columns = classifier. Values are per-class accuracy on the test set.

left · thumb

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.769	0.769	0.692	0.462	0.846	0.385	1.000	1.000	0.923
curl_straight	0.583	0.250	0.250	0.333	0.417	0.250	0.417	0.417	0.417
straight_curl	0.250	0.250	0.333	0.167	0.250	0.333	0.167	0.167	0.333
straight_straight	0.250	0.333	0.417	0.333	0.500	0.250	0.333	0.333	0.333

left · index

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.769	0.769	0.769	0.615	0.615	0.769	0.692	0.692	0.692
curl_straight	1.000	0.417	0.500	0.417	0.500	0.333	0.583	0.583	0.583
straight_curl	0.333	0.333	0.333	0.500	0.500	0.417	0.500	0.500	0.500
straight_straight	0.833	0.500	0.583	0.667	0.583	0.333	0.750	0.750	0.583

left · middle

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SVM+RF+KNN+LogReg)	Voting Soft (SVM+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.769	0.615	0.923	0.692	0.692	0.692	0.769	0.769	0.846

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+ RF+KNN+LogReg)
curl_straight	0.667	0.500	0.417	0.500	0.583	0.667	0.667	0.667	0.583
straight_curl	0.667	0.583	0.583	0.583	0.667	0.500	0.583	0.583	0.750
straight_straight	0.583	0.417	0.500	0.500	0.667	0.500	0.500	0.500	0.500

left · ring

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+ RF+KNN+LogReg)
curl_curl	0.846	0.769	0.846	0.692	0.769	0.923	0.769	0.769	0.769
curl_straight	0.667	0.583	0.750	0.583	0.583	0.583	0.667	0.667	0.750
straight_curl	0.667	0.500	0.833	0.583	0.583	0.417	0.750	0.750	0.750
straight_straight	0.583	0.583	0.667	0.667	0.583	0.583	0.667	0.667	0.583

left · pinky

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+ RF+KNN+LogReg)
curl_curl	0.692	0.769	0.923	0.769	0.846	0.538	0.692	0.692	0.769
curl_straight	0.167	0.417	0.417	0.500	0.500	0.250	0.417	0.417	0.417
straight_curl	0.250	0.500	0.333	0.250	0.333	0.250	0.333	0.333	0.500
straight_straight	0.583	0.417	0.583	0.500	0.333	0.500	0.583	0.583	0.667

right · thumb

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+ RF+KNN+LogReg)
curl_curl	0.385	0.538	0.154	0.385	0.385	0.154	0.385	0.385	0.385
curl_straight	0.417	0.417	0.583	0.500	0.500	0.333	0.583	0.583	0.583
straight_curl	0.333	0.417	0.250	0.583	0.417	0.417	0.417	0.417	0.333
straight_straight	0.667	0.250	0.417	0.417	0.417	0.250	0.500	0.500	0.500

right · index

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+K NN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+ RF+KNN+LogReg)
curl_curl	0.615	0.692	0.846	0.462	0.846	0.692	0.692	0.692	0.846
curl_straight	0.583	0.583	0.750	0.667	0.583	0.167	0.750	0.750	0.750
straight_curl	0.583	0.583	0.667	0.417	0.583	0.083	0.500	0.500	0.583
straight_straight	0.667	0.500	0.500	0.750	0.583	0.750	0.750	0.750	0.583

right · middle

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.538	0.615	0.385	0.615	0.462	0.538	0.538	0.538	0.538
curl_straight	0.417	0.667	0.333	0.333	0.500	0.167	0.333	0.333	0.417
straight_curl	0.417	0.500	0.583	0.500	0.500	0.250	0.417	0.417	0.500
straight_straight	0.500	0.250	0.583	0.500	0.417	0.333	0.417	0.417	0.333

right · ring

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.385	0.462	0.538	0.462	0.538	0.462	0.308	0.308	0.385
curl_straight	0.583	0.500	0.833	0.667	0.583	0.167	0.917	0.917	0.583
straight_curl	0.333	0.250	0.583	0.333	0.333	0.000	0.417	0.417	0.417
straight_straight	0.583	0.417	0.500	0.667	0.333	0.417	0.750	0.750	0.667

right · pinky

Finger	SVM (RBF)	SVM (Linear)	Random Forest	KNN	Logistic Regression	LDA	Voting Soft (SV M+RF+KNN+Log Reg)	Voting Soft (SV M+RF)	Stacking (SVM+RF+KNN+LogReg)
curl_curl	0.692	0.615	0.769	0.231	0.538	0.308	0.615	0.615	0.538
curl_straight	0.250	0.583	0.417	0.500	0.583	0.250	0.500	0.500	0.500
straight_curl	0.333	0.333	0.333	0.167	0.333	0.167	0.167	0.167	0.083
straight_straight	0.833	0.583	0.667	0.833	0.583	0.583	0.750	0.750	0.750