

Team notebook

August 27, 2016

Contents

1	BellmanFord
2	ConvexHull
3	Dijkstra
4	Dinic
5	Euclid
6	FastExpo
7	FastIO
8	FenwickTree
9	FenwickTree2D
10	FloydWar
11	Geom3D
12	Geometry
13	Kadane1DMaxSum
14	Kruskal
15	LCA
16	LongestIncreasingSubsequence

17	MaxFlow	19
18	Primes	19
19	RollingHash	20
20	SCC	21
21	SegmentTree	21
22	SuffixArray	25
23	UnionFind	25
1	BellmanFord	
11	<hr/>	
11	<code>// This function runs the Bellman-Ford algorithm for single source</code>	
11	<code>// shortest paths with negative edge weights. The function returns</code>	
12	<code>// false if a negative weight cycle is detected. Otherwise, the</code>	
12	<code>// function returns true and dist[i] is the length of the shortest</code>	
12	<code>// path from start to i.</code>	
12	<code>//</code>	
12	<code>// Running time: $O(V ^3)$</code>	
12	<code>//</code>	
16	<code>// INPUT: start, w[i][j] = cost of edge from i to j</code>	
16	<code>// OUTPUT: dist[i] = min weight path from start to i</code>	
16	<code>// prev[i] = previous node on the best path from the</code>	
16	<code>// start node</code>	
17	<code>#include <iostream></code>	
17	<code>#include <queue></code>	
18	<code>#include <cmath></code>	

```

#include <vector>

using namespace std;

typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

typedef vector<int> VI;
typedef vector<VI> VVI;

bool BellmanFord (const VVT &w, VT &dist, VI &prev, int start){
    int n = w.size();
    prev = VI(n, -1);
    dist = VT(n, 1000000000);
    dist[start] = 0;

    for (int k = 0; k < n; k++){
        for (int i = 0; i < n; i++){
            for (int j = 0; j < n; j++){
                if (dist[j] > dist[i] + w[i][j]){
                    if (k == n-1) return false;
                    dist[j] = dist[i] + w[i][j];
                    prev[j] = i;
                }
            }
        }
    }

    return true;
}

```

2 ConvexHull

```

#include <bits/stdc++.h>
using namespace std;

// Compute the 2D convex hull of a set of points using the monotone chain
// algorithm. Eliminate redundant points from the hull if
// REMOVE_REDUNDANT is
// #defined.
//

```

```

// Running time: O(n log n)
//
// INPUT: a vector of input points, unordered.
// OUTPUT: a vector of points in the convex hull, counterclockwise,
//         starting
//         with bottommost/leftmost point

#define REMOVE_REDUNDANT

typedef double T;
const T EPS = 1e-7;
struct PT {
    T x, y;
    PT() {}
    PT(T x, T y) : x(x), y(y) {}
    bool operator<(const PT &rhs) const { return make_pair(y,x) <
        make_pair(rhs.y,rhs.x); }
    bool operator==(const PT &rhs) const { return make_pair(y,x) ==
        make_pair(rhs.y,rhs.x); }
};

T cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
T area2(PT a, PT b, PT c) { return cross(a,b) + cross(b,c) + cross(c,a); }

#ifdef REMOVE_REDUNDANT
bool between(const PT &a, const PT &b, const PT &c) {
    return (fabs(area2(a,b,c)) < EPS && (a.x-b.x)*(c.x-b.x) <= 0 &&
        (a.y-b.y)*(c.y-b.y) <= 0);
}
#endif

void ConvexHull(vector<PT> &pts) {
    sort(pts.begin(), pts.end());
    pts.erase(unique(pts.begin(), pts.end()), pts.end());
    vector<PT> up, dn;
    for (int i = 0; i < pts.size(); i++) {
        while (up.size() > 1 && area2(up[up.size()-2], up.back(), pts[i]) >=
            0) up.pop_back();
        while (dn.size() > 1 && area2(dn[dn.size()-2], dn.back(), pts[i]) <=
            0) dn.pop_back();
        up.push_back(pts[i]);
        dn.push_back(pts[i]);
    }
    pts = dn;
    for (int i = (int) up.size() - 2; i >= 1; i--) pts.push_back(up[i]);
}

```

```

#ifdef REMOVE_REDUNDANT
    if (pts.size() <= 2) return;
    dn.clear();
    dn.push_back(pts[0]);
    dn.push_back(pts[1]);
    for (int i = 2; i < pts.size(); i++) {
        if (between(dn[dn.size()-2], dn[dn.size()-1], pts[i])) dn.pop_back();
        dn.push_back(pts[i]);
    }
    if (dn.size() >= 3 && between(dn.back(), dn[0], dn[1])) {
        dn[0] = dn.back();
        dn.pop_back();
    }
    pts = dn;
#endif
}

int main()
{
    vector<PT> pts(10);

    pts[0] = (PT(0,0));
    pts[1] = (PT(1,5));
    pts[2] = (PT(-4,7));
    pts[3] = (PT(8,9));
    pts[4] = (PT(20,20));
    pts[5] = (PT(1,1));
    pts[6] = (PT(-16,4));
    pts[7] = (PT(0,-20));
    pts[8] = (PT(30,45));
    pts[9] = (PT(20,0));

    ConvexHull(pts);

    for(PT pt:pts)
    {
        cout << pt.x << " " << pt.y << endl;
    }

    /*
    should print:
    0 -20
    20 0
    30 45

```

```

-16 4
*/

```

```

    return 0;
}

```

3 Dijkstra

```

// Implementation of Dijkstra's algorithm using adjacency lists
// and priority queue for efficiency.
//
// Running time: O(|E| log |V|)

```

```

#include <queue>
#include <stdio.h>

```

```

using namespace std;
const int INF = 2000000000;
typedef pair<int,int> PII;

```

```

int main(){

    int N, s, t;
    scanf ("%d%d%d", &N, &s, &t);
    vector<vector<PII> > edges(N);
    for (int i = 0; i < N; i++){
        int M;
        scanf ("%d", &M);
        for (int j = 0; j < M; j++){
            int vertex, dist;
            scanf ("%d%d", &vertex, &dist);
            edges[i].push_back (make_pair (dist, vertex)); // note order of
                arguments here
        }
    }
}

```

```

// use priority queue in which top element has the "smallest" priority
priority_queue<PII, vector<PII>, greater<PII> > Q;
vector<int> dist(N, INF), dad(N, -1);
Q.push (make_pair (0, s));
dist[s] = 0;

```

```

while (!Q.empty()){
    PII p = Q.top();
    if (p.second == t) break;
    Q.pop();

    int here = p.second;
    for (vector<PII>::iterator it=edges[here].begin();
        it!=edges[here].end(); it++){
        if (dist[here] + it->first < dist[it->second]){
            dist[it->second] = dist[here] + it->first;
            dad[it->second] = here;
            Q.push (make_pair (dist[it->second], it->second));
        }
    }
}

printf ("%d\n", dist[t]);
if (dist[t] < INF)
    for(int i=t; i!=-1; i=dad[i])
        printf ("%d%c", i, (i==s?'\\n':' '));

return 0;
}

```

4 Dinic

```

// Adjacency list implementation of Dinic's blocking flow algorithm.
// This is very fast in practice, and only loses to push-relabel flow.
//
// Running time:
//  $O(|V|^2 |E|)$ 
//
// INPUT:
// - graph, constructed using AddEdge()
// - source and sink
//
// OUTPUT:
// - maximum flow value
// - To obtain actual flow values, look at edges with capacity > 0
// (zero capacity edges are residual edges).

#include <iostream>

```

```

#include <vector>

using namespace std;
typedef long long LL;

struct Edge {
    int from, to, cap, flow, index;
    Edge(int from, int to, int cap, int flow, int index) :
        from(from), to(to), cap(cap), flow(flow), index(index) {}
    LL rcap() { return cap - flow; }
};

struct Dinic {
    int N;
    vector<vector<Edge> > G;
    vector<vector<Edge *> > Lf;
    vector<int> layer;
    vector<int> Q;

    Dinic(int N) : N(N), G(N), Q(N) {}

    void AddEdge(int from, int to, int cap) {
        if (from == to) return;
        G[from].push_back(Edge(from, to, cap, 0, G[to].size()));
        G[to].push_back(Edge(to, from, 0, 0, G[from].size() - 1));
    }

    LL BlockingFlow(int s, int t) {
        layer.clear(); layer.resize(N, -1);
        layer[s] = 0;
        Lf.clear(); Lf.resize(N);

        int head = 0, tail = 0;
        Q[tail++] = s;
        while (head < tail) {
            int x = Q[head++];
            for (int i = 0; i < G[x].size(); i++) {
                Edge &e = G[x][i]; if (e.rcap() <= 0) continue;
                if (layer[e.to] == -1) {
                    layer[e.to] = layer[e.from] + 1;
                    Q[tail++] = e.to;
                }
                if (layer[e.to] > layer[e.from]) {
                    Lf[e.from].push_back(&e);
                }
            }
        }
    }
}

```

```

    }
}
if (layer[t] == -1) return 0;

LL totflow = 0;
vector<Edge *> P;
while (!Lf[s].empty()) {
    int curr = P.empty() ? s : P.back()->to;
    if (curr == t) { // Augment
        LL amt = P.front()->rcap();
        for (int i = 0; i < P.size(); ++i) {
            amt = min(amt, P[i]->rcap());
        }
        totflow += amt;
        for (int i = P.size() - 1; i >= 0; --i) {
            P[i]->flow += amt;
            G[P[i]->to][P[i]->index].flow -= amt;
            if (P[i]->rcap() <= 0) {
                Lf[P[i]->from].pop_back();
                P.resize(i);
            }
        }
    }
    else if (Lf[curr].empty()) { // Retreat
        P.pop_back();
        for (int i = 0; i < N; ++i)
            for (int j = 0; j < Lf[i].size(); ++j)
                if (Lf[i][j]->to == curr)
                    Lf[i].erase(Lf[i].begin() + j);
    }
    else { // Advance
        P.push_back(Lf[curr].back());
    }
}
return totflow;
}

LL GetMaxFlow(int s, int t) {
    LL totflow = 0;
    while (LL flow = BlockingFlow(s, t))
        totflow += flow;
    return totflow;
}
};

// BEGIN CUT

```

// The following code solves SPOJ problem #4110: Fast Maximum Flow (FASTFLOW)

```

int main() {
    int n, m;
    scanf("%d%d", &n, &m);

    Dinic flow(n);
    for (int i = 0; i < m; i++) {
        int a, b, c;
        scanf("%d%d%d", &a, &b, &c);
        if (a == b) continue;
        flow.AddEdge(a-1, b-1, c);
        flow.AddEdge(b-1, a-1, c);
    }
    printf("%Ld\n", flow.GetMaxFlow(0, n-1));
    return 0;
}

// END CUT

```

5 Euclid

// This is a collection of useful code for solving problems that involve modular linear equations. Note that all of the algorithms described here work on nonnegative integers.

```

#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

typedef vector<int> VI;
typedef pair<int, int> PII;

// return a % b (positive value)
int mod(int a, int b) {
    return ((a%b) + b) % b;
}

// computes gcd(a,b)

```

```

int gcd(int a, int b) {
    while (b) { int t = a%b; a = b; b = t; }
    return a;
}

// computes lcm(a,b)
int lcm(int a, int b) {
    return a / gcd(a, b)*b;
}

// (a^b) mod m via successive squaring
int powermod(int a, int b, int m)
{
    int ret = 1;
    while (b)
    {
        if (b & 1) ret = mod(ret*a, m);
        a = mod(a*a, m);
        b >>= 1;
    }
    return ret;
}

// returns g = gcd(a, b); finds x, y such that d = ax + by
int extended_euclid(int a, int b, int &x, int &y) {
    int xx = y = 0;
    int yy = x = 1;
    while (b) {
        int q = a / b;
        int t = b; b = a%b; a = t;
        t = xx; xx = x - q*xx; x = t;
        t = yy; yy = y - q*yy; y = t;
    }
    return a;
}

// finds all solutions to ax = b (mod n)
VI modular_linear_equation_solver(int a, int b, int n) {
    int x, y;
    VI ret;
    int g = extended_euclid(a, n, x, y);
    if (!(b%g)) {
        x = mod(x*(b / g), n);
        for (int i = 0; i < g; i++)
            ret.push_back(mod(x + i*(n / g), n));
    }
}

```

```

    }
    return ret;
}

// computes b such that ab = 1 (mod n), returns -1 on failure
int mod_inverse(int a, int n) {
    int x, y;
    int g = extended_euclid(a, n, x, y);
    if (g > 1) return -1;
    return mod(x, n);
}

// Chinese remainder theorem (special case): find z such that
// z % m1 = r1, z % m2 = r2. Here, z is unique modulo M = lcm(m1, m2).
// Return (z, M). On failure, M = -1.
PII chinese_remainder_theorem(int m1, int r1, int m2, int r2) {
    int s, t;
    int g = extended_euclid(m1, m2, s, t);
    if (r1%g != r2%g) return make_pair(0, -1);
    return make_pair(mod(s*r2*m1 + t*r1*m2, m1*m2) / g, m1*m2 / g);
}

// Chinese remainder theorem: find z such that
// z % m[i] = r[i] for all i. Note that the solution is
// unique modulo M = lcm_i (m[i]). Return (z, M). On
// failure, M = -1. Note that we do not require the a[i]'s
// to be relatively prime.
PII chinese_remainder_theorem(const VI &m, const VI &r) {
    PII ret = make_pair(r[0], m[0]);
    for (int i = 1; i < m.size(); i++) {
        ret = chinese_remainder_theorem(ret.second, ret.first,
            m[i], r[i]);
        if (ret.second == -1) break;
    }
    return ret;
}

// computes x and y such that ax + by = c
// returns whether the solution exists
bool linear_diophantine(int a, int b, int c, int &x, int &y) {
    if (!a && !b)
    {
        if (c) return false;
        x = 0; y = 0;
        return true;
    }
}

```

```

}
if (!a)
{
    if (c % b) return false;
    x = 0; y = c / b;
    return true;
}
if (!b)
{
    if (c % a) return false;
    x = c / a; y = 0;
    return true;
}
int g = gcd(a, b);
if (c % g) return false;
x = c / g * mod_inverse(a / g, b / g);
y = (c - a*x) / b;
return true;
}

int main() {
    // expected: 2
    cout << gcd(14, 30) << endl;

    // expected: 2 -2 1
    int x, y;
    int g = extended_euclid(14, 30, x, y);
    cout << g << " " << x << " " << y << endl;

    // expected: 95 451
    VI sols = modular_linear_equation_solver(14, 30, 100);
    for (int i = 0; i < sols.size(); i++) cout << sols[i] << " ";
    cout << endl;

    // expected: 8
    cout << mod_inverse(8, 9) << endl;

    // expected: 23 105
    //          11 12
    PII ret = chinese_remainder_theorem(VI({ 3, 5, 7 }), VI({ 2, 3, 2
    }));
    cout << ret.first << " " << ret.second << endl;
    ret = chinese_remainder_theorem(VI({ 4, 6 }), VI({ 3, 5 }));
    cout << ret.first << " " << ret.second << endl;
}

```

```

// expected: 5 -15
if (!linear_diophantine(7, 2, 5, x, y)) cout << "ERROR" << endl;
cout << x << " " << y << endl;
return 0;
}

```

6 FastExpo

```

/*
Uses powers of two to exponentiate numbers and matrices. Calculates
n^k in O(log(k)) time when n is a number. If A is an n x n matrix,
calculates A^k in O(n^3*log(k)) time.
*/

#include <iostream>
#include <vector>

using namespace std;

typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

T power(T x, int k) {
    T ret = 1;

    while(k) {
        if(k & 1) ret *= x;
        k >>= 1; x *= x;
    }
    return ret;
}

VVT multiply(VVT& A, VVT& B) {
    int n = A.size(), m = A[0].size(), k = B[0].size();
    VVT C(n, VT(k, 0));

    for(int i = 0; i < n; i++)
        for(int j = 0; j < k; j++)
            for(int l = 0; l < m; l++)
                C[i][j] += A[i][l] * B[l][j];
}

```

```

    return C;
}

VVT power(VVT& A, int k) {
    int n = A.size();
    VVT ret(n, VT(n)), B = A;
    for(int i = 0; i < n; i++) ret[i][i]=1;

    while(k) {
        if(k & 1) ret = multiply(ret, B);
        k >>= 1; B = multiply(B, B);
    }
    return ret;
}

int main()
{
    /* Expected Output:
       2.37^48 = 9.72569e+17

       376 264 285 220 265
       550 376 529 285 484
       484 265 376 264 285
       285 220 265 156 264
       529 285 484 265 376 */
    double n = 2.37;
    int k = 48;

    cout << n << "^" << k << " = " << power(n, k) << endl;

    double At[5][5] = {
        { 0, 0, 1, 0, 0 },
        { 1, 0, 0, 1, 0 },
        { 0, 0, 0, 0, 1 },
        { 1, 0, 0, 0, 0 },
        { 0, 1, 0, 0, 0 } };

    vector <vector <double> > A(5, vector <double>(5));
    for(int i = 0; i < 5; i++)
        for(int j = 0; j < 5; j++)
            A[i][j] = At[i][j];

    vector <vector <double> > Ap = power(A, k);

    cout << endl;

```

```

for(int i = 0; i < 5; i++) {
    for(int j = 0; j < 5; j++)
        cout << Ap[i][j] << " ";
    cout << endl;
}
}

```

7 FastIO

```

import java.io.*;
import java.util.InputMismatchException;

/**
 * Created by Shreyans on $DATE at $TIME using IntelliJ IDEA (Fast IO
 * Template)
 */

class $NAME
{
    public static void main(String[] args) throws Exception
    {
        InputReader in = new InputReader(System.in);
        OutputWriter out = new OutputWriter(System.out);
        out.println("Hello World");
        {
            out.close();
        }
    }

    //FAST IO
    private static class InputReader
    {
        private InputStream stream;
        private byte[] buf = new byte[1024];
        private int curChar;
        private int numChars;
        private SpaceCharFilter filter;

        public InputReader(InputStream stream)
        {
            this.stream = stream;
        }
    }

```



```

public int read()
{
    if (numChars == -1)
        throw new InputMismatchException();
    if (curChar >= numChars)
    {
        curChar = 0;
        try
        {
            numChars = stream.read(buf);
        } catch (IOException e)
        {
            throw new InputMismatchException();
        }
        if (numChars <= 0)
            return -1;
    }
    return buf[curChar++];
}

public int readInt()
{
    int c = read();
    while (isSpaceChar(c))
        c = read();
    int sgn = 1;
    if (c == '-')
    {
        sgn = -1;
        c = read();
    }
    int res = 0;
    do
    {
        if (c < '0' || c > '9')
            throw new InputMismatchException();
        res *= 10;
        res += c - '0';
        c = read();
    } while (!isSpaceChar(c));
    return res * sgn;
}

public String readString()

```

```

{
    int c = read();
    while (isSpaceChar(c))
        c = read();
    StringBuilder res = new StringBuilder();
    do
    {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public double readDouble() {
    int c = read();
    while (isSpaceChar(c))
        c = read();
    int sgn = 1;
    if (c == '-') {
        sgn = -1;
        c = read();
    }
    double res = 0;
    while (!isSpaceChar(c) && c != '.' && c != 'E') {
        if (c == 'e' || c == 'E')
            return res * Math.pow(10, readInt());
        if (c < '0' || c > '9')
            throw new InputMismatchException();
        res *= 10;
        res += c - '0';
        c = read();
    }
    if (c == '.') {
        c = read();
        double m = 1;
        while (!isSpaceChar(c)) {
            if (c == 'e' || c == 'E')
                return res * Math.pow(10, readInt());
            if (c < '0' || c > '9')
                throw new InputMismatchException();
            m /= 10;
            res += (c - '0') * m;
            c = read();
        }
    }
    return res * sgn;
}

```

```

    }
    public long readLong() {
        int c = read();
        while (isSpaceChar(c))
            c = read();
        int sgn = 1;
        if (c == '-') {
            sgn = -1;
            c = read();
        }
        long res = 0;
        do {
            if (c < '0' || c > '9')
                throw new InputMismatchException();
            res *= 10;
            res += c - '0';
            c = read();
        } while (!isSpaceChar(c));
        return res * sgn;
    }
    public boolean isSpaceChar(int c)
    {
        if (filter != null)
            return filter.isSpaceChar(c);
        return c == ' ' || c == '\n' || c == '\r' || c == '\t' || c ==
            -1;
    }
    public String next()
    {
        return readString();
    }
    public interface SpaceCharFilter
    {
        public boolean isSpaceChar(int ch);
    }
}

private static class OutputWriter
{
    private final PrintWriter writer;

    public OutputWriter(OutputStream outputStream)
    {

```

```

        writer = new PrintWriter(new BufferedWriter(new
            OutputStreamWriter(outputStream)));
    }

    public OutputWriter(Writer writer)
    {
        this.writer = new PrintWriter(writer);
    }

    public void print(Object... objects)
    {
        for (int i = 0; i < objects.length; i++)
        {
            if (i != 0)
                writer.print(' ');
            writer.print(objects[i]);
        }
    }

    public void printLine(Object... objects)
    {
        print(objects);
        writer.println();
    }

    public void close()
    {
        writer.close();
    }

    public void flush()
    {
        writer.flush();
    }

    }
    /* USAGE

    //initialize
        InputReader in      = new InputReader(System.in);
        OutputWriter out    =      new OutputWriter(System.out);

    //read int
        int i = in.readInt();

    //read string

```

```

    String s = in.readString();
//read int array of size N
    int[] x = IOUtils.readIntArray(in,N);
//printline
    out.println("X");

//flush output
    out.flush();

//remember to close the
//outputstream, at the end
    out.close();

*/
/*class IOUtils {

    public static int[] readIntArray(InputReader in, int size) {
        int[] array = new int[size];
        for (int i = 0; i < size; i++)
            array[i] = in.readInt();
        return array;*/
}

```

8 FenwickTree

```

class FenwickTree {
private: vi ft;
    // recall that vi is: typedef vector<int> vi;
public:
    FenwickTree(long n) { ft.assign(n + 1, 0); }
    // init n + 1 zeroes
    long LSOne(long n){return (n & (-n));}
    long long rsq(long b)
    {
        // returns RSQ(1, b)
        long long sum = 0; for (; b; b -= LSOne(b)) sum += ft[b];
        return sum;
    }
    long long rsq(long a, long b)
    {
        return rsq(b) - (a == 1 ? 0 : rsq(a - 1));
    }
}

```

```

    }
    // adjusts value of the k-th element by v (v can be +ve/inc or
    // -ve/dec)
    void adjust(long k, long v)
    {
        // note: n = ft.size() - 1
        for (; k < (long)ft.size(); k += LSOne(k)) ft[k] += v;
    }
};

```

9 FenwickTree2D

```

long tree[max_xy][max_xy];

void update(long x , long y , long val){
    long y1;
    while (x <= max_xy){
        y1 = y;
        while (y1 <= max_xy){
            tree[x][y1] += val;
            y1 += (y1 & -y1);
        }
        x += (x & -x);
    }
}

long long read(long x,long y){ // return sum from 1,1 to x,y.
    long long sum= 0;
    while(x){
        long y1 = y;
        while(y1){
            sum += tree[x][y1];
            y1 -= y1 & -y1;
        }
        x -= x & -x;
    }
    return sum;
}

int main()
{
}

```

```

    long long suma = read(x2+1,y2+1) + read(x1,y1) - read(x2+1,y1) -
        read(x1,y2+1); //suma de rango entre x1,y1 y x2,y2
    update(x+1,y+1, num ); //aumenta en num
}

```

10 FloydWar

```

//ASSP!!!
// This function runs the Floyd-Warshall algorithm for all-pairs
// shortest paths. Also handles negative edge weights. Returns true
// if a negative weight cycle is found.
//
// Running time:  $O(|V|^3)$ 
//
// INPUT: w[i][j] = weight of edge from i to j
// OUTPUT: w[i][j] = shortest path from i to j
//         prev[i][j] = node before j on the best path starting at i

bool FloydWarshall (VVT &w, VVI &prev){
    int n = w.size();
    prev = VVI (n, VI(n, -1));

    for (int k = 0; k < n; k++){
        for (int i = 0; i < n; i++){
            for (int j = 0; j < n; j++){
                if (w[i][j] > w[i][k] + w[k][j]){
                    w[i][j] = w[i][k] + w[k][j];
                    prev[i][j] = k;
                }
            }
        }
    }

    // check for negative weight cycles
    for(int i=0;i<n;i++){
        if (w[i][i] < 0) return false;
    }
    return true;
}

```

11 Geom3D

```

public class Geom3D {
    // distance from point (x, y, z) to plane aX + bY + cZ + d = 0
    public static double ptPlaneDist(double x, double y, double z,
        double a, double b, double c, double d) {
        return Math.abs(a*x + b*y + c*z + d) / Math.sqrt(a*a + b*b + c*c);
    }

    // distance between parallel planes aX + bY + cZ + d1 = 0 and
    // aX + bY + cZ + d2 = 0
    public static double planePlaneDist(double a, double b, double c,
        double d1, double d2) {
        return Math.abs(d1 - d2) / Math.sqrt(a*a + b*b + c*c);
    }

    // distance from point (px, py, pz) to line (x1, y1, z1)-(x2, y2, z2)
    // (or ray, or segment; in the case of the ray, the endpoint is the
    // first point)
    public static final int LINE = 0;
    public static final int SEGMENT = 1;
    public static final int RAY = 2;
    public static double ptLineDistSq(double x1, double y1, double z1,
        double x2, double y2, double z2, double px, double py, double pz,
        int type) {
        double pd2 = (x1-x2)*(x1-x2) + (y1-y2)*(y1-y2) + (z1-z2)*(z1-z2);

        double x, y, z;
        if (pd2 == 0) {
            x = x1;
            y = y1;
            z = z1;
        } else {
            double u = ((px-x1)*(x2-x1) + (py-y1)*(y2-y1) + (pz-z1)*(z2-z1)) /
                pd2;
            x = x1 + u * (x2 - x1);
            y = y1 + u * (y2 - y1);
            z = z1 + u * (z2 - z1);
            if (type != LINE && u < 0) {
                x = x1;
                y = y1;
                z = z1;
            }
            if (type == SEGMENT && u > 1.0) {

```

```

        x = x2;
        y = y2;
        z = z2;
    }
}

return (x-px)*(x-px) + (y-py)*(y-py) + (z-pz)*(z-pz);
}

public static double ptLineDist(double x1, double y1, double z1,
    double x2, double y2, double z2, double px, double py, double pz,
    int type) {
    return Math.sqrt(ptLineDistSq(x1, y1, z1, x2, y2, z2, px, py, pz,
        type));
}
}

```

12 Geometry

// C++ routines for computational geometry.

```

#include <iostream>
#include <vector>
#include <cmath>
#include <cassert>

using namespace std;

double INF = 1e100;
double EPS = 1e-12;

struct PT {
    double x, y;
    PT() {}
    PT(double x, double y) : x(x), y(y) {}
    PT(const PT &p) : x(p.x), y(p.y) {}
    PT operator + (const PT &p) const { return PT(x+p.x, y+p.y); }
    PT operator - (const PT &p) const { return PT(x-p.x, y-p.y); }
    PT operator * (double c) const { return PT(x*c, y*c ); }
    PT operator / (double c) const { return PT(x/c, y/c ); }
};

```

```

double dot(PT p, PT q) { return p.x*q.x+p.y*q.y; }
double dist2(PT p, PT q) { return dot(p-q,p-q); }
double cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
ostream &operator<<(ostream &os, const PT &p) {
    os << "(" << p.x << ", " << p.y << ")";
}

```

```

// rotate a point CCW or CW around the origin
PT RotateCCW90(PT p) { return PT(-p.y,p.x); }
PT RotateCW90(PT p) { return PT(p.y,-p.x); }
PT RotateCCW(PT p, double t) {
    return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos(t));
}

```

```

// project point c onto line through a and b
// assuming a != b
PT ProjectPointLine(PT a, PT b, PT c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);
}

```

```

// project point c onto line segment through a and b
PT ProjectPointSegment(PT a, PT b, PT c) {
    double r = dot(b-a,b-a);
    if (fabs(r) < EPS) return a;
    r = dot(c-a, b-a)/r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b-a)*r;
}

```

```

// compute distance from c to segment between a and b
double DistancePointSegment(PT a, PT b, PT c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)));
}

```

```

// compute distance between point (x,y,z) and plane ax+by+cz=d
double DistancePointPlane(double x, double y, double z,
    double a, double b, double c, double d)
{
    return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);
}

```

```

// determine if lines from a to b and c to d are parallel or collinear
bool LinesParallel(PT a, PT b, PT c, PT d) {
    return fabs(cross(b-a, c-d)) < EPS;
}

```

```

}

bool LinesCollinear(PT a, PT b, PT c, PT d) {
    return LinesParallel(a, b, c, d)
        && fabs(cross(a-b, a-c)) < EPS
        && fabs(cross(c-d, c-a)) < EPS;
}

// determine if line segment from a to b intersects with
// line segment from c to d
bool SegmentsIntersect(PT a, PT b, PT c, PT d) {
    if (LinesCollinear(a, b, c, d)) {
        if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
            dist2(b, c) < EPS || dist2(b, d) < EPS) return true;
        if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-b, d-b) > 0)
            return false;
        return true;
    }
    if (cross(d-a, b-a) * cross(c-a, b-a) > 0) return false;
    if (cross(a-c, d-c) * cross(b-c, d-c) > 0) return false;
    return true;
}

// compute intersection of line passing through a and b
// with line passing through c and d, assuming that unique
// intersection exists; for segment intersection, check if
// segments intersect first
PT ComputeLineIntersection(PT a, PT b, PT c, PT d) {
    b=b-a; d=c-d; c=c-a;
    assert(dot(b, b) > EPS && dot(d, d) > EPS);
    return a + b*cross(c, d)/cross(b, d);
}

// compute center of circle given three points
PT ComputeCircleCenter(PT a, PT b, PT c) {
    b=(a+b)/2;
    c=(a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-b), c,
        c+RotateCW90(a-c));
}

// determine if point is in a possibly non-convex polygon (by William
// Randolph Franklin); returns 1 for strictly interior points, 0 for
// strictly exterior points, and 0 or 1 for the remaining points.
// Note that it is possible to convert this into an *exact* test using

```

```

// integer arithmetic by taking care of the division appropriately
// (making sure to deal with signs properly) and then by writing exact
// tests for checking point on polygon boundary
bool PointInPolygon(const vector<PT> &p, PT q) {
    bool c = 0;
    for (int i = 0; i < p.size(); i++){
        int j = (i+1)%p.size();
        if ((p[i].y <= q.y && q.y < p[j].y ||
            p[j].y <= q.y && q.y < p[i].y) &&
            q.x < p[i].x + (p[j].x - p[i].x) * (q.y - p[i].y) / (p[j].y -
            p[i].y))
            c = !c;
    }
    return c;
}

// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<PT> &p, PT q) {
    for (int i = 0; i < p.size(); i++)
        if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()], q), q) < EPS)
            return true;
    return false;
}

// compute intersection of line through points a and b with
// circle centered at c with radius r > 0
vector<PT> CircleLineIntersection(PT a, PT b, PT c, double r) {
    vector<PT> ret;
    b = b-a;
    a = a-c;
    double A = dot(b, b);
    double B = dot(a, b);
    double C = dot(a, a) - r*r;
    double D = B*B - A*C;
    if (D < -EPS) return ret;
    ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
    if (D > EPS)
        ret.push_back(c+a+b*(-B-sqrt(D))/A);
    return ret;
}

// compute intersection of circle centered at a with radius r
// with circle centered at b with radius R
vector<PT> CircleCircleIntersection(PT a, PT b, double r, double R) {
    vector<PT> ret;

```

```

double d = sqrt(dist2(a, b));
if (d > r+R || d+min(r, R) < max(r, R)) return ret;
double x = (d*d-R*R+r*r)/(2*d);
double y = sqrt(r*r-x*x);
PT v = (b-a)/d;
ret.push_back(a+v*x + RotateCCW90(v)*y);
if (y > 0)
    ret.push_back(a+v*x - RotateCCW90(v)*y);
return ret;
}

// This code computes the area or centroid of a (possibly nonconvex)
// polygon, assuming that the coordinates are listed in a clockwise or
// counterclockwise fashion. Note that the centroid is often known as
// the "center of gravity" or "center of mass".
double ComputeSignedArea(const vector<PT> &p) {
    double area = 0;
    for(int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        area += p[i].x*p[j].y - p[j].x*p[i].y;
    }
    return area / 2.0;
}

double ComputeArea(const vector<PT> &p) {
    return fabs(ComputeSignedArea(p));
}

PT ComputeCentroid(const vector<PT> &p) {
    PT c(0,0);
    double scale = 6.0 * ComputeSignedArea(p);
    for (int i = 0; i < p.size(); i++){
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*(p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

// tests whether or not a given polygon (in CW or CCW order) is simple
bool IsSimple(const vector<PT> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == l || j == k) continue;

```

```

        if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
            return false;
        }
    }
    return true;
}

int main() {

    // expected: (-5,2)
    cerr << RotateCCW90(PT(2,5)) << endl;

    // expected: (5,-2)
    cerr << RotateCW90(PT(2,5)) << endl;

    // expected: (-5,2)
    cerr << RotateCCW(PT(2,5),M_PI/2) << endl;

    // expected: (5,2)
    cerr << ProjectPointLine(PT(-5,-2), PT(10,4), PT(3,7)) << endl;

    // expected: (5,2) (7.5,3) (2.5,1)
    cerr << ProjectPointSegment(PT(-5,-2), PT(10,4), PT(3,7)) << " "
        << ProjectPointSegment(PT(7.5,3), PT(10,4), PT(3,7)) << " "
        << ProjectPointSegment(PT(-5,-2), PT(2.5,1), PT(3,7)) << endl;

    // expected: 6.78903
    cerr << DistancePointPlane(4,-4,3,2,-2,5,-8) << endl;

    // expected: 1 0 1
    cerr << LinesParallel(PT(1,1), PT(3,5), PT(2,1), PT(4,5)) << " "
        << LinesParallel(PT(1,1), PT(3,5), PT(2,0), PT(4,5)) << " "
        << LinesParallel(PT(1,1), PT(3,5), PT(5,9), PT(7,13)) << endl;

    // expected: 0 0 1
    cerr << LinesCollinear(PT(1,1), PT(3,5), PT(2,1), PT(4,5)) << " "
        << LinesCollinear(PT(1,1), PT(3,5), PT(2,0), PT(4,5)) << " "
        << LinesCollinear(PT(1,1), PT(3,5), PT(5,9), PT(7,13)) << endl;

    // expected: 1 1 1 0
    cerr << SegmentsIntersect(PT(0,0), PT(2,4), PT(3,1), PT(-1,3)) << " "
        << SegmentsIntersect(PT(0,0), PT(2,4), PT(4,3), PT(0,5)) << " "
        << SegmentsIntersect(PT(0,0), PT(2,4), PT(2,-1), PT(-2,1)) << " "
        << SegmentsIntersect(PT(0,0), PT(2,4), PT(5,5), PT(1,7)) << endl;
}

```

```

// expected: (1,2)
cerr << ComputeLineIntersection(PT(0,0), PT(2,4), PT(3,1), PT(-1,3)) << endl;

// expected: (1,1)
cerr << ComputeCircleCenter(PT(-3,4), PT(6,1), PT(4,5)) << endl;

vector<PT> v;
v.push_back(PT(0,0));
v.push_back(PT(5,0));
v.push_back(PT(5,5));
v.push_back(PT(0,5));

// expected: 1 1 1 0 0
cerr << PointInPolygon(v, PT(2,2)) << " "
    << PointInPolygon(v, PT(2,0)) << " "
    << PointInPolygon(v, PT(0,2)) << " "
    << PointInPolygon(v, PT(5,2)) << " "
    << PointInPolygon(v, PT(2,5)) << endl;

// expected: 0 1 1 1 1
cerr << PointOnPolygon(v, PT(2,2)) << " "
    << PointOnPolygon(v, PT(2,0)) << " "
    << PointOnPolygon(v, PT(0,2)) << " "
    << PointOnPolygon(v, PT(5,2)) << " "
    << PointOnPolygon(v, PT(2,5)) << endl;

// expected: (1,6)
//      (5,4) (4,5)
//      blank line
//      (4,5) (5,4)
//      blank line
//      (4,5) (5,4)
vector<PT> u = CircleLineIntersection(PT(0,6), PT(2,6), PT(1,1), 5);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
u = CircleLineIntersection(PT(0,9), PT(9,0), PT(1,1), 5);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
u = CircleCircleIntersection(PT(1,1), PT(10,10), 5, 5);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
u = CircleCircleIntersection(PT(1,1), PT(8,8), 5, 5);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
u = CircleCircleIntersection(PT(1,1), PT(4.5,4.5), 10, sqrt(2.0)/2.0);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
u = CircleCircleIntersection(PT(1,1), PT(4.5,4.5), 5, sqrt(2.0)/2.0);
for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;

```

```

// area should be 5.0
// centroid should be (1.1666666, 1.166666)
PT pa[] = { PT(0,0), PT(5,0), PT(1,1), PT(0,5) };
vector<PT> p(pa, pa+4);
PT c = ComputeCentroid(p);
cerr << "Area: " << ComputeArea(p) << endl;
cerr << "Centroid: " << c << endl;

return 0;
}

```

13 Kadane1DMaxSum

```

#include <bits/stdc++.h>

using namespace std;

int max1DSum(int* arr,int size)
{
    int max_ending_here,max_so_far;
    max_ending_here = max_so_far = arr[0];
    for (int i = 1; i < size; ++i)
    {
        max_ending_here = max(arr[i],max_ending_here + arr[i]);
        max_so_far = max(max_so_far, max_ending_here);
    }
    return max_so_far;
}

int main()
{
    int arr[9] = {5,3, -16,7,-8,9,10,-14,33};
    //print: max 1D sum = 38
    cout << "max 1D sum = " << max1DSum(arr,9) << endl;
    return 0;
}

```

14 Kruskal


```

/*
Uses Kruskal's Algorithm to calculate the weight of the minimum spanning
forest (union of minimum spanning trees of each connected component) of
a possibly disjoint graph, given in the form of a matrix of edge weights
(-1 if no edge exists). Returns the weight of the minimum spanning
forest (also calculates the actual edges - stored in T). Note: uses a
disjoint-set data structure with amortized (effectively) constant time per
union/find. Runs in  $O(E \log(E))$  time.
*/

#include <iostream>
#include <vector>
#include <algorithm>
#include <queue>

using namespace std;

typedef int T;

struct edge
{
    int u, v;
    T d;
};

struct edgeCmp
{
    int operator()(const edge& a, const edge& b) { return a.d > b.d; }
};

int find(vector<int>& C, int x) { return (C[x] == x) ? x : C[x] = find(C, C[x]); }

T Kruskal(vector<vector<T>>& w)
{
    int n = w.size();
    T weight = 0;

    vector<int> C(n), R(n);
    for(int i=0; i<n; i++) { C[i] = i; R[i] = 0; }

    vector<edge> T;
    priority_queue<edge, vector<edge>, edgeCmp> E;

    for(int i=0; i<n; i++)
        for(int j=i+1; j<n; j++)
            if(w[i][j] >= 0)
            {
                edge e;
                e.u = i; e.v = j; e.d = w[i][j];
                E.push(e);
            }

    while(T.size() < n-1 && !E.empty())
    {
        edge cur = E.top(); E.pop();

        int uc = find(C, cur.u), vc = find(C, cur.v);
        if(uc != vc)
        {
            T.push_back(cur); weight += cur.d;

            if(R[uc] > R[vc]) C[vc] = uc;
            else if(R[vc] > R[uc]) C[uc] = vc;
            else { C[vc] = uc; R[uc]++; }
        }
    }

    return weight;
}

int main()
{
    int wa[6][6] = {
        { 0, -1, 2, -1, 7, -1 },
        { -1, 0, -1, 2, -1, -1 },
        { 2, -1, 0, -1, 8, 6 },
        { -1, 2, -1, 0, -1, -1 },
        { 7, -1, 8, -1, 0, 4 },
        { -1, -1, 6, -1, 4, 0 } };

    vector<vector<int>> w(6, vector<int>(6));

    for(int i=0; i<6; i++)
        for(int j=0; j<6; j++)
            w[i][j] = wa[i][j];

    cout << Kruskal(w) << endl;
    cin >> wa[0][0];
}

```

```

for(int i=0; i<n; i++)
    for(int j=i+1; j<n; j++)
        if(w[i][j] >= 0)
        {
            edge e;
            e.u = i; e.v = j; e.d = w[i][j];
            E.push(e);
        }

while(T.size() < n-1 && !E.empty())
{
    edge cur = E.top(); E.pop();

    int uc = find(C, cur.u), vc = find(C, cur.v);
    if(uc != vc)
    {
        T.push_back(cur); weight += cur.d;

        if(R[uc] > R[vc]) C[vc] = uc;
        else if(R[vc] > R[uc]) C[uc] = vc;
        else { C[vc] = uc; R[uc]++; }
    }
}

return weight;
}

int main()
{
    int wa[6][6] = {
        { 0, -1, 2, -1, 7, -1 },
        { -1, 0, -1, 2, -1, -1 },
        { 2, -1, 0, -1, 8, 6 },
        { -1, 2, -1, 0, -1, -1 },
        { 7, -1, 8, -1, 0, 4 },
        { -1, -1, 6, -1, 4, 0 } };

    vector<vector<int>> w(6, vector<int>(6));

    for(int i=0; i<6; i++)
        for(int j=0; j<6; j++)
            w[i][j] = wa[i][j];

    cout << Kruskal(w) << endl;
    cin >> wa[0][0];
}

```

```
}
```

15 LCA

```
const int max_nodes, log_max_nodes;
int num_nodes, log_num_nodes, root;

vector<int> children[max_nodes]; // children[i] contains the children
    of node i
int A[max_nodes][log_max_nodes+1]; // A[i][j] is the 2^j-th ancestor of
    node i, or -1 if that ancestor does not exist
int L[max_nodes]; // L[i] is the distance between node
    i and the root

// floor of the binary logarithm of n
int lb(unsigned int n)
{
    if(n==0)
        return -1;
    int p = 0;
    if (n >= 1<<16) { n >>= 16; p += 16; }
    if (n >= 1<< 8) { n >>= 8; p += 8; }
    if (n >= 1<< 4) { n >>= 4; p += 4; }
    if (n >= 1<< 2) { n >>= 2; p += 2; }
    if (n >= 1<< 1) { p += 1; }
    return p;
}

void DFS(int i, int l)
{
    L[i] = l;
    for(int j = 0; j < children[i].size(); j++)
        DFS(children[i][j], l+1);
}

int LCA(int p, int q)
{
    // ensure node p is at least as deep as node q
    if(L[p] < L[q])
        swap(p, q);
```

```
    // "binary search" for the ancestor of node p situated on the same
        level as q
    for(int i = log_num_nodes; i >= 0; i--)
        if(L[p] - (1<<i) >= L[q])
            p = A[p][i];

    if(p == q)
        return p;

    // "binary search" for the LCA
    for(int i = log_num_nodes; i >= 0; i--)
        if(A[p][i] != -1 && A[p][i] != A[q][i])
        {
            p = A[p][i];
            q = A[q][i];
        }

    return A[p][0];
}

int main(int argc, char* argv[])
{
    // read num_nodes, the total number of nodes
    log_num_nodes=lb(num_nodes);

    for(int i = 0; i < num_nodes; i++)
    {
        int p;
        // read p, the parent of node i or -1 if node i is the root

        A[i][0] = p;
        if(p != -1)
            children[p].push_back(i);
        else
            root = i;
    }

    // precompute A using dynamic programming
    for(int j = 1; j <= log_num_nodes; j++)
        for(int i = 0; i < num_nodes; i++)
            if(A[i][j-1] != -1)
                A[i][j] = A[A[i][j-1]][j-1];
            else
                A[i][j] = -1;
```

```

    // precompute L
    DFS(root, 0);

    return 0;
}

```

16 LongestIncreasingSubsequence

```

// Given a list of numbers of length n, this routine extracts a
// longest increasing subsequence.
//
// Running time: O(n log n)
//
// INPUT: a vector of integers
// OUTPUT: a vector containing the longest increasing subsequence

```

```

#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

typedef vector<int> VI;
typedef pair<int,int> PII;
typedef vector<PII> VPII;

#define STRICTLY_INCREASNG

VI LongestIncreasingSubsequence(VI v) {
    VPII best;
    VI dad(v.size(), -1);

    for (int i = 0; i < v.size(); i++) {
#ifdef STRICTLY_INCREASNG
        PII item = make_pair(v[i], 0);
        VPII::iterator it = lower_bound(best.begin(), best.end(), item);
        item.second = i;
#else
        PII item = make_pair(v[i], i);
        VPII::iterator it = upper_bound(best.begin(), best.end(), item);
#endif
    }
}

```

```

    if (it == best.end()) {
        dad[i] = (best.size() == 0 ? -1 : best.back().second);
        best.push_back(item);
    } else {
        dad[i] = dad[it->second];
        *it = item;
    }
}

VI ret;
for (int i = best.back().second; i >= 0; i = dad[i])
    ret.push_back(v[i]);
reverse(ret.begin(), ret.end());
return ret;
}

```

17 MaxFlow

```

vector<vector<long>> res; //adj
vector<vi> edgeflows; //edge flow

long mf, f, s, t; // global variables
vi p; // p stores the BFS spanning tree from s

void augment(long v, long minEdge)
{ // traverse BFS spanning tree from s->t
    if (v == s) { f = minEdge; return; } // record minEdge in a global
    var f
    else if (p[v] != -1)
    {
        augment(p[v], min(minEdge, edgeflows[p[v]][v]));
        edgeflows[p[v]][v] -= f; edgeflows[v][p[v]] += f;
    }
}

int main()// inside int main(): set up res, s, and t with
appropriate values
{
    while (1)
    {

```

```

f = 0;

vi dist(MAX_V, INF); dist[s] = 0; queue<long> q; q.push(s);
p.assign(MAX_V, -1); // record the BFS spanning tree, from
    s to t!
while (!q.empty())
{
    long u = q.front(); q.pop();
    if (u == t) break; // immediately stop BFS if we
        already reach sink t
    for (long v:res[u]) // note: this part is slow
        if (edgeflows[u][v] > 0 && dist[v] == INF)
            dist[v] = dist[u] + 1, q.push(v),
                p[v] = u; // 3 lines in 1!
}

augment(t, INF); // find the min edge weight f in this
    path, if any
if (f == 0) break; // we cannot send any more flow (f =
    0), terminate
mf += f; // we can still send a flow, increase the max
    flow!
}
printf("%ld\n", mf);
}

```

18 Primes

```

// O(sqrt(x)) Exhaustive Primality Test
#include <cmath>
#define EPS 1e-7
typedef long long LL;
bool IsPrimeSlow (LL x)
{
    if(x<=1) return false;
    if(x<=3) return true;
    if (!(x%2) || !(x%3)) return false;
    LL s=(LL)(sqrt((double)(x))+EPS);
    for(LL i=5;i<=s;i+=6)
    {
        if (!(x%i) || !(x%(i+2))) return false;
    }
}

```

```

}
return true;
}

// Primes less than 1000:
//   2   3   5   7   11  13  17  19  23  29  31  37
//   41  43  47  53  59  61  67  71  73  79  83  89
//   97 101 103 107 109 113 127 131 137 139 149 151
//  157 163 167 173 179 181 191 193 197 199 211 223
//  227 229 233 239 241 251 257 263 269 271 277 281
//  283 293 307 311 313 317 331 337 347 349 353 359
//  367 373 379 383 389 397 401 409 419 421 431 433
//  439 443 449 457 461 463 467 479 487 491 499 503
//  509 521 523 541 547 557 563 569 571 577 587 593
//  599 601 607 613 617 619 631 641 643 647 653 659
//  661 673 677 683 691 701 709 719 727 733 739 743
//  751 757 761 769 773 787 797 809 811 821 823 827
//  829 839 853 857 859 863 877 881 883 887 907 911
//  919 929 937 941 947 953 967 971 977 983 991 997

// Other primes:
//   The largest prime smaller than 10 is 7.
//   The largest prime smaller than 100 is 97.
//   The largest prime smaller than 1000 is 997.
//   The largest prime smaller than 10000 is 9973.
//   The largest prime smaller than 100000 is 99991.
//   The largest prime smaller than 1000000 is 999983.
//   The largest prime smaller than 10000000 is 9999991.
//   The largest prime smaller than 100000000 is 99999989.
//   The largest prime smaller than 1000000000 is 999999937.
//   The largest prime smaller than 10000000000 is 999999967.
//   The largest prime smaller than 100000000000 is 9999999977.
//   The largest prime smaller than 1000000000000 is 9999999989.
//   The largest prime smaller than 10000000000000 is 99999999971.
//   The largest prime smaller than 100000000000000 is 999999999973.
//   The largest prime smaller than 1000000000000000 is 9999999999989.
//   The largest prime smaller than 10000000000000000 is
999999999999937.
//   The largest prime smaller than 100000000000000000 is
999999999999997.
//   The largest prime smaller than 1000000000000000000 is
9999999999999989.

```

19 RollingHash

```
#include <bits/stdc++.h>
using namespace std;

struct RollingHash
{
    string s;
    const long L;
    long long hashValue;
    long ini;
    long end;
    long long base;

    RollingHash(const string &s, long
        hlength): L(hlength), s(s), ini(0), end(L-1), hashValue(0)
    {
        base = 1;
        for (long i = L-1; i >= 0; --i)
        {
            //hashValue += (s[i])<<((L-1) - i);
            hashValue += s[i] * base;
            if(i!=0)base*=127;
        }
    }

    long long getHashValue(){return hashValue;}

    //returns the next hash value. If the last value is reached, next
    //calls will return the last value.
    long long nextHashValue()
    {
        if(end == s.length()) return hashValue;
        hashValue -= (s[ini] * base); //<< (L-1);
        hashValue*=127;
        hashValue+= (s[end+1]);
        ini++;
        end++;
        return hashValue;
    }

    void reset()
    {
        hashValue = 0;
    }
};
```

```
        for (long i = 0; i < L; ++i)
        {
            hashValue += (s[i])<<((L-1) - i);
        }
        end = end - ini;
        ini = 0;
    }

    bool finished()
    {
        return end==s.length();
    }
};

int main()
{
    string s1 = "aggg";
    string s2 = "aggtmreaggaggtmreagg";

    RollingHash RH(s1,s1.length());
    long long h1 = RH.getHashValue();

    RollingHash RH2(s2,s1.length());

    long long count = RH2.getHashValue()==h1?1:0;
    while(!RH2.finished())
    {
        if(RH2.nextHashValue()==h1)count++;
    }

    //occurrences of "agg" in "aggtmreaggaggtmreagg" are 4
    cout << "occurrences of \""<< s1 << "\" in \""<< s2<< "\" are "<<
        count << endl;
}
```

20 SCC

```
#define INF INT_MAX;

vector<vii> AdjList;
vi dfs_num, dfs_low, S, visited;
```

```

int dfsNumberCounter, numSCC, UNVISITED=-1, VISITED=1;

void tarjanSCC(int u)
{
    dfs_low[u] = dfs_num[u] = dfsNumberCounter++; // dfs_low[u] <=
        dfs_num[u]
    S.push_back(u);
    // stores u in a vector based on order of visitation
    visited[u] = 1;
    for (int j = 0; j < (int)AdjList[u].size(); j++)
    {
        int v = AdjList[u][j];
        if (dfs_num[v.first] == UNVISITED)
            tarjanSCC(v.first);
        if (visited[v.first])
            // condition for update
            dfs_low[u] = min(dfs_low[u], dfs_low[v.first]);
    }
    if (dfs_low[u] == dfs_num[u])
    {
        bool agg = false;
        while (1)
        {
            int v = S.back(); S.pop_back(); visited[v] = 0;
            //aca se ouede imprimir la visita si es necesario
            if (u == v) break;
        }
    }
}

```

21 SegmentTree

```

#include <bits/stdc++.h>

using namespace std;

typedef vector<long long> vi;

#define MAX (1+(1<<6)) // Why? :D
#define inf 0x7fffffff //9223372036854775807 max llong

//st para max queries

```

```

class SegmentTree
{
private:
    int N;
    vi arr;
    long long tree[MAX];
    long long lazy[MAX];

    /**
     * Build and init tree
     */
    void build_tree(long long node, long long a, long long b) {
        if(a > b) return; // Out of range

        if(a == b) { // Leaf node
            tree[node] = arr[a]; // Init value
            return;
        }

        build_tree(node*2, a, (a+b)/2); // Init left child
        build_tree(node*2+1, 1+(a+b)/2, b); // Init right child

        tree[node] = max(tree[node*2], tree[node*2+1]); // Init
            root value
    }

    /**
     * Increment elements within range [i, j] with value value
     */
    void update_tree(long long node, long long a, long long b, long
        long i, long long j, long long value) {

        if(lazy[node] != 0) { // This node needs to be updated
            tree[node] += lazy[node]; // Update it

            if(a != b) {
                lazy[node*2] += lazy[node]; // Mark child as
                    lazy
                lazy[node*2+1] += lazy[node]; // Mark child
                    as lazy
            }

            lazy[node] = 0; // Reset it
        }
    }
}

```

```

    if(a > b || a > j || b < i) // Current segment is not
        within range [i, j]
        return;

    if(a >= i && b <= j) { // Segment is fully within range
        tree[node] += value;

        if(a != b) { // Not leaf node
            lazy[node*2] += value;
            lazy[node*2+1] += value;
        }

        return;
    }

    update_tree(node*2, a, (a+b)/2, i, j, value); // Updating
        left child
    update_tree(1+node*2, 1+(a+b)/2, b, i, j, value); //
        Updating right child

    tree[node] = max(tree[node*2], tree[node*2+1]); //
        Updating root with max value
}

/**
 * Query tree to get max element value within range [i, j]
 */
long long query_tree(long long node, long long a, long long b,
    long long i, long long j) {

    if(a > b || a > j || b < i) return -inf; // Out of range

    if(lazy[node] != 0) { // This node needs to be updated
        tree[node] += lazy[node]; // Update it

        if(a != b) {
            lazy[node*2] += lazy[node]; // Mark child as
                lazy
            lazy[node*2+1] += lazy[node]; // Mark child
                as lazy
        }

        lazy[node] = 0; // Reset it
    }
}

```

```

    if(a >= i && b <= j) // Current segment is totally within
        range [i, j]
        return tree[node];

    long long q1 = query_tree(node*2, a, (a+b)/2, i, j); //
        Query left child
    long long q2 = query_tree(1+node*2, 1+(a+b)/2, b, i, j);
        // Query right child

    long long res = max(q1, q2); // Return final result

    return res;
}

public:

    SegmentTree(long long N):N(N)
    {
        arr.assign(N,0);
        build_tree(1, 0, N-1);
        memset(lazy, 0, sizeof lazy);
    }

    void update(long long i, long long j, long long v)
    {
        update_tree(1, 0, N-1, i, j, v);
    }

    long long rmq(long long i, long long j)
    {
        query_tree(1, 0, N-1, i, j);
    }
};

//st para sum queries
class SegmentTreeSum
{
private:
    int N;
    vi arr;
    long long tree[MAX];
    long long lazy[MAX];

    /**
     * Build and init tree
     */
}

```

```

void build_tree(long long node, long long a, long long b) {
    if(a > b) return; // Out of range

    if(a == b) { // Leaf node
        tree[node] = arr[a]; // Init value
        return;
    }

    build_tree(node*2, a, (a+b)/2); // Init left child
    build_tree(node*2+1, 1+(a+b)/2, b); // Init right child

    tree[node] = tree[node*2] + tree[node*2+1]; // Init root
    value
}

/**
 * Increment elements within range [i, j] with value value
 */
void update_tree(long long node, long long a, long long b, long
long i, long long j, long long value) {

    if(lazy[node] != 0) { // This node needs to be updated
        tree[node] += (b-a+1)*lazy[node]; // Update it

        if(a != b) {
            lazy[node*2] += lazy[node]; // Mark child as
            lazy
            lazy[node*2+1] += lazy[node]; // Mark child
            as lazy
        }

        lazy[node] = 0; // Reset it
    }

    if(a > b || a > j || b < i) // Current segment is not
        within range [i, j]
        return;

    if(a >= i && b <= j) { // Segment is fully within range
        tree[node] += (b-a+1)*value;

        if(a != b) { // Not leaf node
            lazy[node*2] += value;
            lazy[node*2+1] += value;
        }
    }
}

```

```

        return;
    }

    update_tree(node*2, a, (a+b)/2, i, j, value); // Updating
        left child
    update_tree(1+node*2, 1+(a+b)/2, b, i, j, value); //
        Updating right child

    tree[node] = (tree[node*2] + tree[node*2+1]); // Updating
        root with max value
}

/**
 * Query tree to get max element value within range [i, j]
 */
long long query_tree(long long node, long long a, long long b,
long long i, long long j) {

    if(a > b || a > j || b < i) return 0; // Out of range

    if(lazy[node] != 0) { // This node needs to be updated
        tree[node] += (b-a+1)*lazy[node]; // Update it

        if(a != b) {
            lazy[node*2] += lazy[node]; // Mark child as
            lazy
            lazy[node*2+1] += lazy[node]; // Mark child
            as lazy
        }

        lazy[node] = 0; // Reset it
    }

    if(a >= i && b <= j) // Current segment is totally within
        range [i, j]
        return tree[node];

    long long q1 = query_tree(node*2, a, (a+b)/2, i, j); //
        Query left child
    long long q2 = query_tree(1+node*2, 1+(a+b)/2, b, i, j);
        // Query right child

    long long res = (q1 + q2); // Return final result
}

```



```

        return res;
    }
public:

    SegmentTreeSum(long long N):N(N)
    {
        arr.assign(N,0);
        build_tree(1, 0, N-1);
        memset(lazy, 0, sizeof lazy);
    }

    void update(long long i,long long j, long long v)
    {
        update_tree(1, 0, N-1, i, j, v);
    }

    long long rsq(long long i,long long j)
    {
        return query_tree(1, 0, N-1, i, j);
    }
};

int main()
{
    int N = 20;
    SegmentTree st(N);
    st.update(0, 6, 5); // Increment range [0, 6] by 5. here 0, N-1
                        // represent the current range.
    st.update(7, 10, 12); // Increment range [7, 10] by 12. here 0,
                        // N-1 represent the current range.
    st.update(11, N-1, 100); // Increment range [10, N-1] by 100. here
                        // 0, N-1 represent the current range.

    cout << st.rmqs(0, N-1) << endl; // Get max element in range [0,
    // N-1]
    return 0;
}

```

22 SuffixArray

// Suffix array construction in $O(L \log^2 L)$ time. Routine for
 // computing the length of the longest common prefix of any two

```

// suffixes in  $O(\log L)$  time.
//
// INPUT:  string s
//
// OUTPUT: array suffix[] such that suffix[i] = index (from 0 to L-1)
//         of substring s[i...L-1] in the list of sorted suffixes.
//         That is, if we take the inverse of the permutation suffix[],
//         we get the actual suffix array.

#include <bits/stdc++.h>

using namespace std;

struct SuffixArray {
    const int L;
    string s;
    vector<vector<int>> > P;
    vector<pair<pair<int,int>,int> > M;

    SuffixArray(const string &s) : L(s.length()), s(s), P(1, vector<int>(L,
        0)), M(L) {
        for (int i = 0; i < L; i++) P[0][i] = int(s[i]);
        for (int skip = 1, level = 1; skip < L; skip *= 2, level++) {
            P.push_back(vector<int>(L, 0));
            for (int i = 0; i < L; i++)
                M[i] = make_pair(make_pair(P[level-1][i], i + skip < L ?
                    P[level-1][i + skip] : -1000), i);
            sort(M.begin(), M.end());
            for (int i = 0; i < L; i++)
                P[level][M[i].second] = (i > 0 && M[i].first == M[i-1].first) ?
                    P[level][M[i-1].second] : i;
        }
    }

    vector<int> GetSuffixArray() { return P.back(); }

    // returns the length of the longest common prefix of s[i...L-1] and
    // s[j...L-1]
    int LongestCommonPrefix(int i, int j) {
        int len = 0;
        if (i == j) return L - i;
        for (int k = P.size() - 1; k >= 0 && i < L && j < L; k--) {
            if (P[k][i] == P[k][j]) {
                i += 1 << k;
                j += 1 << k;
            }
        }
    }
}

```

```

        len += 1 << k;
    }
}
return len;
}
};

int main() {

    // bobocel is the 0'th suffix
    // obocel is the 5'th suffix
    // bocel is the 1'st suffix
    // ocel is the 6'th suffix
    // cel is the 2'nd suffix
    // el is the 3'rd suffix
    // l is the 4'th suffix
    string s = "amandamandaamandamanda";
    SuffixArray suffix(s);
    vector<int> v = suffix.GetSuffixArray();

    // Expected output: 0 5 1 6 2 3 4
    //                2
    for (int i = 0; i < v.size(); i++) cout << v[i] << " ";
    cout << endl;
    vector<int> v2(v.size(),0);
    for (int i = 0; i < v.size(); i++)
    {
        v2[v[i]] = i;
    }
    for(int n:v2)
    {
        cout << s.substr(n) << endl;
    }
}

```

23 UnionFind

```

#include <iostream>
#include <vector>
using namespace std;

//map implementation, requires c++11

```

```

class UnionFind
{
    private: unordered_map<int,int> p, rank; // remember: vi is
           vector<int>
    public:
        UnionFind(int N)
        {
            //rank.assign(N, 0);
            //p.assign(N, 0);
            //for (int i = 0; i < N; i++) p[i] = i;
        }
        int findSet(int i) { if(p.count(i)==0)p[i]=i; return (p[i]
            == i) ? i : (p[i] = findSet(p[i])); }
        bool isSameSet(int i, int j) { return findSet(i) ==
            findSet(j); }
        void unionSet(int i, int j)
        {
            if (!isSameSet(i, j))
            { // if from different set
                int x = findSet(i), y = findSet(j);
                if (rank[x] > rank[y]) p[y] = x; // rank
                    keeps the tree short
                else
                {
                    p[x] = y;
                    if (rank[x] == rank[y]) rank[y] =
                        rank[y]+1;
                }
            }
        }
};

```