Soundvision

Version: 2026.3.1

Date: 2026/10/13

Distance unit:	m
Scale factor:	1.000000
Weight unit:	kg
Delay unit:	ms

---

1. Source: KS28 1

1. 1. Physical configuration

Configuration: vertical, flown array

Bumper: KS28-BUMP
motors: 2
Front left pickup position (X; Y; Z, m): EXT (0.6; -0.35; 10.06)
Front right pickup position (X; Y; Z, m): EXT (-0.6; -0.35; 10.06)

Position (X; Y; Z, m): 0; 0; 10
Site: -1.6 °
Azimuth: 0 °

Spatial dimensions (X; Y; Z, m): 1.34; 0.76; 2.32
Bottom elevation: 7.77 m
Top site: -1.6 °
Bottom site: -1.6 °

Total weight (Enclosures + Frames): 331 kg

Total enclosure weight: 316 kg

Front left motor load: 165.5 kg

Front right motor load: 165.5 kg

#	Type	Site (°)	Top Z (m)	Bottom Z (m)
#1	KS28	-1.6	10	9.45
#2	KS28	-1.6	9.44	8.89
#3	KS28	-1.6	8.88	8.33
#4	KS28	-1.6	8.32	7.77

1. 2. Acoustic configuration

None

2. Source: KS21 1

2. 1. Physical configuration

Configuration: vertical, flown array

Bumper: A15-BUMP

motors: 2

Front pickup position (X; Y; Z, m): F (10; 0.02; 12.04)

Rear pickup position (X; Y; Z, m): R (10; -0.62; 12.04)

Position (X; Y; Z, m): 10; 0; 12

Site: 0 °

Azimuth: 0 °

Spatial dimensions (X; Y; Z, m): 0.75; 0.66; 1.79

Bottom elevation: 10.29 m

Top site: 0 °

Bottom site: 0 °

Total weight (Enclosures + Frames): 166 kg

Total enclosure weight: 147 kg

Front motor load: 87.8 kg

Rear motor load: 78.2 kg

#	Type	Site (°)	Top Z (m)	Bottom Z (m)
#1	KS21	0	12	11.43
#2	KS21	0	11.43	10.86
#3	KS21	0	10.86	10.29

2. 2. Acoustic configuration

None